

☐ Close this window

MSDS

Common Name: TOUGH GUY DUST MOP TREATMENT, 2DCC4**Manufacturer:** W.W. GRAINGER**MSDS Revision Date:** 8/30/2007**Grainger Item Number(s):** 2DCC4**Manufacturer Model Number(s):**

MSDS Table of Contents

Click the desired link below to jump directly to that section in the MSDS.

[SECTION 1: COMPANY IDENTIFICATION](#)[SECTION 2: INGREDIENTS/IDENTITY INFORMATION](#)[SECTION 3: HAZARDS IDENTIFICATION](#)[SECTION 4: EMERGENCY AND FIRST AID PROCEDURES](#)[SECTION 5: FIRE FIGHTING MEASURES](#)[SECTION 6: ACCIDENTAL RELEASE MEASURES](#)[SECTION 7: HANDLING AND STORAGE](#)[SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION](#)[SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES](#)[SECTION 10: STABILITY AND REACTIVITY](#)[SECTION 11: TOXICOLOGICAL INFORMATION](#)[SECTION 12: ECOLOGICAL INFORMATION](#)[SECTION 13: DISPOSAL CONSIDERATION](#)[SECTION 14: TRANSPORT INFORMATION](#)[SECTION 15: REGULATORY INFORMATION](#)[SECTION 16: ADDITIONAL INFORMATION](#)

MATERIAL SAFETY DATA SHEET

HMIS (R*) :

HEALTH 1

FLAMMABILITY 0

REACTIVITY 0

PERSONAL PROTECTION A

IDENTITY: TOUGH GUY DUST MOP TREATMENT

PART NUMBER: 2DCC4

NOTE:

BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, OR NO INFORMATION IS AVAILABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.

SECTION 1: COMPANY IDENTIFICATION



MANUFACTURED FOR: W.W. GRAINGER, INC.

ADDRESS (NUMBER, STREET, CITY, STATE, AND ZIP CODE):

100 GRAINGER PARKWAY
LAKE FOREST, IL 60045

EMERGENCY TELEPHONE NUMBER: 1-800-228-5635

TELEPHONE NUMBER FOR INFORMATION: 1-847-535-5400

SIGNATURE OF PREPARER (OPTIONAL):

SECTION 2: INGREDIENTS/IDENTITY INFORMATION



COMPONENTS (CHEMICAL IDENTITY, COMMON NAME(S))	CAS NO.	OSHA PEL	ACGIH- TLV	OTHER LIMITS RECOMMENDED	% (OPT.)
WATER	7732-18-5	NONE	NONE		60 - 100%
ISOBUTANE	75-28-5	800 PPM	800 PPM		5 - 10%
PROPANE	74-98-6	1000 PPM	ASPHYXIAN		1 - 5%

ANY SUBSTANCE LISTED AS HAZARDOUS BY THE STATES OF CALIFORNIA, FLORIDA, ILLINOIS, MICHIGAN, NEW JERSEY, OHIO, PENNSYLVANIA OR TEXAS IS DESCRIBED ABOVE IF KNOWN PRESENT IN REGULATED CONCENTRATIONS.

SECTION 3: HAZARDS IDENTIFICATION



ROUTE(S) OF ENTRY:

EYES?: YES

INHALATION?: NO

SKIN?: NO

INGESTION?: YES

ACUTE HEALTH HAZARDS:

CAUTION. MAY CAUSE EYE AND SKIN IRRITATION. CONTENTS UNDER PRESSURE.
FOLLOW GOOD CHEMICAL HYGIENE PRACTICES WHEN USING THIS AND OTHER CLEANING PRODUCTS.

CHRONIC HEALTH HAZARDS:

REPEATED OR PROLONGED OCCUPATIONAL OVEREXPOSURES MAY CAUSE DERMATITIS.

CARCINOGENICITY:

CHEMICAL: NONE

OSHA: NO

NTP: NO

IARC: NO

SIGNS AND SYMPTOMS OF EXPOSURE:

REDNESS, TEARING, BURNING IN EYES. REDNESS, DRYING, CRACKING OF SKIN.
IRRITATION OF NOSE AND THROAT.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

PRE-EXISTING SKIN DISORDERS.

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES



EYES:

IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES LIFTING EYELIDS TO INSURE COMPLETE REMOVAL. SEE A PHYSICIAN IMMEDIATELY.

INGESTION:

RINSE OUT MOUTH WITH WATER. DO NOT INDUCE VOMITING UNLESS DIRECTED BY A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

INHALATION:

GET TO FRESH AIR. IF BREATHING HAS STOPPED, QUALIFIED PERSONNEL SHOULD ADMINISTER ARTIFICIAL RESPIRATION.

SKIN:

IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING. IF IRRITATION ARISES AND PERSISTS, CALL A PHYSICIAN. LAUNDER CONTAMINATED CLOTHING AND SHOES BEFORE REUSE.

SECTION 5: FIRE FIGHTING MEASURES



USA FLAME PROJECTION TEST (ASTM D-3065): 0" - NON-FLAMMABLE

FLAMMABLE LIMITS: NO DATA

LEL: NO DATA

UEL: NO DATA

EXTINGUISHING MEDIA:

THIS PRODUCT DOES NOT SUPPORT COMBUSTION. USE EXTINGUISHING AGENT SUITABLE TO FUEL SOURCE.

SPECIAL FIRE FIGHTING PROCEDURES:

KEEP CONTAINERS COOL AND VAPORS DOWN WITH WATER SPRAY. PREVENT RUNOFF FROM ENTERING SEWERS AND PUBLIC WATERWAYS. WEAR SELF-CONTAINED BREATHING APPARATUS (SCBA) IN CHEMICAL FIRES.

HAZARDOUS PRODUCTS OF COMBUSTION:

CARBON DIOXIDE, CARBON MONOXIDE, SMOKE, SOOT, AMMONIACAL AND NITROUS OXIDE FUMES, SMOKE, SOOT AND VARIOUS ORGANIC OXIDATION BY PRODUCTS.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

AEROSOL CONTAINER (PRESSURIZED) MAY BURST IF HEATED OVER 120 DEG. F.

SECTION 6: ACCIDENTAL RELEASE MEASURES



SMALL SPILL:

WIPE UP SMALL RELEASES WITH A DRY ABSORBENT CLOTH OR OTHER ABSORBENT MATERIAL.

LARGE SPILL:

ABSORB LIQUID WITH VERMICULITE, ABSORBENT CLOTH, OR OTHER ABSORBENT MATERIAL. PREVENT MATERIAL FROM ENTERING SEWERS OR DRAINS. VENTILATE AREA AND BLOCK TRAFFIC. TRANSFER CONTAMINATED MATERIAL INTO SUITABLE CONTAINER FOR PROPER DISPOSAL.

SECTION 7: HANDLING AND STORAGE



HANDLING:

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WASH THOROUGHLY AFTER HANDLING.

AVOID INHALING MIST AND VAPORS. DO NOT DELIBERATELY CONCENTRATE AND INHALE VAPORS. USE WITH ADEQUATE VENTILATION. DO NOT USE AROUND IGNITION SOURCES SUCH AS HEAT, SPARKS, OPEN FLAME, ETC. DIRECT SPRAY AWAY FROM FACE.

STORAGE:

FOLLOW LABEL DIRECTIONS CAREFULLY. KEEP OUT OF REACH OF CHILDREN. STORE IN A COOL (UNDER 120 DEG. F) DRY LOCATION AWAY FROM HEAT, SPARKS, OPEN FLAME, AND DIRECT SUNLIGHT. REPLACE CAP WHEN NOT IN USE.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION



EYE PROTECTION:

YES, IF DIRECT CONTACT IS POSSIBLE USE APPROVED SAFETY GLASSES OR GOGGLES. (ANSI Z87)

SKIN PROTECTION: NOT USUALLY NEEDED.

RESPIRATORY PROTECTIONS:

NOT USUALLY NECESSARY. USE WITH ADEQUATE VENTILATION. USE NIOSH/MSHA APPROVED RESPIRATOR IF PELS OR TLVS ARE EXCEEDED.

ENGINEERING CONTROLS:

VENTILATION NOT USUALLY NECESSARY BUT SHOULD BE PROVIDED IN THE EVENT OF OVEREXPOSURE.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES



APPEARANCE AND ODOR:

WHITE OPAQUE LIQUID WITH A LEMON SCENT IN AN AEROSOL CAN.

pH: 10 +/- 0.5

SPECIFIC GRAVITY (70 DEG. F): 0.999

BOILING POINT: 212 DEG. F

MELTING POINT: NO DATA

EVAPORATION RATE (BUTYL ACETATE = 1): NO DATA

PRESSURE (PSIG. @ 70 DEG. F): 65 +/- 10

VAPOR DENSITY (AIR = 1): >1

SOLUBILITY IN WATER: COMPLETE

VOLATILE ORGANIC COMPOUNDS (VOCs): 92 GRAMS PER LITER OR 10% BY WEIGHT VOCs

SECTION 10: STABILITY AND REACTIVITY



HAZARDOUS POLYMERIZATION:

THIS PRODUCT WILL NOT UNDERGO HAZARDOUS POLYMERIZATION.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

CARBON DIOXIDE, CARBON MONOXIDE, SMOKE, SOOT, AMMONIACAL AND NITROUS OXIDE FUMES, SMOKE, SOOT AND VARIOUS ORGANIC OXIDATION BY PRODUCTS.

CHEMICAL STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID):
STRONG OXIDIZERS, ACIDS, BASES, AND REDUCING AGENTS.

SECTION 11: TOXICOLOGICAL INFORMATION



NO DATA

SECTION 12: ECOLOGICAL INFORMATION



NO DATA

SECTION 13: DISPOSAL CONSIDERATION



DISPOSAL METHOD:
DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS.

RCRA WASTE INFORMATION:
IF THIS PRODUCT BECOMES A WASTE, IT WOULD NOT BE A HAZARDOUS WASTE AS DEFINED BY RCRA (40 CFR 261). HOWEVER THE WASTE SHOULD BE PROPERLY CHARACTERIZED TO EVALUATE WHETHER ITS COMPOSITION HAS BEEN MODIFIED PRIOR TO DISPOSAL.

SECTION 14: TRANSPORT INFORMATION



DOT INFORMATION - 49 CFR 172.101:
PROPER SHIPPING DESCRIPTION: CONSUMER COMMODITY
HAZARD CLASS: ORM-D
IDENTIFICATION NUMBER: NONE
PACKING GROUP: NONE

WATER TRANSPORTATION:
PROPER SHIPPING DESCRIPTION: AEROSOLS
HAZARD CLASS: 2
IDENTIFICATION NUMBER: UN 1950
PACKING GROUP: NONE

AIR TRANSPORTATION:
PROPER SHIPPING DESCRIPTION: AEROSOLS, NON-FLAMMABLE
HAZARD CLASS: 2.2
IDENTIFICATION NUMBER: UN 1950
PACKING GROUP: NONE

MARINE POLLUTANTS: NONE

SECTION 15: REGULATORY INFORMATION



US FEDERAL REGULATIONS:

TSCA (TOXIC SUBSTANCES CONTROL ACT) STATUS:
ALL INGREDIENTS ARE ON THE TSCA INVENTORY OR ARE NOT REQUIRED TO BE LISTED ON THE TSCA INVENTORY.

CERCLA RQ - 40 CFR 302.4 (A): NONE LISTED

SARA 313 COMPONENTS - 40 CFR 372.65: NONE

STATE AND LOCAL REGULATIONS:

CALIFORNIA PROPOSITION 65:

WARNING:

THIS PRODUCT CONTAINS TRACE CHEMICALS (ETHYLENE OXIDE AND PROPYLENE OXIDE) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, AND/OR BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

SECTION 16: ADDITIONAL INFORMATION



DATE PREPARED: 08/30/07

WARNING!

THE USE OF THIS PRODUCT IS BEYOND THE CONTROL OF THE MANUFACTURER; THEREFORE, NO GUARANTEE, EXPRESSED OR IMPLIED, IS MADE AS TO THE EFFECTS OF SUCH OR THE RESULTS TO BE OBTAINED IF NOT USED IN ACCORDANCE WITH DIRECTIONS OR ESTABLISHED SAFE PRACTICE. THE USER MUST ASSUME ALL RESPONSIBILITY, INCLUDING INJURY OR DAMAGE, RESULTING FROM ITS MISUSE AS SUCH, OR IN COMBINATION WITH OTHER MATERIALS. THE MANUFACTURER WARRANTS ONLY THAT THIS PRODUCT MEETS THE MANUFACTURER'S SPECIFICATIONS FOR SUCH PRODUCT. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AS TO DESCRIPTION, QUALITY, MERCHANTABILITY. FITNESS FOR ANY PARTICULAR PURPOSE, PRODUCTIVENESS, OR ANY OTHER MATTER, OF THIS PRODUCT. THE MANUFACTURER SHALL BE IN NO WAY RESPONSIBLE FOR THE IMPROPER USE OF THIS PRODUCT. THE SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER FOR BREACH OF WARRANTY SHALL BE REIMBURSEMENT OF THE PURCHASE PRICE OF THE PRODUCT IN THE EVENT THAT A DEFECTIVE CONDITION OF THE PRODUCT SHALL BE FOUND TO EXIST. NO OTHER REMEDY (INCLUDING BUT NOT LIMITED TO INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR INJURY TO PERSON OR PROPERTY OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE.