

# MATERIAL SAFETY DATA SHEET

## LS - LIQUID SOLDER

### MANUFACTURER:

NAME: Leech Products, Inc.  
ADDRESS: 1430 West Fourth Street  
ADDRESS: Hutchinson KS 67504-2147

EMERGENCY PHONE #: 800-424-9300 - CHEMTREC  
INFORMATIONAL PHONE #: 316-669-0145  
DATE: 03/15/91

### - SECTION 1 - PRODUCT -

Trade name: Liquid Solder  
Synonym: Putty

A245

### - SECTION II - HAZARDOUS INGREDIENTS -

MATERIALS OR COMPONENTS	% (W/W)	CAS NO.	HAZARD DATA
Methyl Ethyl Ketone	40-50%	78-93-3	ACGIH TLV 50 ppm STEL 75 ppm
Methyl Isobutyl Ketone	20-25%	100-10-1	ACGIH TLV 50 ppm STEL 75 ppm OSHA PEL/TWA 100 ppm
Butyl Benzyl Phthalate	2-5%	85-68-7	ACGIH TWA 5 mg/m3
Aluminum Powder	5-10%	7429-90-5	ACGIH TWA 10 mg/m3; STEL 20 mg/m3
Caster Oil Derivative	1-5%	8001-78-3	OSHA: PEL 15 mg/m3

### - SECTION III - PHYSICAL PROPERTIES -

Boiling Point:	N/A	Melting Point:	N/A
Vapor Pressure:	Unknown	Specific Gravity (Water=1):	0.96
Vapor Density (AIR=1):	Unknown	Volatile by Volume:	Unknown
Water Solubility:	Nil	Evaporation Rate (Ethyl Ether=1):	Slower than
Appearance:	Silver-Gray paste	V.O.C.:	617 gas/ltr

### - SECTION IV - FIRE & EXPLOSION DATA -

Flash Point 0°: 24°F Seta Closed Cup  
Fire Extinguishing Media: Co2, Dry Chemicals, Foam  
Special Fire Fighting Procedures: Firefighters wear self-contained breathing apparatus. Fight like a fuel oil fire.  
Unusual Fire & Explosion Hazard: Closed containers exposed to high temperatures such as fire conditions may rupture.  
Flammable Limits: N/E

### - SECTION V - HEALTH HAZARD INFORMATION -

Threshold Limit Value: Product TLV not established. Component TWA is 5 mg/m3  
Health Hazards: Chronic exposure may affect the CNS, respiratory system, eyes, skin, lungs. Acute exposure may irritate eyes, mucous membranes, nose and throat.

STATE REGULATIONS: Trace amounts of epichlorohydrin and vinyl and chloride monomer, substances which are human carcinogen hazards, may be contained in this product. The level does not constitute a significant risk.

CARCINOGENICITY: IARC has concluded that there is "sufficient" evidence for the carcinogenicity of crystalline silica to experimental animals; and "limited evidence" with respect to humans.

CALIFORNIA PROPOSITION 65: Trace amounts of some chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm may be present in this product.

#### FIRST AID PROCEDURES:

SKIN: Wash with soap and excess water. Obtain medical attention if irritation occurs.  
EYE CONTACT: Flush promptly with excess water for 15 minutes. Call a physician.  
IF SWALLOWED: Do NOT induce vomiting. Call a physician. If conscious, give a glass of water to person.  
INHALATION: Remove from contaminated areas, apply artificial respiration if necessary, call a physician.

### - SECTION VI - TOXICITY -

Oral (acute) (rats):	N/E	Acute Intraperitoneal (mice):	N/E
Inhalation (acute) (rats):	N/E	Chronic, Subchronic, Etc.:	N/E

## - SECTION VII - REACTIVITY DATA -

Stability: Stable  
Incompatibility: Strong oxidizing agents and strong alkalis.  
Hazardous Decomposition Products: Thermal decomposition will yield carbon monoxide and carbon dioxide and organic decomposition products  
Hazardous Polymerization: Will not occur  
Conditions to Avoid: Heat, sparks, and open flames

## - SECTION VIII - SPILL & DISPOSAL METHOD -

Steps to be Taken if Material is Released or Spilled: Dike spills with absorbent material. Correct with non-sparking tools and place in container.  
Waste Disposal Method: Disposal method must comply with local, state and federal regulations.

## - SECTION IX - SPECIAL PROTECTION INFORMATION -

Respiratory Protection: Ventilate with air flow to keep vapor concentration below TLV or wear NIOSH approved respirator.  
Ventilation Requirements: Fan or forced air  
Local: Exhaust  
Mechanical: Acceptable (explosion proof motor)  
Special: See Handling and Storage Precautions  
Eye: Safety goggles or face shield to protect against spraying  
Hand: Neoprene or equivalent required  
Other Protective Equipment: Eye wash fountain and safety shower should be available. Prevent inhalation of dust when sanding cured product. When ventilation is inadequate, use NIOSH approved air line mask or self-contained breathing apparatus.

## - SECTION X - HANDLING AND STORAGE PRECAUTIONS -

Other Storage and Handling Conditions: Keep away from extreme heat, open flames, or other sources of ignition. Store with adequate ventilation. Do not store above 100°F.  
Miscellaneous: HMIS Rating: HEALTH - 2, FLAMMABILITY - 3, REACTIVITY - 1;  
Code: Least Hazardous - 0, Greatest Hazard - 4  
Section 313:  
Supplier Notification: This product contains the following toxic chemical subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372:

CHEMICAL NAME	CAS NO.	% BY WT.
Methyl Ethyl Ketone	78-93-3	40-45%
Butyl Benzyl Phthalate	85-68-7	2-5%
Aluminum Powder	7429-90-5	5-10%
Methyl Isobutyl Ketone	108-10-1	20-25%

This information must be included in all MSDS's that are copied and distributed for this material.

NOTES: N/E=Not Established N/D=Not Determined N/A=Not Applicable

## - SECTION XI - DISCLAIMER -

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of Leech Products, Inc. knowledge, or is obtained from sources believed by Leech Products, Inc., to be accurate. No warranty is express or implied regarding the accuracy of this information or the results to be obtained from its use thereof. Leech Products, Inc., assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in the Data Sheet. Additionally, Leech Products, Inc., assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.