

Super HD II Motor Oil (All Grades)

Page 1 of 6



MATERIAL SAFETY DATA SHEET

Super HD II Motor Oil (All Grades)

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Synonyms: Super II, HD II, 10W, 10W-30, 15W-40, 20W-20, 30, 40, 50
Formula: Mixture
Chemical Family: Hydrocarbon
CAS Number: Mixture
SAP Code: 1031441; 1031442; 1012683; 1012684; 1012685; 1012686; 1012687; 1012688; 1012734; 1012735; 1012736; 1012737; 1012739; 1012741; 1012744; 1012745; 1012746; 1012747; 1012748; 1012751; 1012753; 1012754; 1012755; 1012757; 1012758
Product Code: 49400; 49591; 63160; 63260; 63360; 63460; 63560
MSDS Number: US036840
NFPA Ratings: Health 0, Flammability 1, Reactivity 0
HMS Ratings: Health 0, Flammability 1, Reactivity 0
Intended Use(s): Diesel Engine Oil

The intended use of this product is indicated above, if any additional use is known please contact us at the Technical Information number listed below.

Manufactured By:
 Phillips 66 Company
 A Division of Phillips Petroleum Company
 Bartlesville, Oklahoma 74004

Phone Numbers

Emergency: (918) 661-8118

Technical Information: (800) 766-0050

For Additional MSDSs: (918) 661-5974

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Specification and CAS #	Weight % In Product*	ACGIH TLV (TWA)	ACGIH Short Term Exposure Limit	ACGIH Ceiling Limits	ACGIH Skin Designation	OSHA Final PEL (TWA)	OSHA - Final PELs - Ceiling Limits	OSHA - Final PELs - Skin Notation
Base stock 64741-88-4	0 to 90	NE	NE	NE	NE	NE	NE	NE
Petroleum based lubricants 64742-54-7	0 to 90	NE	NE	NE	NE	NE	NE	NE
Solvent refined residuum 64742-01-4	15 to 65	NE	NE	NE	NE	NE	NE	NE
Borated polyisobutenyl succinic anhydride nitrogen	0 to 15	NE	NE	NE	NE	NE	NE	NE
Ethylene-propylene copolymer 9010-79-1	0 to 10	NE	NE	NE	NE	NE	NE	NE
Mineral Oil	< 5	NE	NE	NE	NE	NE	NE	NE
Magnesium and calcium alkylaryl detergent	< 5	NE	NE	NE	NE	NE	NE	NE
Acrylic copolymers 63197-48-8	0 to 1	NE	NE	NE	NE	NE	NE	NE
2-Propenoic acid, 2-methyl-, eicosyl ester, polymer with 1-ethenyl-2-pyrrolidinone, hexadecyl 2-methyl-2-propenoate, isodecyl 2-	0 to 1	NE	NE	NE	NE	NE	NE	NE

Super HD II Motor Oil (All Grades)

Page 2 of 6

methyl-2-propenoate, etc. 68171-46-0								
Zinc dialkyldithiophosphate 68649-42-3	.7 to 1	NE	NE	NE	NE	NE	NE	NE
Polybutene 9003-29-6	0 to 1	NE	NE	NE	NE	NE	NE	NE

See Section 8 for additional Exposure Limits.

*1% = 10,000 ppm

3. HAZARDS IDENTIFICATION

Emergency Overview

Non-Hazardous. Pressure Injection.

Potential Acute Health Effects

Eye Contact: May cause mild irritation.

Skin Contact: May cause mild irritation with prolonged or repeated contact.

Inhalation: No acute effects expected due to low vapor pressure.

Ingestion: Slightly toxic (LD50 > 5 gm/kg).

Aggravated Medical Conditions: Skin Disorders.

4. FIRST AID MEASURES

Eye Contact: Flush eyes with running water. If irritation or adverse symptoms develop, seek medical attention.

Skin Contact: Wash skin with soap and water. If irritation or adverse symptoms develop, seek medical attention.

Inhalation: Remove from exposure. If illness or adverse symptoms develop, seek medical attention.

Ingestion: If illness or adverse symptoms develop, seek medical attention.

Notes To Physician: For injection injuries, immediate medical treatment is required. Physicians may call the emergency number (918) 661-8118.

5. FIRE FIGHTING MEASURES

Flash Point: > 377F (>192C)
FP Method: COC, ASTM D92
Ignition Temperature: Unknown
Flammable Limits (% by Volume in Air)
Lower Explosive Limit - Not Established
Upper Explosive Limit - Not Established

Fire Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam

Super HD II Motor Oil (All Grades)

Page 3 of 6

Fire Fighting Procedures: Evacuate area and fight fire from a safe distance. Shut off source, if possible. Use NIOSH approved self-contained breathing apparatus and other protective equipment and/or garments described in Section 8 if conditions warrant. Use water spray to cool nearby containers and structures exposed to fire.

Fire and explosion hazards: Carbon oxides and various hydrocarbons forms when burned.

6. ACCIDENTAL RELEASE MEASURES

Sweep or gather up material and place in proper container for disposal or recovery.

7. HANDLING AND STORAGE

Avoid contact with eyes, skin or clothing. Avoid breathing vapors, mist, fume or dust. Wear protective equipment and/or garments described in Section 8 if exposure conditions warrant. Wash thoroughly after handling. Launder contaminated clothing before reuse. Store in closed container. Store in well-ventilated area.

If pressure injected under the skin, can cause gangrene if not treated.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection: Wear safety glasses.

Respiratory Protection: For concentrations exceeding an applicable exposure limit, use NIOSH approved air purifying respirator equipped with P95 filters, for particulate with time weighted average exposure limit not less than 0.5 mg/M3.

Skin Protection: Use gloves resistant to the material(s) contained in this product.

Ventilation: Use adequate ventilation to control concentrations below applicable exposure limits.

Other Personal Protection: Personal protection information shown in Section 8 is based upon general information as to normal uses and conditions. Where special or unusual uses or conditions exist, it is suggested that the expert assistance of an industrial hygienist or other qualified professional be sought.

Exposure Limits: OSHA PEL and ACGIH TLV for oil mists is 5 mg/m3

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Appearance:	Amber to dark amber
Odor:	Mild
Odor Threshold (ppm):	Unknown
Boiling Point:	High with wide range
Melting/Freeze Point:	Not Established
Vapor Pressure:	< 1 mm Hg @ 68F (20C)
Vapor Density (Air=1):	> 12+ - 20+
Specific Gravity @ 20 C (Water=1):	0.87 - 0.89 @ 60F (16C)
Percent Volatile by Volume:	Negligible
Evaporation Rate (Butyl Acetate=1):	Negligible
Water Solubility:	Negligible
Viscosity:	43 - 236 cSt @ 104F (40C)

Super HD II Motor Oil (All Grades)

Page 4 of 6

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous Polymerization:	Will Not Occur
Incompatibility (Materials to Avoid):	Contact with oxidizing agents. Oxygen and strong oxidizing agents.
Hazardous Decomposition Products:	Carbon oxides and various hydrocarbons are formed when burned.

11. TOXICOLOGICAL INFORMATION

Subchronic and Chronic Effects:

Prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as lung inflammation. This condition usually causes no symptoms.

Other Health Effects:

Pressurized injection of product under the skin can lead to seriously inflamed tissue. If left untreated injury can become gangrenous.

Continuous skin contact with used motor oils has caused skin cancer in laboratory animals. Avoid prolonged skin contact with used motor oil.

These products may contain petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking or severe hydrotreating. None of the oils require a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

12. ECOLOGICAL INFORMATION

No data at this time.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT Shipping Description:	Not Regulated
IMDG Shipping Description:	Not Regulated
ICAO/IATA Proper Shipping Name:	Not Regulated

15. REGULATORY INFORMATION

EPA SARA 311/312 (Title III Hazard Categories)

Acute Health:	No
Chronic Health:	No
Fire Hazard:	No
Pressure Hazard:	No
Reactivity Hazard:	No

Base stock 0 to 90 64741-88-4
Regulated Substance on TSCA Inventory: Listed

Super HD II Motor Oil (All Grades)

Page 5 of 6

Canada - Domestic Substances List: Listed**Petroleum based lubricants 0 to 90 64742-54-7****Regulated Substance on TSCA Inventory: Listed****Canada - Domestic Substances List: Listed****Solvent refined residuum 15 to 65 64742-01-4****Regulated Substance on TSCA Inventory: Listed****Canada - Domestic Substances List: Listed****Borated polyisobutenyl succinic anhydride nitrogen 0 to 15****Regulated Substance on TSCA Inventory: Listed****Canada - Domestic Substances List: Listed****Ethylene-propylene copolymer 0 to 10 9010-79-1****Regulated Substance on TSCA Inventory: Listed****Canada - Domestic Substances List: Listed****Mineral Oil < 5****Regulated Substance on TSCA Inventory: Listed****Canada - Domestic Substances List: Listed****Magnesium and calcium alkylaryl detergent < 5****Regulated Substance on TSCA Inventory: Listed****Canada - Domestic Substances List: Listed****Acrylic copolymers 0 to 1 63197-48-8****Regulated Substance on TSCA Inventory: Listed****Canada - Domestic Substances List: Listed****2-Propenoic acid, 2-methyl-, eicosyl ester, polymer with 1-ethenyl-2-pyrrolidinone, hexadecyl 2-methyl-2-propenoate, isodecyl 2-methyl-2-propenoate, etc. 0 to 1 68171-46-0****Regulated Substance on TSCA Inventory: Listed****Canada - Domestic Substances List: Listed****Zinc dialkyldithiophosphate .7 to 1 68649-42-3****Regulated Substance on TSCA Inventory: Listed****Canada - Domestic Substances List: Listed****Polybutene 0 to 1 9003-29-6****Regulated Substance on TSCA Inventory: Listed****Canada - Domestic Substances List: Listed****16. OTHER INFORMATION****Revision Summary:**

Section 1 - Chemical Product and Company Identification.

Preparer: Health, Environment and Safety Department**Date Prepared:** 08/15/2001**Supersedes:** 08/06/2001

Phillips Petroleum Company (references to Phillips Petroleum Company or Phillips includes its divisions, affiliates and subsidiaries) believes that the

Super HD II Motor Oil (All Grades)**Page 6 of 6**

information contained herein (including data and statements) is accurate as of the date hereof. NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE AS CONCERNS THE INFORMATION HEREIN PROVIDED. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and information referred to herein are beyond the control of Phillips, Phillips expressly disclaim any and all liability as to any results obtained or arising from any use of the product or such information. No statement made herein shall be construed as a permission or recommendation for the use of any product in a manner that might infringe existing patents.