

PORTER PAINT CO. -- 1332 TARSET SUPER-BLACK,PART B -- 8010-00N008129

===== Product Identification =====

Product ID:1332 TARSET SUPER-BLACK,PART B
MSDS Date:01/01/1987
FSC:8010
NIIN:00N008129
MSDS Number: BCPMD
=== Responsible Party ===
Company Name:PORTER PAINT CO.
Address:400 S 13TH ST
City:LOUISVILLE
State:KY
ZIP:40203-1714
Country:US
CAGE:2N948
=== Contractor Identification ===
Company Name:COURTAULDS COATINGS INC
Address:400 S 13TH STREET
Box:City:LOUISVILLE
State:KY
ZIP:40203-1714
Country:US
Phone:502-588-9651
CAGE:50411
Company Name:PORTER PAINT CO.
Address:400 S. 13TH STREET
Box:City:LOUISVILLE
State:KY
ZIP:40203
Country:US
Phone:502-588-9200
CAGE:2N948

===== Composition/Information on Ingredients =====

Ingred Name:COAL TAR PITCH VOLATILES (BENZENE SOLUBLES) (ACCD TO
ACGIH, IS RECOGNIZED TO-SEE SUPP DATA
CAS:8007-45-2
RTECS #:GF8600000
Fraction by Wt: <1%
ACGIH TLV:0.2 MG/CUM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 10%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150 STEL; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: <5%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 5%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TETRAETHYLENE PENTAMINE (CAS #:112-57-2) (VAPOR
PRESSURE:<1MMHG @20C)
CAS:112-57-2
RTECS #:KH8585000
Fraction by Wt: 5%

===== Hazards Identification =====

Health Hazards Acute and Chronic:ACUTE:EYE & SKIN:PHOTOSENSITIZATION
MAY OCCUR. CHRONIC:PROLONGED OR REPEATED EXPOSURES MAY LEAD TO
DERMATITIS,SKIN CANCER. THE AMINE CAN BE A PULMONARY (LUNG)
SENSITIZER.

Effects of Overexposure:INHALATION:IRRITATION OF THE RESPIRATORY TRACT
OR ACUTE NERVOUS SYSTEM DEPRESSION CAUSING HEADACHE,DIZZINESS OR
NAUSEA. ACUTE:EYE & SKIN:PRIMARY IRRITATION.

===== First Aid Measures =====

First Aid:VAPORS:REMOVE FROM EXPOSURE.KEEP WARM,QUIET.NOTIFY PHYSICIAN.
SPLASH IN EYES:FLUSH IMMED W/LARGE AMOUNTS OF H*2O FOR AT LEAST 15
MINUTES.TAKE TO PHYSICIAN FOR MEDICAL TREATMENT. SPLASH ON
SKIN:WASH AFFECTED AREAS W/LRG AMTS H*2O.REMOVE CONTAM CLOTHES

===== Fire Fighting Measures =====

Flash Point:80F,26.7C (PMCC)
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE
Fire Fighting Procedures:IN THE ABSENCE OF ELECTRICITY,A WATER SPRAY (A
FOG NOZZLE IS PREFERRED) MAY BE USED TO COOL CONTAINERS. WEAR SCBA.
Unusual Fire/Explosion Hazard:KEEP CNTNRS TIGHTLY CLOSED.ISOLATE FROM
HEAT,SPARKS,ELECTRICAL EQUIP,OPEN FLAME.CLOSED CNTNR MAY EXPLODE
W/EXPOS TO EXTRM HEAT.SEE DOT P5800.3 GUIDE# 26,ID#1263

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT
SURFACES & ELECTRICAL,STATIC,FRICITION SPARKS). AVOID BREATHING
VAPORS,WEAR APPROVED (NIOSH/MSHA) RESPIRATOR & VENTILATE AREA.
REMOVE W/INERT ABSORBANT SUCH AS SAND,KITTY LITTER,ETC. & USE
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE LRG AMT IN BLDG ACCD TO OSHA
1910.106.DONT STORE @>120F.DONT TAKE INTERNAL.DONT GET IN EYE/ON
SKIN.DONT INHAL VAP/SPRAY.KEEP FROM IGNITN SOURCE.
Other Precautions:AVOID LIQ FREEFALL >FEW IN.USE NONFERROUS
TOOLS,NONSPARK SHOES IF EXPLO HAZ.FLAME
CUT,BRAZE,WELD,SPRAY,BLAST-USE NIOSH/MSHA APVD MECH FILTER RSPTR
ADEQ VENT,ENGINEER/ADMIN CRTLS-KEEP EXP 1
Spec Gravity:1.2620
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:24

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:NONE KNOWN
Hazardous Decomposition Products:POSS HAZ FUMES WHEN HEAT TO
DECOMP:CO*2,CO,OXIDES OF NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN A SAFE MANNER IN ACCORDANCE
W/LOCAL,STATE & FEDERAL REGULATIONS THAT APPLY TO INCINERATION OR
SECURE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.