



Common Name: ALEX PLUS ACRYLIC LATEX CAULK PLUS SILICONE - ALL COLORS

Manufacturer: DAP

MSDS Revision Date: 4/21/2005

Grainger Item Number(s): 3AZZ2, 3AZZ3, 3AZZ4, 3AZZ5, 3AZZ6, 3AZZ7, 3AZZ8, 3WEW3

Manufacturer Model Number(s):

MSDS Table of Contents

Click the desired link below to jump directly to that section in the MSDS.

- [SECTION 1 - CHEMICAL PRODUCT / COMPANY INFORMATION](#)
- [SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS](#)
- [SECTION 3 - HAZARDS IDENTIFICATION](#)
- [SECTION 4 - FIRST AID MEASURES](#)
- [SECTION 5 - FIRE FIGHTING MEASURES](#)
- [SECTION 6 - ACCIDENTAL RELEASE MEASURES](#)
- [SECTION 7 - HANDLING AND STORAGE](#)
- [SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION](#)
- [SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES](#)
- [SECTION 10 - STABILITY AND REACTIVITY](#)
- [SECTION 11 - TOXICOLOGICAL INFORMATION](#)
- [SECTION 12 - ECOLOGICAL INFORMATION](#)
- [SECTION 13 - DISPOSAL INFORMATION](#)
- [SECTION 14 - TRANSPORTATION INFORMATION](#)
- [SECTION 15 - REGULATORY INFORMATION](#)
- [SECTION 16 - OTHER INFORMATION](#)

MATERIAL SAFETY DATA SHEET

24 HOUR EMERGENCY PHONE NUMBERS:

MEDICAL:
1-800-327-3874
1-513-558-5111

TRANSPORTATION:
1-800-535-5053
1-352-323-3500

NOTE:
NATIONAL RESPONSE CENTER EMERGENCY NUMBERS TO BE USED ONLY IN THE EVENT OF
CHEMICAL EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT
INVOLVING CHEMICALS.

IMPORTANT:
PROVIDE THIS INFORMATION TO EMPLOYEES, CUSTOMERS, AND USERS OF THIS PRODUCT.
READ THIS MSDS BEFORE HANDLING OR DISPOSING OF THIS PRODUCT. THIS PRODUCT IS
COVERED BY THE OSHA HAZARD COMMUNICATION STANDARD AND THIS DOCUMENT HAS BEEN
PREPARED IN ACCORDANCE WITH REQUIREMENTS OF THIS STANDARD. ALL ABBREVIATED
TERMS USED IN THIS MSDS ARE FURTHER DESCRIBED IN SECTION 16.

SECTION 1 - CHEMICAL PRODUCT / COMPANY INFORMATION



THIS MATERIAL SAFETY DATA SHEET IS AVAILABLE IN CANADIAN FRENCH AND HISPANIC AMERICAN SPANISH UPON REQUEST.

PRODUCT NAME: ALEX PLUS ACRYLIC LATEX CAULK PLUS SILICONE - ALL COLORS

PRODUCT UPC NUMBER:
18103 18118 18120 18122 18124 18126 18128 18130 18134 18136 18139 18152
18172 18656 30108 35000 35004 35006 35008 35010 35012 35014 74225 74230
74241 74243 74250 74254 74256 74258 74260 74270 74275 76250

PRODUCT USE/CLASS: LATEX CAULK

MANUFACTURER:
DAP INC.
2400 BOSTON STREET
SUITE 200 BALTIMORE, MD 21224-4723
888-327-8477 (NON-EMERGENCY MATTERS)

REVISION DATE: 04/21/2005

SUPERCEDES: 12/05/2002

MSDS NUMBER: 00010002001

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS



CHEMICAL NAME	CASRN			WT %			
CALCIUM CARBONATE	1317-65-3			40-70			
ESTER BRANCHED & LINEAR (C7&C9)	PHTHALATE ESTER			1-5			
TITANIUM DIOXIDE	13463-67-7			0.1-1.0			
CARBON BLACK	1333-86-4			0.0-1.5			
SILICA, CRYSTALLINE	14808-60-7			0.1-1.0			
ETHYLENE GLYCOL	107-21-1			0.1-1.0			
AMMONIA	7664-41-7			<0.010			
FORMALDEHYDE	50-00-0			<0.02			
ETHYL ACRYLATE	140-88-5			<0.009			
ACETALDEHYDE	75-07-0			<0.002			
ACRYLONITRILE	107-13-1			<0.0003			
CHEMICAL NAME	ACGIH TWA	ACGIH STEL	ACGIH CEIL	OSHA TWA	OSHA STEL	OSHA CEIL	SKIN
CALCIUM CARBONATE	10 MGM3	N.E.	N.E.	5 MGM3	N.E.	N.E.	NO
ESTER BRANCHED & LINEAR (C7&C9)	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.	NO
TITANIUM DIOXIDE	10 MGM3	N.E.	N.E.	15 MGM3	N.E.	N.E.	NO
CARBON BLACK	3.5 MGM3	N.E.	N.E.	3.5 MGM3	N.E.	N.E.	NO
SILICA, CRYSTALLINE	0.05 MGM3	N.E.	N.E.	(10 / % SiO2) / 2 MGM3	N.E.	N.E.	NO
ETHYLENE GLYCOL	N.E.	N.E.	100 MGM3	N.E.	N.E.	N.E.	NO
AMMONIA	25 PPM	35 PPM	N.E.	50 PPM	N.E.	N.E.	NO
FORMALDEHYDE	N.E.	N.E.	0.3 PPM	0.75 PPM	2 PPM	N.E.	NO
ETHYL ACRYLATE	5 PPM	15 PPM	N.E.	25 PPM	N.E.	N.E.	YES
ACETALDEHYDE	N.E.	N.E.	25 PPM	200 PPM	N.E.	N.E.	NO
ACRYLONITRILE	2 PPM	N.E.	N.E.	2 PPM	10 PPM	N.E.	YES

EXPOSURE NOTES:
107-13-1 ACRYLONITRILE IS A SPECIALLY REGULATED SUBSTANCE FOR WHICH AN OSHA CHEMICAL-SPECIFIC EXPOSURE STANDARD EXISTS. DETAILED INFORMATION REGARDING THIS SUBSTANCE MAY BE FOUND IN 29 CFR 1910.1045. MEDICAL SURVEILLANCE INFORMATION REGARDING THIS SUBSTANCE MAY BE FOUND IN APPENDIX C TO 29 CFR 1910.1045.

50-00-0 FORMALDEHYDE IS A SPECIALLY REGULATED SUBSTANCE FOR WHICH AN OSHA CHEMICAL-SPECIFIC EXPOSURE STANDARD EXISTS. DETAILED INFORMATION REGARDING THIS SUBSTANCE MAY BE FOUND IN 29 CFR 1910.1048. MEDICAL SURVEILLANCE INFORMATION REGARDING THIS SUBSTANCE MAY BE FOUND IN APPENDIX C TO 29 CFR 1910.1048.

IMPORTANT:
LISTED PERMISSIBLE EXPOSURE LEVELS (PEL) ARE FROM THE U.S. DEPT. OF LABOR OSHA FINAL RULE LIMITS (CFR 29 1910.1000); THESE LIMITS MAY VARY BETWEEN STATES.

NOTE:
AN EMPLOYEE'S SKIN EXPOSURE TO SUBSTANCES HAVING A "YES" IN THE "SKIN" COLUMN IN THE TABLE ABOVE SHALL BE PREVENTED OR REDUCED TO THE EXTENT NECESSARY UNDER THE CIRCUMSTANCES THROUGH THE USE OF GLOVES, COVERALLS, GOGGLES OR OTHER APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT, ENGINEERING CONTROLS OR WORK PRACTICES

SECTION 3 - HAZARDS IDENTIFICATION



EMERGENCY OVERVIEW: A COLORED PASTE PRODUCT.

WARNING!
HARMFUL IF SWALLOWED OR ABSORBED THROUGH THE SKIN. MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION. THIS PRODUCT CONTAINS ETHYLENE GLYCOL.

REFER TO OTHER MSDS SECTIONS FOR OTHER DETAILED INFORMATION.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: MAY CAUSE EYE IRRITATION.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:
HARMFUL IF ABSORBED THROUGH THE SKIN. MAY CAUSE SENSITIZATION BY SKIN CONTACT. MAY CAUSE SKIN IRRITATION AND/OR DERMATITIS.

EFFECTS OF OVEREXPOSURE - INHALATION:
HARMFUL IF INHALED. MAY CAUSE IRRITATION OF RESPIRATORY TRACT. PROLONGED, REPEATED, OR HIGH EXPOSURES MAY CAUSE WEAKNESS AND DEPRESSION OF THE CENTRAL NERVOUS SYSTEM. INHALATION OF VAPORS MAY CAUSE IRRITATION OF THE NOSE, THROAT, LUNGS AND RESPIRATORY TRACT.

EFFECTS OF OVEREXPOSURE - INGESTION: HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:
PROLONGED AND REPEATED SKIN CONTACT MAY CAUSE IRRITATION AND POSSIBLY DERMATITIS. REPEATED OR PROLONGED EXPOSURE MAY CAUSE RESPIRATORY SYSTEM DAMAGE. OVEREXPOSURE MAY CAUSE KIDNEY, CARDIOVASCULAR, SKIN AND LIVER DAMAGE.

FORMALDEHYDE VAPOR IS A KNOWN ANIMAL CARCINOGEN ACCORDING TO OSHA AND NTP AND IS CONSIDERED POSSIBLY CARCINOGENIC TO HUMANS BY INHALATION. THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER CONSIDERS FORMALDEHYDE TO BE A HUMAN CARCINOGEN.

ETHYLENE GLYCOL MAY CAUSE KIDNEY AND LIVER DAMAGE UPON PROLONGED AND REPEATED OVEREXPOSURES. STUDIES HAVE SHOWN THAT REPEATED INHALATION OF ETHYLENE GLYCOL HAS PRODUCED ADVERSE CARDIOVASCULAR CHANGES IN LABORATORY ANIMALS. ETHYLENE GLYCOL HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT, INHALATION, EYE CONTACT

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY EXPOSURE: NONE KNOWN.

SECTION 4 - FIRST AID MEASURES



FIRST AID - EYE CONTACT:

IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES UNTIL IRRITATION SUBSIDES. GET MEDICAL ATTENTION IMMEDIATELY.

FIRST AID - SKIN CONTACT:
WASH OFF IMMEDIATELY WITH SOAP AND PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL AID IF SYMPTOMS PERSIST. REMOVE AND WASH CONTAMINATED CLOTHING.

FIRST AID - INHALATION:
IF INHALED, REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED BREATHING DIFFICULTY IS EXPERIENCED, GET MEDICAL ATTENTION IMMEDIATELY.

FIRST AID - INGESTION:
IF SWALLOWED, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

NOTE TO PHYSICIAN: NONE.

COMMENTS:
CALL MEDICAL EMERGENCY AT 1-800-327-3874 IF ANY IRRITATION OR COMPLICATION ARISES FROM ANY OF THE ABOVE ROUTES OF ENTRY.

SECTION 5 - FIRE FIGHTING MEASURES



FLASH POINT, F: GREATER THAN 200 DEGREES FAHRENHEIT
METHOD: (SETA CLOSED CUP)

LOWER EXPLOSIVE LIMIT, %: NOT ESTABLISHED
UPPER EXPLOSIVE LIMIT, %: NOT ESTABLISHED

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:
NO SPECIAL PROTECTIVE MEASURES AGAINST FIRE REQUIRED.

SPECIAL FIREFIGHTING PROCEDURES:
WEAR SELF-CONTAINED BREATHING APPARATUS PRESSURE-DEMAND (NIOSH APPROVED OR EQUIVALENT) AND FULL PROTECTIVE GEAR. USE WATER SPRAY TO COOL EXPOSED SURFACES.

SECTION 6 - ACCIDENTAL RELEASE MEASURES



STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:
WEAR PROPER PROTECTIVE EQUIPMENT AS SPECIFIED IN SECTION 8.
USE ABSORBENT MATERIAL OR SCRAPE UP DRIED MATERIAL AND PLACE IN CONTAINER.

SECTION 7 - HANDLING AND STORAGE



HANDLING:
KEEP OUT OF REACH OF CHILDREN!
DO NOT TAKE INTERNALLY. DO NOT BREATHE VAPORS. USE ONLY WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING VAPOR AND CONTACT WITH EYES, SKIN AND CLOTHING. OPEN ALL WINDOWS AND DOORS OR USE OTHER MEANS TO ENSURE CROSS-VENTILATION AND FRESH AIR ENTRY DURING APPLICATION AND DRYING. ODOR IS NOT AN ADEQUATE WARNING FOR HAZARDOUS CONDITIONS.

STORAGE:
CLOSE CONTAINER AFTER EACH USE. STORE CONTAINERS AWAY FROM EXCESSIVE HEAT AND FREEZING. DO NOT STORE AT TEMPERATURES ABOVE 120 DEGREES F. STORE AWAY FROM CAUSTICS AND OXIDIZERS.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION



PRECAUTIONARY MEASURES:
PLEASE REFER TO OTHER SECTIONS AND SUBSECTIONS OF THIS MSDS.

ENGINEERING CONTROLS:

GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT TO CONTROL AIRBORNE LEVELS. ENSURE ADEQUATE VENTILATION, ESPECIALLY IN CONFINED AREAS. LOCAL VENTILATION OF EMISSION SOURCES MAY BE NECESSARY TO MAINTAIN AMBIENT CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS.

RESPIRATORY PROTECTION:
IN CASE OF INSUFFICIENT VENTILATION, WEAR SUITABLE RESPIRATORY EQUIPMENT. A NIOSH-APPROVED AIR PURIFYING RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE NECESSARY UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS. A RESPIRATORY PROTECTION PROGRAM THAT MEETS THE OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE.

SKIN PROTECTION: RUBBER GLOVES.

EYE PROTECTION: GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE EQUIPMENT: NOT REQUIRED UNDER NORMAL USE.

HYGIENIC PRACTICES:
REMOVE AND WASH CONTAMINATED CLOTHING BEFORE RE-USE.
WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES



BOILING RANGE: 210 - 220 DEG. F

VAPOR DENSITY: HEAVIER THAN AIR

ODOR: VERY SLIGHT AMMONIA

ODOR THRESHOLD: NOT ESTABLISHED

APPEARANCE: COLORED

EVAPORATION RATE: SLOWER THAN n-BUTYL ACETATE

SOLUBILITY IN H2O: NOT ESTABLISHED

SPECIFIC GRAVITY: 1.69

FREEZE POINT: NOT ESTABLISHED

pH: BETWEEN 7.0 AND 12.0

VAPOR PRESSURE: NOT ESTABLISHED

VISCOSITY: NOT ESTABLISHED

PHYSICAL STATE: PASTE

WHEN REPORTED, VAPOR PRESSURE OF THIS PRODUCT HAS BEEN CALCULATED THEORETICALLY BASED ON ITS CONSTITUENT MAKEUP AND HAS NOT BEEN DETERMINED EXPERIMENTALLY.

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

SECTION 10 - STABILITY AND REACTIVITY



CONDITIONS TO AVOID: EXCESSIVE HEAT AND FREEZING.

INCOMPATIBILITY: INCOMPATIBLE WITH STRONG BASES AND OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS:
NORMAL DECOMPOSITION PRODUCTS, I.E., COx, NOx.

HAZARDOUS POLYMERIZATION:
HAZARDOUS POLYMERIZATION WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY: STABLE UNDER RECOMMENDED STORAGE CONDITIONS.

SECTION 11 - TOXICOLOGICAL INFORMATION



PRODUCT LD50: NOT ESTABLISHED
PRODUCT LC50: NOT ESTABLISHED

CASRN	CHEMICAL NAME	LD50	LC50	WT %
PHTHALATE ESTER	ESTER BRANCHED & LINEAR (C7&C9)	ORAL RAT: 10 MG/KG		1-5
107-21-1	ETHYLENE GLYCOL	RAT: 4700 MG/KG	RAT: 10876 MG/KG	0.1-1.0
7664-41-7	AMMONIA		RAT: 2000 PPM/4H	<0.010
50-00-0	FORMALDEHYDE		RAT: 203 MG/M3	<0.02
140-88-5	ETHYL ACRYLATE		RAT: 1414 PPM/4H	<0.009
75-07-0	ACETALDEHYDE		RAT: 13300 PPM/4H	<0.002
107-13-1	ACRYLONITRILE	ORAL RAT: 78 MG/KG	RAT: 425 PPM/4H	<0.0003

CARCINOGENICITY:

CAS NO.	CHEMICAL NAME
13463-67-7	TITANIUM DIOXIDE
14808-60-7	SILICA, CRYSTALLINE
50-00-0	FORMALDEHYDE
140-88-5	ETHYL ACRYLATE
75-07-0	ACETALDEHYDE
107-13-1	ACRYLONITRILE
79-06-1	ACRYLAMIDE

CHEMICAL NAME	ACGIH	OSHA	IARC	NTP	WT %
TITANIUM DIOXIDE			CLASSIFICATION NOT POSSIBLE FROM CURRENT DATA.		0.1-1.0
SILICA, CRYSTALLINE	SUSPECTED HUMAN CARCINOGEN.			KNOWN CARCINOGEN.	0.1-1.0
FORMALDEHYDE	SUSPECTED HUMAN CARCINOGEN.	POTENTIAL CANCER HAZARD.	HUMAN CARCINOGEN.	ANTICIPATED CARCINOGEN.	<0.02
ETHYL ACRYLATE			POSSIBLE CARCINOGEN.		<0.009
ACETALDEHYDE	CONFIRMED ANIMAL CARCINOGEN WITH UNKNOWN RELEVANCE TO HUMANS.		POSSIBLE CARCINOGEN.	ANTICIPATED CARCINOGEN.	<0.002
ACRYLONITRILE	CONFIRMED ANIMAL CARCINOGEN WITH UNKNOWN RELEVANCE TO HUMANS.	CANCER HAZARD.	POSSIBLE CARCINOGEN.	ANTICIPATED CARCINOGEN.	<0.0003
ACRYLAMIDE	CONFIRMED ANIMAL CARCINOGEN		PROBABLE CARCINOGEN.	ANTICIPATED CARCINOGEN.	<0.0001

WITH UNKNOWN
RELEVANCE
TO HUMANS.

SIGNIFICANT DATA WITH POSSIBLE RELEVANCE TO HUMANS:
THIS PRODUCT CONTAINS TRACE AMOUNTS OF FREE FORMALDEHYDE. OSHA AND NTP IDENTIFY FORMALDEHYDE AS A POTENTIAL CARCINOGEN. IARC IDENTIFIES FORMALDEHYDE AS A HUMAN CARCINOGEN. FORMALDEHYDE HAS BEEN SHOWN TO CAUSE MUTATIONS IN A VARIETY OF IN-VITRO TEST SYSTEMS, THE SIGNIFICANCE OF WHICH TO HUMANS IS UNKNOWN. IN A TWO-YEAR INHALATION STUDY, RATS SHOWED CARCINOGENIC EFFECTS IN THE RESPIRATORY SYSTEM AT 15 PPM OF FORMALDEHYDE. THERE SHOULD BE MINIMAL RISK WHEN USED WITH VENTILATION ADEQUATE TO KEEP THE ATMOSPHERIC CONCENTRATION OF FORMALDEHYDE BELOW THE RECOMMENDED EXPOSURE LIMITS. MAINTAIN ADEQUATE VENTILATION TO PREVENT EXPOSURE ABOVE CURRENT OSHA / ACGIH EXPOSURE LIMITS. WORKPLACE MONITORING OF THE AIR TO DEFINE FORMALDEHYDE EXPOSURE LEVELS MAY BE NECESSARY.

THIS PRODUCT CONTAINS TRACE AMOUNTS OF ACRYLONITRILE. IT IS EXEMPT FROM THE OSHA ACRYLONITRILE STANDARD 29 CFR 1910.1045, PARAGRAPH (A) (2) (II). ACRYLONITRILE HAS BEEN CLASSIFIED BY IARC AS POSSIBLY CARCINOGENIC TO HUMANS, BY OSHA AS CARCINOGENIC AND BY NTP AS REASONABLY ANTICIPATED TO BE A HUMAN CARCINOGEN.

SECTION 12 - ECOLOGICAL INFORMATION



ECOLOGICAL INFORMATION:
ECOLOGICAL INJURIES ARE NOT KNOWN OR EXPECTED UNDER NORMAL USE.

SECTION 13 - DISPOSAL INFORMATION



DISPOSAL INFORMATION:
DISPOSE OF MATERIAL IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. STATE AND LOCAL REGULATIONS/RESTRICTIONS ARE COMPLEX AND MAY DIFFER FROM FEDERAL REGULATIONS. RESPONSIBILITY FOR PROPER WASTE DISPOSAL IS WITH THE OWNER OF THE WASTE.

EPA WASTE CODE IF DISCARDED (40 CFR SECTION 261): NONE

SECTION 14 - TRANSPORTATION INFORMATION



DOT PROPER SHIPPING NAME: NOT REGULATED

PACKING GROUP: N.A.

DOT TECHNICAL NAME: N.A.

HAZARD SUBCLASS: N.A.

DOT HAZARD CLASS: N.A.

DOT UN/NA NUMBER: N.A.

NOTE:
THE SHIPPING INFORMATION PROVIDED IS APPLICABLE FOR DOMESTIC GROUND TRANSPORT ONLY. DIFFERENT CATEGORIZATION MAY APPLY IF SHIPPED VIA OTHER MODES OF TRANSPORTATION AND/OR TO NON-DOMESTIC DESTINATIONS.

SECTION 15 - REGULATORY INFORMATION



CERCLA - SARA HAZARD CATEGORY:
THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA 'HAZARD CATEGORIES' PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:
IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD

SARA SECTION 313:
THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING

REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME	CAS NUMBER	WT %
ETHYLENE GLYCOL	107-21-1	0.5-1.5

TOXIC SUBSTANCES CONTROL ACT:
ALL INGREDIENTS IN THIS PRODUCT ARE EITHER ON TSCA INVENTORY LIST, OR OTHERWISE EXEMPT.

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:
NONE

U.S. STATE REGULATIONS:

NEW JERSEY RIGHT-TO-KNOW:
THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT:

CHEMICAL NAME	CAS NUMBER	WT %
NON-HAZARDOUS POLYMER	PROPRIETARY	10-30
WATER	7732-18-5	10-30

PENNSYLVANIA RIGHT-TO-KNOW:
THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%:

CHEMICAL NAME	CAS NUMBER	WT %
NON-HAZARDOUS POLYMER	PROPRIETARY	10-30
WATER	7732-18-5	10-30

CALIFORNIA PROPOSITION 65:

WARNING:
THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER	DEFINITION	DATE LISTED	WT %
SILICA, CRYSTALLINE	14808-60-7	CARCINOGENIC.	LISTED: OCTOBER 1, 1988	0.1-1.0
FORMALDEHYDE	50-00-0	CARCINOGENIC.	LISTED: JANUARY 1, 1988	<0.02
ETHYL ACRYLATE	140-88-5	CARCINOGENIC.	LISTED: JULY 1, 1989	<0.009
ACETALDEHYDE	75-07-0	CARCINOGENIC.	LISTED: APRIL 1, 1988	<0.002
ACRYLONITRILE	107-13-1	CARCINOGENIC.	LISTED: JULY 1, 1987	<0.0003
ACRYLAMIDE	79-06-1	CARCINOGENIC.	LISTED: JANUARY 1, 1990	<0.0001

WARNING:
THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: NONE

SECTION 16 - OTHER INFORMATION



HMIS RATINGS:
HEALTH 1
FLAMMABILITY 1
REACTIVITY 0
PERSONAL PROTECTION B

VOLATILE ORGANIC COMPOUNDS:
GR/LTR: 39.1

LB/GAL: 0.3
WT %: 1.700

REASON FOR REVISION: PERIODIC UPDATE

LEGEND:

- N.A. - NOT APPLICABLE
- N.E. - NOT ESTABLISHED
- N.D. - NOT DETERMINED
- VOC - VOLATILE ORGANIC COMPOUND
- PEL - PERMISSIBLE EXPOSURE LIMIT
- TLV - THRESHOLD LIMIT VALUE
- STEL - SHORT TERM EXPOSURE LIMIT
- LD50 - LETHAL DOSE 50
- F - DEGREE FAHRENHEIT
- MSDS - MATERIAL SAFETY DATA SHEET
- ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
- SARA - SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986
- NJRTK - NEW JERSEY RIGHT-TO-KNOW LAW
- OSHA - OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
- HMIS - HAZARDOUS MATERIALS IDENTIFICATION SYSTEM
- NTP - NATIONAL TOXICOLOGY PROGRAM
- CEIL - CEILING EXPOSURE LIMIT
- LC50 - LETHAL CONCENTRATION 50
- C - DEGREE CELSIUS
- CASRN - THE CHEMICAL ABSTRACTS SERVICE REGISTRY NUMBER

DAP BELIEVES THE DATA AND STATEMENTS CONTAINED HEREIN ARE ACCURATE AS OF THE DATE HEREOF. THEY ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. SINCE THIS DOCUMENT IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE USE AND PRECAUTIONARY HANDLING OF THE REFERENCED PRODUCT BY A PROPERLY TRAINED PERSON, IT IS THEREFORE THE RESPONSIBILITY OF THE USER TO (I) REVIEW THE RECOMMENDATIONS WITH DUE CONSIDERATION FOR THE SPECIFIC CONTEXT OF THE INTENDED USE AND (II) DETERMINE IF THEY ARE APPROPRIATE.