

H1BAK1259 Balkamp 30 Weight Bar & Chain Oil 765-1386, 765-1424

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 3-22-95 Revision Date: none

Balkamp 30 Weight Bar & Chain Oil 765-1386, 765-1424

Code: SPE

Page: 1

=====

Section 1 - Product and Company Identification

PRODUCT NAME: Balkamp 30 Weight Bar & Chain Oil 765-1386, 765-1424

MANUFACTURER'S NAME:

EMERGENCY TELEPHONE NUMBER

Spectrum Acquisitions, Inc.
Fulghum Street
Hornsby, TN 38044

(901)658-9050

MISCELLANEOUS INFORMATION

=====

Section 2 - Hazardous Ingredients

NAME	CAS#	APP %	REG AGEN	EXP LIMIT
Base Oil	64742-52-5	90-100	OSHA/ACGIH	5mg/m3 Mist
Tackifier	64742-52-5	0.25-5.0	OSHA/ACGIH	5mg/m3 Mist

HMIS/NFPA CODE: Health-1, Flammability-1, Reactivity-0
Protective Equipment C, D, or H

See section section 3, Chronic effects, for potential over-exposure hazard.

=====

Section 3 - Hazards Indentification

INHALATION: Inhalation of fumes may result in dizziness, headache and respiratory irritation.

EYE CONTACT: Contact with eyes may cause minimal irritation.

SKIN CONTACT: Mild irritation may occur with prolonged or repeated contact.

INGESTION: Slightly toxic. Pulmonary aspiration hazard if vomiting occurs.

TLV: 5mg/m3 as mist. ACGIH 1984-85

CHRONIC EFFECTS: Product has a low order of acute oral toxicity.

Ingredients of this product are NOT listed as potential carcinogens in N.T.P. ANNUAL REPORT ON CARCINOGENS, I.A.R.C. MONOGRAPHS, or by O.S.H.A. HCS (g) (2) (vii).

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 3-22-95 Revision Date: none

Balkamp 30 Weight Bar & Chain Oil 765-1386, 765-1424

Code: SPE

Page: 2

=====

Section 4 - First Aid Measures

SKIN: Wash skin with soap and warm water. Wash clothing before re-use.

EYE: If splashed into eyes flush with clear water for five(5) minutes.

INHALATION: If overcome by fumes remove from exposure immediately.

ORAL: If ingested, do not induce vomiting. Call a physician.

=====

Section 5 - Firefighting Measures

FLASH POINT : 425F

FIRE POINT : 450F

EXTINGUISHING MEDIA(s): Water fog, chemical foam, dry chemical powder, CO₂.

SPECIAL FIREFIGHTING PROCEDURES: Cool exposed containers with water spray.
Avoid breathing fumes.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Pressure increase in over heated closed containers. Cool containers with water spray.

=====

Section 6 - Environmental Release Measures

SPILL PROCEDURES: Remove ignition sources. Recover liquid. Add absorbent to spill area. Ventilate confined spaces. Advise authorities if product enters sewers, etc.

=====

Section 7 - Handling and Storage

HANDLING AND

STORAGE PRECAUTIONS: Keep containers closed when not in use. Do not handle or store near heat or flames. Use chemical resistant gloves and apron.

=====

Section 8 - Exposure Controls/Personal Protection

VENTILATION PROCEDURE: Ventilate as needed to comply with exposure limit.

GLOVES PROTECTION: Use impervious gloves to avoid repeated/prolonged skin contact.

EYE PROTECTION: Use goggles/face shield to avoid eye contact.

WORK/HYGIENIC PRACTICES: If clothing becomes contaminated, change to fresh clean clothing. Do not wear until thoroughly laundered.

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 3-22-95

Revision Date: none

Balkamp 30 Weight Bar & Chain Oil 765-1386, 765-1424

Code: SPE

Page: 3

=====

Section 9 - Physical and Chemical Properties

VAPOR PRESSURE(mmHg) at 20C: <1
SPECIFIC GRAVITY AT 60F : .9194
WATER SOLUBILITY : Negligible
BOILING POINT : Wide range
VAPOR DENSITY(Air=1) : >1
EVAPORATION RATE(BUAC=1) : <1
ODOR : Mild hydrocarbon odor
APPEARANCE : Red colored liquid
VISCOSITY AT 100C CST : 10.3

=====

Section 10 - Stability and Reactivity

STABILITY : Stable
INCOMPATIBILITY : Avoid strong oxidants.
POLYMERIZATION : Will not occur.
THERMAL DECOMPOSITION: Partial burning produces fumes, smoke and carbon monoxide.

=====

Section 11 - Toxicological Information

Not available.

Section 12 - Ecological Information

Not available.

Section 13 - Disposal Considerations

WASTE DISPOSAL: Assure conformity with applicable disposal regulations.
Dispose of absorbed material at approved waste site.

Section 14 - Transport Information

CHEMICAL FAMILY: Petroleum Lubricating Oil
NOTE: Petroleum lubricating oils with a flashpoint above 200F, are not regulated by D.O.T. standards.

Section 15 - Regulatory Information

Not available.

MATERIAL SAFETY DATA SHEET

Effective Date: 3-22-95 Revision Date: none
Balkamp 30 Weight Bar & Chain Oil 765-1386, 765-1424
Code: SPE Page: 4

Section 16 - Other Information

FOR CHEMICAL EMERGENCY SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT Call Chemtrec

Day or Night ***800-424-9300*** Toll-Free in the Continental U.S. Add long-distance access number if required 483-7616 in District of Columbia for calls originating outside the continental U.S.:

202-483-7617-Washington, DC, Collect (All calls are recorded)

The Data presented herein is based upon tests and information which we believe to be reliable. However, users should make their own investigations to determine the suitability of the information for their particular purpose.