

Material Safety Data Sheet



1. Chemical product and company identification

Product name	PREMIUM DIESEL FUELS
MSDS #	12638
Historic MSDS #:	None.
Code	12638
Product use	Fuel.
Synonyms	Amoco Premier Diesel Fuel, Amoco PowerBlend Diesel Fuel, High Sulfur BP Diesel Supreme, Ultra Low Sulfur BP Diesel Supreme
Supplier	BP Products North America Inc. 150 West Warrenville Road Naperville, Illinois 60563-8460 USA
EMERGENCY HEALTH INFORMATION:	1 (800) 447-8735 Outside the US: +1 703-527-3887 (CHEMTREC)
EMERGENCY SPILL INFORMATION:	1 (800) 424-9300 CHEMTREC (USA)
OTHER PRODUCT INFORMATION	1 (866) 4 BP - MSDS (866-427-6737 Toll Free - North America) email: bpcares@bp.com

2. Composition/information on ingredients

Ingredient name	CAS #	% by weight
Petroleum distillates	68476-34-6	100
Contains: naphthalene	91-20-3	1 - 3

May also contain small quantities of proprietary performance additives.

3. Hazards identification

Physical state	Liquid.
Color	Colorless. to Various colors. (may be dyed Red., Light Green. ,Yellow.)
Emergency overview	WARNING! COMBUSTIBLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. HARMFUL IF SWALLOWED. ASPIRATION HAZARD. HARMFUL OR FATAL IF LIQUID IS ASPIRATED INTO LUNGS. CAUSES SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. INHALATION CAUSES HEADACHES, DIZZINESS, DROWSINESS, AND NAUSEA, AND MAY LEAD TO UNCONSCIOUSNESS.

Product name PREMIUM DIESEL FUELS

Product code 12638

Page: 1/7

Version 1 Date of issue 08/29/2006.

Format US-COMP

Language ENGLISH.

Build 4.2.8

(ENGLISH)

Do not ingest. If ingested do not induce vomiting. Avoid contact with eyes, skin and clothing. Do not breathe vapor or mist. Keep away from heat, sparks and flame. Keep container closed. Use with adequate ventilation. Use only with adequate ventilation. Wash thoroughly after handling.

Routes of entry

Dermal contact. Eye contact. Inhalation. Ingestion.

Potential health effects

Eyes

Slightly irritating to the eyes.

Skin

Causes skin irritation.

Inhalation

May cause respiratory tract irritation. Inhalation causes headaches, dizziness, drowsiness, and nausea, and may lead to unconsciousness. See toxicological Information (section 11).

Ingestion

Harmful if swallowed. Aspiration hazard if swallowed -- harmful or fatal if liquid is aspirated into lungs. See toxicological Information (section 11).

Medical conditions aggravated by over-exposure

None identified.

See toxicological Information (section 11).

4. First aid measures

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

Skin contact

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion

If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed- can enter lungs and cause damage. Get medical attention immediately.

5. Fire-fighting measures

Flammability of the product

Combustible liquid.

Flash point

>38 °C (Closed cup) Pensky-Martens.

Explosion limits

Lower: 0.6 %
Upper: 7.5 %

Products of combustion

These products are carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide).

Unusual fire/explosion hazards

Combustible liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.

Fire-fighting media and instructions

In case of fire, use water fog, foam, dry chemicals, or carbon dioxide. DO NOT FIGHT FIRE WHEN IT REACHES MATERIAL. Withdraw from fire and let it burn. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. First move people out of line-of-sight of the scene and away from windows.

Protective clothing (fire)

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Special remarks on fire hazards

Do not use water jet.

6. Accidental release measures

Personal precautions

Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures"). Do not touch or walk through spilled material.

Environmental precautions and clean-up methods

If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilled material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information.

Personal protection in case of a large spill

Splash goggles. Chemical resistant protective suit. Vapor respirator. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

CAUTION: The protection provided by air-purifying respirators is limited. Use a positive pressure air-supplied respirator if there is any potential for an uncontrolled release, if exposure levels are not known, or if concentrations exceed the protection limits of air-purifying respirator.

7. Handling and storage

Handling

Aspiration hazard if swallowed- can enter lungs and cause damage. Never siphon by mouth. Do not ingest. If ingested do not induce vomiting. When using do not eat, drink or smoke. Avoid contact with skin and clothing. Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Use only with adequate ventilation. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Wash thoroughly after handling. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards.

Storage

Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Store and use only in equipment/containers designed for use with this product.

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name

Petroleum distillates

Contains:
naphthalene

Occupational exposure limits

ACGIH TLV (United States, 1/2006). Skin

TWA: 100 mg/m³ 8 hour(s). Form: Total hydrocarbons

ACGIH TLV (United States, 1/2006).

STEL: 79 mg/m³ 15 minute(s).

STEL: 15 ppm 15 minute(s).

TWA: 52 mg/m³ 8 hour(s).

TWA: 10 ppm 8 hour(s).

OSHA PEL (United States, 8/1997).

TWA: 50 mg/m³ 8 hour(s).

TWA: 10 ppm 8 hour(s).

May also contain small quantities of proprietary performance additives.

Product name PREMIUM DIESEL FUELS

Product code 12638

Page: 3/7

Version 1 **Date of issue** 08/29/2006.

Format US-COMP

Language ENGLISH.

Build 4.2.8

(ENGLISH)

Control Measures	Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.
Personal protection	
Eyes	Avoid contact with eyes. Safety glasses with side shields.
Skin and body	Avoid contact with skin and clothing. Wear suitable protective clothing.
Respiratory	Use only with adequate ventilation Do not breathe vapor or mist. If ventilation is inadequate, use a NIOSH certified respirator with an organic vapor cartridge and P95 particulate filter. CAUTION: The protection provided by air-purifying respirators is limited. Use a positive pressure air-supplied respirator if there is any potential for an uncontrolled release, if exposure levels are not known, or if concentrations exceed the protection limits of air-purifying respirator.
Hands	Wear gloves that cannot be penetrated by chemicals or oil. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions. Consult your supervisor or S.O.P. for special handling directions

Consult local authorities for acceptable exposure limits.

9. Physical and chemical properties

Physical state	Liquid.
Odor	Petroleum
Color	Colorless. to Various colors. (may be dyed Red., Light Green. ,Yellow.)
Heat of combustion	Not available.
Specific gravity	<1 (Water = 1)
Density	820 to 875 kg/m ³ (0.82 to 0.875 g/cm ³)
Solubility	negligible <0.1%
Viscosity	Kinematic: 1.7 to 4.1 mm ² /s (1.7 to 4.1 cSt) at 40°C

10. Stability and reactivity

Stability and reactivity	Stable under recommended storage and handling conditions (See Section: "Handling and storage").
Conditions to avoid	Keep away from heat, sparks and flame. Avoid all possible sources of ignition (spark or flame).
Incompatibility with various substances	Reactive or incompatible with the following materials: oxidizing materials, acids and alkalis. halogenated compounds.
Hazardous decomposition products	These products are carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide)
Hazardous polymerization	Will not occur.

Product name	PREMIUM DIESEL FUELS	Product code	12638	Page: 4/7
Version 1	Date of issue 08/29/2006.	Format US-COMP	Language ENGLISH.	
		Build 4.2.8	(ENGLISH)	

11. Toxicological information

Acute toxicity

Aspiration of this product into the lungs can cause chemical pneumonia and can be fatal. Aspiration into the lungs can occur while vomiting after ingestion of this product. Do not siphon by mouth.

Chronic toxicity

Carcinogenic effects

Contains material which may cause cancer.
Risk of cancer depends on duration and level of exposure.
Classified 2B (Possible for human.) by IARC: [naphthalene]
Classified 2 (Reasonably Anticipated To Be Human Carcinogens.) by NTP: [naphthalene]

Other chronic toxicity data

Middle distillate: From skin-painting studies of petroleum distillates of similar composition and distillate range, it has been shown that these types of materials often possess weak carcinogenic activity in laboratory animals. In these tests, the material is painted on the shaved backs of mice twice a week for their lifetime. The material is not washed off between applications. Therefore, there may be a potential risk of skin cancer from prolonged or repeated skin contact with this product in the absence of good personal hygiene. This particular product has not been tested for carcinogenic activity, but we have chosen to be cautious in light of the findings with other distillate streams.

Occasional skin contact with this product is not expected to have serious effects, but good personal hygiene should be practiced and repeated skin contact avoided. This product can also be expected to produce skin irritation upon prolonged or repeated skin contact. Personal hygiene measures taken to prevent skin irritation are expected to be adequate to prevent risk of skin cancer.

Diesel exhaust particulates have been classified by the National Toxicological Program (NTP) to be a reasonably anticipated human carcinogen. Exposure should be minimized to reduce potential risk.

Naphthalene has been reported to cause developmental toxicity in mice after oral exposure to relatively high dose levels, but developmental toxicity was not observed in NTP (National Toxicology Program) sponsored studies in rats and rabbits. Ingestion or inhalation of naphthalene can result in hemolysis and other blood abnormalities, and individuals (and infants) deficient in glucose-6-phosphate dehydrogenase may be especially susceptible to these effects. Inhalation of naphthalene may cause headache and nausea. Airborne exposure can result in eye irritation. Naphthalene exposure has been associated with cataracts in animals and humans.

12. Ecological information

Ecotoxicity

Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Mobility

Spillages may penetrate the soil causing ground water contamination.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

13. Disposal considerations

Waste information




Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and national regulations.

Consult your local or regional authorities.

Product name	PREMIUM DIESEL FUELS	Product code	12638	Page: 5/7
Version 1	Date of issue 08/29/2006.	Format US-COMP	Language ENGLISH.	
		Build 4.2.8	(ENGLISH)	

14. Transport information

International transport regulations

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	NA1993	Diesel Fuel	Combustible liquid.	III	-----	Reportable quantity 100 lbs. (45.36 kg)
TDG Classification	UN1202	Gas oil	3	III		Not determined.
IMDG Classification	UN1202	Gas oil	3	III		Not determined.
IATA Classification	UN1202	Gas oil	3	III		Not determined.

15. Regulatory information

U.S. Federal regulations

US INVENTORY (TSCA): In compliance.

TSCA 12(b) one-time export notification:: naphthalene

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: PREMIUM DIESEL FUELS: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard

SARA 313

Form R - Reporting requirements

Supplier notification

Product name

naphthalene

CAS number

91-20-3

Concentration

1 - 3

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):: o-Xylene: 1000 lbs. (453.6 kg); naphthalene: 100 lbs. (45.36 kg); xylene: 100 lbs. (45.36 kg); Ethylbenzene: 1000 lbs. (453.6 kg); Xylene: 100 lbs. (45.36 kg); Cumene: 5000 lbs. (2268 kg); xylene: 100 lbs. (45.36 kg);

State regulations

Massachusetts RTK: Straight run kerosine; 1,2,4-Trimethylbenzene

New Jersey: Straight run kerosine; 1,2,4-Trimethylbenzene

Pennsylvania RTK: Straight run kerosine (generic environmental hazard); 1,2,4-Trimethylbenzene (environmental hazard, generic environmental hazard)

WARNING: This product contains a chemical known to the State of California to cause cancer.
; Ethylbenzene; naphthalene

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Toluene

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Benzene

Prop 65 chemicals will result under certain conditions from the use of this material. For example, burning fuels produces combustion products including diesel exhaust, a Prop 65 carcinogen, and carbon monoxide, a Prop 65 reproductive toxin.

Product name PREMIUM DIESEL FUELS

Product code 12638

Page: 6/7

Version 1

Date of issue 08/29/2006.

Format US-COMP

Language ENGLISH.

Build 4.2.8

(ENGLISH)

Inventories

AUSTRALIAN INVENTORY (AICS): Not determined.

CANADA INVENTORY (DSL): In compliance.

CHINA INVENTORY (IECS): Not determined.

EC INVENTORY (EINECS/ELINCS): Not determined.

JAPAN INVENTORY (ENCS): Not determined.

KOREA INVENTORY (ECL): Not determined.

PHILIPPINE INVENTORY (PICCS): Not determined.

16. Other information

Label requirements

WARNING!

COMBUSTIBLE LIQUID AND VAPOR.

VAPOR MAY CAUSE FLASH FIRE.

HARMFUL IF SWALLOWED.

ASPIRATION HAZARD.

HARMFUL OR FATAL IF LIQUID IS ASPIRATED INTO LUNGS.

CAUSES SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

INHALATION CAUSES HEADACHES, DIZZINESS, DROWSINESS, AND NAUSEA, AND MAY LEAD TO UNCONSCIOUSNESS.

HMIS® Rating :

Health 0
Flammability 2
Physical Hazard 0
Personal protection X

National Fire
Protection
Association
(U.S.A.)



History

Date of issue

08/29/2006.

Date of previous issue

No Previous Validation.

Prepared by

Product Stewardship

Notice to reader

NOTICE : This Material Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. We are not responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product.

Product name PREMIUM DIESEL FUELS

Product code 12638

Page: 7/7

Version 1

Date of issue 08/29/2006.

Format US-COMP

Language ENGLISH.

Build 4.2.8

(ENGLISH)