

U. S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved OMB NO. 1218-0072 MSDS 9-D

Note: Blank spaces are not permitted. If any item is not applicable or not applicable,
or no information is available, the space must be marked not applicable.

Page No. _____

Date 07/19/88

Emergency Telephone Number

(608) 879-0511 X4636

Telephone Number for Information

சென்னை

Date Prepared

07/19/88

Signature of Preparer (optional)

JUL 03 1989
LAKESHORE STATE HOSPITAL
ENGINEERING DEPARTMENT

OSTIA PEL

ACEIH TLV

Other Links

Record needed

% (approx)

Although none of the ingredients are classified as hazardous materials by OSHA terms, Ethylene Glycol has an

LD₅₀ of 6,000 mg/kg.

CAS #107-21-1

Boiling Point	212°F	Specific Gravity (H ₂ O = 1)	1.08
Vapor Pressure (mm Hg)	0.3	Melting Point	None
Vapor Density (AIR = 1)	1.84	Evaporation Rate (Water = 1)	1.0

Solubility in Water Complete

Dark liquid, mild odor

Flash Point	240°F	Flammable Limits	N/A	N/A	LEL	N/A	UEL
-------------	-------	------------------	-----	-----	-----	-----	-----

Extinguishing Media: NA

De v Fighting Procedures

Internal Fire and Explosion Hazards

N/A

Production	Locality
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

0944 474 0-4440

Section V -- Reactivity Data

Stability	Unstable		Conditions to Avoid	N/A
	Stable	X		N/A

Incompatibility (Reagents to Avoid) N/A

Hazardous Decomposition or Byproducts

Hazardous Polymerization	May Occur		Conditions to Avoid	N/A
	Will Not Occur	X		N/A

Section VI -- Health Hazard Data

Route(s) of Entry: Inhalation? NO Skin? NO Ingestion? NO

Health Hazards (Acute and Chronic) Is not considered a primary irritant. Black and Red: Non-eye irritant. Blue, purple, brown and green are considered to be eye irritants. - CFR 1500.42

Carcinogenicity: NO NTP? NO IARC Monographs? NO OSHA Regulated? NO

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures
 Eye contact: Blue, purple, brown and green - Flush with plenty of water. Call a physician. Skin Contact: Wash with soap and water.

Section VII -- Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Flush with water. Absorb with towels or cloths.

Waste Disposal Method Flush with water. Adhere to state and local regulations.

Precautions to Be Taken in Handling and Storing Normal

Other Precautions Because blue, purple, brown and green stamp pad inks could be irritating to the eyes, it would be good practice to keep out of the reach of small children.

Section VIII -- Control Measures

Engineering Protection Other Precautions N/A

Ventilation	Local Exhaust	N/A	Special	N/A
	Mechanical (General)	N/A	Other	N/A

Protective Gloves N/A Eye Protection If desired

Other Protective Clothing or Equipment N/A

Work/Hygiene Practices Wash Hands

NOTICE FROM DENNISON MFG. CO.

To the best of our knowledge this information is accurate; however, we do not warrant or guarantee its accuracy and cannot be liable for any damages, consequential or actual which might result from any reliance thereon.