

SHERWIN WILLIAMS SPECIALTY DIV -- CWA1211 SATIN BLACK POLYURETHANE GLOSS ENAMEL --

=====

MSDS Safety Information

=====

FSC: 8010
MSDS Date: 11/01/1995
MSDS Num: CJBFC
LIIN: 00F057057
Tech Review: 12/09/2001
Product ID: CWA1211 SATIN BLACK POLYURETHANE GLOSS ENAMEL
Responsible Party
Cage: 54626
Name: SHERWIN WILLIAMS CO THE SPECIALTY DIV
Address: 31500 SOLON ROAD
City: SOLON OH 44139-5000 US
Info Phone Number: 800-777-2966/800-247-3266
Emergency Phone Number: 800-777-2966/216-292-7400
Review Ind: N

=====

Preparer Co. when other than Responsible Party Co.

=====

Cage: 54626
Assigned Ind: N
Name: SHERWIN WILLIAMS COMPANY
Address: 101 PROSPECT AVE NW
City: CLEVELAND OH 44115

=====

Contractor Summary

=====

Cage: 54626
Name: SHERWIN WILLIAMS COMPANY
Address: 101 PROSPECT AVE NW
City: CLEVELAND OH 44115 US
Phone: 216-566-2902
Cage: 09800
Name: SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.
Address: 26300 FARGO AVENUE
City: BEDFORD HEIGHTS OH 44146 US
Phone: 216-292-7400 OR 216-595-8634

=====

Ingredients

=====

Cas: 14807-96-6
RTECS #: WW2710000
Name: TALC (POWDER), (ASBESTOS FREE), TALCUM; HYDROUS MAGNESIUM SILICATE
(IARC - GROUP 3) *98-3*
% by Wt: 2
OSHA PEL: 2 MG/CUM (RESP DUST)
ACGIH TLV: 2 MG/CUM (RESP DUST)
Ozone Depleting Chemical: N

Cas: 471-34-1
RTECS #: FF9335000
Name: CARBONIC ACID, CALCIUM SALT (1:1), CALCIUM CARBONATE, DURAMITE
98-3
% by Wt: 5
Other REC Limits: 10 MG/CUM (DUST)
Ozone Depleting Chemical: N

Cas: 74-98-6

RTECS #: TX2275000
Name: PROPANE (DIMETHYLMETHANE) *98-3*
% by Wt: 15
Other REC Limits: 1800 MG/CUM
OSHA PEL: 1000 PPM
ACGIH TLV: SIMPLE ASPHYXIA
Ozone Depleting Chemical: N

Cas: 106-97-8
RTECS #: EJ4200000
Name: BUTANE, N-BUTANE *98-3*
% by Wt: 14
Other REC Limits: 800 PPM
OSHA PEL: 800 PPM
ACGIH TLV: 1900 MG/CUM
Ozone Depleting Chemical: N

Cas: 108-88-3
RTECS #: XS5250000
Name: TOLUENE, TOLUOL (IARC CARC- GROUP 3) *98-3*
% by Wt: 10
Other REC Limits: 375 MG/CUM
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS
Ozone Depleting Chemical: N

Cas: 100-41-4
RTECS #: DA0700000
Name: ETHYL BENZENE *98-3*
% by Wt: 2
Other REC Limits: 100 PPM
OSHA PEL: 435 MG/CUM
ACGIH TLV: 434 MG/CUM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS
Ozone Depleting Chemical: N

Cas: 1330-20-7
RTECS #: ZE2100000
Name: XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *98-3*
% by Wt: 14
Other REC Limits: 100 PPM
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM, SKIN
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS
Ozone Depleting Chemical: N

Cas: 67-64-1
RTECS #: AL3150000
Name: ACETONE; DIMETHYL KETONE; 2-PROPANONE *98-3*
% by Wt: 21
OSHA PEL: 2400 MG/CUM
ACGIH TLV: 750 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS
Ozone Depleting Chemical: N
=====

Health Hazards Data

Route Of Entry Inds - Inhalation: YES

Skin: NO

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: INHALATION: IRRITATION OF EYES, SKIN & RESPIRATORY SYSTEM. NERVOUS SYSTEM DEPRESSION/POSSIBLY DEATH. PROLONGED OVEREXPOSURE TO SOLVENT MAY CAUSE ADVERSE EFFECTS TO THE LIVER, URINARY, CARDIOVASCULAR & REPRODUCTIVE SYSTEMS. REPEATED/PROLONGED OVEREXPOSURE MAY CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

Explanation Of Carcinogenicity: NONE

Signs And Symptoms Of Overexposure: IRRITATION, UNCONSCIOUSNESS, HEADACHE, DIZZINESS, NAUSEA, LOSS OF COORDINATION, REDNESS, ITCHING, BURNING SENSATION

Medical Cond Aggravated By Exposure: NONE

First Aid: INHALATION: REMOVE FROM EXPOSURE. SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Handling and Disposal

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE & REMOVE W/INERT ABSORBENT.

Waste Disposal Methods: WASTE MUST BE TESTED FOR IGNITABILITY TO DETERMINE THE APPLICABLE EPA HAZARDOUS WASTE NUMBERS. DON'T INCINERATE. DEPRESSURIZE CONTAINER. DISPOSE OF IAW/LOCAL, STATE & FEDERAL REGULATIONS.

Handling And Storage Precautions: KEEP FROM HEAT/SPARKS/OPEN FLAME. USE APPROVED BONDING/GROUNDING PROCEDURES. DON'T PUNCTURE/INCINERATE/EXPOSE TO TEMPS >120F. AVOID BREATHING VAPORS.

Other Precautions: KEEP OUT OF REACH OF CHILDREN. DURING USE & UNTIL ALL VAPORS ARE GONE; KEEP AREA VENTILATED. DON'T TAKE INTERNALLY. HEAT FROM SUNLIGHT, RADIATORS, STOVES, HOT WATER & OTHER HEAT SOURCES MAY CAUSE CONTAINERS TO BURST. AVOID SKIN/EYE CONTACT.

Fire and Explosion Hazard Information

Flash Point Method: PMCC

Flash Point Text: <0F

Lower Limits: 0.7

Upper Limits: 12.8

Extinguishing Media: CO2, DRY CHEMICAL, FOAM

Fire Fighting Procedures: USE FULL PROTECTIVE EQUIPMENT W/SCBA. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERRED. WATER MAY BE USED TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard: ISOLATE FROM IGNITION SOURCES/HOT SURFACES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY ACCUMULATE READILY & MAY IGNITE EXPLOSIVELY.

Control Measures

Respiratory Protection: IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA. IF SANDING/ABRADING THE DRIED FILM, WEAR NIOSH/MSHA DUST/MIST RESPIRATOR.

Ventilation: LOCAL EXHAUST: PREFERABLE. GENERAL EXHAUST: TO MAINTAIN <APPLICABLE EXPOSURE LIMITS. OSHA STANDARDS.

Protective Gloves: CHEMICAL RESISTANT

Eye Protection: REQUIRED

Other Protective Equipment: SAFETY SPECTACLES W/UNPERFORATED SIDESHIELDS.

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE. WASH HANDS AFTER USING. DON'T SMOKE.

Supplemental Safety and Health: INTENTIONAL MISUSE BY DELIBERATELY
CONCENTRATING & INHALING THE CONTENTS CAN BE HARMFUL/FATAL.

=====

Physical/Chemical Properties

=====

B.P. Text: <0-292F

Vapor Density: >1

Evaporation Rate & Reference: FASTER THAN ETHER

=====

Reactivity Data

=====

Stability Indicator: YES

Stability Condition To Avoid: HEAT, ELECTRICAL EQUIPMENT, SPARKS, OPEN
FLAME, HOT SURFACES

Hazardous Decomposition Products: BY FIRE: CO₂, CO

Hazardous Polymerization Indicator: NO

=====

Toxicological Information

=====

Ecological Information

=====

MSDS Transport Information

=====

Regulatory Information

=====

Other Information

=====

Other Information: VOLATILE ORGANIC CONTENT: 78%/WT

=====

HAZCOM Label

=====

Product ID: CWA1211 SATIN BLACK POLYURETHANE GLOSS ENAMEL

Cage: 54626

Company Name: SHERWIN WILLIAMS COMPANY

Street: 101 PROSPECT AVE NW

City: CLEVELAND OH

Zipcode: 44115 US

Health Emergency Phone: 800-777-2966/216-292-7400

Date Of Label Review: 10/12/1999

Hazard And Precautions: INHALATION: IRRITATION OF EYES, SKIN & RESPIRATORY
SYSTEM. NERVOUS SYSTEM DEPRESSION/POSSIBLY DEATH. PROLONGED OVEREXPOSURE
TO SOLVENT MAY CAUSE ADVERSE EFFECTS TO THE LIVER, URINARY,
CARDIOVASCULAR & REPRODUCTIVE SYSTEMS. REPEATED/PROLONGED OVEREXPOSURE
MAY CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

=====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of
Defense. The United States of America in no manner whatsoever expressly
or implied warrants, states, or intends said information to have any
application, use or viability by or to any person or persons outside the
Department of Defense nor any person or persons contracting with any

instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.