

# TEXWIPE CO -- TX284, ANTISTATIC SCREEN CLEANER (NON-AEROS -- 6850-00N033184

## ===== Product Identification =====

Product ID:TX284, ANTISTATIC SCREEN CLEANER (NON-AEROS

MSDS Date:05/01/1987

FSC:6850

NIIN:00N033184

MSDS Number: BPLWK

=== Responsible Party ===

Company Name:TEXWIPE CO

Address:650 EAST CRESCENT AVE

City:UPPER SADDLE RIVER

State:NJ

ZIP:07458

Country:US

Info Phone Num:201-327-9100

Emergency Phone Num:201-327-9100

Preparer's Name:SCOTT FAHY

CAGE:21994

=== Contractor Identification ===

Company Name:TEXWIPE CO

Address:650 E CRESENT AVE

Box:308

City:UPPER SADDLE RIVER

State:NJ

ZIP:07458-1827

Country:US

Phone:201-327-5577

CAGE:21994

## ===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III). VP:33 @ 68F. VAP DENS:2.1.

LEL:2%. UEL:12.7%.

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 29%

OSHA PEL:400 PPM;500 PPM STEL

ACGIH TLV:400 PPM;500 PPM STEL

Ingred Name:WATER; (DEIONIZED WATER)

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 70.5%

Ingred Name:N-ALKYL DIMETHYLBENZYL AMMONIUM CHLORIDE; (N-ALKYL DIMETHYLBENZYL)

CAS:68391-01-5

Fraction by Wt: <1%

Ingred Name:ETHYLBENZENE AMMONIUM CHLORIDE; (ETHYLBENZYL AMMONIUM CHLORIDES)

CAS:68956-79-6

Fraction by Wt: <1%

Ingred Name:AMMONIUM HYDROXIDE (SARA III)

CAS:1336-21-6

RTECS #:BQ9625000

Fraction by Wt: <1%

ACGIH TLV:50 PPM (MFR)

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

## ===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MILD IRRIT TO NOSE & THROAT. PRLNG

EXPOS ABOVE TLV MAY CAUSE NARCOS, NAUS & HDCH. EYE CONT WILL CAUSE

LOC IRRIT & BURNING SENSATIONS, W/POSS EYE DMG. SKIN CONT WILL

CAUSE STINGING & BURNING SENSATION W/DEFAT & POSS IRRIT FROM PRLNG

CONT. THIS ALCOHOL IS CONSIDERED POISON, W/INGEST OF 20 ML CAUSING

(EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ:SERIOUS ILLNESS. SINGLE LETHAL ORAL

DOSE FOR AN ADULT IS APPROXIMATELY 250 ML.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/LG AMTS OF WATER FOR AT LST 15 MINS WHILE HOLDING EYELIDS OPEN. GET MD IF IRRIT PERSISTS. SKIN:FLUSH W/WATER. INHAL:REMOVE TO FRESH AIR. RESTORE &/OR SUPPORT BRTHG AS NEEDED. GIVE O\*2 IF B RTHG IS DFCLT. INGEST:GET PROMPT MED HELP. GIVE WATER TO DRINK TO DILUTE. IF MED HELP NOT READILY AVAIL, AMT INGESTED WAS LG & VICTIM IS CONSCIOUS & ALERT, INDUCE VOMIT.

===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:102F,39C  
Lower Limits:SEE ING 1  
Upper Limits:SEE ING 1  
Extinguishing Media:CO\*2, DRY CHEMICAL, ALCOHOL TYPE FOAM.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. OSHA CLASS IB FLAMMABLE LIQUID.  
Unusual Fire/Explosion Hazard:THIS PRODUCT CONTAINS ISOPROPYL ALCOHOL AS ITS PRIMARY SOLV. ALTHOUGH THE PROD CONTAINS A HIGH PERCENTAGE OF WATER, ENOUGH VAP ARE PRESENT TO PROPAGATE FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN-UP PERSONNEL NEED PROTECTION AGAINST LIQUID CONTACT & VAPOR INHALATION. ABSORB SMALL SPILLS W/PAPER TOWELS, EVAPORATE FLAMMABLE ALCOHOL IN EXHAUST HOOD & BURN DRY PAPER.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID INHALATION OF VAPORS & REPEATED OR PROLONGED CONTACT OF LIQUID W/SKIN OR CLOTHING. DO NOT TAKE INTERNALLY.  
Other Precautions:REPLACEMENT & PERIODIC MEDICAL EXAMS SHOULD EMPHASIZE SKIN, SINUSES & RESPIRATORY SYSTEM. ALUMINUM CONTAINERS ARE NOT TO BE USED FOR ISOPROPYL ALCOHOL. DO NOT USE NEAR SPARKS OR OPEN FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN.  
Ventilation:PROVIDE GEN EXHST VENT (EXPLO-PROOF) TO MEET TLV REQUIREMENTS. EXHST HOODS SHLD MAINTAIN 100 LIN FACE VELOCITY.  
Protective Gloves:IMPERVIOUS GLOVES.  
Eye Protection:CHEMICAL WORKERS GOGGLES.  
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.  
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. DO NOT SMOKE OR EAT IN AREAS OF STORAGE OR USE.  
Supplemental Safety and Health  
MATLS TO AVOID:COMBINATION, POTASSIUM TERT-BUTOXIDE, HYPOCHLOROUS ACID, ISOCYANATES, NITROFORM, PHOSGENE, OLEUM, PERCHLORIC ACID & STRONG OXIDIZING AGENTS.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:180F,82C  
Vapor Pres:SEE ING 1  
Vapor Density:SEE ING 1  
Spec Gravity:0.986  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:COMPLETE  
Appearance and Odor:CLEAR LIQUID  
Percent Volatiles by Volume:29

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
ACETADEHYDE, CHLORINE, ETHYLENE OXIDE, HYDROGEN-PALLADIUM COMBINATION, HYDROGEN PEROXIDE-SULFURIC ACID (SUPP DATA)  
Stability Condition to Avoid:SPARKS OR OPEN FLAMES.ALUMINUM CONTAINERS ARE NOT TO BE USED.  
Hazardous Decomposition Products:CO, CO\*2 & OTHER UNIDENTIFIED CMPDS MAY FORM UPON COMBUST. THERMAL-OXIDIATIVE DEGRADATION PRODS CAN INCL CO.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL  
REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.