

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 7 RELEASE PASTE COMPOUND

EMERGENCY TELEPHONE NO. (517) 496-5900

A-271

SECTION I - GENERAL INFORMATION

MANUFACTURER'S NAME: DOW CORNING CORP. PRODUCT INFORMATION NO. (517) 496-6000
ADDRESS: SOUTH SAGINAW ROAD, MIDLAND MI 48686

PROPER SHIPPING NAME(49CFR 172.101): NONE
D.O.T. HAZARD NAME(49CFR 172.101): NONE
D.O.T. ID NO(49CFR 172.101): NONE
D.O.T. HAZARD CLASS(49CFR 172.101): NONE
RCRA HAZARD CLASS(40CFR 261)(IF DISCARDED): NONE
E.P.A. PRIORITY POLLUTANTS(40CFR 122.53): NONE
NFPA = NATIONAL FIRE PROTECTION ASSOCIATION - 704
HEALTH (NFPA): 1 FLAMMABILITY (NFPA): 1 REACTIVITY (NFPA): 0
CAS NO: MIXTURE DOW CORNING WARNING CODE: NOT
GENERIC DESCRIPTION: SILICONE USED

SECTION II - HAZARDOUS INGREDIENTS AS DEFINED IN 29 CFR 1910.1200
(CARCINOGENS IDENTIFIED WITH AN ASTERISK *)

CAS NO.	INGREDIENT	WT. %	EXPOSURE LIMITS
007631869	SILICA, AMORPHOUS	8	OSHA PEL: TWA 6 MG/M3, ACGIH TLV: TWA 10 MG/M3 TOTAL DUST

SECTION III - EFFECTS OF OVEREXPOSURE

EYE: DIRECT CONTACT MAY CAUSE TEMPORARY DISCOMFORT WITH MILD REDNESS AND DRYNESS SIMILAR TO WINDBURN.

SKIN: A SINGLE, PROLONGED EXPOSURE (24 TO 48 HOURS) CAUSES NO KNOWN ADVERSE EFFECT.

INHALATION: NO IRRITATION TO EYES AND RESPIRATORY PASSAGES. NO INJURY IS LIKELY FROM RELATIVELY SHORT EXPOSURE OF LESS THAN 8 HOURS.

ORAL: SMALL AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS DURING USE, ETC., SHOULD NOT INJURE. SWALLOWING LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.

COMMENTS: NO INJURY FROM SILICA DUSTS SHOULD OCCUR DURING REASONABLE USE. IF USE CREATES RESPIRABLE PARTICLES SOME RESPIRATORY SYSTEM INJURY MAY OCCUR. THIS PRODUCT, AS WITH ANY CHEMICAL, MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE. WE DO NOT KNOW OF ANY MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 7 RELEASE PASTE COMPOUND

SECTION IV - EMERGENCY AND FIRST AID PROCEDURES

EYES: IMMEDIATELY FLUSH WITH WATER.

SKIN: WIPE OFF AND FLUSH WITH WATER.

INHALATION: NO FIRST AID SHOULD BE NEEDED.

ORAL: NO FIRST AID SHOULD BE NEEDED.

COMMENTS: NONE.

SECTION V - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): CLOSED CUP ABOVE 212F/100C.

AUTOIGNITION: NOT DETERMINED

FLAMMABILITY LIMITS IN AIR : LOWER:N.D. UPPER:N.D.

EXTINGUISHING MEDIA: WATER WATER FOG X CO2 X DRY CHEMICAL X FOAM X OTHER

SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN TO DOW CORNING.

COMMENTS: N.D. = NOT DETERMINED.

SECTION VI - PHYSICAL DATA

BOILING POINT(AT 760 MM HG): NOT APPLICABLE

SPECIFIC GRAVITY (AT 77 DEG F/25 DEG C): 1.1

MELTING POINT: NOT APPLICABLE

VAPOR PRESSURE (AT 77 DEG F/25 DEG C): LESS THAN 5 MM.

VAPOR DENSITY (AIR = 1 AT 77 DEG F/25 DEG C): NOT APPLICABLE

PERCENT VOLATILE BY WEIGHT (%): LESS THAN 5

EVAPORATION RATE (ETHER = 1): NOT APPLICABLE

SOLUBILITY IN WATER(%): LESS THAN 0.1

ODOR, APPEARANCE, COLOR: VERY LITTLE ODOR, PASTE-LIKE, SOME COLOR.

NOTE: THE ABOVE INFORMATION IS NOT INTENDED FOR USE IN PREPARING PRODUCT SPECIFICATIONS. CONTACT DOW CORNING BEFORE WRITING SPECIFICATIONS.

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 7 RELEASE PASTE COMPOUND

SECTION IX - ROUTINE HANDLING PRECAUTIONS

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN *: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE.

INHALATION: NO RESPIRATORY PROTECTION SHOULD BE NEEDED.

VENTILATION:

LOCAL EXHAUST: NONE SHOULD BE NEEDED.

MECHANICAL (GENERAL): RECOMMENDED.

SUITABLE RESPIRATOR: NONE SHOULD BE NEEDED.

THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING; USE AT ELEVATED TEMPERATURES, OR AEROSOL/SPRAY APPLICATIONS, MAY REQUIRE ADDED PRECAUTIONS.

* GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING.

COMMENTS: NONE.

SECTION X - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: USE REASONABLE CARE AND CAUTION.

OTHER PRECAUTIONS: NONE KNOWN TO DOW CORNING.

COMMENTS: TRACES OF FORMALDEHYDE (CARCINOGEN) MAY FORM IF HEATED IN AIR ABOVE 300F/149C. PROVIDE VENTILATION TO CONTROL VAPOR EXPOSURE WITHIN INHALATION GUIDELINES WHEN HANDLING AT ELEVATED TEMPERATURES. REVIEW THE OSHA FORMALDEHYDE REGULATIONS FOR DETAILED INFORMATION ON SAFE HANDLING REQUIREMENTS.

SECTION XI - COMMENT

ADDITIONAL SARA REGULATORY COMPLIANCE INFORMATION

SEC. 312 HAZARD CLASS: NONE.

SEC. 313 NOTIFICATION: NOT APPLICABLE - EITHER NONE PRESENT OR NONE PRESENT IN REGULATED QUANTITIES.

SECTION XII - COMMENT

SUPPLEMENTAL STATE COMPLIANCE INFORMATION

PENNSYLVANIA:	8%	7631869	SILICA, AMORPHOUS
		63148629	POLYDIMETHYLSILOXANE
		70131678	POLYDIMETHYLSILOXANE, HYDROXY-TERMINATED
MASSACHUSETTS:	8%	7631869	SILICA, AMORPHOUS
NEW JERSEY:	8%	7631869	SILICA, AMORPHOUS, FUMED; #1655
		63148629	POLYDIMETHYLSILOXANE
		70131678	POLYDIMETHYLSILOXANE, HYDROXY-TERMINATED

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 7 RELEASE PASTE COMPOUND

SECTION VII - REACTIVITY DATA

STABILITY: STABLE.

INCOMPATABILITY(MATERIAL TO AVOID): OXIDIZING MATERIAL CAN CAUSE A REACTION.

CONDITIONS TO AVOID: NOT APPLICABLE.

HAZARDOUS DECOMPOSITION PRODUCTS: SILICON DIOXIDE, CARBON DIOXIDE, AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NOT APPLICABLE.

COMMENTS: NONE.

SECTION VIII - SPILL, LEAK, MAINTENANCE/REPAIR AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE PRODUCT AND USE ABSORBENT MATERIAL TO TAKE CARE OF ANY OIL-LIKE RESIDUES.

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE.

INHALATION: NO RESPIRATORY PROTECTION SHOULD BE NEEDED.

WASTE DISPOSAL METHOD: DOW CORNING SUGGESTS THAT ALL LOCAL, STATE, AND FEDERAL REGULATIONS CONCERNING HEALTH AND POLLUTION BE REVIEWED TO DETERMINE APPROVED DISPOSAL PROCEDURES. CONTACT DOW CORNING IF THERE ARE AND DISPOSAL QUESTIONS.

D.O.T. (49CFR 171.8)/E.P.A. (40CFR 117) SPILL REPORTING INFORMATION

HAZARDOUS SUBSTANCE: NONE

REPORTABLE QUANTITY: NOT APPLICABLE

CONCENTRATION OF HAZARDOUS SUBSTANCE: NOT APPLICABLE

REPORTABLE QUANTITY OF PRODUCT: NOT APPLICABLE

COMMENTS: PRODUCT CONTAINS NO INGREDIENT SUBJECT TO D.O.T OR E.P.A. CERCLA/SARA ENVIRONMENTAL RELEASE REPORTING REGULATIONS. SEE SEC. XI FOR ADDITIONAL SARA COMPLIANCE INFORMATION.

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 7 RELEASE PASTE COMPOUND

THESE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.

PREPARED BY: JACK L. SHENEBERGER
LAST REVISION DATE: MARCH 12, 1990
PREVIOUS REVISION DATE: AUGUST 20, 1987
DATE: SEPTEMBER 27, 1990

(R) INDICATES REGISTERED OR TRADEMARK OF THE DOW CORNING CORPORATION.

