

# Material Safety Data Sheet

MSDS# P600

Page 1 of 3

Sanford Corporation  
2711 Washington Boulevard  
Bellwood, IL 60104

Telephone No:  
Date of Last Revision:  
Medical Emergency No:

1-800-323-0749  
October 15, 2001  
1-800-228-5635

## SECTION ONE: PRODUCT INFORMATION

PRODUCT NAME: Pre-Tested Oil Colors

PRODUCT SIZES: 37 and 150 ml

PRODUCT CLASS: Artists' Oil Color

## SECTION TWO: HAZARDOUS INGREDIENTS

INGREDIENTS	CAS #	PEL/TLV	MAX WT. %	NTP	IARC
None					

## SECTION THREE: PHYSICAL AND CHEMICAL CHARACTERISTICS

BOILING POINT: Not determined

MELTING POINT: Not determined

VAPOR PRESSURE: Not determined

SPECIFIC GRAVITY: Not determined

SPECIFIC VAPOR DENSITY (AIR = 1) Not determined

SOLUBILITY IN WATER: Not determined

REACTIVITY IN WATER: Non-reactive

EVAPORATION RATE (BUTYL ACETATE = 1): Not determined

APPEARANCE AND ODOR: Colored paints; oily odor

This Material Safety Data Sheet is applicable for the consumer use of the following products: P001, P002, P006, P016, P021, P023, P024, P061, P064, P076, P080, P086, P110, P112, P115, P116, P120, P134, P142, P150, P156, P160, P163, P168, P169, P170, P171, P172, P182, P202, P203, P205, P208, P211, P215, P216, P220, P222, P223, P230, P244, P306, P307

SECTION FOUR: FIRE AND EXPLOSION INFORMATION

FLASH POINT (METHOD):	Not available		
FLAMMABILITY LIMITS (% BY VOLUME):	LOWER:	Not explosive	UPPER: Not explosive
EXTINGUISHING MEDIA:	As appropriate for surrounding area.		
FIRE FIGHTING PROCEDURES:	No special fire fighting procedures required.		
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Not combustible		

SECTION FIVE: REACTIVITY DATA

STABILITY:	Stable
CONDITIONS TO AVOID:	Excessive heat
CHEMICAL INCOMPATIBILITY:	None known
HAZARDOUS DECOMPOSITION:	None known
HAZARDOUS POLYMERIZATION:	Will not occur.

SECTION SIX: HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL: See Section Two for component PEL/TLV's.

PRIMARY ROUTES OF ENTRY:

Inhalation:	None under normal use conditions.
Skin:	None under normal use conditions.
Eye:	None under normal use conditions.
Ingestion:	None under normal use conditions.

EFFECTS/SYMPTOMS OF ACUTE EXPOSURE: None expected.

EFFECTS/SYMPTOMS OF CHRONIC EXPOSURE: None expected.

CARCINOGEN LISTING:	NTP:	NO	IARC:	NO	OSHA:	NO
---------------------	------	----	-------	----	-------	----

See Section Two for components affected.

# Material Safety Data Sheet

MSDS# P600

Page 3 of 3

MEDICAL CONDITIONS USUALLY AGGRAVATED  
BY OVEREXPOSURE TO THIS PRODUCT: Unknown

## FIRST AID MEASURES:

Inhalation: Not an inhalation hazard.

Skin: Wash with soap and water.

Eye: Rinse through with water. If irritation persists, seek medical attention.

Ingestion: Seek medical attention. Note to physician: No acute health effects expected.

## SECTION SEVEN: SPILL OR LEAK PROCEDURES

PRECAUTIONS TO BE TAKEN  
DURING STORAGE/HANDLING: KEEP OUT OF REACH OF CHILDREN.

STEPS TO BE TAKEN IN CASE  
MATERIAL IS SPILLED: No special spill procedures required.

WASTE DISPOSAL METHOD: Dispose in accordance with Federal, State, and Local Regulations.

## SECTION EIGHT: PROTECTIVE EQUIPMENT AND CONTROL MEASURES

RESPIRATORY PROTECTION AND  
SPECIAL VENTILATION  
REQUIREMENTS: None required.

OTHER PROTECTIVE EQUIPMENT  
(GLOVES, GOGGLES, ETC.): None

WORK/HYGIENE PRACTICES: Studio hygiene rules should be observed. Wash thoroughly before eating, drinking, or smoking.

HMIS CODE	
Health	0
Flammability	0
Reactivity	0
Personal Protection	N/A

0=Minimal/4=Extreme Hazard

Sanford Corporation is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D4236 and is labeled with the AP Nontoxic Seal. Products bearing the AP Approved Product Seal of The Art and Creative Materials Institute, Inc. are certified in a program of toxicological evaluation by a medical expert, subject to the approval of the Institute Toxicological Advisory Board, to contain no materials in sufficient quantities to be toxic or injurious to humans, or to cause acute or chronic health problems.

May be used to comply with OSHA Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.

