

Faster Lossy Generalized Flow via Interior Point Algorithms*

Samuel I. Daitch

Department of Computer Science
Yale University

Daniel A. Spielman

Program in Applied Mathematics and
Department of Computer Science
Yale University

May 30, 2018

Abstract

We present asymptotically faster approximation algorithms for the generalized flow problems in which multipliers on edges are at most 1. For this lossy version of the maximum generalized flow problem, we obtain an additive ϵ approximation of the maximum flow in time $\tilde{O}(m^{3/2} \log^2(U/\epsilon))$, where m is the number of edges in the graph, all capacities are integers in the range $\{1, \dots, U\}$, and all loss multipliers are ratios of integers in this range. For minimum cost lossy generalized flow with costs in the range $\{1, \dots, U\}$, we obtain a flow that has value within an additive ϵ of the maximum value and cost at most the optimal cost. In many parameter ranges, these algorithms improve over the previously fastest algorithms for the generalized maximum flow problem by a factor of $m^{1/2}$ and for the minimum cost generalized flow problem by a factor of approximately $m^{1/2}/\epsilon^2$.

The algorithms work by accelerating traditional interior point algorithms by quickly solving the linear equations that arise in each step. The contributions of this paper are twofold. First, we analyze the performance of interior point algorithms with approximate linear system solvers. This analysis alone provides an algorithm for the standard minimum cost flow problem that runs in time $\tilde{O}(m^{3/2} \log^2 U)$ —an improvement of approximately $\tilde{O}(n/m^{1/2})$ over previous algorithms.

Second, we examine the linear equations that arise when using an interior point algorithm to solve generalized flow problems. We observe that these belong to the family of symmetric M-matrices, and we then develop $\tilde{O}(m)$ -time algorithms for solving linear systems in these matrices. These algorithms reduce the problem of solving a linear system in a symmetric M-matrix to that of solving $\mathcal{O}(\log n)$ linear systems in symmetric diagonally-dominant matrices, which we can do in time $\tilde{O}(m)$ using the algorithm of Spielman and Teng.

All of our algorithms operate on numbers of bit length at most $\mathcal{O}(\log nU/\epsilon)$.

*This material is based upon work supported by the National Science Foundation under Grant Nos. CCF-0707522 and CCF-0634957. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation.

1 Introduction

Interior-point algorithms are one of the most popular ways of solving linear programs. These algorithms are iterative, and their complexity is dominated by the cost of solving a system of linear equations at each iteration. Typical complexity analyses of interior point algorithms apply worst-case bounds on the running time of linear equations solvers. However, in most applications the linear equations that arise are quite special and may be solved by faster algorithms. Each family of optimization problem leads to a family of linear equations. For example, the maximum flow and minimum cost flow problems require the solution of linear systems whose matrices are symmetric and diagonally-dominant. The generalized versions of these flow problems result in symmetric M-matrices.

The generalized maximum flow problem is specified by a directed graph (V, E) , an inward capacity $c(e) > 0$ and a multiplier $\gamma(e) > 0$ for each edge e , and source and sink vertices s and t . For every unit flowing into edge e , $\gamma(e)$ flows out. In lossy generalized flow problems, each multiplier $\gamma(e)$ is restricted to be at most 1. In the generalized maximum flow problem, one is asked to find the flow $f : E \rightarrow \mathbb{R}^+$ that maximizes the flow into t given an unlimited supply at s , subject to the capacity constraints on the amount of flow entering each edge. In the generalized minimum cost flow problem, one also has a cost function $q(e) \geq 0$, and is asked to find the maximum flow of minimum cost (see [AMO93]).

In the following chart, we compare the complexity of our algorithms with the fastest algorithms of which we are aware. The running times are given for networks in which all capacities and costs are positive integers less than U and every loss factor is a ratio of two integers less than U . For the standard flow problems, our algorithms are exact, but for the generalized flow problems our algorithms find additive ϵ approximations, while the other approximation algorithms have multiplicative error $(1 + \epsilon)$. However, we note that our algorithms only require arithmetic with numbers of bit-length $\mathcal{O}(\log(nU/\epsilon))$, whereas we suspect that the algorithms obtaining multiplicative approximations might require much longer numbers.

In the chart, C refers to the value of the flow.

Exact algorithms	Approximation algorithms	Our algorithm
Generalized Maximum Flow $\mathcal{O}(m^2(m + n \log n) \log U)$ [GJO97] $\mathcal{O}(m^{1.5}n^2 \log(nU))$ [Vai89]	$\tilde{\mathcal{O}}(m^2/\epsilon^2)$ [FW02] $\tilde{\mathcal{O}}(m(m + n \log \log B) \log \epsilon^{-1})$ [GFNR98][TW98][FW02]	$\tilde{\mathcal{O}}(m^{1.5} \log^2(U/\epsilon))$
Generalized Minimum Cost Flow $\mathcal{O}(m^{1.5}n^2 \log(nU))$ [Vai89]	$\tilde{\mathcal{O}}(m^2 \log \log B/\epsilon^2)$ [FW02]	$\tilde{\mathcal{O}}(m^{1.5} \log^2(U/\epsilon))$
Maximum Flow $\mathcal{O}(\min(n^{3/2}, m^{1/2})m \log(n^2/m) \log U)$ [GR98]		$\tilde{\mathcal{O}}(m^{1.5} \log^2 U)$
Minimum Cost Flow $\mathcal{O}(nm \log(n^2/m) \log(nC))$ [GT87] $\mathcal{O}(nm(\log \log U) \log(nC))$ [AGOT92] $\mathcal{O}((m \log n)(m + n \log n))$ [Orl88]		$\tilde{\mathcal{O}}(m^{1.5} \log^2 U)$

1.1 The solution of systems in M-matrices

A symmetric matrix M is *diagonally dominant* if each diagonal is at least the sum of the absolute values of the other entries in its row. A symmetric matrix M is an *M-matrix* if there is a positive diagonal matrix D for which DMD is diagonally dominant. Spielman and Teng [ST04, ST06] showed

how to solve linear systems in diagonally dominant matrices to ϵ accuracy in time $\tilde{\mathcal{O}}(m \log \epsilon^{-1})$. We show how to solve linear systems in M -matrices by first computing a diagonal matrix D for which DMD is diagonally dominant, and then applying the solver of Spielman and Teng. Our algorithm for finding the matrix D applies the solver of Spielman and Teng an expected $\mathcal{O}(\log n)$ times. While iterative algorithms are known that eventually produce such a diagonal matrix D , they have no satisfactory complexity analysis [Li02, LLH⁺98, BCPT05].

1.2 Analysis of interior point methods

In our analysis of interior-point methods, we examine the complexity of the short-step dual path following algorithm of Renegar [Ren88] as analyzed by Ye [Ye97]. The key observations required by our complexity analysis are that none of the slack variables become too small during the course of the algorithm and that the algorithm still works if one $\mathcal{O}(1/\sqrt{m})$ -approximately solves each linear system in the matrix norm (defined below). Conveniently, this is the same type of approximation produced by our algorithm and that of Spielman and Teng. This is a very crude level of approximation, and it means that these algorithms can be applied very quickly. While other analyses of the behavior of interior point methods with inexact solvers have appeared [Ren96], we are unaware of any analyses that are sufficiently fine for our purposes.

This analysis is given in detail in Appendix C.

1.3 Outline of the paper

In Section 2, we describe the results of our analysis of interior point methods using approximate solvers. In Section 3, we describe the formulation of the generalized flow problems as linear programs, and discuss how to obtain the solutions from the output of an interior-point algorithm. In Section 4, we give our algorithm for solving linear systems in M -matrices.

2 Interior-Point Algorithm using an Approximate Solver

Our algorithm uses numerical methods to solve a linear program formulation of the generalized flow problems. The fastest interior-point methods for linear programs, such as that of Renegar [Ren88] require only $\mathcal{O}(\sqrt{n})$ iterations to approach the solution, where each iteration takes a step through the convex polytope by solving a system of linear equations.

In this paper, we consider stepping through the linear program using an only an approximate solver, i.e. an algorithm $\mathbf{x} = \text{Solve}(M, \mathbf{b}, \epsilon)$ that returns a solution satisfying

$$\|\mathbf{x} - M^{-1}\mathbf{b}\|_M \leq \epsilon \|M^{-1}\mathbf{b}\|_M$$

where the **matrix norm** $\|\cdot\|_M$ is given by $\|\mathbf{v}\|_M = \sqrt{\mathbf{v}^T M \mathbf{v}}$.

As mentioned above, we have analyzed the Renegar [Ren88] version of the dual path-following algorithm, along the lines of the analysis that found in [Ye97], but modified to account for the use of an approximate solver.

In particular, using the approximate solver we implement an interior-point algorithm with the following properties:

Theorem 2.1. $\mathbf{x} = \text{InteriorPoint}(A, \mathbf{b}, \mathbf{c}, \lambda_{\min}, T, \mathbf{y}^0, \epsilon)$ takes input that satisfies

- A is an $n \times m$ matrix;
- $\mathbf{b}$ is a length n vector; $\mathbf{c}$ is a length m vector

- AA^T is positive definite, and $\lambda_{\min} > 0$ is a lower bound on the eigenvalues of AA^T
- $T > 0$ is an upper bound on the absolute values of the coordinates in the dual linear program, i.e.

$$\|\mathbf{y}\|_\infty \leq T \text{ and } \|\mathbf{s}\|_\infty \leq T$$

$$\text{for all } (\mathbf{y}, \mathbf{s}) \text{ that satisfy } \mathbf{s} = \mathbf{c} - A^T \mathbf{y} \geq 0$$

- initial point $\mathbf{y}^0$ is a length n vector where $A^T \mathbf{y}^0 < \mathbf{c}$
- error parameter ϵ satisfies $0 < \epsilon < 1$

and returns $\mathbf{x} > 0$ such that $\|A\mathbf{x} - \mathbf{b}\| \leq \epsilon$ and $\mathbf{c}^T \mathbf{x} < z^* + \epsilon$.

Let us define

- U is the largest absolute value of any entry in $A, \mathbf{b}, \mathbf{c}$
- $s_{\min}^0$ is the smallest entry of $\mathbf{s}^0 = \mathbf{c} - A^T \mathbf{y}^0$

Then the algorithm makes $\mathcal{O}\left(\sqrt{m} \log \frac{TUm}{\lambda_{\min} s_{\min}^0 \epsilon}\right)$ calls to the approximate solver, of the form

$$\text{Solve}(AS^{-2}A^T + \mathbf{v}\mathbf{v}^T, \cdot, \epsilon')$$

where S is a positive diagonal matrix with condition number $\mathcal{O}\left(\frac{T^2 U m^2}{\epsilon}\right)$, and $\mathbf{v}, \epsilon'$ satisfy

$$\log \frac{\|\mathbf{v}\|}{\epsilon'} = \mathcal{O}\left(\log \frac{TUm}{s_{\min}^0 \epsilon}\right)$$

In Appendix C, we present a complete description of this algorithm, with analysis and proof of correctness.

3 Solving Generalized Flow

We consider network flows on a directed graph (V, E) with $V = [n]$, $E = \{e_1, \dots, e_m\}$, source $s \in V$ and sink $t \in V$. Edge e_j goes from vertex v_j to vertex w_j . and has inward capacity $c(e_j)$, flow multiplier $\gamma(e_j) < 1$, and cost $q(e_j)$.

We assume without loss of generality that t has a single in-edge, which we denote as e_t , and no out-edges.

The generalized max-flow approximation algorithm will produce a flow that sends no worse than ϵ less than the maximum possible flow to the sink.

The generalized min-cost approximation algorithm will produce a flow that, in addition to being within ϵ of a maximum flow, also has cost no greater than the minimum cost of a maximum flow (see [FW02]).

3.1 Fixing Approximate Flows

The interior-point algorithm described in the previous section produces an output that may not exactly satisfy the linear constraints $A\mathbf{x} = \mathbf{b}$. In particular, when we apply the algorithm to a network flow linear program, the output may only be an approximate flow:

Definition 3.1. *An ϵ -approximate flow approximately satisfies all capacity constraints and flow conservation constraints. In particular, every edge may have flow up to ϵ over capacity, and every vertex besides s and t may have up to ϵ excess or deficit flow.*

An exact flow satisfies all capacity constraints and has exact flow conservation at all vertices except s and t .