
Django Inelastic Models Documentation

Release 7.1.0

PSU OIT Web & Mobile Team

Apr 07, 2022

Contents

1	Introduction	1
1.1	Usage	1
1.2	Tests	2
2	Changelog	3
2.1	7.0	3
2.2	1.5	3
2.3	1.4	4
2.4	1.3	4
2.5	1.2	4
2.6	1.1	4
2.7	1.0	4

CHAPTER 1

Introduction

This package provides a small library for declaratively specifying indexes for [Django](#) models using an [Elasticsearch](#) back-end.

It requires Django, [elasticsearch-dsl](#) and an available Elasticsearch instance.

1.1 Usage

1. Add `inelastic_models` to `INSTALLED_APPS`.
2. Mixin the type `inelastic_models.indexes.SearchMixin` to your models.
3. Implement a type `inelastic_models.indexes.Search` and bind it to models:

```
from .models import Foo

class FooIndex(Search):
    attribute_fields = ('foo', 'baz')

FooIndex.bind_to_model(Foo)
```

You must define `ELASTICSEARCH_CONNECTIONS`. Pass index and connection parameters to the generated indices and the underlying Elasticsearch instance via the `INDEX_OPTIONS` and `CONNECTION_OPTIONS` mappings, respectively:

```
ELASTICSEARCH_CONNECTIONS = {
    'default': {
        'HOSTS': ['http://localhost:9200'],
        'INDEX_NAME': 'inelastic_models',
        'INDEX_OPTIONS': {
            'number_of_replicas': 3
        },
        'CONNECTION_OPTIONS': {
            'timeout': 42,
        }
    }
}
```

(continues on next page)

(continued from previous page)

```
        'retry_on_timeout': True
    }
},
```

1.2 Tests

Run tests using the make rule:

```
make test [venv=<path>] [python=<python executable name, e.g., 'python3.5'>]
```

It is assumed that you have an Elasticsearch index available at `elasticsearch:9200` and that `virtualenv` is available on your path.

2.1 7.0

2021-11-23

This release adds support for, and requires, the use of ES 7.x.

This release marks a departure from the previous release strategy. To reduce confusion and to provide better support for a variety of Elasticsearch installations, releases will follow the major ES release versions as is done with the ‘elasticsearch-py’ and the ‘elasticsearch-dsl-py’ packages.

- Uses analyzer, tokenizer constructions compatible with ES ≥ 5.0
- Replaces the use of the ‘string’ type field with ‘text’ [ES ≥ 5.0].
- Removes use of ‘flush’ API [ES ≥ 6].
- Removes support for Python 2 and related compatibility shims.
- Replaces deprecated ngram type names [ES ≥ 8.0].
- Revises index construction to support mapping type removal [ES ≥ 8.0].
- Adds new field ‘KitchenSinkField’ to replace the functionality of the historical ‘_all’ index field [ES ≥ 6.0].

2.2 1.5

2020-02-27

- Fixes exception handling during chunked indexing.
- Improves performance of ‘bulk_prune’ operation.
- Fixes erroneous dict modification during iteration.
- Adds missing assertions, guards for empty index requests.

- Adds support for WDT PYPI instance.

2.3 1.4

- Adds explicit support for translated fields.
- Replaces uses of print function.
- Uses memory-efficient record iteration for bulk operations.

2.4 1.3

- Adds support for connection parameter configuration via 'ELASTICSEARCH_CONNECTIONS'.

2.5 1.2

- Enforces a one-to-one relation between Elasticsearch indices and mappings in order to simplify implementation and behavior.
- Retargets to the Elasticsearch 2.x release series.
- Revises incorrect test case specifications.
- Adds new index API 'Search.check_mapping'.
- Adds new management command 'migrate_index'.

2.6 1.1

Adds explicit index-binding.

2.7 1.0

The initial pre-release which serves to replicate 'oro.search' as an external package.