RCS Platform Minimal API Guide

Production base URL https://rcs.ostpl.com

This guide contains only the six endpoints required to authenticate, create and approve a template, send a campaign, monitor it, and download its report.

Required flow

1. Generate an access token using the portal username and password.
2. Create a template and save the returned template_id.
3. Check the template status until it is approved.
4. Upload a CSV or TXT number file to create the campaign.
5. Check the campaign status until processing completes.
6. Download the CSV report.

Endpoint summary

Method	Endpoint	Purpose
POST	/api/v1/auth/token	Generate access token
POST	/api/v1/templates	Create template
GET	/api/v1/templates/{template_id}/status	Check template approval
POST	/api/v1/campaigns/upload	Upload and send campaign
GET	/api/v1/campaigns/{campaign_id}/status	Monitor campaign
GET	/api/v1/campaigns/{campaign_id}/report	Download CSV report

1 Authentication

POST `/api/v1/auth/token`

Generate an access token using the same username and password used in the portal.

```
curl -X POST "https://rcs.ostpl.com/api/v1/auth/token" \
  -H "Content-Type: application/json" \
  -d '{"username":"YOUR_USERNAME","password":"YOUR_PASSWORD"}'
```

Use the returned access_token in every protected request:

```
Authorization: Bearer ACCESS_TOKEN
```

2 Create template

POST `/api/v1/templates`

Create a template. A non-admin template remains pending until an administrator approves it.

```
curl -X POST "https://rcs.ostpl.com/api/v1/templates" \
  -H "Authorization: Bearer ACCESS_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "name": "October Offer",
    "template_type": "plain",
    "content": {"text": "Your offer message"}
  }'
```

Save template_id from the response.

3 Check template approval

GET `/api/v1/templates/{template_id}/status`

Continue only after the returned status becomes approved.

```
curl "https://rcs.ostpl.com/api/v1/templates/TEMPLATE_ID/status" \
  -H "Authorization: Bearer ACCESS_TOKEN"
```

4 Upload and send campaign

POST `/api/v1/campaigns/upload`

Create a campaign from a UTF-8 CSV or TXT file containing mobile numbers.

```
curl -X POST "https://rcs.ostpl.com/api/v1/campaigns/upload" \
  -H "Authorization: Bearer ACCESS_TOKEN" \
  -F "campaign_name=October Campaign" \
  -F "template_id=TEMPLATE_ID" \
  -F "numbers_file=@numbers.csv"
```

The Idempotency-Key header is not required. The server automatically generates a UUID and returns it as idempotency_key. A caller may optionally provide a stable key when retrying the same request.

Upload limits: 20 MB and 500,000 unique valid Indian mobile numbers. Accepted files are UTF-8 CSV or plain text.

5 Monitor campaign

GET `/api/v1/campaigns/{campaign_id}/status`

Use the campaign_id returned by the upload endpoint.

```
curl "https://rcs.ostpl.com/api/v1/campaigns/CAMPAIGN_ID/status" \
  -H "Authorization: Bearer ACCESS_TOKEN"
```

6 Download report

GET `/api/v1/campaigns/{campaign_id}/report`

Download the authorized campaign report as CSV.

```
curl "https://rcs.ostpl.com/api/v1/campaigns/CAMPAIGN_ID/report" \
  -H "Authorization: Bearer ACCESS_TOKEN" \
  --output campaign-report.csv
```

Optional filter: add ?status=delivered, ?status=failed, ?status=read, or another supported message status.

Security and error handling

- Use HTTPS only and keep passwords and access tokens out of URLs and logs.
- HTTP 401 means the access token is missing, invalid, or expired. Generate a new token.
- HTTP 402 means the wallet balance is insufficient.
- HTTP 404 means the template or campaign was not found or is not accessible to the user.
- HTTP 413 means the upload exceeds the file or number limit.
- HTTP 422 means a required request field is missing or invalid.