



STEPHENSON THEATRE

AUDIO SYSTEM RIDER

The Phoenix Theatre Company | 1825 N Central Ave, Phoenix, AZ 85004

Audio Supervisor: Matthew Gibney (m.gibney@phoenixtheatre.com) | House A1: Jess Baker

Version 1.2 — July 3, 2026

Stephenson is PTC's mainstage-musical venue (recent/current productions: Les Misérables, Ever After). Full-production Dante infrastructure at 96 kHz throughout, with a bridged 48 kHz island for playback and personal monitoring. This rider reflects the house system of record as of the date above; advance all production-specific needs with the Audio Supervisor.

FRONT OF HOUSE CONTROL

Console	Yamaha RIVAGE PM5 (CS-R5 surface) with DSP-RX-EX expansion — Theatre Mode, 96 kHz, delay compensation enabled on input inserts / output buses
I/O cards	3× HY expansion cards: HY1 — Dante 96k (Rio stage box inputs); HY3 — SRC bridge to the 48 kHz island; HY4 — Nuendo recording/virtual soundcheck at 96k
Virtual soundcheck	Nuendo (dedicated record computer, Dante)
External FX	Yamaha VST Rack host — Bricasti reverb presets in regular use
Show control	QLab 5 with Dante (DVS) returns; console UDKs mapped to QLab GO/UP/DOWN/PANIC on recent productions

LOUDSPEAKER SYSTEM (L-ACOUSTICS)

Mains / center	4× L-Acoustics ARC A15 (passive, house-dedicated)
Front fills	5× L-Acoustics 5XT ultra-compact coaxial
House delays	6× L-Acoustics X8 compact coaxial
Subwoofers	4× L-Acoustics KS21 (installed)
Amplification	6× L-Acoustics LA4X, 2× LA2Xi, 1× QSC CX-Q 8K8 network amplifier — all on the audio control network

STAGE I/O & NETWORK

Stage boxes	3× Yamaha Rio3224-D (Band 1, Band 2, FOH positions) + 1× Yamaha Rio1608-D2 (booth utility) — Dante, 96 kHz
Dante network	Fully redundant primary/secondary Dante on dedicated audio VLANs; word clock leader: Focusrite RedNet A8R
Wireless control	Dedicated audio-control Wi-Fi at FOH and band positions for console/RF remote control
Interdepartment	OSC bridge network to Lighting and Video departments (MSC/LTC show-control integration available)

WIRELESS MICROPHONES (SHURE AXIENT DIGITAL)

Receivers	8× Shure AD4Q four-channel receivers assigned to Stephenson (32 channels; 13 AD4Q house-wide)
Bodypacks	Shure ADX1M micro-bodypack pool (52 house-wide, allocated per production)

Handhelds	2× Shure ADX2
RF management	Shure AXT600 Axient Spectrum Manager, UA845UWB antenna distribution, RF Venue 4-zone antenna combiner
House lav standard	Countryman B3 (LEMO) for vocals; DPA 4099 series (C/V/BC/STC clips) as the instrument-mic house standard

MONITORING & COMMS

Personal mixers	Allen & Heath ME-1 (24-unit house pool) via ME-U hub; Aviom units (×13) on the 48 kHz island
Wedges / spot monitors	Shared house stock: QSC K8/K10/K12, JBL EON15, Meyer UPM-1P, EAW JF80 — allocated per production
Comms core	Clear-Com Arcadia Central Station (AES67, shared across venues) with HRM-4X remote stations
Wireless comms	Clear-Com FreeSpeak II — 3× IP transceivers in Stephenson; HXii wireless beltack pool (venue-assigned)
Assistive listening	Listen Technologies Auri IR transmission (house system)

BAND MICROPHONE STOCK (SELECTED)

Sennheiser e604/e609/e904, MKH-50, MD-441 · DPA 4099 family (largest recurring deployment) · AKG 414 · Shure SM57/KSM137 · Neumann KM184. Full 125-line inventory available on request; allocations advanced per production.

NOT COVERED HERE — ADVANCE WITH THE DEPARTMENT

Company power/tie-in specifications, rigging and line-set schedule, seating capacity/house dimensions, and touring-package interconnect points are not part of this document — contact the Audio Supervisor to advance. Network addressing and credentials are not published; visiting engineers requiring Dante or control-network access will be provisioned on site.

Prepared from the AUD-IT department system of record (inventory snapshot 2026-07-03; network register 2026). Subject to change — confirm current configuration when advancing.