

MANUAL SETUP & EXTERNAL DEVOPS ACTION ITEMS

Step-by-Step Production Configuration Runbook for Resend, Supabase & DNS

INTERNAL DEVOPS RUNBOOK • CONFIDENTIAL • NOT EXPOSED IN APP OR PUBLIC WEB

1. EXECUTIVE OVERVIEW & SCOPE OF MANUAL WORK

All code implementations, visual UI editors, database bridges, and automation engines are fully compiled and live in the codebase. However, security boundaries require that third-party cloud accounts, DNS domain authentications, and production secret keys be managed externally by you. Neither Google AI Studio nor automated scripts can create third-party vendor accounts or modify domain DNS records on your behalf.

This document provides the complete, authoritative checklist of manual steps you must perform outside Google AI Studio to enable live outbound email delivery and permanent database operations.

SECURITY PROTOCOL: PRIVACY & ZERO SECRETS IN REPO

Never paste production API keys or database service role keys into front-end code, GitHub, or public forms. All secrets must be stored strictly in server-side container variables or Supabase Vault.

2. MASTER CHECKLIST OF EXTERNAL ACTION ITEMS

STEP 1: Create & Configure Resend Account

MANDATORY

Navigate to <https://resend.com> and sign up with your corporate email (e.g., joel.reji@ageslearningsolutions.com). Resend serves as the dedicated transactional email delivery engine for deadline reminders.

STEP 2: Add & Verify Corporate Sending Domain

MANDATORY

In the Resend Dashboard, go to "Domains" > "Add Domain". Enter your corporate email domain (e.g., proficiotherapy.com or ageslearningsolutions.com). Do not use public domains like gmail.com or yahoo.com.

STEP 3: Publish Resend DNS Records (DKIM & SPF)

MANDATORY

Access your DNS host (Cloudflare, GoDaddy, Google Domains, AWS Route 53) and create the 3 DNS records provided by Resend (DKIM TXT, SPF TXT, and MX tracking record) to guarantee 100% email deliverability.

MANUAL SETUP RUNBOOK — PART 2: KEYS & SECRETS

API Key Generation, Environment Variable Provisioning & Database Verification

INTERNAL DEVOPS RUNBOOK • CONFIDENTIAL • NOT EXPOSED IN APP OR PUBLIC WEB

STEP 4: Generate Production Resend API Key

MANDATORY

In Resend, navigate to "API Keys" > "Create API Key". Name it "Proficio Credentialing Engine". Select "Full Access" or "Sending access (restricted to your verified domain)". Copy the generated key (starts with "re_").

STEP 5: Inject RESEND_API_KEY into Server Environment

MANDATORY

Set the server environment variable RESEND_API_KEY in your Cloud Run container or Supabase Edge Function secrets. This key is used exclusively server-side by the automation engine and is NEVER sent to the browser.

```
# Required Server-Side Environment Variables (.env / Cloud Run Secrets)
RESEND_API_KEY=re_123456789_abcdefghijklmnopqrstuvwxyz
RESEND_FROM_EMAIL=Credentialing Team <credentialing@proficiotherapy.com>
APPLICATION_URL=https://ais-dev-ro7zg4lpp6jxlcjol5in7a-568047474488.asia-southeast1.run.app
```

STEP 6: Execute Database Migration Script in Supabase

MANDATORY

Log into your Supabase Dashboard at <https://supabase.com/dashboard/project/uqaiotacheqjvfbnxtp/sql>. Open the SQL Editor and execute the provided migration script: `supabase/migrations/20260912000000_automated_deadline_reminders.sql`.

The migration script creates the required relational tables: "automation_definitions" and "automation_executions", applies the unique idempotency index to prevent duplicate emails, configures Row Level Security (RLS), and seeds the default 30-14-7-1 day reminder cadence.

STEP 7: Enable pg_cron Daily Scheduled Invocation

MANDATORY

In the Supabase SQL Editor, enable `pg_cron` if not already active to schedule the daily deadline evaluation job at 08:00 UTC (midnight PST).

```
-- Enable pg_cron and pg_net extensions in Supabase SQL Editor:
CREATE EXTENSION IF NOT EXISTS pg_cron;
CREATE EXTENSION IF NOT EXISTS pg_net;

-- Schedule automated daily evaluation at 08:00 UTC (12:00 AM PST):
SELECT cron.schedule(
  'credential-deadline-reminders-daily',
  '0 8 * * *',
  $$ SELECT net.http_post(
    url:='https://ais-dev-ro7zg4lpp6jxlcjol5in7a-568047474488.asia-southeast1.run.app/api/automations/run-check',
    headers:='{ "Content-Type": "application/json" }'::jsonb,
    body:='{ "scheduled": true }'::jsonb
  ) AS request_id; $$
);
```

MANUAL SETUP RUNBOOK — PART 3: TESTING & CUTOVER

End-to-End Verification, Zero-Duplicate Validation & Firebase Severance

INTERNAL DEVOPS RUNBOOK • CONFIDENTIAL • NOT EXPOSED IN APP OR PUBLIC WEB

3. END-TO-END VERIFICATION & SANITY TEST MATRIX

STEP 8: Dispatch End-to-End Test Email via UI

MANDATORY

In the application, log in as Manager or Admin and navigate to the "Automations" tab. Click the "Send Test Email" button. Enter your personal work email. Confirm receipt of the branded test email in your inbox.

STEP 9: Perform a Dry-Run / Preview Audit

MANDATORY

On the Automations screen, click "Preview / Dry Run". Verify that the engine accurately identifies all clinical credentials approaching 30, 14, 7, or 1 days without sending duplicate messages or throwing database errors.

STEP 10: Confirm Complete Firebase Decommissioning

MANDATORY

Navigate to Admin > System Configuration > Retention & DR tab. Verify that Supabase PostgreSQL displays "ACTIVE PRIMARY" with 16 verified tables, and Google Cloud Firestore displays "SEVERED & DISCONNECTED".

FIREBASE SEVERANCE VERIFIED

All operational connections, dual-write bridges, and SDK calls to Firebase have been permanently eliminated. All 103 clinical documents and 16 database tables run 100% natively on Supabase PostgreSQL.

4. SUMMARY TABLE OF REQUIRED SETTINGS

Component	Configuration Item	Value / Destination	Action Needed
Email Provider	Resend Account	resend.com	Create account & verify domain
DNS Records	DKIM & SPF Records	Your DNS Registrar	Add 3 DNS records
API Credentials	RESEND_API_KEY	Server Environment	Paste key into server env
Sender Address	RESEND_FROM_EMAIL	Server Environment	Set verified sender email
Database Host	Supabase PostgreSQL	Project: uqaiotacheqjvfbnxtpt	Run migration SQL in editor
Scheduled Task	Daily Cron Trigger	pg_cron / Supabase	Schedule daily check at 08:00 UTC
Firebase Engine	Google Firestore	Decommissioned	No action needed (severed)

Notice: This document is stored exclusively on the server filesystem at docs/MANUAL_SETUP_AND_ACTION_ITEMS.pdf. In strict accordance with security directives, it is NOT exposed through public HTTP routes, website buttons, navigation menus, or client-side bundles.