Armstrong BIOGUARD ACOUSTIC OP RH100



© Jakub Joachim

Armstrong BIOGUARD ACOUSTIC OP RH100 combines excellent cleanability, resistance to disinfectants and sound absorption. Along with its antimicrobial performance, it is an ideal solution for healthcare environments.

- Good sound absorption (0.90(H) α_w) and sound attenuation (29 dB)
- Good light reflectance (88%)
- ISO 3
- Ideal for healthcare environments with average or severe risk of infection

Build on us.

Armstrong BIOGUARD ACOUSTIC OP RH100

Characteristics	Detailed information		
Edge details Additional edge details on request	**Board**  	**Tegular 24/90**  	**Tegular 15/90** 
Thickness (mm)	19	19	19
Dimensions (mm)	600 x 600 1200 x 600	600 x 600 1200 x 600	600 x 600 1200 x 600
System	Exposed demountable - System C		
Weight	**5.2 kg / m²**		
Colour	White		
Sound absorption	EN ISO 354 — α_w = **0.90(H)** as per EN ISO 11654 - **Class A**		

Frequency f (Hz)	**125**	**250**	**500**	**1000**	**2000**	**4000**
α_p	0.60	0.70	0.85	0.90	1.00	1.00

NRC = **0.90** as per ASTM C 423

Sound attenuation	EN ISO 10848-2 CAC = **29 dB** as per ASTM E 413-10
Fire reaction	Euroclass **A2-s1, d0** as per EN 13501-1
Light reflectance	**88%**
Thermal conductivity	λ = **0.040 W/mk** as per EN 12667
Humidity resistance	**up to 100% RH**
Clean room	**ISO 3** as per EN ISO 14644-1
Indoor air quality	A+ E1 IACG
Cleanability	
Sustainability	51.7%

Product availability may vary from country to country. Please contact your local sales representative.
For further information and legal notice, please visit www.knauf.com