Supplement to Screening Chaos

Converted χ: Strategic Advantage Through Chaos-to-Probability Transformation

Aligned with: Screening Chaos 0.1, IEH v1.0.2 and PNP v2.0

1. Introduction

The Screening Chaos "framework" (v0.1) defines a two-stage procedure: first, expand the model-expressive event space $\mathcal{E}$ to include all events and trajectories to which the current model can assign non-zero probability (P_M > 0, where M denotes the current model); then identify the residual $\chi = \Omega \setminus \mathcal{E}$ as the domain that remains structurally inexpressible under that model. Two regimes of χ were proposed: low-amplitude (structured noise, parametric perturbation) and high-amplitude (disruptive operator, state-space shattering). Formally, let Ω denote the (unknown) world-space of possible events (and trajectories), and let $\mathcal{E} \subset \Omega$ denote the modelled subset. The model operates on $\mathcal{E}$, while χ corresponds to $\Omega \setminus \mathcal{E}$: the residual beyond the model's expressive capacity. Screening chaos means: first identify and parameterize everything that can be assigned P_M > 0 by the current model; only then use the word 'chaos' for what remains. Section 2 (below) introduces M_o as a specific instance of M, with P_{M_o} denoting the corresponding probability assignment.

This supplement introduces a third regime: Converted χ - chaos that has been systematically captured, transformed, and incorporated into $\mathcal{E}$ through novel formalisms. The regime addresses not the management of chaos (defensive posture) but the deliberate conversion of χ into probabilistically tractable structure (offensive posture).

The central claim is that systems capable of performing this conversion acquire a form of strategic advantage that is qualitatively distinct from superior modelling within an already-known state-space.

2. Symbols introduced in this supplement

M_o - the initial model whose expressive capacity defines $\mathcal{E}_o$.

$\mathcal{E}_o$ - the modelled event space at the initial stage: the set of all events and trajectories to which model M_o can assign non-zero probabilities (P_{M_o} > 0) before the conversion operator is applied.

χ_o - the initial chaos residual: $\chi_o = \Omega \setminus \mathcal{E}_o$. Everything that the model, in its present form, cannot name, parameterise, or assign probability to.

M_1 - the updated model after introducing F (the conversion operator), whose expressive capacity defines $\mathcal{E}_1$.

$\mathcal{E}_1$ - the updated event space after conversion: $\mathcal{E}_1 = \mathcal{E}_o \cup \chi_F$. The model's expressive reach has expanded to include what F captured.

χ_1 - the updated chaos residual: $\chi_1 = \chi_o \setminus \chi_F = \Omega \setminus \mathcal{E}_1$. What remains beyond the model even after the conversion. Strictly smaller than χ_o, but still non-empty - conversion reduces χ, it does not eliminate it. Under sufficiently disruptive conditions (paradigm shifts, model breakdowns, changed input conditions), elements previously captured in $\mathcal{E}_1$ may return to χ, and χ_1 may grow again (see Section 6.3).

χ_F - the converted subset: $\chi_F \subset \chi_o$. The specific portion of the initial chaos residual that F renders expressible and probabilistically tractable. These are events that were not overlooked but structurally inexpressible before F was introduced.

F - the conversion operator. Not a single equation, but a structural package: new variables, new state-space dimensions, mapping rules, measurement hooks, and inference procedures that jointly enable the representation of what was previously inexpressible within $\mathcal{E}_o$.

P_{M_o} - the probability assignment induced by model M_o over events representable in $\mathcal{E}_o$.

P_{M_1} - the probability assignment induced by model M_1 over events representable in $\mathcal{E}_1$.

3. The Third Regime: Converted χ

3.1. Definition

Let M_o denote the initial model and $\mathcal{E}_o$ its model-expressive event space. Let P_{M_o} denote the probability assignment induced by M_o over events representable in $\mathcal{E}_o$. Suppose that at a later stage a new formalism F is developed, yielding an updated model M_1, such that a subset $\chi_F \subset \chi_o$ becomes representable and probabilistically tractable, and can therefore be assigned non-zero probability under M_1 (P_{M_1}(e) > 0 for e ∈ χ_F). In representation space, the updated event space becomes:

$$\mathcal{E}_1 = \mathcal{E}_o \cup \chi_F$$
$$\chi_1 = \Omega \setminus \mathcal{E}_1 = \chi_o \setminus \chi_F$$

The union above is a bookkeeping identity over representable event-descriptions; the conversion is not the physical 'addition' of events to Ω, but the enlargement of what the model can name and assign probability to. The elements of χ_F are converted χ: events and trajectories that were previously outside the model's expressive capacity and are now inside it, with non-zero probabilities under M_1. The formalism F is the conversion operator - understood not as a single set of equations but as a structural package: new variables, new state-space dimensions, mapping rules, and inference procedures that jointly enable the representation of what was previously inexpressible.

3.2. Distinction from ordinary model expansion

Standard scientific progress routinely expands a model's expressive event space by refining parameters, adding variables, or incorporating new data. Converted χ differs from such incremental expansion in a specific way: the events brought into $\mathcal{E}_1$ through F were not merely overlooked under M_o; they were structurally inexpressible within the state-space of $\mathcal{E}_o$, meaning that P_{M_o} was undefined for them (they are not in the domain of P_{M_o}), rather than merely small. The conversion therefore requires not better calibration of existing equations, but the introduction of a qualitatively new formalism: equations, variables, or structural categories that did not exist in $\mathcal{E}_o$ and could not be obtained by incremental refinement alone.

In other words: converted χ is what becomes visible when someone invents a new way of seeing, not when someone looks harder with the old instruments.

4. Strategic Advantage Through χ ⇒ P Conversion

4.1. The asymmetry of perception

Consider two "agents", A and B, operating in the same physical environment Ω. Agent A works with event space $\mathcal{E}_A$ (model M_A). Agent B (model M_B) has access to a conversion operator F and works with $\mathcal{E}_B = \mathcal{E}_A \cup \chi F$. In the sense of Section 2, M_B plays the role of an updated model M_1 relative to M_A, because it incorporates F while M_A does not. Then:

(a) Events in χ_F are invisible to A: they cannot be named, anticipated, or assigned probability within A's model.

(b) The same events are visible to B: they can be assigned non-zero probability under M_B (P_{M_B}(e) > 0 for e ∈ χ_F) and can be incorporated into planning, prediction, and decision-making.

(c) Agent A cannot close this gap by working harder within $\mathcal{E}_A$. **The gap is not merely informational but model-structural: B inhabits a wider modelable world, not because of superior data, but because of a richer representational framework.**

This asymmetry constitutes a structural advantage. Where A sees noise, randomness, or inexplicable disruption, B sees structure with estimable likelihood. The advantage is not a matter of degree (better prediction accuracy within the same model) but a matter of kind (access to a larger modelable world).

4.2. Non-transferability

A critical property of the converted χ regime is that the advantage is difficult to transfer or replicate. The conversion operator F is not a dataset, a parameter set, or a calibration that can be copied. It is a new formalism plus its operational embedding: new variables, new state-space dimensions, mapping rules, measurement hooks, and inference procedures. Without grasping that embedding (here: Screening Chaos, PNP, and the Δ-based ontology of change), the formalism can be copied syntactically but cannot be executed meaningfully.

This is analogous to possessing a set of equations from general relativity without understanding the geometric interpretation of spacetime: the symbols can be reproduced, but the capacity to extend, apply, or diagnose them is absent. Transfer of the advantage is possible only through teaching the formalism, transmitting the structural understanding from which F derives, not through copying its outputs.

5. Chaotic Equations as Conversion Operators

The existing mathematical treatment of chaos (Lorenz, Rössler, the logistic map, Lyapunov exponents) describes deterministic dynamics within a defined (assumed) state space. These are classical systems and measures used to characterise sensitivity to initial conditions, not formalisms designed to reach beyond a model's boundary.

The proposal in this document concerns a qualitatively different class of formalisms: chaotic equations operating at the boundary between $\mathcal{E}$ and χ. Such equations do not yet exist in the standard mathematical canon, in the sense that there is no canonical class of equations whose aim is to generate new representational degrees of freedom for a model from boundary signatures. This claim must be distinguished from existing techniques such as out-of-distribution detection, Bayesian nonparametrics, or symbolic regression: these methods identify anomalies or extend parameter spaces within a given representational framework. What is proposed here is a class of formalisms that generate genuine extensions of the model itself - new variables, new state-space categories, and new mappings to probabilistic structure - from boundary signatures alone. Their defining property would be:

(a) They take as input the structure of the current $\mathcal{E}$ (what the model can currently name).

(b) They identify boundary signatures - patterns at the edge of $\mathcal{E}$ that suggest the presence of structure just beyond it.

(c) They generate candidate extensions: proposed variables, state-space dimensions, or event categories that, if incorporated, would convert a subset of χ into $\mathcal{E}$; candidate extensions here mean structural additions to the model's representational scheme, such as new state variables, additional state-space dimensions or geometry, new event categories, or new mapping rules that connect boundary signatures to probabilistic structure.

This programme is speculative, but not without precedent. Historically, breakthroughs in physics and mathematics have often proceeded by exactly this logic: recognising that anomalies at the boundary of a model are not noise but signals of a richer structure waiting to be formalised (e.g., the ultraviolet catastrophe leading to quantum mechanics; Mercury's perihelion precession leading to general relativity).

A conversion operator is therefore not defined by flexibility of fit, but by the creation of new representational degrees of freedom that were not definable inside $\mathcal{E}$.

6. Implications and Open Questions

6.1. For strategic foresight and resilience engineering

The converted χ regime reframes resilience not as the ability to withstand unknown shocks (defensive), but as the ability to systematically reduce the domain of the unknown (offensive). Organisations or systems that develop and deploy conversion operators F will, over time, operate in a larger modelable world than their peers. This advantage compounds: each conversion enlarges the current $\mathcal{E}$, which in turn exposes new boundary signatures, which in turn enable further conversions. This also suggests near-term operational directions. In resilience engineering, screening chaos can be used as a disciplined procedure for exhausting the catalogue of scenarios with P > 0 under the current model, explicitly marking the residual as χ, and then designing structures that remain functional even when χ-events occur. In strategic foresight, the same logic supports scenario exploration beyond standard risk registers: first exhaust all "thinkable" scenarios, then treat what remains as structurally inexpressible under the current frame, and design institutions and decision processes under the assumption that such events will eventually occur. A similar heuristic reading applies to quantum computing: because quantum algorithms explore large state spaces in parallel and use interference to amplify some trajectories while suppressing others, a screening chaos-style procedure could deliberately de-emphasise "typical" trajectories and focus post-selection or amplitude amplification on extreme, low-classical-probability regions that are most likely to reveal hidden structure in the problem.

6.2. For the development of chaotic equations

The central open question is whether a general mathematical framework for χ ⇒ P conversion can be constructed, or whether each conversion is necessarily *ad hoc* - a one-time insight that expands $\mathcal{E}$ in a specific direction but does not generalise. **If the former is possible, it would represent a new branch of mathematics: not the study of chaos within models, but the study of how models can be extended to capture what was previously beyond them.**

The author is currently developing a concept under the working title "Toward a Mathematics of χ ⇒ P Conversion: A Research Programme for Formalising the Boundary Between the Modelled and the Unmodelled", which attempts to formalise and operationalise a parameterised family of chaos-to-probability conversion operators (an excerpt follows).

"The Axiom of χ-Irreducibility

The question arises: does this hierarchy converge to zero? Can every element of χ eventually be converted by some operator in the sequence?

The answer is no, and this is not merely an empirical observation but a structural necessity. If χ were reducible to zero, then Ω = $\mathcal{E}$ and the concept of chaos would dissolve. ***The Screening Chaos framework would annihilate itself at the moment of its own success.*** *The conversion cycle, Δ, and the very notion of residuum would become vacuous, therefore:* ***Axiom of χ-Irreducibility:*** *For every finite hierarchy of conversion operators $\{F_k\}$ from k = 0 to n, there exists a non-empty irreducible residuum:*

$$\forall \{F_k\}_{k=0}^{n} : \chi_{irr} = \cap_k \chi_{irr}(F_k) \neq \emptyset$$

Symbols used in the excerpt above:
$\{F_k\}_{k=0}^{n}$ *- a finite hierarchy of conversion operators, where each successive F_k is assumed to be capable of converting a subset of the current χ that its predecessors could not.*
$\chi_{irr}(F_k)$ *- the irreducible residuum relative to operator F_k: the portion of χ that F_k cannot convert.*
χ_{irr} *- the intersection $\cap_k \chi_irr(F_k)$ across the full hierarchy: the portion of χ that no operator in the hierarchy can convert. The axiom asserts that this set is non-empty: not as a theorem derived from deeper principles, but as a necessary consistency condition of the framework. Were $\chi_{irr} = \emptyset$ possible,*

*conversion would be finite, χ would vanish, and (since **$\mathcal{E} \subseteq \Omega$** by definition) **$\Omega = \mathcal{E}$**, so the concept of chaos as residuum would lose its meaning. Three consequences follow:*

***First** - the conversion cycle is infinite but asymptotic. There is always work to do, but it will never be complete. This is consistent with Δ as the measure of change: change does not end.*

***Second** - chaos is not an enemy to be defeated but a permanent partner in navigation. The word used in earlier discussion was domestication: not elimination, not control, but coexistence with what cannot be expressed.*

***Third** - this mirrors the structure of the Relational Sufficiency Hypothesis (RSH) in the Triptych framework (Addendum I - Relational Sufficiency Hypothesis (RSH) published as a separate document within the same Zenodo record as the main Triptych release): a relation is never fully knowable. There is always a residuum that escapes the metric. But what the metric captures is real and has value. Each step of conversion matters, even though the process has no final step."*

The research programme (Toward a Mathematics of χ ⇒ P Conversion /…/) proposes a formal architecture for this conversion, including boundary entropy H_∂($\mathcal{E}$), a convertibility coefficient κ_i, a dimension-generating operator G_i, and an axiom of χ-irreducibility stating that for any finite hierarchy of conversion operators, a non-empty irreducible residuum persists - not as an empirical claim but as a structural consistency condition of the framework.

6.3. For the reversibility of conversion

As noted in the main Screening Chaos document and confirmed in subsequent analysis: χ is not a fixed set. It is a dynamic residuum that can both shrink (as the current $\mathcal{E}$ expands) and grow (as models fail, paradigms shift, or conditions change). Converted χ is therefore not permanently captured. Under sufficiently disruptive conditions, events converted into $\mathcal{E}$ may return to χ if the formalism F that captured them ceases to apply. This implies that χ-conversion is a continuous process, not a one-time achievement, consistent with Δ as the measure of monotonically accumulated change.

7. Summary

This supplement extends the Screening Chaos framework by introducing a third regime of the chaos function χ:

(a) **Low-amplitude χ** - structured noise, parametric perturbation within the model.
(b) **High-amplitude χ** - disruptive operator that shatters the current state-space.
(c) **Converted χ** - chaos deliberately captured and transformed into probabilistically tractable structure through novel formalisms.

The core proposition is that the capacity to convert χ into P_M constitutes a qualitative, non-transferable strategic advantage: "agents" who can perform this conversion inhabit a wider modelable world than those who cannot. The development of formalisms capable of systematic χ ⇒ P_M conversion - chaotic equations that operate on the boundary between the modelled and the unmodelled - is identified as an open mathematical programme with potential applications in strategic foresight, resilience engineering, quantum computing heuristics, and collaborative human-AI cognition (semisymbiosis; see Triptych: https://doi.org/10.5281/zenodo.17219502).

***
© 2026 Mariusz Włodarczyk
mariusz.wlodarczyk@hotmail.com
www.linkedin.com/in/mariusz-włodarczyk-7bb61027
***
This work is licensed under the Creative Commons
Attribution-NonCommercial-NoDerivatives 4.0 International License (CC BY-NC-ND 4.0)
Supplement v0.1_2026 (aligned with: IEH v1.0.2, PNP v2.0 and Screening Chaos v0.1)
***