


California State Polytechnic University, Pomona
Autonomous Vehicle Laboratory
IGVC 2026 Design Report

MARVIN

Challenge Targeted: AutoNav



I hereby certify that the development of the vehicle, *MARVIN*, as described in this report, is equivalent to the work involved in a senior design course.

Faculty Advisor Signature

Submitted May 15, 2026

Role	Name / E-mail / Phone
Team Captain (primary)	Parsa Ghasemi — mghasemi@cpp.edu — 424-844-8222
Key Team Member (secondary)	[Name – email – phone]
Faculty Advisor (tertiary)	Dr. Behnam Bahr — bbahr@cpp.edu — 949-690-5519

Scan of Faculty Advisor's Signed Statement of Integrity attached as a separate PDF per IGVC 2026 rule IV.3.

0. Contents

1	System and Subsystem Requirements	1
1.1	System Engineering Process	1
1.2	Requirements Summary	1
2	Mechanical Design	2
2.1	Overview	2
2.2	Drivetrain	3
2.3	Frame, Housing, and Sensor Mast	3
2.4	Weatherproofing	4
2.5	Mechanical Requirements Compliance	4
3	Safety	5
3.1	Transport, Parked, and Charging Safety	5
3.2	On-Course Safety	5
3.3	Safety Requirements Compliance	6
4	Electrical and Electronic Design	6
4.1	Overview	6
4.2	Power Distribution	7
4.3	Motor Control	8
4.4	Sensors	8
4.5	Network and Computation	8
4.6	Bill of Materials	9
4.7	Electrical Requirements Compliance	9
5	Perception	9
5.1	LiDAR Perception (Velodyne VLP-16)	10
5.2	Vision Perception (3× ZED X)	10
5.3	Internal Course Representation (Costmap)	10
5.4	AutoNav Course-Specific Behavior	10
5.5	Perception Requirements Compliance	11
6	Driving Logic	11
6.1	Planning and Path Generation	11
6.2	Localization	12
6.3	Drive Control	12
6.4	AutoNav Driving Logic	12
6.5	Driving Logic Requirements Compliance	13
7	Key Performance Indicators	13
8	Analysis of Complete Vehicle	13
8.1	Lessons Learned	13
8.2	Failure Points and Resolutions	14

8.3	Safety, Reliability, and Durability	14
8.4	Software Testing, Bug Tracking, and Version Control	14
8.5	Simulation and Physical Testing	14
9	Cyber Security Analysis	15

1. System and Subsystem Requirements

1.1 System Engineering Process

The Cal Poly Pomona Autonomous Vehicle Lab (AVL) at California State Polytechnic University, Pomona presents MARVIN, our entry for the IGVC 2026 AutoNav challenge. AVL is an undergraduate research lab within the College of Engineering focused on autonomy, embedded systems, and ground-vehicle perception. The IGVC subteam of **[N]** students is organized across software, mechanical, and electrical disciplines, advised by Dr. Behnam Bahr, and led by Parsa Ghasemi as project captain. MARVIN is a fully autonomous differential-drive tracked vehicle built on the AndyMark Raptor chassis, fusing a Velodyne VLP-16 3D LiDAR, three Stereolabs ZED X stereo cameras, and an Xsens MTi-680G IMU+GNSS, with autonomy running on an NVIDIA Jetson Orin under ROS 2 Humble. The team followed an iterative *research* → *design* → *prototype* → *test* cycle: rulebook analysis → system-level requirements; parallel subsystem development; incremental bench/actuator/fusion/Nav2 integration; and iterative field testing at the Cal Poly Pomona Engineering Meadow to tune HSV thresholds, EKF covariances, costmap parameters, and MPPI critic weights. Figure 1 shows the resulting system architecture.




Figure 1: MARVIN system architecture. Sensors feed perception and localization; Nav2 composes costmaps, plans (NavfnPlanner), and follows the plan (MPPI Controller). The actuator node converts `/cmd_vel` to per-wheel RPM and forwards it to the Teensy over USB serial; the Teensy bridges to two SparkMAX motor controllers over CAN.

1.2 Requirements Summary

Per IGVC 2026 rule IV.3 §3, the requirements below list at least 2 each for mechanical, safety, electrical/electronic, perception, driving logic, and key performance indicators. We are targeting

the AutoNav challenge, so 12 requirements are listed. Each row cites the rule (or internal source) driving it, the measurement method, and the target value.

Table 1: System and subsystem requirements (AutoNav target, 12 rows).

Category	Requirement	Source / Measurement	Target
Mechanical	Vehicle length within 3–7 ft	IGVC I.2 / tape measure	36" (3 ft)
Mechanical	E-stop button mounted 2–4 ft above ground, centered rear	IGVC I.2 / tape measure	24"
Safety	Wireless E-stop range (margin over 100 ft minimum)	IGVC I.2 & I.4 / open-field radio range test	≥ 150 ft
Safety	Hardware-governed maximum ground speed	IGVC I.2 / GPS + treadmill	≤ 5 mph
Electrical	Battery runtime under nominal autonomous load	IGVC IV.3 §6 / dyno burndown	≥ 6 min (1 margin run)
Electrical	Per-rail fault isolation	Internal / short one rail, verify others	All other rails active
Perception	Obstacle detection range (local costmap)	IGVC II.2 / VLP-16 ranging on barrel	≥ 2 m
Perception	Lane detection pixel recall under varied lighting	Internal / labeled image set	$\geq 95\%$
Driving logic	Obstacle reaction time	Internal / log latency STVL update $\rightarrow$ cmd_vel	≤ 250 ms
Driving logic	Waypoint arrival accuracy (2 m IGVC tolerance)	IGVC I.4 / GPS log distance to waypoint	≤ 1 m
KPI	Course completion time (6 min IGVC ceiling)	IGVC II.2 / wall clock	≤ 5 min
KPI	Ramp ascension success ($\leq 15\%$ gradient per IGVC II.2)	IGVC II.2 / pass-fail	Pass

Each “Requirements Compliance” subsection at the end of §2–§6 compares these target values against the most recently measured values.

2. Mechanical Design

2.1 Overview

As first-year IGVC participants, the mechanical subteam prioritized a simple, modular, and cost-effective platform that concentrates budget on the sensors and compute required for autonomous navigation. MARVIN is built on the commercially available AndyMark[®] Raptor Track Drive, a tracked differential base selected for its all-terrain traction and short delivery lead time. A reconfigurable 80/20 T-slot aluminum superstructure is mounted directly to the chassis, allowing rapid iteration on sensor mounts and shelf geometry through the design cycle. The same chassis can host different electronics housings for future competitions; for IGVC 2026 the housing is mounted on the upper shelf so that the electronics, payload, and E-stop are all readily accessible during operation and inspection. The integrated vehicle is shown on the cover page; a rear-three-quarter view is in Figure 2.




Figure 2: Rear three-quarter view of MARVIN; the rear shelf supports the mechanical E-stop and extends the chassis to meet the IGVC 3 ft length minimum.

2.2 Drivetrain

MARVIN uses a tracked **differential-drive** architecture: two REV NEO brushless motors, each commanded by a REV SparkMAX controller over CAN, independently drive the left and right track loops. The choice eliminates steering linkages, reduces the part count, and produces a control plant that maps cleanly onto the ROS 2 Nav2 / MPPI controller running on the Jetson. With v_L and v_R the left and right track linear velocities, the body-frame linear and angular rates are

$$v = \frac{1}{2}(v_R + v_L), \quad \omega = \frac{1}{b}(v_R - v_L), \quad (1)$$

where b is the track width (effective lever arm between contact patches). The planner uses three operating modes: pivot turn (one track held, robot rotates about the stationary contact patch); in-place spin ($v_R = -v_L$, ICR at the vehicle center, maximum yaw rate); and gradual curve (both tracks forward, $v_R \neq v_L$).

The full electromechanical signal path (also shown in Figure 1 and Figure 4) is: Jetson Orin issues `geometry_msgs/Twist` at 50 Hz over USB serial to the Teensy 4.1; the Teensy decomposes commands into per-side wheel velocities and forwards them over CAN at 1 Mbit/s to the two SparkMAX controllers; each SparkMAX closes a 1 kHz velocity loop around its NEO motor using the integrated Hall encoders.

2.3 Frame, Housing, and Sensor Mast

The Raptor base contributes the drive sprockets, idlers, and rubber-track belts that distribute vehicle weight over a large contact patch, improving traction and stability on the uneven turf and gravel sections of the IGVC course. A 21.5" × 30", 1/8" thick A36 diamond-plate steel base is bolted directly to the Raptor mounting rails. The diamond plate serves three functions: (i) a rigid surface for heavy components, (ii) an EMI-attenuating ground plane between battery and tracked drive, and (iii) a low-mounted mass that lowers the center of gravity. The superstructure is built from 80/20® 20-Series T-slot aluminum extrusion — modular, reconfigurable, and free of exposed threaded ends.

Weight placement was an explicit design priority. The 48 V battery is mounted at the geometric center of the diamond plate; the 20 lb payload bay sits at the front of the deck on a 3D-printed cradle. The resulting center of gravity sits slightly forward of the track midpoint and low on the deck, minimizing pitch moment on inclines and during skid-steer turns. The diamond-plate deck is $21.5'' \times 30''$ and the upper sensor shelf is $23'' \times 23'' \times 6''$ mounted 20 in above ground; the rear shelf carries the E-stop button at 24'' (Figure 2). The chassis was extended with that rear shelf to satisfy both the IGVC 3 ft minimum length and the 2–4 ft E-stop mounting requirement.

Table 2: MARVIN vehicle specifications.

Parameter	Value
Drive configuration	Tracked differential (skid-steer)
Base platform	AndyMark Raptor Track Drive
Overall length $\times$ width	$\sim 36'' \times 24''$ (meets 3 ft min.)
Overall vehicle height (excl. E-stop antenna)	$\sim 29''$ (~ 2.4 ft; well under 6 ft IGVC max)
Sensor-shelf height	20'' (top surface)
E-stop mounting height	24'' (rear shelf, centered)
Payload capacity (verified)	≥ 20 lb
Drive motors	2 $\times$ REV NEO brushless (12–48 V)
Motor controllers	2 $\times$ REV SparkMAX (CAN, 1 Mbit/s)
Battery pack	Aegis 48 V 25 Ah LiFePO ₄ , center-mounted
Frame material	80/20 20-Series T-slot aluminum extrusion
Deck material	1/8" A36 diamond-plate steel
Weather panels	Polycarbonate / acrylic in T-slot grooves

2.4 Weatherproofing

Outdoor operation requires the electronics bay to tolerate rain and direct sun. The sensor-shelf walls are cut-to-fit acrylic panels that slide directly into the 20-Series T-slot grooves; weather-stripping gasket fills the residual gap and remains seated under track vibration. The top panel is mildly angled for water runoff and incorporates a sliding access door. The LiDAR is mounted externally above the shelf to keep its 360° field of view unobstructed; the ZED X cameras sit behind AR-coated windows.

2.5 Mechanical Requirements Compliance

Table 3: Mechanical requirements: target vs. measured.

Requirement	Target	Measured
Vehicle length (3–7 ft IGVC range)	36''	$\sim 36''$ (verified)
Vehicle width (2–4 ft IGVC range)	24''	$\sim 24''$ (verified)
Vehicle height (≤ 6 ft IGVC excl. antenna)	$\sim 29''$	$\sim 29''$ (verified)
E-stop button mounting height (2–4 ft IGVC band)	24''	24'' (verified)
Payload capacity (20 lb cinder block per IGVC I.3)	≥ 20 lb	≥ 20 lb (verified)
Track width b for diff-drive kinematics	0.7366 m	0.7366 m (verified)

3. Safety

3.1 Transport, Parked, and Charging Safety

[Describe transport tie-downs, parked-state interlocks, and battery charging procedures. Required items per IGVC 2026 rule IV.3 §5: how the robot is secured during transport; how the motor controllers are de-energized when parked; and the safety procedure used during battery charging (cutoff thresholds, charger isolation from drive bus, location, and supervision).]

3.2 On-Course Safety

The on-course safety architecture (Figure 3) implements a hardware-enforced two-channel emergency stop: either the rear-mounted mechanical E-stop button or the wireless remote E-stop receiver opens a relay in series with the motor-controller enable line. When the relay opens, the SparkMAX controllers immediately disable PWM output and brake the NEO motors via the integrated short-brake mode; software is not in the loop, so a Jetson hang or ROS crash cannot defeat the stop. Indicator LEDs visible from outside the chassis show the armed/disarmed state for the IGVC safety inspection.




Figure 3: Two-channel emergency stop. The mechanical (rear-shelf) and wireless E-stops are wired in series with the motor-enable relay; either one open de-energizes both SparkMAX controllers, independent of software state.

In software, the actuator node additionally zeroes `cmd_vel` on stale input (300 ms watchdog) so a Jetson stall or ROS-node crash defaults the vehicle to a stop even before the hardware relay reacts. A firmware speed clamp at ± 4600 RPM (1.53 m/s ground speed) further limits the worst-case motion even if upstream commands are malformed.

3.3 Safety Requirements Compliance

Table 4: Safety requirements: target vs. measured.

Requirement	Target	Measured
Wireless E-stop range (IGVC 100 ft minimum)	≥ 150 ft	>100 ft (verified)
Hardware max ground speed cap	≤ 5 mph	3.4 mph (1.53 m/s)
E-stop button mounting height	2–4 ft	24" (verified)
Software serial watchdog timeout	≤ 500 ms	300 ms
SparkMAX CAN heartbeat timeout (per controller)	≤ 200 ms	100 ms
Firmware RPM clamp ($\rightarrow$ ground-speed cap)	≤ 4600 RPM (≤ 5 mph)	± 4600 RPM (1.53 m/s)

4. Electrical and Electronic Design

4.1 Overview

The 2026 electrical architecture is organised into four subsystems: power distribution, network and computation, sensing, and motor control. Figure 4 shows how these subsystems interconnect.

- **Power** — a 48 V battery feeds two buck converters (12 V and 5 V rails) that supply the rest of the vehicle (§4.2).
- **Compute** — a Jetson Orin GPU handles perception and high-level control. It commands a Teensy 4.1 microcontroller over USB serial (§4.5).
- **Sensing** — three ZED X stereo cameras, a Velodyne LiDAR, and an Xsens GPS feed the Jetson (§4.4).
- **Motor control** — the Teensy runs a closed-loop controller and commands two SPARK MAX motor controllers over CAN, which in turn drive two NEO brushless motors (§4.3).




Figure 4: System-level electrical block diagram.

4.2 Power Distribution

The vehicle is powered by an Aegis 48 V 25 Ah LiFePO₄ deep-cycle lithium battery (1.2 kWh nominal). LiFePO₄ chemistry was selected for its thermal stability, ~ 2000 -cycle service life, and tolerance to partial-state-of-charge operation between practice runs. The battery passes through a main switch into two buck converters (also shown in Figure 4): a 12 V / 20 A converter for the motor controllers and other high-power loads, and a 5 V / 6 A converter for the Teensy 4.1 and low-power peripherals. Each rail is split into three independently fused output branches (battery $\rightarrow$ switch $\rightarrow$ buck $\rightarrow$ 3 fused branches per rail) so a short on one load does not pull down the rest of the vehicle.

Run time and recharge. A 25 Ah pack at 48 V stores ~ 1200 Wh. Estimated nominal load under autonomous operation is ~ 155 W (Jetson Orin ~ 30 W, VLP-16 LiDAR 8 W, $3 \times$ ZED X ~ 9 W, Xsens IMU/GPS 1 W, router 5 W, Teensy < 1 W, drive motors ~ 100 W average over typical IGVC speeds), which corresponds to ~ 3.2 A at the 48 V bus. Allowing for buck-converter and battery losses ($\eta_{\text{tot}} \approx 0.85$), the calculated runtime is $\sim 1200 \text{ Wh} \times 0.85 / 155 \text{ W} \approx 6.5$ hours — two orders of magnitude above the 6-minute IGVC II.2 course ceiling and enough for a full practice day on a single charge under realistic load.

The pack is recharged with a DC House 48 V 18 A LiFePO₄ portable charger (model S-US-L131211800092-1, 58.4 V CV output, 18 A bulk-charge current, IP65). At 18 A bulk current, a fully depleted 25 Ah pack reaches $\sim 80\%$ state of charge in ~ 1.4 hours; with the LiFePO₄ absorption phase and cell balancing, a full recharge takes approximately 1.5–2 hours. Charging is performed outside the vehicle with the battery disconnected from the drive bus.

4.3 Motor Control

The drivetrain uses two NEO brushless motors, each driven by a SPARK MAX motor controller. Both controllers share a single CAN bus to the Teensy 4.1, which acts as the real-time control node. Each SPARK MAX reports position and velocity from its integrated encoder back over the same bus. The Teensy closes a PID velocity loop per wheel, using encoder feedback from the SPARK MAX controllers and reference velocities published by the Jetson over USB serial. Because the motor controllers, the encoders, and the microcontroller all live on one CAN bus, no separate signal wiring between the motor controllers and the Teensy is required.

Firmware. The Teensy 4.1 translates ASCII RPM commands into SparkMAX CAN velocity setpoints at 1 Mbit/s and echoes encoder feedback at 50 Hz. Three independent timeouts protect the drivetrain: a 300 ms serial watchdog on the Teensy, a 100 ms CAN heartbeat timeout per SparkMAX, and a firmware clamp of ± 4600 RPM (1.53 m/s ground speed, below the 5 mph IGVC cap).

4.4 Sensors

Stereo cameras. Three ZED X cameras (front-left, front, front-right) connect to a ZED Link Quad over GMSL2; the ZED Link Quad attaches to the Jetson over PCIe, keeping the cameras off the Ethernet network.

LiDAR. A Velodyne VLP-16 provides 360° 3D point clouds at 10 Hz. It reports to the Jetson over Ethernet through the on-board router.

GPS / IMU. An Xsens MTi-680G provides 9-axis inertial data at 100 Hz and a standalone GNSS fix at 5 Hz (RTK disabled per IGVC rules). It connects directly to the Jetson over USB.

4.5 Network and Computation

The Jetson Orin is the primary computation unit; it runs perception, sensor fusion, and trajectory generation, and publishes wheel velocity commands to the Teensy. An on-board router carries Ethernet between the Jetson and the Velodyne LiDAR. The Teensy 4.1 connects to the Jetson via USB serial (115200 baud) rather than Ethernet. The high-bandwidth camera link is kept separate: the ZED Link Quad attaches directly to the Jetson over PCIe so that the three ZED X feeds do not contend for the Ethernet network. The Xsens GPS connects directly to the Jetson. The same router also exposes a Wi-Fi link to a remote laptop for monitoring, data capture, and remote shutdown during testing.

4.6 Bill of Materials

Table 5: Bill of significant components (estimated team cost).

Qty	Component	Subsystem	Cost
1	NVIDIA Jetson AGX Orin 64GB Developer Kit (JetPack 6, ROS 2 Humble)	Compute	\$1,999.00
2	REV NEO Brushless Motor v1.1 (REV-21-1650) @ \$50.00 ea	Drivetrain	\$100.00
2	REV SPARK MAX Motor Controller (REV-11-2158) @ \$100.00 ea	Drivetrain	\$200.00
1	PJRC Teensy 4.1 (SparkFun)	Firmware bridge	\$31.50
1	Waveshare SN65HVD230 CAN transceiver breakout	Firmware bridge	\$8.00
1	Velodyne VLP-16 Puck 3D LiDAR (discontinued by Ouster 2025; last announced retail)	Perception	\$4,000.00
3	Stereolabs ZED X stereo camera (GMSL2) @ \$599.00 ea	Perception	\$1,797.00
1	ZED Link Quad GMSL2 capture card	Perception	\$489.00
1	Xsens MTi-680G RTK GNSS/INS (DigiKey)	Localization	\$3,612.50
1	AndyMark Raptor Track Drive (full chassis)	Mechanical	\$423.00
1	Aegis 48 V 25 Ah LiFePO ₄ deep-cycle battery	Power	\$464.78
1	DC House 48 V 18 A LiFePO ₄ charger (58.4 V CV, IP65)	Power	\$129.99
1	Safety light, wireless E-stop, push-button, wiring, misc.	Safety / Misc.	\$500.00
Total estimated market cost			\$13,754.77

4.7 Electrical Requirements Compliance

Table 6: Electrical/electronic requirements: target vs. measured.

Requirement	Target	Measured
Battery runtime (1 course run @ 6 min + margin)	≥ 6 min	~ 6.5 h calc.; [measured min]
Battery pack voltage	48 V nominal	48 V (verified)
12 V rail capacity (motor controllers)	≥ 20 A	20 A buck (verified)
5 V rail capacity (Teensy + low-power)	≥ 6 A	6 A buck (verified)
Per-rail fault isolation	All other rails active	[verified pass/fail]
Full recharge time (18 A bulk, 25 Ah pack)	≤ 2 h	~ 1.5 – 2 h calc.; [measured]
CAN bus rate	≥ 500 kbit/s	1 Mbit/s (verified)

5. Perception

The perception stack splits responsibilities between LiDAR (physical obstacles) and cameras (painted lane lines and color-coded objects), with both feeding a unified costmap consumed by the driving-logic layer. We are targeting the AutoNav challenge, so this section discusses lane and obstacle perception specific to the AutoNav course.

5.1 LiDAR Perception (Velodyne VLP-16)

The VLP-16 publishes a 360° point cloud at 10 Hz into Nav2's `spatio_temporal_voxel_layer` (STVL), which maintains a 0.1 m voxel grid with 5 s linear voxel decay. A minimum obstacle height of 0.2 m filters ground hits and low grass while keeping short barrels and pedestrians. Detection range is 1–15 m local and 1–50 m global. STVL replaces the standard `VoxelLayer` because the VLP-16's 16-beam $\pm 15^\circ$ vertical FOV leaves angular gaps that defeat ray-trace clearing when the robot is stationary; STVL clears via time-based voxel decay plus a frustum-accelerated decay term that handles the sparse-scan case cleanly.

5.2 Vision Perception (3× ZED X)

Each ZED X publishes rectified HD1080 color and a COMPACT-resolution organized point cloud at 10 Hz. The `avros_perception` package runs one `perception_node` per camera; each subscribes to its camera's RGB and cloud topics through an `ApproximateTimeSynchronizer` (20 ms slop) and runs a pluggable pipeline. The production pipeline (`hsv`) performs three-class HSV thresholding (white lane, orange barrel, pothole) with an adaptive value-channel floor ($V_{\text{floor}} = \mu_V + k\sigma_V$, recomputed every N frames) and a polygonal sky-rejection ROI. Class IDs: 1 = lane, 2 = barrel, 3 = pothole. All thresholds are runtime-tunable via `ros2 param set` for field calibration.

Every pipeline outputs the four-topic contract consumed by the `kiwicampus/semantic_segmentation_layer`: a mono8 class-ID mask, a mono8 confidence plane, the organized point cloud (relayed), and a latched `vision_msgs/LabelInfo`.

5.3 Internal Course Representation (Costmap)

Perception outputs are fused into two Nav2 costmaps: a 50×50 m rolling local costmap at 0.2 m resolution (`stvl_layer` + 3× `semantic_layer` front/left/right + `inflation_layer`) and a 100×100 m rolling global costmap (`obstacle_layer` + `inflation_layer`). The robot footprint is rectangular 1.00 × 0.74 m with $r_{\text{inscr}} = 0.5$ m and an inflation radius of 0.65 m. STVL voxel decay (5 s) keeps stale cells from blocking the planner after the robot moves; semantic raytrace clearing handles cells that have been re-observed as free.

5.4 AutoNav Course-Specific Behavior

The AutoNav course (IGVC II.2) features painted white lane lines $\sim 3''$ wide on asphalt, randomly placed construction barrels (white/orange/brown/green/black) at ≥ 5 ft clearance from the lane, an $\leq 15\%$ gradient ramp, simulated potholes (2 ft white circles), and GPS waypoint pairs at course entry/exit and ramp entry. The HSV pipeline tagged with class 1 isolates white lane paint; barrels register under class 2; potholes register under class 3; the VLP-16 STVL marks any other physical obstacle. A startup auto-calibration routine samples the ground at run start and adapts the V -channel threshold to current lighting before mobility is enabled.

5.5 Perception Requirements Compliance

Table 7: Perception requirements: target vs. measured.

Requirement	Target	Measured
Obstacle detection range (local costmap)	≥ 2 m	15 m (VLP-16 STVL range)
Obstacle detection range (global costmap)	≥ 2 m	50 m
Lane detection pixel recall	$\geq 95\%$	[measured]

6. Driving Logic

The driving-logic stack converts the perception costmap and current pose into wheel commands. Nav2 provides path planning, trajectory generation, and behavior orchestration (§6.1); `robot_localization` maintains the pose (§6.2); and the actuator node converts `cmd_vel` to wheel RPM (§6.3). AutoNav-specific course handling — lane following, obstacle avoidance, ramp, and waypoint navigation — is described in §6.4.

6.1 Planning and Path Generation

Table 8: Nav2 configuration (`nav2_params_humble.yaml`).

Component	Configuration
Planner	<code>NavfnPlanner</code> (Dijkstra) — chosen over <code>SmacPlannerHybrid</code> because the IGVC lane spacing (2–3 m) is narrower than Hybrid’s 2.31 m minimum turning radius
Controller	<code>MPPIController</code> — DiffDrive motion model, 2000 rollouts, 56 timesteps, model Δt 50 ms, 8 active critics
Local costmap	50×50 m rolling, 0.2 m resolution
Global costmap	100×100 m rolling, 0.2 m resolution
Footprint	Rectangular 1.00×0.74 m, $r_{\text{inset}} = 0.5$ m
Inflation	$r_{\text{infl}} = 0.65$ m, $k_{\text{scale}} = 3.0$
Goal tolerance	xy 2.0 m (IGVC waypoint acceptance), yaw 0.5 rad
Controller frequency	20 Hz; planner replans at 1 Hz via BT <code>RateController</code>

MPPI samples 2,000 rollout trajectories per 20 Hz control cycle, scores them against eight plugin-based critics (constraint, cost, goal, goal-angle, path-align, path-follow, path-angle, prefer-forward), and emits the noise-weighted optimal command. Unlike pursuit controllers that only *follow* a path, MPPI *generates* trajectories that deviate from the global plan to avoid newly observed obstacles — critical for IGVC’s randomly-placed barrels.

Behavior tree. The active BT (`navigate_igvc_autonav_humble.xml`) wraps the standard plan-follow pipeline with several IGVC-specific guards. An outer `Timeout` of 45 s margins the 60 s hold-up-traffic disqualification rule. A `RecoveryNode` retries the pipeline up to three times; recovery actions form a `RoundRobin` escalating clear-costmap → wait → short backup → crawl forward. Spin-in-place is intentionally omitted: the 1.00×0.74 m footprint sweeps a 2.48 m diameter circle when off-center, exceeding the half-lane width.

Waypoint orchestration. The `mission_manager` node loads competition waypoints from `waypoints.yaml` as a lat/lon list, converts each to map frame via `/fromLL`, and fires `NavigateToPose` action goals sequentially. The cursor advances on a 2 m acceptance radius (IGVC rule); `ABORTED/CANCELED` failures fall through to the next waypoint.

6.2 Localization

Localization uses two instances of `robot_localization`'s EKF; both run at 30 Hz in 2D mode. The local EKF (`odom` $\rightarrow$ `base_link`) fuses Xsens IMU (100 Hz), wheel odometry from the actuator node (50 Hz), and ZED X VIO yaw (yaw-only, fused differentially to avoid the lever-arm bias from the camera's offset mount). The global EKF (`map` $\rightarrow$ `odom`) fuses the IMU stream with GPS odometry from `navsat_transform_node` in differential mode with a 6σ Mahalanobis outlier-rejection threshold. Integrating per-step GPS deltas rather than absolute fixes prevents costmap jumps from ± 2 –5 m consumer-grade GNSS noise (RTK is disabled per IGVC rules).

6.3 Drive Control

The `actuator_node` bridges Nav2 to the physical drivetrain. It subscribes to `/cmd_vel` (from Nav2, teleop, or the velocity smoother) and runs a 50 Hz loop: (1) source arbitration; (2) slew-rate limit (linear 0.5 m/s^2 accel, 1.5 m/s^2 brake; angular 1.0 rad/s^2); (3) IMU-based heading hold ($K_p = 1.5$) when $|\omega_{\text{cmd}}| < 0.05 \text{ rad/s}$, or gyro-stabilized turn ($K_p = 0.3$) otherwise; (4) diff-drive inverse kinematics with `track_width_m=0.7366`, `m_per_motor_rev=0.01994`; (5) ASCII serial write to the Teensy at 115200 baud. In parallel, encoder feedback is integrated into a 50 Hz `/wheel_odom` message that the local EKF consumes.

6.4 AutoNav Driving Logic

- **Lane following:** HSV white-lane masks feed the local costmap's `semantic_layer` as lethal cells; MPPI generates rollouts that stay inside the lane corridor.
- **Obstacle avoidance:** VLP-16 STVL marks barrels in both costmaps; MPPI's `PreferForwardCritic` and `PathFollowCritic` bias toward forward motion along the global plan when no obstacles intrude.
- **Ramp handling:** The 2D-mode EKF assumption holds for the IGVC ramp; pitch is monitored from the IMU. MPPI's cost-regulated velocity scaling automatically slows the robot near costmap inflation.
- **Switchbacks and dead-ends:** The BT recovery escalation (clear-costmap $\rightarrow$ wait 2 s $\rightarrow$ backup 1.5 m at 0.08 m/s $\rightarrow$ crawl forward 0.15 m at 0.10 m/s) reorients the planner when the global plan is repeatedly blocked, allowing the robot to back out of dead-ends and switchbacks.
- **Potholes:** The HSV pipeline's class 3 channel marks the IGVC 2 ft white-circle simulated potholes as lethal in the local costmap; MPPI rollouts that would enter a pothole are scored as collisions and rejected.
- **Traps and complex obstacles:** The 50×50 m local costmap holds obstacles long enough for MPPI to consider alternate paths; the inflation gradient ($k_{\text{scale}} = 3.0$) gives MPPI a smooth cost field so rollouts naturally funnel through the widest gap between barrels.

6.5 Driving Logic Requirements Compliance

Table 9: Driving logic requirements: target vs. measured.

Requirement	Target	Measured
Obstacle reaction time (STVL update $\rightarrow$ cmd_vel)	≤ 250 ms	47 ms
Waypoint arrival accuracy (2 m IGVC tolerance)	≤ 1 m	< 1 m
Minimum average speed (44 ft IGVC stretch)	≥ 1 mph	[measured]

7. Key Performance Indicators

Table 10: AutoNav key performance indicators: target vs. measured.

KPI	Target	Measured
Course completion time (Webots simulation)	≤ 5 min	[measured min]
Course completion time (field, IGVC 6 min ceiling)	≤ 5 min	[measured min]
Ramp ascension ($\leq 15\%$ gradient per IGVC II.2)	Pass	[Pass/fail]
Maximum ground speed (hardware-governed)	≤ 5 mph	3.4 mph (1.53 m/s)
Minimum average speed (44 ft hold-up rule)	≥ 1 mph	[measured mph]
Obstacle reaction time	≤ 250 ms	47 ms
Battery runtime under autonomous load	≥ 6 min	~ 6.5 h calc.; [measured min]
Wireless E-stop range (100 ft IGVC minimum)	≥ 150 ft	> 100 ft (verified)

Target rationale. Course completion is set at ≤ 5 min, one minute under the IGVC II.2 six-minute ceiling, leaving margin for a slow restart after a `RecoveryNode` fallback. Maximum speed is hardware-governed at 3.4 mph (below the 5 mph rule cap and above the 1 mph minimum hold-up threshold), giving the MPPI controller a stable operating point. Battery runtime targets at least one full 6 min course run plus margin for warm-up and a queued retry. The wireless E-stop has been verified to operate beyond the IGVC 100 ft minimum with a comfortable margin to absorb multipath and antenna-orientation variability during the open-field range test.

8. Analysis of Complete Vehicle

8.1 Lessons Learned

[Describe what the team learned during construction and system integration. Examples: integration sequencing (bench $\rightarrow$ stand-up $\rightarrow$ field), benefit of starting with a COTS chassis, importance of fusing IMU yaw rather than wheel-only odometry, field-tuning of HSV thresholds, etc.]

8.2 Failure Points and Resolutions

Table 11: Known failure modes and mitigations.

Layer	Failure	Mitigation
Mechanical	Fasteners loosen under vibration	Loctite + Nyloc nuts; periodic torque checks
Electrical	Motor inrush brown-out on shared rail	Separate Jetson power rail
Electrical	Wireless E-stop link loss	Heartbeat timeout cuts motor relay power
Sensing	Encoder dropout	Local EKF reverts to IMU prediction
Sensing	GPS multipath / dropout	6σ outlier rejection; differential fusion
Perception	HSV threshold drift across lighting	Adaptive V-floor; live-tunable HSV bounds
Costmap	Stale semantic cells linger	STVL 5 s decay; semantic raytrace clearing
Software	Stale <code>cmd_vel</code>	300 ms watchdog forces motor stop

8.3 Safety, Reliability, and Durability

Safety is enforced at every layer: a hardware speed cap (4600 RPM $\rightarrow$ 1.53 m/s) in the Teensy firmware, a 300 ms serial watchdog on the Teensy, a 100 ms CAN heartbeat timeout per SparkMAX, a software slew-rate limit in the actuator node, and Nav2’s MPPI collision critic plus a costmap inflation radius of 0.65 m. The MPPI `CostCritic` uses `consider_footprint: true` so the rectangular 1.00×0.74 m footprint is swept along every rollout trajectory.

8.4 Software Testing, Bug Tracking, and Version Control

Software is developed in a Git repository (github.com/Paarseus/IGVC_ROS2) with feature branches, pull-request review, and automated linting via `colcon test`. All parameters — perception thresholds, EKF covariances, Nav2 gains, MPPI critic weights, actuator slew limits — live in version-controlled YAML.

8.5 Simulation and Physical Testing

Development and regression testing use the `avros_sim` package, which runs Webots with a `cpp_campus.wbt` world imported from the Cal Poly Pomona OpenStreetMap extract. A custom Webots driver publishes simulated VLP-16, ZED, and GNSS topics that the rest of the stack consumes unchanged, enabling perception and Nav2 development without field time.

Physical testing progresses through four stages: bench (subsystem in isolation), simulation (Webots full stack), low-speed field tests on a flat surface, and full-speed field tests on the IGVC practice course.

[Identify the key differences observed between simulation and the real-world test course (e.g., GPS noise floor, lighting variance vs. Webots, suspension dynamics not modeled in Webots). Describe how the test data drove parameter changes.]

9. Cyber Security Analysis

Modern robotic and human-driven vehicles are network-connected, contain large amounts of software from multiple vendors, and are an inviting target for cyber-attacks. Per IGVC 2026 rule IV.3 §11, we list three cyber vulnerabilities present in our vehicle and discuss the steps that should be taken to harden or remove them before the system enters series production.

Table 12: Top three cyber vulnerabilities and hardening steps.

Vulnerability	Risk	Hardening / Remediation
Onboard network breach	Wi-Fi foothold exposes the ROS 2 discovery service (unauthenticated by default), allowing <code>cmd_vel</code> injection.	Dedicated subnet with WPA2 (SC-7); CycloneDDS Security with X.509 identities and access-control governance (AC-3).
WebSocket joystick hijack	The <code>avros_webui</code> WebSocket can override autonomous <code>cmd_vel</code> from a local-network attacker.	WSS with pinned cert; session token at pair time; fail-safe disconnect → E-stop (AC-3, IA-2).
GPS spoofing / multipath	Spoofed GPS could feed the global EKF a false position, advancing the waypoint cursor prematurely.	Differential GPS fusion (per-step deltas); 6σ Mahalanobis outlier rejection (SI-4, SI-7); cross-check GPS heading vs IMU heading.

In addition to the three vulnerabilities above, safety-critical motion is gated by three independent stop mechanisms (physical E-stop, wireless E-stop, software interlock in the actuator node) so a single cyber-compromise of the autonomy stack does not by itself produce uncontrolled motion — the hardware relay must be re-enabled by a human operator.