White test

1.set the root password to “azerty”

Rd.break, ctrl+x

Mount –o remount,rw /sysroot

Chroot /sysroot /

Echo “azerty” | passwd –stdin root

Exit

Reboot

2.set the network configuration as follows:

*ip : 192.168.4.110

*subnet mask : 255.255.255.0

*gateway: 192.168.4.2

* dns :192.168.4.110

Nmcli connection modify eth0 ipv4.addresses 192.168.4.110/24 ipv4.gateway “192.168.4.2” ipv4.dns 192.168.4.110 ipv4.method manual connection.autoconnect yes

Nmcli connection up eth0

Ip a

*hostname: rhcsa.example.com

Hostnamctl set-hostname rhcsa.example.com

3.set selinux policy to enforcing

Vim /etc/selinux/config

Selinux=enforcing

Getenforcing pour verifier si enforcing ou bien permissive

4.created users and groups have a minimum uid and gid of 1100 and 1900 as maximum

Vim /etc/login.defs

Min-UID = 1100

Min-GID = 1900

5.set the password policy as follows:

*minimum 8 caracteres length

*1 digit

*1 special character

Vim /etc/security/pwquality.conf

Minlen=8

Dcredit=-1

Ocredit= -1

6.create groups redhat and tekup with respective gid 1300 and 1345

groupadd redhat –g 1300
groupadd tekup –g 1345

7.create users :

user1 , user2 and user3 as follow:

useradd user1

useradd user2

useradd user3

* all users have their password set to “azerty”

Passwd user1, azerty

Passwd user2, azerty

Passwd user3, azerty

*user1 has 1300 as uid and a comment “admin”

Usermod –a user1 –u 1300 –c “admin” –g tekup

*user2 has a service account

Usermod –a user2 –g redhat –s /sh/bin

*user3 has a home directory “/home/test”

Usermod –a –G tekup –G redhat –d /home/test

*user1 has tekup as his primary group , user2 has redhat as primary group, user3 has both groups as secondary

8.

user2 password will expire after 30 days , has a minimum password age of 5 and 20 for maximum , 7 days of warning.

Chage –E 2020-01-13 user2

Chage –m 5 user2

Chage –M 20 user2

Chage –W 7 user2

make user2’s password expire

chage –l user2

9.create directory “/home/tekup”.

Mkdir –p /home/tekup

tekup group members have full permissions on this directory

setfacl –m g:tekup:rwx /home/tekup

redhat group members has read and write permissions,

setfacl –m g:redhat:rw- /home/tekup

and others have none.

Chmod o=--- /home/tekup

Files created in this directory have redhat as a group.

Chgrp redhat /home/tekup

Chmod 2770 /home/tekup ou bien chmod g+s /home/tekup

user1 have full permissions on the directory group.

Setfacl –m u:user1:rwx /home/tekup

10.copy ‘/etc/passwd’ under ‘/tmp’.

Cp /etc/passwd /tmp

user1 has the right to read and change it user2 has none

setfacl –m u:user1:r-- /tmp

setfacl –m u:user2:--- /tmp

11.create a 1G swap partition automounted by system boot.

Fdisk –l

Fdisk /dev/sdb

n, l(logical), entrer, +1G, t, 82, p,w

partprobe –s
mkswap /dev/sdb5
free –m
swapon /dev/sdb5
vim /etc/fstab
/dev/sdb5 swap swap defaults 0 0
Le swap monter au niveau de swapon

12.create a 15M ext4 partition autmounted by system boot at “/mnt/ext”

Fdisk /dev/sdb
n, l(logical), entrer, +15M, p,w
mkdir –p /mnt/ext
mkfs.ext4 /dev/sdb6
vim /etc/fstab
/dev/sdb6 /mnt/ext4 ext4 defaults 0 0
Mount –a
Mount

13.create an lvm called lv0 with 200M size under a volume group with 4M extent size and a total size of 400. lv0 is formatted with xfs and autmounted by system boot at “/mnt/lv0”

Fdisk /dev/sdb
n, l(logical), entrer, +400M, t,8^{e},p,w
partprobe –s
pvcreat /dev/sdb7
vgcreat vg0 –s 4M /dev/sdb7
lvcreate –n lv0 –L 200M vg0
mkdir –p /mnt/lv0
mkfs.xfs /dev/vg0/lv0
vim /etc/fstab
/dev/vg0/lv0 /mnt/lv0 xfs defaults 0 0
Mount –a
Mount

14. create a file named score under ‘/home/tekup’

Cd /home/tekup
touch score

containing the score of the password ‘azerty’

15.compress /tmp under “/home/tekup/tmp.tar.bz2”

tar cvfj /home/tekup/tmp.tar.bz2 /tmp

ls , pour verifier

16. copy all files and directories owned by “user” under “/opt/dir”

Mkdir –p /opt/dir

Find / -user user –exec cp {} /opt/dir/ \;

17. copy “/etc/passwd” under “/home/tekup/”,

cp –p /etc/passwd /home/tekup

create a new file called users containing all lines that ends with bash.

Grep $bash /etc/tekup > users

18.change in the file users ,’/bin/bash’ with shell

Sed –e ‘s/bin/bash/shel/g’ users

19. under ‘/home/tekup’ create a file called start containing the process with pid 10.

cd /home/tekup

ps aux | grep “10” > start

20.create a file with all files from the package kernel called kernelfiles

rpm –qa |kernel > kernelfile

21. change in the pervious file every “/” with “#”

sed –e ‘s/\/#/g’ kernelfile

cat kernelfile

22. setup a new repository to download packages locally from ‘/var/ftp/repo’

vim /etc/yum.repo.d/localy.repo

[localy]

Name = this is my repo

Baseurl = ftp:///var/ftp/repo

Gpgcheck =0

Enable=1

Yum repolist

23.configure the system so it can use ldap configuration via server rhcsa.example.com with tls certificate from 192.168.4.110://var/ftp/pub/ca.crt

NB: test your configuration with ldapuser1 through 5 (no home directory will be mounted until it gets configured in the next quesiton)

yum install authconfig-gtk sssd krb5-workstation –y
authconfig-gtk
dc=exemple , dc=com
utlise le passwd ldap
LTS downloade
192.168.4.110://var/ftp/pub/ca.crt
Aplay
Su – ldapuser5

24. when he connects , ldapuser1 will have his home folder mounted on “/home/remote/ldapuser1” from 192.168.4.11°://home/ldapuser1 other ldapusers will have the same.

Yum install autofs –y
Vim /etc/auto.master
/home/ldapuser1 /etc/auto.home
Vim /etc/auto.home
Ldapuser1 rw,intr,soft 192.168.4.11°://home/&

25. set the system to sync time with server 192.168.4.110

yum install chronyd –y
vim /etc/chronyd.conf
server rhcsa.example.com iburst
systemctl start chronyd
systemctl enable chronyd
chronyc sources –V
timedatectl set-ntp true
timedatectl status