White test

1.set the root password to “thuctive” 2.set

Reboot
Rd.break
Ctrl+x
Mount –o remount ,rw /sysroot
Chroot /sysroot
Echo “thuctive” | passwd –stdin root
Touch /.autorelable
Exit
reboot

the network configuration as follows:

*ip : 192.168.4.210
*subnet mask : 255.255.255.0
*gateway: 192.168.4.2
* dns :192.168.4.210
*hostname: exam.example.com

Ip a
Nmcli connection show
Nmcli connection modify eth0 ipv4.addresses 192.168.4.210/24 ipv4.gateway 192.168.4.2 ipv4.dns 192.168.4.210 ipv4.method manual connection.autoconnect yes
Nmcli connection up eth0
Systemctl restart NetworkManager
Systemctl enable NetworkManager
Hostnamectl set-hostname exam.example.com

3.set selinux policy to enforcing

Vim /etc/selinux/config
SELINUX=enforcing
Getenforcing
reboot

5.create groups redhat and tekup

Groupadd redhat
Groupadd tekup

6.create users : foulen1 , flouen2 and foulen3 as follow:

* all users have their password set to “thuctive”

Useradd foulen1
Useradd foulen2
Useradd foulen3
Passwd foulen1
Passwd foulen2
Passwd foulen3

*foulen1 has 1300 as uid and a comment “guest”

Usermod –u 1300 –c “guest” –g tekup foulen1

*foulen2 has “/bin/bash” as a shell

Usermod –s /bin/bash –g redhat –G tekup foulen2

*foulen3 has a home directory “/home/test” and uid of 1301

Usermod –u 1301 –d /home/test –G tekup,redhat

Ou

Usermod –u 1301 –d /home/test –G tekup –aG redhat

*fouen1 has tekup as his primary group , foulen2 has redhat as primary group and tekup as secondary, foulen3 has both groups as secondary

7. foulen2 password will expire on april 5th 2020 , has a minimum password age of 5 , 7 days of warning
flouen3’s password is inactive.

Chage –E 2020-04-05 foulen2
Chage –m 5 foulen2
Chage –W 7 foulen2
Chage –l foulen2
Chage –I -1 foulen3

8.create directory “/home/tekup”. owned by root and its group is redhat.

Chgrp redhta /home/tekup

redhat members has access permission , others have none files created in this direcetory inherit the group too and cannot be deleted only by their owners or root

Mkdir –p /home/tekup
Chmod 3770 /home/tekup

9. foulen1 has 0 permission on tekup. tekup group has full permissions

Setfacl-m u:foulen1:--- /home/tekup
Seetfacl –m g:tekup:rwx /home/tekup

10.copy '/etc/passwd' under '/tmp'.

Cp –r /etc/passwd /tmp

foulen1 has the right to read and change it
foulen2 has none

setfacl –m u:foulen1:rw- /tmp/passwd
setfacl –m u:foulen2:--- /tmp/passwd

11.create a 1G swap partition automounted by system boot.

Fdisk –l
Fdisk /dev/sda
n
E
Entrer
Enter
N
+1G
T
82
P
W
Partprobe
Mkswap /dev/sda5
Free –m
Vim /etc/fstab
/dev/sda5 swap swap defaults 0 0
Swapon /dev/sda5
Swapon –a /dev/sda5
Free –m
Df –hT

12.create a 150M xfs partition autmounted by system boot at *"/mnt/xfs"*

Fdisk /dev/sda
N

L
Enter
+150M
P
W
Partprobe
Mkfs.xfs /dev/sda6
Mkdir - /mnt/xfs
Vim /etc/fstab
/dev/sda6 /mnt/xfs xfs defaults 0 0
Mount –a
Mount

13. create an lvm called lv0 with 20 extents automounted on /mnt/lv0 by system boot and formatted with xfs

Fdisk /dev/sda
N
L
Enter
+50M
T
8e
P
W
Partprobe
Pvcreate /dev/sda7
Pvs ou pvdispaly
Vgcreate vg0 /dev/sda7
Vgs ou vgdisplay
Lvcreate –n lv0 –l 50 vg0
Lvs ou lvdisplay
Mkfs.xfs /dev/vg0/lv0
Mkdir –p /mnt/lv0
Vim /etc/fstab
/dev/vg0/lv0 /mnt/lv0 xfs defaults 0 0
Mount –a
Mount

14.compress /tmp under "/home/tekup/tmp.tar.gz"

Tar cvfz /home/tekup/tmp.tar.gz /tmp

15. copy all files owned by "user" under "/opt/dir"

mkdir –p /opt/dir
useradd user
find / -user user –exec cp {} /opt/dir/ \;

16. copy "/etc/shadow" under "/home/tekup/",

cp –r /etc/shadow /home/tekup

create a new file called nopass containing all lines that have "!!" in them.

Grep \!! /etc/shadow > nopass

18.change in the file nopass ,'!!' with "nopass"

Sed –i 's/\!!/\nopass/g' nopass

19. under '/home/tekup'

create a file called start containing all system targets

cd /home/tekup
systemctl –list-units –all > start

20.create a file with the kernel version called version

Uname –r
uname –r > version

21. create a file with all packages that starts with s , call it sp

rpm –qa
rpm –qa | grep ^s > sp

22. change in the pervious file every "/" with ":"

sed -i 's/\//\:/g' sp

23. setup a new repository to download packages locally from '/var/ftp/repo'

Vim /etc/yum.repo.d/localy.repo
[localy]
Name = this is my repo
Baseurl = ftp:///var/ftp/repo
Gpgcheck = 0
Enable = 1
Yum repolist

24.configure the system so it can use ldap configuration via server exam.example.com with tls certificate from 192.168.4.210://var/ftp/pub/ca.crt

NB: test your configuration with ldapuser1 through 5 (no home directory will be mounted until it gets configured in the next quesiton)

Authconfig-tui
[*] ldap
[*] ldap Athentification
[ok]
server exam.example.com
dc=example, dc= com
[ok]
Ouvrire un autre terminale
Scp 192.168.4.210://var/ftp/pub/ca.crt /etc/ldap/cacert
Cd /etc/ldap/cacert
Su – ldapuser5
Pwd
Rendre sur l'autre terminale est taper [ok]
Est la certification est copie

when he connects , ldapuser1 will have his home folder mounted on "/home/remote/ldapuser1" from 192.168.4.210://home/ldapuser1 other ldapusers will have the same.

Vim /etc/auto.master
/home /etc/auto.nfs 192.168.4.210://home/
Vim /etc/auto.nfs
Ldapuser1 rw,intr,soft 192.168.4.210://home/ldapuser1
Systemctl start autofs
Systemctl restart autofs
Systemctl enable autofs

25. set the system to sync time with server 192.168.4.210

vim /etc/chrony.conf
Commenter tous l'autre serveur avec #
server 192.168.4.210 iburst
chronyc sources –V
timedatectl set-ntp true
timedatectl status
systemctl start chronyd
systemctl restart chronyd
systemctl enable chronyd