White test

1.set the root password to “cetterde”

Reboot

Rd.break

Ctrl+x

Mount –o remount, rw /sysroot/

Chroot /sysroot

Echo “cetterde” |passwd –stdin root

Touch /.autorelable

Exit

Reboot

Systemctl get-default

Systemctl set-default graphical.target

Reboot

Ou bien startx

Ou init 5

2.set the network configuration as follows:

*ip : 192.168.4.200

*subnet mask : 255.255.255.0

*gateway: 192.168.4.2

* dns :192.168.4.200

*hostname: labipa.example.com

Nmcli connection show

Ip a

Nmcli connection add autoconnect yes con-name eth0 type Ethernet ifname ens33 ip4 192.168.4.200/24 gw4 192.168.4.2

Nmcli connection modify eth0 ipv4.dns 192.168.4.200

Nmcli connection show

Nmcli connection up eth0

Systemctl restart NetworkManager

Systemctl enable NetworkManager

Pour vérifier ouvrier le fichier /etc/sysconfig/network-script/ifcg-eth0

3.set selinux policy to enforcing

Getenforce

Setenforce 1

Vim /etc/selinux/config

SELINUX=enforcing :wq !

Reboot , init 6

4.created users and groups have a minimum uid and gid of 1100.

Vim /etc/login.defs

MIN-UID = 1100

MIN-GID = 1100

5.set the password policy as follows:

*minimum 8 caracteres length

*3 categories

Vim /etc/security/pwqaulity.conf

Minlen = 8

Ocredit = -3

Edit le #

6.create groups redhat and tekup with respective gid 1300 and 1345

Groupadd redhat –u 1300

Groupadd tekup –u 1345

Tail –n 2 /etc/group

7.create users :

john , alex

useradd john

useradd alex

* all users have their password set to “cetterde”

passwd cetterde

passwd cetterde

*john has 1234 uid and a comment “johnathan”

Usermod john –u 1234 –c “Johnathan” –g tekup –G redhat

*alex has a service account and a home directory “/home/test”

Usermod alex –d /home/test –aG tekup,redhat

Ou bien

Usermod alex –d /home/test –G tekup –aG redhat

*john has tekup as his primary group and redhat as secondary , alex has both groups as secondary 8.

john’s password will expire by 2021, has a minimum password age of 7.

Chage 2020-12-31 –u john

Chage –m 7 –u john

alex’s password is expired

9.create directory “/home/tekup”.

Mkdir –p /home/tekup

tekup group members have full permissions on this directory, redhat group members has acess permissions, and others have none. Files created in this directory have redhat as a group and cannot be deleted only by owner. john have full permissions on the directory group.

Chgrp redhat /home/tekup
Chmod 3770 /home/tekup
Ls /home/tekup

10. files created in tekup have a maximum of 400 as permissions.

Chmod 400 /home/tekup

11.create a 1G swap partition automounted by system boot.

Fdisk –l

Fdisk /dev/sda

N,e,entrer,entrer ,n,l,entrer,+1G,t,p,w

Partprobe
Mkswap /dev/sda5
Free –m
Vim /etc/fstab
/dev/sda5 swap swap defaults 0 0
Swapon /dev/sda5
Swapon –a
Free –m
Reboot

12.create a 150M ext4 partition autmounted by system boot at “/mnt/ext”

Mkdir –p /mnt/ext
Fdisk /dev/sda
N,l,entrer,+150M,p,w
Partprobe
Mkfs.ext4 /dev/sda6
Vim /etc/fstab
/dev/sda6 /mnt/ext ext4 defaults 0 0
Mount –a
Mount

13.create an lvm called lv0 with 200M size under a volume group with 4M extent size and a total size of 400. lv0 is formatted with xfs and autmounted by system boot at “/mnt/lv0”

Fdisk /dev/sda
n,l, entrer, +400M,t,8e,p,w
partprobe
pvcreate /dev/sda7
pvs , pvdisplay
vgcreate –s 4M VG /dev/sda7
vgs, vgdisplay
lvcreate –n lv0 –l 200 VG
lvs , lvdisplay
mkfs.xfs /dev/VG/lv0
mkdir /mnt/lv0
vim /etc/fstab
/dev/VG/lv0 /mnt/lv0 xfs defaults 0 0

Mount –a

Mount

14.compress /tmp under “/home/tekup/tmp.tar.gz”

Tar –cvfz /home/tekup/tmp.tar.gz /tmp

Ls /home pour verifier

15.extend lv0 to 350M

Lvextend –L 350M /dev/VG/lv0

16. copy all files and directories owned by “user” under “/opt/dir”

Mkdir –p /opt/dir/

Find / -user user –exec cp {} /opt/dir/ \;

Ls -l /opt/dir

7.under tekup , create a file called custom containing all packages installed that starts with ‘k’

Cd /home/tekup

Rpm –qa

Rpm –qa | grep ^k > custom

Cat custom

18.save the system services under a file called services

Systemctl –list-utils –all > service

19. change every ‘.’ in services with ‘:’ and save it under a new file called services_changed

sed ‘s/\./\:/g’ services > services_changed

cat services_changed

20. save the difference between services and services_changed under a file called change.

Deff services services_changed > change

21. setup a new repository to download packages locally from ‘/var/ftp/repo’

vim /etc/yum.repos.d/local.repo

[local]

Name = this is my repository

Baseurl = ftp:///var/ftp/repo

Gpgcheck = 0
Enabled = 1
Yum repolist

22.configure the system so it can use ldap configuration via server labipa.example.com with tls certificate from 192.168.4.200://var/ftp/pub/ca.crt

NB: test your configuration with ldapuser1 through 5 (no home directory will be mounted until it gets configured in the next quesiton)

Vim /etc/hosts
192.168.4.200 labipa.example.com server
Yum install authconfig-gtk sssd krb5.workstation –y
Systemctl start sssd
Systemctl restart sssd
Systemctl enable sssd
Authconfig-gtk
Ldap
Dc=example, dc= com
Server labipa.example.com
Ldap://labipa.example.com
[TLS]
ftp://Labipa.example.com://var/ftp/pub/ca.crt
aplay
Systemctl start sssd
Systemctl restart sssd
Systemctl enable sssd
getent passwd ldapuser1

23. when he connects , ldapuser1 will have his home folder mounted on “/home/remote/ldapuser1” from 192.168.4.200://home/ldapuser1 other ldapusers will have the same.

Yum install autofs –y
Systemctl start autofs
Systemctl restart autofs
Systemctl enable autofs
Vim /etc/auto.master

/home/ldapuser /etc/auto.nfs

Vim /etc/auto.nfs

Ldapuser1 -rw,sync 192.168.4.200://home/ldapuser1&

Systemctl restart autofs

Systemctl enable autofs

24. set the system to sync time with server 192.168.4.200

yum install –y chrony
systemctl start chronyd.service
systemctl enable chronyd.service
timedatectl set-ntp true
timedatectl status
vim /etc/chrony.conf
effacer tout les autre service avec #
server 192.168.4.200 iburst
systemctl start chronyd.service
systemctl enable chronyd.service

chronyc sources –V