# 10.0.0White test1-V8

**1.**Set the root password to “azerty”
**2.**Set the network configuration as follows: nmcli dev sh
*ip : 192.168.4.210
*subnet mask : 255.255.255.0
*gateway: 192.168.4.2
* dns :192.168.4.210
*hostname: rhcsa.example.com

**3.**Set a second ip address 10.0.0.10/24 on the same network interface

Set selinux to enforcingpolicy.

Create groups redhat and tekup

**4.** Create users : admin1 , admin2 and admin3 as follow:

* all users have their password set to “thuctive” passwd admin1

*foulen1 has 1300 as uid and a comment “guest” *admin2 has “/bin/bash” as a shell *admin3 has a home directory “/home/test” and uid of1301

*admin1 has tekup as his primary group , admin2 has redhatas primary group and tekup as secondary, admin3 has bothgroups as secondary.

**5.** Admin2 password will expire on december 30th 2021 , has a minimum password age of 5 , 7 days of warning.

Admin3’s password is inactive.

**6.** Create a shared directory “/home/tekup”owned by root and its group is

Files created in this direcetory inherit the group too and cannotbe deleted only by theiot.

**7.**admin1 has no permission on tekup.g tekup group has full permissions

Copy ‘/etc/passwd’ under ‘/tmp’.admin1 has the right to read and change it. admin2 has none.

**8.**Schedule a task every thuesday and Friday at 7 :15a.m. in order to compress /tmp under "/home/tekup/tmp.tar.gz"

**9.**Copy all files owned by "user" under "/opt/dir"

**10.**Copy "/etc/shadow" under "/home/tekup/", create a newfile called nopass containing all lines that have "!!" in them.

Change in the file nopass ,'!!' with "nopass"

**11.**Under '/home/tekup', create a file called start containing all system targets

Create a file with the kernel version called version

**12.**Create a file with all packages that starts with s , call it sp

**13.**Change in the pervious file every "." with ":"

Poweroff your machine and add 6 hard disks on your machine respectively (before performing the tasks (a-b-c-d-e-f-g)) : 2GB, 5GB, 1GB, 2GB, 1GB, 1GB.

**13-a**.Add 2GiB hard disk to your virtual machine. Configure one Stratis volume with the name **vol1**on top of these hard drive and make sure the volume is mounted persistently and automatically while booting.

**13-b.**Create a snapshoat called snap-1 for **vol1**and mount it in /mount/snap

**13-c.**Add a new disk to your virtual machine(5GiB). On this disk, create a VDO volume with a virtual size of 3TiB, format it and mount it in /mount/vdo1

**13-d.**Create a 1Gb swap partition automounted by system bootin /home/swap from a new hard disk(2GiB)

**13-e.** Create a 300M ext4 partition autmounted on /mnt/newpart by system boot from a new hard disk(1GiB).

**13-f.** Create an lvm with a **200M** size named **lv0** formatted in xfs andautomounted on /home**/lvm** from a new hard disk(1GiB)

**14.**Setup two new repositories AppStream and BaseOS to download packages locally from'/var/ftp/repo'.

**15.**Add ftp firewall to firewall-services and make it permenant.

**16.** On both server1 and server2, add two lines that make it possible to resolve the names of the virtual host you are going to create to the IP address of the virtual machine

Create a file with the name index.html in the account document root, and make sure its contents read "Welcome to account."

Temporarily switch off SELinux

***17.*** verify that both the account and the sales servers are accessible

**18.**Set the system to sync time with server 192.168.4.210