White Test RHCSA

1.set the root password to “cetterde”

2.set the network configuration as follows:

*ip : 192.168.4.110

*subnet mask: 255.255.255.0

*gateway: 192.168.4.2

* dns :192.168.4.110

*hostname: rhcsa.example.com

3.created users and groups have a minimum uid and gid of 1100 and 1900 as maximum

4.set the password policy as follows: *minimum 8 caracteres length *1 digit *1 special character

5.create groups redhat and tekup with respective gid 1300 and 1345

6.create users : user1 , user2 and user3 as follow: * all users have their password set to “azerty” user1 has 1300 as uid and a comment “admin” user2 has a service account

*user3 has a home directory “/home/test”

user1 has tekup as his primary group , user2 has redhat as primary group, user3 has both groups as secondary

7. user2 password will expire after 30 days , has a minimum password age of 5 and 20 for maximum , 7 days of warning.

8. make user2’s password expire

9. create directory “/home/tekup”.

10. tekup group members have full permissions on this directory , redhat group members has read and write permissions, and others have none.

11. Files created in this directory have redhat as a group

12. User1 have full permissions on the directory group

13.create a 1G swap partition automounted by system boot

14.create a 15M ext4 partition autmounted by system boot at “/mnt/ext

15.create an lvm called lv0 with 200M size under a volume group with 4M extent size and a total size of 400. lv0 is formatted with xfs and autmounted by system boot at “/mnt/lv0

16. copy all files and directories owned by “user” under “/opt/dir”

17. copy “/etc/passwd” under “/home/tekup/”, create a new file called users containing all lines that ends with bash.

19. under ‘/home/tekup’ create a file called start containing the process with pid 10.

20.create a file with all files from the package kernel called kernelfiles

21. change in the pervious file every “/” with “#”