



inglés



español ▼

[L](#) [CSS](#) [JAVASCRIPT](#) [SQL](#) [PITÓN](#) [JAVA](#) [PHP](#) [CÓMO](#) [W3.CSS](#)

Tipos de datos SQL para MySQL, SQL Server y MS Access

[< Anterior](#)[Próximo >](#)

El tipo de datos de una columna define qué valor puede contener la columna: entero, carácter, dinero, fecha y hora, binario, etc.

Tipos de datos SQL

Cada columna de una tabla de base de datos debe tener un nombre y un tipo de dato.

Al crear una tabla, un desarrollador de SQL debe decidir qué tipo de datos se almacenarán en cada columna. El tipo de dato sirve de guía para que SQL comprenda qué tipo de datos se espera en cada columna y también identifica cómo interactuará SQL con los datos almacenados.

Nota: Los tipos de datos pueden tener nombres diferentes en distintas bases de datos. Incluso si el nombre es el mismo, el tamaño y otros detalles pueden variar. ¡ **Consulte siempre la documentación!**

Tipos de datos de MySQL (versión 8.0)



Data type	Description
CHAR(size)	A FIXED length string (can contain letters, numbers, and special characters). The <i>size</i> parameter specifies the column length in characters - can be from 0 to 255. Default is 1
VARCHAR(size)	A VARIABLE length string (can contain letters, numbers, and special characters). The <i>size</i> parameter specifies the maximum string length in characters - can be from 0 to 65535
BINARY(size)	Equal to CHAR(), but stores binary byte strings. The <i>size</i> parameter specifies the column length in bytes. Default is 1
VARBINARY(size)	Equal to VARCHAR(), but stores binary byte strings. The <i>size</i> parameter specifies the maximum column length in bytes.
TINYBLOB	For BLOBs (Binary Large Objects). Max length: 255 bytes
TINYTEXT	Holds a string with a maximum length of 255 characters
TEXT(size)	Holds a string with a maximum length of 65,535 bytes
BLOB(size)	For BLOBs (Binary Large Objects). Holds up to 65,535 bytes of data
MEDIUMTEXT	Holds a string with a maximum length of 16,777,215 characters
MEDIUMBLOB	For BLOBs (Binary Large Objects). Holds up to 16,777,215 bytes of data
LONGTEXT	Holds a string with a maximum length of 4,294,967,295 characters
LOBLOB	For BLOBs (Binary Large Objects). Holds up to 4,294,967,295 bytes of data
ENUM(val1, val2, val3, ...)	A string object that can have only one value, chosen from a list of possible values. You can list up to 65535 values in an ENUM list. If a value is inserted that is not in the list, a blank value will be inserted. The values are sorted in the order you enter them



Tipos de datos numéricos

Data type	Description
BIT(<i>size</i>)	A bit-value type. The number of bits per value is specified in <i>size</i> . The <i>size</i> parameter can hold a value from 1 to 64. The default value for <i>size</i> is 1.
TINYINT(<i>size</i>)	A very small integer. Signed range is from -128 to 127. Unsigned range is from 0 to 255. The <i>size</i> parameter specifies the maximum display width (which is 255)
BOOL	Zero is considered as false, nonzero values are considered as true.
BOOLEAN	Equal to BOOL
SMALLINT(<i>size</i>)	A small integer. Signed range is from -32768 to 32767. Unsigned range is from 0 to 65535. The <i>size</i> parameter specifies the maximum display width (which is 255)
MEDIUMINT(<i>size</i>)	A medium integer. Signed range is from -8388608 to 8388607. Unsigned range is from 0 to 16777215. The <i>size</i> parameter specifies the maximum display width (which is 255)
INT(<i>size</i>)	A medium integer. Signed range is from -2147483648 to 2147483647. Unsigned range is from 0 to 4294967295. The <i>size</i> parameter specifies the maximum display width (which is 255)
INTEGER(<i>size</i>)	Equal to INT(<i>size</i>)
BIGINT(<i>size</i>)	A large integer. Signed range is from -9223372036854775808 to 9223372036854775807. Unsigned range is from 0 to 18446744073709551615. The <i>size</i> parameter specifies the maximum display width (which is 255)
FLOAT(<i>size</i> , <i>d</i>)	A floating point number. The total number of digits is specified in <i>size</i> . The number of digits after the decimal point is specified in the <i>d</i> parameter. This syntax is deprecated in



	whether to use FLOAT or DOUBLE for the resulting data type. If <i>p</i> is from 0 to 24, the data type becomes FLOAT(). If <i>p</i> is from 25 to 53, the data type becomes DOUBLE()
DOUBLE(<i>size</i> , <i>d</i>)	A normal-size floating point number. The total number of digits is specified in <i>size</i> . The number of digits after the decimal point is specified in the <i>d</i> parameter
DOUBLE PRECISION(<i>size</i> , <i>d</i>)	
DECIMAL(<i>size</i> , <i>d</i>)	An exact fixed-point number. The total number of digits is specified in <i>size</i> . The number of digits after the decimal point is specified in the <i>d</i> parameter. The maximum number for <i>size</i> is 65. The maximum number for <i>d</i> is 30. The default value for <i>size</i> is 10. The default value for <i>d</i> is 0.
DEC(<i>size</i> , <i>d</i>)	Equal to DECIMAL(<i>size</i> , <i>d</i>)

Nota: Todos los tipos de datos numéricos pueden tener una opción adicional: UNSIGNED o ZEROFILL. Si agrega la opción UNSIGNED, MySQL no permite valores negativos en la columna. Si agrega la opción ZEROFILL, MySQL también agrega automáticamente el atributo UNSIGNED a la columna.

Tipos de datos de fecha y hora

Data type	Description
DATE	A date. Format: YYYY-MM-DD. The supported range is from '1000-01-01' to '9999-12-31'
DATETIME(<i>fsp</i>)	A date and time combination. Format: YYYY-MM-DD hh:mm:ss. The supported range is from '1000-01-01 00:00:00' to '9999-12-31 23:59:59'. Adding DEFAULT and ON UPDATE in the column definition to get automatic initialization and updating to the current date and time
TIMESTAMP(<i>fsp</i>)	A timestamp. TIMESTAMP values are stored as the number of seconds since the Unix epoch ('1970-01-01 00:00:00' UTC). Format: YYYY-MM-DD hh:mm:ss. The supported range is



CURRENT_TIMESTAMP in the column definition

TIME(<i>fsp</i>)	A time. Format: hh:mm:ss. The supported range is from '-838:59:59' to '838:59:59'
YEAR	A year in four-digit format. Values allowed in four-digit format: 1901 to 2155, and 0000. MySQL 8.0 does not support year in two-digit format.

Tipos de datos de MS SQL Server

Tipos de datos de cadena

Data type	Description	Max char length	Storage
char(n)	Fixed-length non-Unicode character data (n must be between 1 and 8000)	8,000	n bytes (uses one byte for each character)
varchar(n)	Variable-length non-Unicode character data (n must be between 1 and 8000)	8,000	n bytes + 2 bytes
varchar(max)	Variable-length non-Unicode character data		up to 2 GB
nchar(n)	Fixed-length Unicode character data (n must be between 1 and 4000)	4,000	2 * n bytes (uses two bytes for each character)
nvarchar(n)	Variable-length Unicode character data (n must be between 1 and 4000)	4,000	2 * n bytes + 2 bytes (uses two bytes for each character)
nvarchar(max)	Variable-length Unicode character data		up to 2 GB



≡	L	CSS	JAVASCRIPT	SQL	PITÓN	JAVA	PHP	CÓMO	W3.CSS
	varbinary(n)		Variable-length binary data (n must be between 1 and 8000)			2GB			
	varbinary(max)		Variable-length binary data			2GB			

Tipos de datos numéricos

Data type	Description	Storage
bit	Integer that can be 0, 1, or NULL	
tinyint	Allows whole numbers from 0 to 255	1 byte
smallint	Allows whole numbers between -32,768 and 32,767	2 bytes
int	Allows whole numbers between -2,147,483,648 and 2,147,483,647	4 bytes
bigint	Allows whole numbers between -9,223,372,036,854,775,808 and 9,223,372,036,854,775,807	8 bytes
decimal(p,s)	Fixed precision and scale numbers. Allows numbers from $-10^{38} + 1$ to $10^{38} - 1$. The p parameter indicates the maximum total number of digits that can be stored (both to the left and to the right of the decimal point). p must be a value from 1 to 38. Default is 18. The s parameter indicates the maximum number of digits stored to the right of the decimal point. s must be a value from 0 to p. Default value is 0	5-17 bytes
numeric(p,s)	Fixed precision and scale numbers. Allows numbers from $-10^{38} + 1$ to $10^{38} - 1$. The p parameter indicates the maximum total number of digits that can be stored (both to the left and to the right of	5-17 bytes



	stored to the right of the decimal point. s must be a value from 0 to p. Default value is 0	
smallmoney	Monetary data from -214,748.3648 to 214,748.3647	4 bytes
money	Monetary data from -922,337,203,685,477.5808 to 922,337,203,685,477.5807	8 bytes
float(n)	Floating precision number data from -1.79E + 308 to 1.79E + 308. The n parameter indicates whether the field should hold 4 or 8 bytes. float(24) holds a 4-byte field and float(53) holds an 8-byte field. Default value of n is 53.	4 or 8 bytes
real	Floating precision number data from -3.40E + 38 to 3.40E + 38	4 bytes

Tipos de datos de fecha y hora

Data type	Description	Storage
datetime	From January 1, 1753 to December 31, 9999 with an accuracy of 3.33 milliseconds	8 bytes
datetime2	From January 1, 0001 to December 31, 9999 with an accuracy of 100 nanoseconds	6-8 bytes
smalldatetime	From January 1, 1900 to June 6, 2079 with an accuracy of 1 minute	4 bytes
date	Store a date only. From January 1, 0001 to December 31, 9999	3 bytes
time	Store a time only to an accuracy of 100 nanoseconds	3-5 bytes
datetimeoffset	The same as datetime2 with the addition of a time zone offset	8-10 bytes



Each table may have only one timestamp variable

Otros tipos de datos

Data type	Description
sql_variant	Stores up to 8,000 bytes of data of various data types, except text, ntext, and timestamp
uniqueidentifier	Stores a globally unique identifier (GUID)
xml	Stores XML formatted data. Maximum 2GB
cursor	Stores a reference to a cursor used for database operations
table	Stores a result-set for later processing

Tipos de datos de MS Access

Data type	Description	Storage
Text	Use for text or combinations of text and numbers. 255 characters maximum	
Memo	Memo is used for larger amounts of text. Stores up to 65,536 characters. Note: You cannot sort a memo field. However, they are searchable	
Byte	Allows whole numbers from 0 to 255	1 byte
Integer	Allows whole numbers between -32,768 and 32,767	2 bytes
Long	Allows whole numbers between -2,147,483,648 and 2,147,483,647	4 bytes
Single	Single precision floating-point. Will handle most decimals	4 bytes
Double	Double precision floating-point. Will handle most decimals	8 bytes



AutoNumber	AutoNumber fields automatically give each record its own number, usually starting at 1	4 bytes
Date/Time	Use for dates and times	8 bytes
Yes/No	A logical field can be displayed as Yes/No, True/False, or On/Off. In code, use the constants True and False (equivalent to -1 and 0). Note: Null values are not allowed in Yes/No fields	1 bit
Ole Object	Can store pictures, audio, video, or other BLOBs (Binary Large Objects)	up to 1GB
Hyperlink	Contain links to other files, including web pages	
Lookup Wizard	Let you type a list of options, which can then be chosen from a drop-down list	4 bytes

Exercise [?]

Which of the following is NOT a string data type in MySQL?

- ☐ VARCHAR
- ☐ TEXT
- ☐ TIMESTAMP
- ☐ CHAR

Submit Answer »

[Tutorials](#)[Exercises](#)[Services](#)[Sign In](#)[L](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PITÓN](#)[JAVA](#)[PHP](#)[CÓMO](#)[W3.CSS](#)

Sigue tu progreso: ¡es gratis!

[Inscribirse](#) [Acceso](#)



SELECTOR DE COLOR



[Tutorials](#)[Exercises](#)[Services](#)[Sign In](#)[L](#) [CSS](#) [JAVASCRIPT](#) [SQL](#) [PITÓN](#) [JAVA](#) [PHP](#) [CÓMO](#) [W3.CSS](#)

CERTIFICACIÓN

[PARA PROFESORES](#)[PARA EMPRESAS](#)

CONTÁCTENOS

Los mejores tutoriales

[Tutorial de HTML](#)
[Tutorial de CSS](#) [Tutorial de JavaScript](#) [Tutorial de procedimientos](#)
[Tutorial de SQL](#)
[Tutorial de Python](#) [Tutorial de W3.CSS](#) [Tutorial de Bootstrap](#) [Tutorial de PHP](#) [Tutorial de Java](#) [Tutorial de C++](#)
[Tutorial de jQuery](#)

Referencias principales

[Referencia HTML](#)
[Referencia CSS](#)
[Referencia JavaScript](#) [Referencia SQL](#) [Referencia Python](#) [Referencia W3.CSS](#) [Referencia Bootstrap](#) [Referencia PHP](#)
[Colores HTML](#)
[Referencia Java](#) [Referencia Angular](#)
[Referencia jQuery](#)

Ejemplos principales

[Ejemplos de HTML](#)
[Ejemplos de CSS](#) [Ejemplos de JavaScript](#) [Ejemplos de procedimientos](#)
[Ejemplos de SQL](#)
[Ejemplos de Python](#) [Ejemplos de W3.CSS](#) [Ejemplos de Bootstrap](#) [Ejemplos de PHP](#)

[Tutorials](#)[Exercises](#)[Services](#)[Sign In](#)[L](#) [CSS](#) [JAVASCRIPT](#) [SQL](#) [PITÓN](#) [JAVA](#) [PHP](#) [CÓMO](#) [W3.CSS](#)

[Certificado HTML](#)
[Certificado CSS](#)
[Certificado JavaScript](#)
[Certificado Front End](#) [Certificado SQL](#)
[Certificado Python](#)
[Certificado PHP](#)
[Certificado jQuery](#)
[Certificado Java](#) [Certificado C++](#) [Certificado C#](#)
[Certificado XML](#)



FORO SOBRE LA ACADEMIA

W3Schools está optimizado para el aprendizaje y la formación. Los ejemplos pueden simplificarse para facilitar la lectura y el aprendizaje.

Los tutoriales, las referencias y los ejemplos se revisan constantemente para evitar errores, pero no podemos garantizar la exactitud total de todo el contenido. Al utilizar W3Schools, acepta haber leído y aceptado nuestros [términos de uso](#) , [cookies](#) y [política de privacidad](#) .

Copyright 1999-2025 de Refsnes Data. Todos los derechos reservados. W3Schools funciona con [W3.CSS](#) .