



Master of Science Thesis

Automatic Age Estimation in Still Images

Pablo Pardo Garcia

Supervisor:

Co-supervisor:

Sergio Escalera Guerrero

Marc Oliu Simón

Dept. Matemàtica Aplicada
i Anàlisi

Dept. Matemàtica Aplicada
i Anàlisi

University of Barcelona

University of Barcelona

Barcelona, 24th April 2015

Acknowledgements

To write some time in the future...

Abstract

Contents

1	Introduction	1
2	State of the art	2
2.1	Historical context	2
2.1.1	Age Representation	2
2.1.2	Age Estimation Algorithm	3
2.1.2.1	Classification Methods	3
2.1.2.2	Regression Methods	3
2.1.2.3	Hybrid Methods	3
2.1.3	Related areas	3
2.2	Applications	5
2.2.1	Security control and surveillance monitoring	5
2.2.2	Biometrics	5
2.2.3	Age-based indexing face images	5
2.2.4	Human-computer interaction	6
2.3	Age-based Databases	6
3	Data Collection	8
3.1	Web Application	9
3.2	HuPBA Age Dataset	9
4	Method	10
4.1	Biological Inspired Method	10
4.1.1	Background	10
4.1.2	System overview	10
4.2	Deep Learning Method	10
4.2.1	Background	10
4.2.2	System overview	10
5	Experimental Results	11
6	Conclusions and Future work	12
	References	12

List of Tables

2.1	Age-based Databases	7
2.2	Age Estimation Methods	7

List of Figures

List of Algorithms

1 Introduction

Computer Vision is a field in Artificial Intelligence that has been going on since 1960 with digital image processing by computers was possible. Since the beginning of artificial vision, facial analysis has been a major interest in the research community (not just in Computer Vision but in other scientific areas such as biology [7], psychology [9], neuroscience [12] and sociology [30]) because its difficulty and its applications. Some of these applications are automatic detection of facial expressions [6], face detection [27], face recognition [52], face verification [50] and automatic estimation of age [17], gender [2] and ethnicity [26].

Age estimation is a field within the facial analysis area in Computer Vision that tackles the problem of automatically predicting the age of people from visual data (still images, video data, depth maps, etc.). One of the main issues that the age estimation problem has is that there are many factors that influence human perception of age, some factors affect the aging of a person, such as smoking, drinking alcohol, doing sports, alimentation, etc. and others affect the face appearance such as scars, plastic surgery, make-up, facial hair, etc.

In this work, the first database in the literature of face image with real and apparent age annotations is collected and studied the difference in performance between the two different labels.

Goal of the thesis

- First database with apparent age collected
- Analysis of the two annotations (real and apparent) with two different baselines.
- Challenge

2 State of the art

2.1 Historical context

Talk about soft computing

Age estimation has historically been one of the most challenging problems within the field of facial analysis [13][24]. Despite the multiple applications in many different areas of age estimation there are relatively few publications compared to other topics in facial analysis. This difficulty is due to many factors:

- Depending on the application scenario, the age estimation problem can be taken as a multiclass classification problem or a regression problem.
- Large database are difficult to collect, especially series of chronological image from the same individuals.
- The factors the affect the aging process are uncontrollable and person specific [15][17][45].

Talk about close related fields (age synthesis, face validation, etc)

The age estimation problem has generally two stages or blocks, the first one is the age representation in the images and the second one the estimation itself with the computed data. There are many different techniques for both stages. [13]

2.1.1 Age Representation

Age Representation: List of techniques

2.1.2 Age Estimation Algorithm

2.1.2.1 Classification Methods

2.1.2.2 Regression Methods

2.1.2.3 Hybrid Methods

2.1.3 Related areas

Age Estimation Algorithm: Classification, Regression and Hybrid

One of the earliest works in age estimation was done by A. Lanitis et al. [34, 35, 36] where the age is modelled by a quadratic aging function. They propose two different aging estimation methods: weighted appearance specific method [35, 36] -where the aging factor of a new individual is computed by the weighted sum of the aging functions of other individual- and appearance and age specific method [34] -where the new individual is first classified into a cluster with similar aging factor patterns, then is classified into different age ranges and an age-specific classifier is applied to estimate the final age-.

There are some drawbacks to this "aging function" approach pointed out by X. Geng et al. [18]. The formula of the aging function is empirically determined, there is no evidence suggesting that the relation between face and age is described just by a quadratic function. The new aging function for the unseen images is simply a linear combination of the already known aging functions. X. Geng et al. claimed to solve these problems in their new proposed method AGing pattErn Subspace (AGES) [18]. Where each face image is represented by a point in the aging pattern subspace.

Later N. Ramanathan et al. [45, 46] approached the age estimation problem in two different scenarios, estimating the age difference between two face images of the same individual based on a Bayesian age-difference classifier [45] and estimating the age of young faces using the facial growth geometry [46]. The problem of the last approach is that only can be applied to face images of young people in a growing age since afterwards the facial geometry does not change as much.

Y. Fu et al. were the first to approach the problem through manifold analysis methods [15, 14]. Each face image is assigned to its low-dimensional

representation via manifold embedding. Following this approach G. Guo and Y. Fu et al. [19] proposed a new method based on a study of different dimensionality reduction and manifold embedding and add a robust regression step to the previous framework. In a posterior work [21], G. Guo et al. introduces a new approach, using kernel partial least square (KPLS) regression which reduces feature dimensionality and learn the aging function in a single step.

G. Guo et al. also proposed different approaches to the age estimation problem such as [20], where they propose probabilistic fusion approach, or [23] where they introduce the Biological Inspired Features (BIF) for the age estimation problem and propose some changes adding a novel "STD" operator. H. Han et al. [24] uses the BIF features in an hybrid classification framework improving the previous results. G. Guo et al. [22], in a recent paper (2014), used the BIF features, and focus to investigate a proposed single-step framework for joint estimation of age, gender and ethnicity. Both the CCA (Canonical Correlation Analysis) and PLS (Partial Least Square) based methods were explored under the joint estimation framework.

Under the same idea as Y. Fu et al. [15], K. Luu et al. [38, 39] reduced dimensionality by using facial landmarks and Active Shape Models (ASM) [38] and an improved version, Contourlet Appearance Model (CAM) [39], where they prove the efficiency of using facial landmarks. Then T. Wu et al. [53] proposed to use facial landmarks and project them into a Grassmann manifold to model the age patterns.

Other different variations of the problem has been addressed, A. Lanitis et al. [33] performed a first approach to age estimation using Head and Mouse tracking movements, Y. Makihara et al. [40] used a gait-based database to estimate the age, B. Xia et al. [54] proposed an age estimation method based on 3D face images.

There are also some surveys in age estimation by N. Ramanathan et al. [47] and Y. Fu et al. [13].

More recently studies have obtained a very high accuracy in face validation using deep learning [50].

2.2 Applications

There are many real-world application related to age estimation. Automatic age estimation is useful in situations where we do not need to specifically identify the individual, such as a government employee, but want to know his or her age.

2.2.1 Security control and surveillance monitoring

In the last years security control and surveillance monitoring have gotten more relevant with the growth of internet content and the spread of technology that allows access to that content to under-age teenagers. Automatic age estimation systems can be used to prevent minors to buy alcohol in a grocery store, enter a bar or purchase tobacco from vending machines.

2.2.2 Biometrics

There are two types of biometric systems based on the number of traits used for recognition, unimodal biometric systems which consist on a single recognition trait and multimodal biometric systems, which combines evidences obtained from multiple sources [25] such as fingerprints, iris, face, etc. The multimodal system is more robust, more reliable and secure against spoof attacks. However, the data acquisition is much more troublesome than the unimodal. In order to overcome this inconveniences, soft-biometrics [28], such as age, height, weight, gender, ethnicity and eye colour, are used in combination with classic biometric traits.

2.2.3 Age-based indexing face images

With the rise of interest for big data new and more efficient ways to retrieve data have to be developed. In large face image datasets, age can be used for index such a databases so the queries to the dataset are simpler and faster. This is specially important in law enforcement where large image databases of suspects have to be filtered in order to find the most accurate suspects.

2.2.4 Human-computer interaction

With the growth of e-commerce, companies want to offer a more personalized experience to their customers. Personalizing the offer or the product itself increase the user's satisfaction and the companies sells. Some examples of such a policies are the following: Google [4] indexes the search results so the links that appear first appeal more to the user, Amazon [37] uses a recommender system to suggest products to the potential buyers according to their previous purchases, Netflix [31] held a competition in 2009 to create a film recommender system and gave a price of US \$1,000,000. Age estimation system could have an important role in the sector since age is a discriminative feature for different client profiles. Visada [29] is an example of the use of age estimation for recommend products.

2.3 Age-based Databases

There are many databases of faces in the literature, however, not so many capture the age of the individuals. This fact is due to the complexity of crawling such an information (if existent) from the usual fonts such as *Flickr* or *Facebook* and due to privacy issues. Moreover, the difficulty is even higher if the database contains chronological image series of individuals. The Table 2.1 shows the most relevant databases used in the literature with the number of samples, the number of subjects, the age range, the type of age and additional information if any. The *FG-NET* [36] is one of the first and most consolidated age database, it is used to compare with other age estimation methods.

After an initial interest on automatic age estimation from images dated back to the early 2000s [34], [36], [41], research in the field has experienced a renewed interest from 2006 on, since the availability of large databases like *MORPH-Album 2* [48], which contains 55 times more age-annotated images than the *FG-NET* database.

¹Surgical points, fracture or laceration on face.

Database	#Faces	#Subj.	Range	Type of age	Controlled Env.	Balanced age Distr.	Other annotation
FG-NET [36, 32]	1,002	82	0 - 69	Real Age	No	No	68 Landmarks
GROUPS [16]	28,231	28,231	0 - 66+	Age group	No	No	-
PAL [41]	580	580	19 - 93	Age group	No	No	-
FRGC [43]	44,278	568	18 - 70	Real Age	Partially	No	-
MORPH2 [48]	55,134	13,618	16 - 77	Real Age	Yes	No	-
YGA [14]	8,000	1,600	0 - 93	Real Age	No	No	-
FERET [44]	14,126	1,199	-	Real Age	Partially	No	-
Iranian face [3]	3,600	616	2 - 85	Real Age	No	No	Kind of skin and cosmetic points ¹
PIE [49]	41,638	68	-	Real Age	Yes	No	-
WIT-BD [51]	26,222	5,500	3 - 85	Age group	No	No	-
Caucasian Face Database [5]	147	-	20 - 62	Real Age	Yes	No	Shape represented in 208 key points
LHI [1]	8,000	8,000	9 - 89	Real Age	Yes	Yes	-
HOIP [11]	306,600	300	15 - 64	Age Group	Yes	No	-
Ni's Web-Collected Database [42]	219,892	-	1 - 80	Real Age	No	No	-
OUI-Adience [8]	26.580	2.284	0 - 60+	Age Group	No	No	Gender

Table 2.1: Age-based Databases

Publication	Year	Database (#subjects, #images)	Age Image Representation	Method	Accuracy	MAE
A. Lanitis et al. [36]	2002	Private (60, 500)	Active Appearance Models	Quadratic Aging Function	71%	3.94 ± 3.8
A. Lanitis et al. [34]	2004	Private (40, 400)	Active Appearance Models	Quadratic Aging Function	N/A	3.82 ± 5.58
X. Geng et al. [18]	2006	FG-NET (82, 1.002)	AGES	Regression	N/A	6.77

Table 2.2: Age Estimation Methods

3 Data Collection

As described in Section 2.3 there are many age-based databases of facial images. However, all existing datasets are based on real age estimation.

The idea of the thesis is to compare the performance between predicting real or apparent age labels.

Re-write and organize

In our proposed challenge, however we propose the first dataset to recognize the age people look like based on the opinion on many users using a new crowdsourcing data collection and labeling application.

We developed a web application in order to collect and label an age estimation dataset online by the community. The application uses the Facebook API to facilitate the access and so reach more people with a broader background and also it allow us to easily collect data from the participants, such as gender, nationality and age. We show some panels of the application in the Figure 1(a), 1(b) and 1(c). The web application was developed in a gamified way, i.e. the users or players get points for uploading and labeling images, the closer the age guess was to the apparent age (average labeled age) the more points the player obtains. In order to increase the engagement of the players we add a global and friends leaderboard where the users can see their position in the ranking. We ask the users to upload images of a single person and we give them tools to crop the image if necessary, we also ask them to give the real age (or as close as possible) of the person in uploaded image, allowing more analysis and comparisons with real age and apparent age.

Few weeks after release the application we have already collected near 1000 images and near 10000 votes. These numbers will continue growing in order to generate the future competition. Some of the properties of the database which is being collected with the web application are listed below:

- Thousands of faces labeled by many users.
- Images with background.
- Non-controlled environments.
- Non-labeled faces neither landmarks, making the estimation problem even harder.

- One of the first datasets in the literature including estimated age labeled by many users to define the ground truth with the objective of estimating the age.
- The evaluation metric will be pondered by the mean and the variance of the labeling by the participants.
- The dataset also provides for each image the real age although not used for recognition (just for analysis purposes).

In the same way for all the labelers we have their nationality, age, and gender, which will allow analyzing demographic and other interesting studies among the correlation of labelers. In relation to the properties of existing datasets shown in Table I, ours include labels of the real age of the individuals and the apparent age given by the collected votes, both age distributions are shown in the Figure 2. The images of our database has been taken under very different conditions, which makes it more challenging for recognition purposes.

3.1 Web Application

3.2 HuPBA Age Dataset

4 Method

4.1 Biological Inspired Method

4.1.1 Background

4.1.2 System overview

4.2 Deep Learning Method

4.2.1 Background

4.2.2 System overview

5 Experimental Results

6 Conclusions and Future work

References

- [1] LHI image database. Available at <http://www.lotushill.org/LHIFrameEn.html>, 2010.
- [2] Luís A Alexandre. Gender recognition: A multiscale decision fusion approach. *Pattern Recognition Letters*, 31(11):1422–1427, 2010.
- [3] A. Bastanfard, M.A. Nik, and M.M. Dehshibi. Iranian face database with age, pose and expression. In *Machine Vision, 2007. ICMV 2007. International Conference on*, pages 50–55, Dec 2007.
- [4] Sergey Brin and Lawrence Page. The anatomy of a large-scale hyper-textual web search engine. *Comput. Netw. ISDN Syst.*, 30(1-7):107–117, April 1998.
- [5] D Michael Burt and David I Perrett. Perception of age in adult caucasian male faces: Computer graphic manipulation of shape and colour information. *Proceedings of the Royal Society of London. Series B: Biological Sciences*, 259(1355):137–143, 1995.
- [6] Ira Cohen, Nicu Sebe, Ashutosh Garg, Lawrence S Chen, and Thomas S Huang. Facial expression recognition from video sequences: temporal and static modeling. *Computer Vision and image understanding*, 91(1):160–187, 2003.
- [7] Charles Darwin. *The expression of the emotions in man and animals / by Charles Darwin*. New York ;D. Appleton and Co., 1916. <http://www.biodiversitylibrary.org/bibliography/4820>.
- [8] E. Eidinger, R. Enbar, and T. Hassner. Age and gender estimation of unfiltered faces. *Information Forensics and Security, IEEE Transactions on*, 9(12):2170–2179, Dec 2014.
- [9] P. Ekman, W.V. Friesen, and J.C. Hager. *Facial Action Coding System (FACS): Manual*. A Human Face, Salt Lake City (USA), 2002.
- [10] Beat Fasel and Juergen Luetttin. Automatic facial expression analysis: a survey. *Pattern recognition*, 36(1):259–275, 2003.
- [11] Softopia Japan Foundation. Human and Object Interaction Processing (HOIP) Face Database. Available at <http://www.hoip.jp/>, 2014.

- [12] Winrich A Freiwald, Doris Y Tsao, and Margaret S Livingstone. A face feature space in the macaque temporal lobe. *Nature neuroscience*, 12(9):1187–1196, 2009.
- [13] Yun Fu, Guodong Guo, and T.S. Huang. Age synthesis and estimation via faces: A survey. *Pattern Analysis and Machine Intelligence, IEEE Transactions on*, 32(11):1955–1976, Nov 2010.
- [14] Yun Fu and T.S. Huang. Human age estimation with regression on discriminative aging manifold. *Multimedia, IEEE Transactions on*, 10(4):578–584, June 2008.
- [15] Yun Fu, Ye Xu, and T.S. Huang. Estimating human age by manifold analysis of face pictures and regression on aging features. In *Multimedia and Expo, 2007 IEEE International Conference on*, pages 1383–1386, July 2007.
- [16] A. Gallagher and T. Chen. Understanding images of groups of people. In *Proc. CVPR*, 2009.
- [17] Xin Geng, Zhi-Hua Zhou, and K. Smith-Miles. Automatic age estimation based on facial aging patterns. *Pattern Analysis and Machine Intelligence, IEEE Transactions on*, 29(12):2234–2240, Dec 2007.
- [18] Xin Geng, Zhi-Hua Zhou, Yu Zhang, Gang Li, and Honghua Dai. Learning from facial aging patterns for automatic age estimation. In *Proceedings of the 14th Annual ACM International Conference on Multimedia*, MULTIMEDIA '06, pages 307–316, New York, NY, USA, 2006. ACM.
- [19] Guodong Guo, Yun Fu, C.R. Dyer, and T.S. Huang. Image-based human age estimation by manifold learning and locally adjusted robust regression. *Image Processing, IEEE Transactions on*, 17(7):1178–1188, July 2008.
- [20] Guodong Guo, Yun Fu, C.R. Dyer, and T.S. Huang. A probabilistic fusion approach to human age prediction. In *Computer Vision and Pattern Recognition Workshops, 2008. CVPRW '08. IEEE Computer Society Conference on*, pages 1–6, June 2008.
- [21] Guodong Guo and Guowang Mu. Simultaneous dimensionality reduction and human age estimation via kernel partial least squares regression. In *Computer Vision and Pattern Recognition (CVPR), 2011 IEEE Conference on*, pages 657–664, June 2011.

- [22] Guodong Guo and Guowang Mu. A framework for joint estimation of age, gender and ethnicity on a large database. *Image and Vision Computing*, 32(10):761 – 770, 2014. Best of Automatic Face and Gesture Recognition 2013.
- [23] Guodong Guo, Guowang Mu, Yun Fu, and Thomas S. Huang. Human age estimation using bio-inspired features. In *CVPR*, pages 112–119. IEEE, 2009.
- [24] Hu Han, Charles Otto, and Anil K. Jain. Age estimation from face images: Human vs. machine performance. In *ICB'13*, pages 1–8, 2013.
- [25] Lin Hong, Anil K. Jain, and Sharath Pankanti. Can multibiometrics improve performance. Technical Report MSU-CSE-99-39, Department of Computer Science, Michigan State University, East Lansing, Michigan, December 1999.
- [26] Satoshi Hosoi, Erina Takikawa, and Masato Kawade. Ethnicity estimation with facial images. In *Automatic Face and Gesture Recognition, 2004. Proceedings. Sixth IEEE International Conference on*, pages 195–200. IEEE, 2004.
- [27] Rein-Lien Hsu, Mohamed Abdel-Mottaleb, and Anil K Jain. Face detection in color images. *Pattern Analysis and Machine Intelligence, IEEE Transactions on*, 24(5):696–706, 2002.
- [28] Anil K. Jain, Sarat C. Dass, and Karthik Nandakumar. Soft biometric traits for personal recognition systems. In David Zhang and Anil K. Jain, editors, *ICBA*, volume 3072 of *Lecture Notes in Computer Science*, pages 731–738. Springer, 2004.
- [29] Praveen Srinivasan JB Duler. Visada, Personalized Beauty Discovery from a Selfie. <http://visada.me/>, 2015. [Online; accessed 08-March-2015].
- [30] T.D. Kemper. *A Social Interactional Theory of Emotions*. A Wiley-interscience publication. Wiley, 1978.
- [31] Yehuda Koren, Robert Bell, and Chris Volinsky. Matrix factorization techniques for recommender systems. *Computer*, 42(8):30–37, August 2009.
- [32] A. Lanitis. FG-NET Aging Data Base, November 2007. Available at http://www.eecs.qmul.ac.uk/~yf300/FG_NET_data/index.html.

- [33] A. Lanitis. Age estimation based on head movements: A feasibility study. In *Communications, Control and Signal Processing (ISCCSP), 2010 4th International Symposium on*, pages 1–6, March 2010.
- [34] A. Lanitis, C. Draganova, and C. Christodoulou. Comparing different classifiers for automatic age estimation. *Trans. Sys. Man Cyber. Part B*, 34(1):621–628, February 2004.
- [35] A. Lanitis, C.J. Taylor, and T.F. Cootes. Modeling the process of ageing in face images. In *Computer Vision, 1999. The Proceedings of the Seventh IEEE International Conference on*, volume 1, pages 131–136 vol.1, 1999.
- [36] A. Lanitis, C.J. Taylor, and T.F. Cootes. Toward automatic simulation of aging effects on face images. *Pattern Analysis and Machine Intelligence, IEEE Transactions on*, 24(4):442–455, Apr 2002.
- [37] Greg Linden, Brent Smith, and Jeremy York. Amazon.com recommendations: Item-to-item collaborative filtering. *IEEE Internet Computing*, 7(1):76–80, January 2003.
- [38] Khoa Luu, Karl Ricanek, Tien D. Bui, and Ching Y. Suen. Age estimation using active appearance models and support vector machine regression. In *Proceedings of the 3rd IEEE International Conference on Biometrics: Theory, Applications and Systems*, BTAS’09, pages 314–318, Piscataway, NJ, USA, 2009. IEEE Press.
- [39] Khoa Luu, Keshav Seshadri, Marios Savvides, Tien D. Bui, and Ching Y. Suen. Contourlet appearance model for facial age estimation. In Anil K. Jain, Arun Ross, Salil Prabhakar, and Jaihy Kim, editors, *IJCB*, pages 1–8. IEEE, 2011.
- [40] Y. Makihara, M. Okumura, H. Iwama, and Y. Yagi. Gait-based age estimation using a whole-generation gait database. In *Biometrics (IJCB), 2011 International Joint Conference on*, pages 1–6, Oct 2011.
- [41] Meredith Minear and Denise C Park. A lifespan database of adult facial stimuli. *Behavior Research Methods, Instruments, & Computers*, 36(4):630–633, 2004.
- [42] Bingbing Ni, Zheng Song, and Shuicheng Yan. Web image mining towards universal age estimator. In *Proceedings of the 17th ACM International Conference on Multimedia*, MM ’09, pages 85–94, New York, NY, USA, 2009. ACM.

- [43] P. Jonathon Phillips, Patrick J. Flynn, Todd Scruggs, Kevin W. Bowyer, Jin Chang, Kevin Hoffman, Joe Marques, Jaesik Min, and William Worek. Overview of the Face Recognition Grand Challenge. In *CVPR*, pages 947–954. IEEE, 2005.
- [44] P. Jonathon Phillips, Harry Wechsler, Jeffery Huang, and Patrick J. Rauss. The {FERET} database and evaluation procedure for face-recognition algorithms. *Image and Vision Computing*, 16(5):295 – 306, 1998.
- [45] N. Ramanathan and R. Chellappa. Face verification across age progression. *Image Processing, IEEE Transactions on*, 15(11):3349–3361, Nov 2006.
- [46] N. Ramanathan and R. Chellappa. Modeling age progression in young faces. In *Computer Vision and Pattern Recognition, 2006 IEEE Computer Society Conference on*, volume 1, pages 387–394, June 2006.
- [47] N. Ramanathan, R. Chellappa, and S. Biswas. Computational methods for modeling : A survey. *Journal of Visual Languages and Computing*, 20(3):131 – 144, 2009.
- [48] K. Ricanek and T. Tesafaye. Morph: a longitudinal image database of normal adult age-progression. In *Automatic Face and Gesture Recognition, 2006. FGR 2006. 7th International Conference on*, pages 341–345, April 2006.
- [49] T. Sim, S. Baker, and M. Bsat. The cmu pose, illumination, and expression (pie) database. In *Automatic Face and Gesture Recognition, 2002. Proceedings. Fifth IEEE International Conference on*, pages 46–51, May 2002.
- [50] Yaniv Taigman, Ming Yang, Marc’Aurelio Ranzato, and Lior Wolf. Deepface: Closing the gap to human-level performance in face verification. In *Computer Vision and Pattern Recognition (CVPR), 2014 IEEE Conference on*, pages 1701–1708. IEEE, 2014.
- [51] Kazuya Ueki, Teruhide Hayashida, and Tetsunori Kobayashi. Subspace-based age-group classification using facial images under various lighting conditions. In *Proceedings of the 7th International Conference on Automatic Face and Gesture Recognition, FGR ’06*, pages 43–48, Washington, DC, USA, 2006. IEEE Computer Society.

- [52] John Wright, Allen Y Yang, Arvind Ganesh, Shankar S Sastry, and Yi Ma. Robust face recognition via sparse representation. *Pattern Analysis and Machine Intelligence, IEEE Transactions on*, 31(2):210–227, 2009.
- [53] Tao Wu, Pavan K. Turaga, and Rama Chellappa. Age estimation and face verification across aging using landmarks. *IEEE Transactions on Information Forensics and Security*, 7(6):1780–1788, 2012.
- [54] Baiqiang Xia, Boulbaba Ben Amor, Mohamed Daoudi, and Hassen Drira. Can 3D Shape of the Face Reveal your Age? In *International Conference on Computer Vision Theory and Applications*, Lisbonne, Portugal, January 2014.