


CollectorManager
-collectors: Dict[str, AbstractInputCollector]
-current_collector: Optional[AbstractInputCollector]
-current_collector_type: Optional[str]
-visualizers: List[Any]
-tracked_keys: List[str]
-event_callbacks: List[Callable]
-data_access_service: DataAccessService
+__init__() : void
+add_collector(collector_type: str, collector: AbstractInputCollector) : void
+set_current_collector(collector_type: str) : bool
+get_available_collectors() : List[Dict[str, str]]
+start_capture() : void
+stop_capture() : void
+register_visualizer(visualizer: Any) : void
+unregister_visualizer(visualizer: Any) : void
+set_tracked_keys(keys: List[str]) : void
+get_active_keys() : List[str]
+on_event(callback: Callable) : void
+remove_event_handler(callback: Callable) : void
+get_current_collector_capabilities() : Dict[str, Any]
+get_current_collector_type() : str
+get_collector(collector_type: str) : Optional[AbstractInputCollector]
+get_current_collector() : Optional[AbstractInputCollector]
-_initialize_collectors() : void
-_get_collector_display_name(collector_type: str) : str
-_update_visualizers() : void
-_update_visualizer(visualizer: Any) : void
-_handle_input_event(event: InputData) : void
-_get_controller_name() : str
1
manages
uses
«interface»
AbstractInputCollector
+start_capture() : void
+stop_capture() : void
+get_input_event() : InputData
+on_event(callback: Callable) : void
+set_supported_keys(keys: List[str]) : void
+get_events_since(timestamp: float) : List[InputData]
+clear_events() : void
+get_active_keys() : List[str]
+get_collector_type() : str
+get_capabilities() : Dict[str, Any]
DataAccessService
+get_instance() : DataAccessService
+update_data(event: InputData) : void
+update_metadata(metadata: Dict) : void
implements
implements
handles
KeyboardMouseCollector
-keyboard_events: List[InputData]
-mouse_events: List[InputData]
-supported_keys: List[str]
-is_capturing: bool
-event_callbacks: List[Callable]
-key_state: Dict[str, bool]
-mouse_state: Dict[str, Any]
-keyboard_listener: Optional[keyboard.Listener]
-mouse_listener: Optional[mouse.Listener]
-mouse_tracking_mode: str
-direction_only: bool
-angle_grouping: int
+__init__() : void
+start_listeners() : void
+stop_listeners() : void
+on_press(key: Any) : bool
+on_release(key: Any) : bool
+on_move(x: int, y: int) : void
+on_click(x: int, y: int, button: Any, pressed: bool) : void
+on_scroll(x: int, y: int, dx: int, dy: int) : void
+set_screen_dimensions(width: int, height: int) : void
+set_joystick_sensitivity(sensitivity: float) : void
+set_mouse_tracking_mode(mode: str, direction_only: bool, angle_grouping: int) : void
-_reset_mouse_state(x: int, y: int) : void
-_reset_wheel(x: int, y: int) : void
-_process_event(event: InputData) : void
-_get_delta_direction() : Optional[str]
-_get_angle_direction() : Optional[str]
-_get_joystick_direction(velocity_x: float, velocity_y: float) : Optional[str]
PS4ControllerCollector
-controller_events: List[InputData]
-is_capturing: bool
-event_callbacks: List[Callable]
-controller: SDL_GameController
-joystick: SDL_Joystick
-controller_name: str
-controller_index: int
-button_states: Dict[str, bool]
-stick_positions: Dict[str, tuple]
-trigger_values: Dict[str, float]
-previous_trigger_values: Dict[str, float]
-previous_stick_positions: Dict[str, tuple]
-event_thread: Optional[threading.Thread]
-event_stop_event: threading.Event
-event_lock: threading.Lock
-max_events: int
-tracked_keys_set: Set[str]
-supported_keys: List[str]
+__init__() : void
+initialize_sdl() : bool
+start_capture() : void
+stop_capture() : void
+scan_controllers() : List[Dict[str, Any]]
+connect_to_first_available() : bool
+connect_to_controller(controller_index: int) : bool
+get_input_event() : InputData
+on_event(callback: Callable) : void
+set_supported_keys(keys: List[str]) : void
+get_events_since(timestamp: float) : List[InputData]
+clear_events() : void
+get_active_keys() : List[str]
+get_collector_type() : str
+get_capabilities() : Dict[str, Any]
-_process_sdl_event(event: sdl2.SDL_Event) : void
-_handle_button_event(button_event: sdl2.SDL_ControllerButtonEvent, is_pressed: bool) : void
-_handle_joystick_button_event(button_event: sdl2.SDL_JoyButtonEvent, is_pressed: bool) : void
-_handle_axis_event(axis_event: sdl2.SDL_ControllerAxisEvent) : void
-_on_controller_disconnected() : void
-_try_reconnect() : void
-_process_event(event: InputData) : void
-_safe_callback(callback: Callable[[InputData], None], event: InputData) : void
-_event_loop() : void
creates
creates
InputData
+timestamp: float
+event_type: str
+key: Optional[str]
+active_keys: List[str]
+mouse_x: Optional[int]
+mouse_y: Optional[int]
+button_pressed: Optional[str]
+direction: Optional[str]
+speed: Optional[float]


+rel_x: Optional[float]
+rel_y: Optional[float]
+is_moving: Optional[bool]