
TECHNICAL DATA SHEET 04

PU ArqUnitec Wall



ABOUT THE PRODUCT

PU ARQUNITEC WALL, better known as polyurethane synthetic stone or PU STONE, is a finishing material for construction used in both interior and exterior applications. It is lightweight, flexible, and moldable, capable of adapting to any surface or environment. Its appearance replicates natural stone in large formats, allowing the creation of modern, luxurious spaces with high-end design. Available in the following colors:



SPECIFICATIONS

Product Name:	
PU Wall – ArqUnitec	
Format (Length × Width):	
3,94 ft x 23,62 In	
Weight:	
0,47 lbs x ft2	
Packaging:	
Unit – Box of 10 units	
Thickness	
1,181 In	
Density	
-	
Main Material:	
Polyurethane	
Country of Origin:	
China	

ADVANTAGES & BENEFITS



USES AND APPLICATIONS

- Reception areas
- Bedrooms
- Training centers
- Living rooms

INSTALLATION GUIDE

Tools: Cutting saw, gloves and safety glasses, installation adhesive.

1. **Surface Preparation:** The surface must be level and free of bituminous materials, moisture, and dust.
2. **Cutting:** Use a saw to cut the PU Stone panels according to the required measurements and shapes. Be sure to follow the manufacturer's instructions for precise cutting.
3. **Fastening:** Apply the adhesive recommended by the manufacturer to the back of each panel. Make sure to distribute the adhesive evenly.
4. **Finishing:** Make additional cuts to the panels as needed to fit corners and edges. Use trims or specific accessories to achieve a professional finish.
5. **Maintenance:** If necessary, remove dust buildup using a garden hose or water pressure not exceeding 100 PSI. Follow the necessary safety precautions to avoid damage.

WARRANTY POLICIES

- Verify and accept the product in good condition at the time of delivery. Claims for missing items, damage, or impacts will not be accepted after receipt of the merchandise.
- UNITEC USA DESIGN does not cover warranties for installed products showing differences in size, shade, color, scratches, warping, or any visible defect that could have been detected prior to installation.
- If any of these defects are found, do not install the product and contact the corresponding sales representative immediately.
- The warranty does not cover damage caused by improper use or handling.
- Follow the technical data sheet recommendations regarding use, applications, and installation.