TECHNICAL DATA SHEET 06

Uniflex Wall



SPECIFICATIONS

Product Name:	
Uniflex Wall	
Format (Length × Width):	
3,94 ft x 23,62 In	
Weight:	
0,60 lbs x ft2	
Packaging:	
Unit – Box of 30 units	
Thickness	
0,079 In	
Density	
-	
Main Material:	
Resins, quartz	
Country of Origin:	
China	

ADVANTAGES & BENEFITS



ABOUT THE PRODUCT

Uniflex walls are flexible decorative finishes made from Modified Mud Composite (MMC), characterized by their main raw materials (quartz sand, alkaline fiberglass mesh fabric, and eco-friendly emulsion). They are molded, baked, and irradiated using a specially designed combing system with temperature control.

Because they initially resemble ceramic tiles during their early development, they are commonly known as soft tiles.

Additionally, due to their light weight and relatively thin structure, they are convenient for transportation and installation.

Available in the following colors:



USES AND APPLICATIONS

- Interior walls
- Exterior façades
- Commercial renovations
- Industrial construction
- Institutional projects

INSTALLATION GUIDE

Tools: Utility knife, 120 cm metal ruler, gloves and safety glasses, mounting adhesive.

1. **Surface Preparation:** The surface must be level and free of organic material, moisture, and dust.
2. **Cutting:** According to the area, cut the first piece if necessary and level it correctly parallel to the floor to start the installation upward.
3. **Fastening:** Apply mounting adhesive on the back of the product in an “O/H” pattern and add safety dots in the hollow areas.
4. **Finishing:** Repeat the process, leaving an expansion gap between each piece of at least 2 mm and a maximum of 5 mm to cover the desired surface.
5. **Maintenance:** Finish the expansion joints using acrylic grout according to the color of the selected reference. Clean and remove excess dust when finished.

WARRANTY POLICIES

- Verify and accept the product in good condition at the time of delivery. Claims for missing items, damage, or impacts will not be accepted after receipt of the merchandise.
- UNITEC USA DESIGN does not cover warranties for installed products showing differences in size, shade, color, scratches, warping, or any visible defect that could have been detected prior to installation.
- If any of these defects are found, do not install the product and contact the corresponding sales representative immediately.
- The warranty does not cover damage caused by improper use or handling.
- Follow the technical data sheet recommendations regarding use, applications, and installation.