unitec U.S.A. DESIGN

TECHNICAL DATA SHEET 18.1

Type 1 Acoustic Panel



ABOUT THE PRODUCT

The Type 1 Acoustic Panel is a decorative acoustic wall covering with a wavy slat design, developed to improve sound absorption while adding visual depth to interior spaces. Its curved geometry creates a continuous vertical pattern that enhances reverberation control and reinforces the architectural continuity of the environment.

Manufactured from MDF with an acoustic backing, it combines a wood-like aesthetic with acoustic functionality, making it ideal for contemporary projects seeking a balance between design, sound comfort, and durability. Its “crisply aligned” slat finish delivers a clean, modern, and sophisticated look.

Available in 4 colors: cedar, wood cedar, ebony, and hazelnut.

SPECIFICATIONS

Product Name:	
Type 1 Acoustic Panel	
Format (Length × Width):	
7,87 ft x 23,62 In	
Weight:	
1,02 lbs x ft2	
Packaging:	
Unit	
Thickness	
0,551 In	
Density	
Approximately 8 kg/m²	
Main Material:	
MDF + Black Felt	
Country of Origin:	
China	

ADVANTAGES & BENEFITS



USES AND APPLICATIONS

- **Wall Cladding:** Interior applications in offices, meeting rooms, hotels, residences, and restaurants.
- **Acoustic Spaces:** Theaters, conference rooms, and lounge areas.
- **Accent Walls:** Behind sofas, work areas, and decorative feature walls.

INSTALLATION GUIDE

Tools: Measuring tape, circular saw or jigsaw, adhesive or metal clips, silicone gun, level, spacers, gloves, and safety glasses.

1. **Surface Preparation:** The wall must be clean, dry, flat, and free of dust or grease.
2. **Cutting:** Mark alignment using a level and pencil. Cut panels with a saw for a precise fit at corners or edges.
3. **Installation:** Use two clips per linear meter; first secure the clips to the frame or wall, then snap the panels into place.
4. **Finishing:** Install trims or moldings at edges, cover visible joints, and ensure perfect vertical alignment between slats.
5. **Maintenance:** Clean with a dry or damp cloth. For stains, use a mild detergent. Avoid abrasives, solvents, or harsh cleaners that may damage the surface.

WARRANTY POLICIES

- Verify and accept the product in good condition at the time of delivery. Claims for missing items, damage, or impacts will not be accepted after receipt of the merchandise.
- UNITEC USA DESIGN does not cover warranties for installed products showing differences in size, shade, color, scratches, warping, or any visible defect that could have been detected prior to installation.
- If any of these defects are found, do not install the product and contact the corresponding sales representative immediately.
- The warranty does not cover damage caused by improper use or handling.
- Follow the technical data sheet recommendations regarding use, applications, and installation.