TECHNICAL DATA SHEET 21

Interior PVC Molding



ABOUT THE PRODUCT

The Interior PVC Slat is an architectural decorative wall covering made from high-quality PVC, designed for interior applications that require lightweight performance, moisture resistance, and low maintenance. Its slatted design with a wood-like finish allows for the creation of continuous, modern, and elegant surfaces, adding visual order and depth to spaces.

It is an ideal solution for residential and commercial interior design projects seeking a practical alternative to natural wood, without the maintenance requirements or limitations related to moisture.

Available in the following colors:



SPECIFICATIONS

Product Name:

Interior PVC Molding

Format (Length × Width):

Solid slat: 9,514 ft (length) × 3,937 In (front width) × 1.97in (height)

Weight:

0,23 lbs x ft2

Packaging:

Unit

Thickness

0,787 In

Density

-

Main Material:

PVC (Polyvinyl Chloride)

Country of Origin:

China

ADVANTAGES & BENEFITS



USES AND APPLICATIONS

- Decorative Walls
- Interior Column Cladding
- Residential and Commercial Interior Design Projects

INSTALLATION GUIDE

Tools: Measuring tape, level, manual or power saw, drill, PVC screws, construction adhesive (optional), rubber mallet, PVC structural slat cap kit 10 cm, clean cloth.

1. **Surface Preparation:** The wall must be dry, clean, smooth, and level. If there are significant imperfections, it is recommended to patch or smooth the surface beforehand to ensure proper alignment of the slats.
2. **Layout and Cutting:** Mark guideline lines on the wall to ensure a straight and continuous installation. Cut the slats to the required size using appropriate manual or power tools.
3. **Slat Installation:** The structural PVC slat can be installed in two ways:
4. **Mechanical fastening (recommended):** Screw the slat directly to the surface or support structure using appropriate screws for PVC.
5. **Adhesive installation (indoor use):** Apply construction adhesive on the back of the slat in continuous beads or evenly spaced dots, then press firmly against the wall.
6. **Cap Kit Installation:** Once the slat is secured:
7. Insert the caps from the PVC Structural Slat Cap Kit (10 cm) into the visible ends of the profile. Press gently to ensure a clean, aligned fit. The caps provide a uniform and secure finish while protecting the interior of the profile.
8. **Finishing:** Check the final alignment of the slats. For corners or terminations, decorative trims can be added if required by the design. Painting or sealing the product is not necessary.

WARRANTY POLICIES

- Verify and accept the product in good condition at the time of delivery. Claims for missing items, damage, or impacts will not be accepted after receipt of the merchandise.
- UNITEC USA DESIGN does not cover warranties for installed products showing differences in size, shade, color, scratches, warping, or any visible defect that could have been detected prior to installation.
- If any of these defects are found, do not install the product and contact the corresponding sales representative immediately.
- The warranty does not cover damage caused by improper use or handling.
- Follow the technical data sheet recommendations regarding use, applications, and installation.