

HydroPacifique — Test Import Files

Five sample CSV files, one per station and series, with randomly generated but physically coherent data. The rainfall series drives the river and groundwater responses, so the files line up when plotted together.
Generated 18 September 2026.

1. The files at a glance

File	Station	ID	Type	Series	Rows
HY-001_RF.csv	HY-001	2581	1 Rainfall	RF	288
TGA-NKL-WLR_WLR.csv	TGA-NKL-WLR	2575	11 Surface water	WLR	288
TGA-NKL-GW01_GWL.csv	TGA-NKL-GW01	2577	5 Groundwater	GWL	288
HY-003_GWL.csv	HY-003	2582	5 Groundwater	GWL	288
TGA-NKL-JGE_JGE.csv	TGA-NKL-JGE	2576	11 Surface water	JGE	12 + 2 hdr

The filename is not cosmetic. The importer reads the station code from everything before the first underscore, and the series initial from what follows. Renaming any of these files will break the import.

2. Each file in detail

HY-001_RF.csv — Rainfall

Station	HY-001 — Nukualofa Rain Gauge (ID 2581, type 1 Rainfall)
Series	RF, millimetres
Period	01/03/2026 00:00 - 03/03/2026 23:45
Rows	288, at 15-minute intervals
Values	0.0 to 8.0 mm per interval; 384.8 mm total across about ten bursts
Shape	Dry spells at 0.0, punctuated by storms. This is the series the other files respond to.

```
01/03/2026 08:00:00;0.2;
01/03/2026 08:15:00;2.6;
01/03/2026 08:30:00;7.6;
01/03/2026 08:45:00;0.0;
```

TGA-NKL-WLR_WLR.csv — River water level

Station	TGA-NKL-WLR — Nuku'alofa River Water Level (ID 2575, type 11 Surface water)
Series	WLR, millimetres
Period	01/03/2026 00:00 - 03/03/2026 23:45
Rows	288, at 15-minute intervals
Values	1,179 to 3,103 mm
Shape	Baseflow near 1180 mm with sharp peaks minutes after each rainfall burst, then quick recession — a normal flashy river hydrograph.

TGA-NKL-GW01_GWL.csv and HY-003_GWL.csv — Groundwater level

Stations	TGA-NKL-GW01 — Nuku'alofa Groundwater Well (ID 2577) HY-003 — Nukualofa (ID 2582) both type 5 Groundwater
Series	GWL, centimetres
Period	01/03/2026 00:00 - 03/03/2026 23:45
Rows	288 each, at 15-minute intervals
Values	GW01: 289.2 to 299.8 cm HY-003: 403.8 to 411.9 cm
Shape	Steady recession between storms, with a smooth lagged rise after each one — the water table responds hours later and far more gently than the river. HY-003 sits deeper and is more damped, so the two wells differ.

TGA-NKL-JGE_JGE.csv — Stream gaugings

Station	TGA-NKL-JGE — Nuku'alofa River Gauging Station (ID 2576, type 11 Surface water)
Series	JGE — a reserved initial, not an ordinary time series
Layout	25 columns, and the first two rows are skipped (title + header). Data starts on line 3.
Period	12 gaugings, February 2024 to February 2026 — episodic, not continuous
Values	Mean stage 42 to 155 cm; discharge 3.868 to 74.512 m ³ /s
Consistency	Discharge follows a single stage-discharge relation with realistic scatter, and area x velocity equals discharge on every row, so these gaugings would produce a sensible rating curve.

Two things to check before importing the gauging file.

1. Your database has no JGE row in data_type yet (only WLR, RF and GWL), so the import will be refused until the seeding script adds it.
2. Stage is recorded in **centimetres** in the gauging file, while the WLR series is in **millimetres**. That is the application's own convention, not an error in these files, but it matters when comparing the two.

3. What is not here: well logs

There is no test file for well logs, because the application has no import route for them. They have no series initial, and the field-report import does not carry them either. Depth / conductivity / temperature profiles are entered through a field report on a Groundwater station, or synced from the Nomad mobile app.

Likewise there are no files for ETL (rating curves), REP (benchmarks), RA (field reports), LAB or TOT. Each has its own distinct layout that would need to be read out of its loader first, in the way the 25-column gauging format was.

4. Importing them

Open the import page, select one or more of these files, and upload. Order does not matter. The three-column files can be re-imported safely; the gauging file updates rows in place on (station, date and time) rather than duplicating them.

These are synthetic values. The numbers are randomly generated, only hydrologically plausible. Load them into a test or demonstration database, not one holding real observations.