

Diagnostics for a tagging-based movement model (**momo**)

Tobias Mildenberger, Anders Nielsen, Mark Maunder

MGWG
ICES HQ, Copenhagen, Denmark
19/11/2024

Outline

- ▶ Why should I care about momo?
- ▶ What is momo?
- ▶ Does it work?
- ▶ Estimating residuals for momo
- ▶ Conclusion

Why should I care about momo?

- ▶ New state-space movement model implemented in TMB and now RTMB
- ▶ Allows to estimate animal movement based on tagging data (conventional and/or archival tags)
- ▶ Allows to estimate natural and fishing mortality and biomass based on tagging data and spatial effort and catch data
- ▶ Incorporates environmental information into stock assessments
- ▶ Was used to estimate relative and absolute biomass indices for stock assessment of skipjack tuna in the Eastern Pacific Ocean

What is momo?

- ▶ Model that describes movement based on the advection-diffusion equation
- ▶ Uses habitat preference functions to estimate advection and diffusion rates as smooth functions of any field (e.g. environmental fields)
- ▶ Allow differentiation between active advection (taxis) informed by gradient of fields and passive advection (advection) informed by rate fields
- ▶ Reconstruct tag history either by matrix exponential approach or by Kalman filter

Advection-diffusion equation and habitat preference functions

- ▶ Advection-diffusion equation

$$\frac{\partial N}{\partial t} = \frac{\partial}{\partial x} \left(D \frac{\partial N}{\partial x} \right) + \frac{\partial}{\partial y} \left(D \frac{\partial N}{\partial y} \right) - \frac{\partial}{\partial x}(uN) - \frac{\partial}{\partial y}(vN)$$

- ▶ Habitat preference function

$$h(g, t) = \sum_{i=1}^n f_i(\xi_i(g, t), k_i, \alpha_i)$$

where f_i is a smooth function of the i th environmental or geographical field $\xi_i(g, t)$ with knot vector k_i and parameter vector α_i ;

Matrix exponential approach (à la Thorson et al. 2021)

- ▶ Instantaneous diffusion rate: D^*

$$d^*(g_2, g_1, t) = \begin{cases} e^{h(g_1, t)} & \text{if } g_1 \text{ and } g_2 \text{ are adjacent} \\ -\sum_{g' \neq g_1} \{d^*(g', g_1, t)\} & \text{if } g_1 = g_2 \\ 0 & \text{otherwise} \end{cases}$$

- ▶ Instantaneous taxis rate: Z^*

$$z^*(g_2, g_1, t) = \begin{cases} h(g_2, t) - h(g_1, t) & \text{if } g_1 \text{ and } g_2 \text{ are adjacent} \\ -\sum_{g' \neq g_1} \{h(g_2, t) - h(g_1, t)\} & \text{if } g_1 = g_2 \\ 0 & \text{otherwise} \end{cases}$$

- ▶ Instantaneous advection rate: V^*

$$v^*(g_2, g_1, t) = \sum_{i=1}^n \gamma_i w^*(g_2, g_1, t, i)$$

- ▶ Movement: M

$$M(t) = e^{(A^* + D^*)\Delta t} = e^{(Z^* + V^* + D^*)\Delta t}$$

Kalman filter

- ▶ Data

- ▶ Archival tag:

$$o_{t_r} = (x_{t_r}, y_{t_r}), o_{t_r + \Delta t} = (x_{t_r + \Delta t}, y_{t_r + \Delta t}), \dots, o_{t_c} = (x_{t_c}, y_{t_c})$$

- ▶ Conventional tag:

$$o_{t_r} = (x_{t_r}, y_{t_r}), o_{t_c} = (x_{t_c}, y_{t_c})$$

where t_r is the time of release and t_c is the time of capture.

- ▶ Model

$$o_t \sim N(\psi_t, \Sigma_o)$$

$$\psi_{t+\Delta t} \sim N(\psi_t + \mathbf{A}^*(\psi_t, t), 2\mathbf{D}^*(\psi_t, t)\Delta t \mathbf{I}_{2 \times 2})$$

where ψ_t is the predicted position at time t , Σ_o is the observation noise covariance matrix for observation o_t , and $\mathbf{I}_{2 \times 2}$ is the identity matrix.

- ▶ As ψ depends on parameter values, differentiable representation of fields are required → local interpolation

Kalman filter

- ▶ Data

- ▶ Archival tag:

$$o_{t_r} = (x_{t_r}, y_{t_r}), o_{t_r + \Delta t} = (x_{t_r + \Delta t}, y_{t_r + \Delta t}), \dots, o_{t_c} = (x_{t_c}, y_{t_c})$$

- ▶ Conventional tag:

$$o_{t_r} = (x_{t_r}, y_{t_r}), o_{t_c} = (x_{t_c}, y_{t_c})$$

where t_r is the time of release and t_c is the time of capture.

- ▶ Model

$$o_t \sim N(\psi_t, \Sigma_o)$$

$$\psi_{t+\Delta t} \sim N(\psi_t + \mathbf{Z}^*(\psi_t, t) + \mathbf{V}^*(\psi_t, t), 2\mathbf{D}^*(\psi_t, t)\Delta t \mathbf{I}_{2 \times 2})$$

where ψ_t is the predicted position at time t , Σ_o is the observation noise covariance matrix for observation o_t , and $\mathbf{I}_{2 \times 2}$ is the identity matrix.

- ▶ As ψ depends on parameter values, differentiable representation of fields are required → local interpolation

Survival and probability of capture

Likelihood contribution of an (archival) tag i recaptured in position $pos_m = (x_m, y_m)$ at time t_m :

$$L_i(M, \lambda|E) = \frac{F_{pos_m, t_m, f}}{M + \sum_{f=1}^F F_{pos_m, t_m, f}} (1 - e^{-(M + \sum_{f=1}^F F_{pos_m, t_m, f}) \Delta t_m}) \prod_{s=1}^{m-1} e^{-(M + \sum_{f=1}^F F_{pos_s, t_s, f}) \Delta t_s}$$

Likelihood contribution of a non-recaptured tag i :


$$\begin{aligned} L_i(M, \lambda|E) &= \frac{M}{M + \sum_{f=1}^F F_{pos_1, t_1, f}} (1 - e^{-(M + \sum_{f=1}^F F_{pos_1, t_1, f}) \Delta t_1}) \\ &+ \sum_{a=1}^A \frac{M}{M + \sum_{f=1}^F F_{pos_a, t_a, f}} (1 - e^{-(M + \sum_{f=1}^F F_{pos_a, t_a, f}) \Delta t_a}) \prod_{s=1}^{a-1} e^{-(M + \sum_{f=1}^F F_{pos_s, t_s, f}) \Delta t_s} \\ &+ \prod_{a=1}^A e^{-(M + \sum_{f=1}^F F_{pos_a, t_a, f}) \Delta t_a} \end{aligned}$$

where M is the constant instantaneous natural mortality rate and F_f is the instantaneous fishing mortality proportional to the locally interpolated effort of fleet f .







Does it work?

- ▶ Simulation-estimation study
- ▶ Generate random environmental fields
- ▶ Draw random parameters defining habitat preference function for taxis and constant diffusion
- ▶ Compare c-tags vs. a-tags vs. both combined
- ▶ Varying number of tags (c-tags/a-tags): 25/5, 100/25, 500/100
- ▶ 500 replicates
- ▶ Apply KF and EXPM to same data sets
- ▶ Calculate relative errors for parameters ($\frac{\hat{\theta} - \theta}{\theta}$)







Simulated data example I









Simulated data example I (KF)




Simulated data example I (EXPM)




Simulated data example II




Simulated data example II (KF)




Simulated data example II (EXPM)



Does it work? (KF)



Does it work? (EXPM)




Recapture position residuals


Recapture position residuals

- ▶ Kalman filter (c-tags):


Recapture position residuals (KF)




Recapture position residuals (KF)



Recapture position residuals (KF)



Recapture position residuals (KF)



Recapture position residuals

- ▶ Kalman filter (c-tags):

$$\epsilon^{\text{kf}} = (\epsilon_x, \epsilon_y) = \left(\frac{x_{t_c} - \hat{x}_{t_c}}{\sqrt{2\mathbf{D}^*(\psi_{t_c}, t_c)\Delta t}\mathbf{I}_{2\times 2}}, \frac{y_{t_c} - \hat{y}_{t_c}}{\sqrt{2\mathbf{D}^*(\psi_{t_c}, t_c)\Delta t}\mathbf{I}_{2\times 2}} \right)$$

Recapture position residuals


- ▶ Kalman filter (c-tags):

$$\epsilon^{\text{kf}} = (\epsilon_x, \epsilon_y) = \left(\frac{x_{t_c} - \hat{x}_{t_c}}{\sqrt{2\mathbf{D}^*(\psi_{t_c}, t_c)\Delta t}\mathbf{I}_{2\times 2}}, \frac{y_{t_c} - \hat{y}_{t_c}}{\sqrt{2\mathbf{D}^*(\psi_{t_c}, t_c)\Delta t}\mathbf{I}_{2\times 2}} \right)$$


- ▶ Matrix exponential:

$$\epsilon^{\text{expm}} = (\epsilon_x, \epsilon_y)$$


Recapture position residuals for x




Recapture position residuals for x




Recapture position residuals for x




Recapture position residuals for x




Recapture position residuals for x




Recapture position residuals for x



Recapture position residuals for x



Recapture position residuals for x



Recapture position residuals

- ▶ Kalman filter (c-tags):


$$\epsilon^{\text{kf}} = (\epsilon_x, \epsilon_y) = \left(\frac{x_{t_c} - \hat{x}_{t_c}}{\sqrt{2\mathbf{D}^*(\psi_{t_c}, t_c)\Delta t}\mathbf{I}_{2\times 2}}, \frac{y_{t_c} - \hat{y}_{t_c}}{\sqrt{2\mathbf{D}^*(\psi_{t_c}, t_c)\Delta t}\mathbf{I}_{2\times 2}} \right)$$

- ▶ Matrix exponential:


$$\epsilon^{\text{expm}} = (\epsilon_x, \epsilon_y)$$

$$\epsilon_x^{\text{expm}} = \Phi^{-1} \left(\text{Uniform} \left(\sum_{j=1}^{i-1} \sum_{k=1}^{N_y} P(x_j, y_k), \sum_{j=1}^i \sum_{k=1}^{N_y} P(x_j, y_k) \right) \right)$$


Recapture position residuals for y




Recapture position residuals for y



Recapture position residuals for y



Recapture position residuals for y



Recapture position residuals

- ▶ Kalman filter (c-tags):

$$\epsilon^{\text{kf}} = (\epsilon_x, \epsilon_y) = \left(\frac{x_{t_c} - \hat{x}_{t_c}}{\sqrt{2\mathbf{D}^*(\psi_{t_c}, t_c)\Delta t}\mathbf{I}_{2\times 2}}, \frac{y_{t_c} - \hat{y}_{t_c}}{\sqrt{2\mathbf{D}^*(\psi_{t_c}, t_c)\Delta t}\mathbf{I}_{2\times 2}} \right)$$

- ▶ Matrix exponential:


$$\epsilon^{\text{expm}} = (\epsilon_x, \epsilon_y)$$

$$\epsilon_x^{\text{expm}} = \Phi^{-1} \left(\text{Uniform} \left(\sum_{j=1}^{i-1} \sum_{k=1}^{N_y} P(x_j, y_k), \sum_{j=1}^i \sum_{k=1}^{N_y} P(x_j, y_k) \right) \right)$$



$$\epsilon_y^{\text{expm}} = \Phi^{-1} \left(\text{Uniform} \left(\sum_{k=1}^{j-1} P(y_k|x_i), \sum_{k=1}^j P(y_k|x_i) \right) \right)$$

where Φ^{-1} is the inverse normal distribution function, $P(x_j, y_k)$ is the probability of a tag being located in the j^{th} row (x-coordinate) and k^{th} column (y-coordinate) and $P(y_k|x_i)$ is the probability of a tag begin located in the k^{th} column (y-coordinate) given that is located in the i^{th} row (x-coordinate).


Correct model (KF)





Correct model (KF)





Correct model (KF)





Correct model (KF)






Using x&y-coordinates fields (KF)





Using x&y-coordinates fields (KF)













Using x&y-coordinates fields (KF)













Using x&y-coordinates fields (KF)




Using x-coordinates fields (KF)





Using y-coordinates fields (KF)




Correct model (EXPM)





Correct model (EXPM)





Correct model (EXPM)





Correct model (EXPM)







Using x&y-coordinates fields (EXPM)












Using x&y-coordinates fields (EXPM)








Using x&y-coordinates fields (EXPM)













Using x&y-coordinates fields (EXPM)



Using x-coordinates fields (EXPM)



Using y-coordinates fields (EXPM)



Conclusion

- ▶ Work in progress - development & testing ongoing
- ▶ Possible to speed up expm?
- ▶ Implement flexible rate and gradient flexible fields
- ▶ Thanks to IATTC for funding this work

References

- Kristensen, K., Nielsen, A., Berg, C.W., Skaug, H., and Bell, B.M. 2016. TMB: Automatic Differentiation and Laplace Approximation. *Journal of Statistical Software*, 70(5), 1-21. <https://doi:10.18637/jss.v070.i05>
- Kristensen, K. 2024. RTMB: 'R' bindings for 'TMB'. R package version 1.6. <https://github.com/kaskr/RTMB>
- Mildenberger, T.K., Nielsen, A., and Maunder, M. 2022. Spatiotemporal tagging model for skipjack tuna in the EPO. DOCUMENT SAC-13-08. Inter-American Tropical Tuna Comission (IATTC). 13th Scientific advisory meeting. (by videoconference). 16-20 May 2022. https://www.iattc.org/getattachment/a89cea47-8552-4ab7-b6ca-5b4115f2e1c9/SAC-13-08_Spatiotemporal-tagging-model-for-skipjack-in-the-EPO.pdf.
- Mildenberger, T.K., Nielsen, A., and Maunder, M. 2024. A spatiotemporal Petersen-type model for skipjack tuna in the EPO. DOCUMENT SAC-15 INF-G. Inter-American Tropical Tuna Comission (IATTC). 15th Scientific advisory meeting. La Jolla, California. 10-14 June 2024. https://www.iattc.org/GetAttachment/5d5a8b6b-8974-4d83-9072-4aeadeae43c2/SAC-14-INF-E_Spatiotemporal-tagging-model-for-skipjack-in-the-EPO.pdf.
- Mildenberger, T.K., Nielsen, A., and Maunder, M. 2023. Length-structured spatiotemporal tagging model for skipjack tuna in the EPO. DOCUMENT SAC-14 INF-E. Inter-American Tropical Tuna Comission (IATTC). 14th Scientific advisory meeting. La Jolla, California. 15-19 May 2023. https://www.iattc.org/GetAttachment/f8eacbc8-92b8-434d-a331-bdc733dc1bc6/SAC-15-INF-G_Spatiotemporal-tagging-model-for-skipjack-in-the-EPO.pdf.
- R Core Team 2024. R: A language and environment for statistical computing. R Foundation for Statistical Computing, Vienna, Austria. URL <https://www.R-project.org/>.
- Thorson, J.T., Barbeaux, S.J., Goethel, D.R., Kearney, K.A., Laman, E.A., Nielsen, J.K., Siskey, M.R., Siwicke, K. and Thompson, G.G. 2021. Estimating fine-scale movement rates and habitat preferences using multiple data sources. *Fish and Fisheries*, 22(6), pp.1359-1376. <https://doi.org/10.1111/faf.12592>