www.pacificears.com | info@pacificears.com

AU: info@pacificears.com.au
1300 90 50 10

NZ: info@pacificears.co.nz
07 542 3659

Specifications

Filters	SNR	H	M	L
PACS PRO17	17	16	16	16
PACS PRO20	20	20	18	17
PACS PRO26	27	26	25	25
PACS PRO27	27	27	24	23

H: Average attenuation characteristics in high frequency spectrum (> 2 kHz)
M: Average attenuation characteristics in mid frequency spectrum (0.5 - 2kHz)
L: Average attenuation characteristics in Low frequency spectrum (<0.5 kHz)
SNR (Single Number Rating): Average attenuation characteristics in the standard frequency spectrum.

Attenuation was determined in accordance with EN352-2:2002

Specifications

Drivercomms / PRO Drivercomms

Type	Single Driver
Freq. Response	40hz-15Khz
Sensitivity @ 1Khz	104.5db
Impedance @ 1Khz	375 ohms

Standard Cable Length	30/140cm
Cable Type	Black or Beige cable
Build Material	25 Shore Medical Grade Silicone

Your ear impressions are now on file. Every ear impression that passes through our lab is scanned using the latest digital technology and stored for up to three years, so if you need any further custom product you can place your order without the need for new impressions. If the impressions we have on record are more than three years old we do request a fresh set to be made in case of any adjustments with your ear.



Revolutionise your performance experience

The PACS Drivercomms is designed from the ground up with the performance racing environment in mind.

Improved and refined over several years, our Drivercomm earpieces offer a superbly clear and comfortable communication experience that's second to none.

The PACS PRO Drivercomms takes all the great features of the original Drivercomms and adds to it, combining our tried and tested PRO hearing protection filter and the PACS Drivercomms to create the perfect motorsport communication and hearing protection product.



Care and Maintenance of your PACS Drivercomms

It is important that you read these notes to ensure longevity of your custom Drivercomms. Cleaning them regularly and paying close attention to their maintenance is vital to ensure their continued performance. We offer full cleaning and reconditioning services for your Drivercomms so please don't hesitate to call if your Drivercomms need attention.





Cleaning and Storage

Use a moist cloth or sterile wipe to clean the silicone moulds and cables. Do not allow any moisture into the cable connections when cleaning. Do not immerse any part of the Drivercomms in any liquid. Do not get your Drivercomms wet. Please store them in the case supplied when not in use. Visually inspect the sound ports on each earpiece after use to check that no wax, skin debris or dirt has penetrated the tubes. Use the wax pick provided to carefully remove any matter.

Sanidry: Sanitiser and Dryer (sold separately)

We recommend that your Drivercomms are cleaned and dried in the Sanidry regularly, including after every race. Please see the separate instruction manual for use of the Sanidry.

NOTE: A common cause of Drivercomm failure is ingression of ear wax or sweat into the sound tubes. This is easily prevented by regular checks and cleaning.

Fitting

Your Drivercomms can be identified with a red logo on the right earpiece and a blue logo on the left earpiece. From a comfort and acoustic perspective, it is important that they are fitted correctly to provide a good seal of the ear.



Begin by placing the tip of the Drivercomms into your ear canal (fig 1) whilst at the same time twisting gently backwards (fig 2). It is sometimes easier to use both hands when fitting the earpieces making sure that the top part of the mould is located under the flap of skin at the top of the ear (fig 3).





Gently press the mould until it feels located and secure (fig 4). Use the comfort cream to help the fitting initially and create a good seal if required. Spread a small amount around the ear canal tip, being careful to avoid the sound tubes. NEVER re-adjust or remove the Drivercomms by pulling the cable.

