ASSIGNMENT NO : A7 - TCP CALCULATOR

Title: Lab Assignment on Unit V: (Mandatory Assignment)

Write a program of Calculator (Arithmetic) using TCP socket for wired network.

CODE :

1. CalClient.java

```
import java.io.DataInputStream;
import
java.io.DataOutputStream;
import java.io.IOException;
import java.net.InetAddress;
import java.net.Socket; import
java.util.Scanner; public class
CalClient {

    public static void main(String[] args) throws IOException {
        InetAddress ip = InetAddress.getLocalHost();
        int port = 4444;
        Scanner sc = new Scanner(System.in);

        // Step 1: Open the socket connection.
        Socket s = new Socket(ip, port);

        // Step 2: Communication-get the input and output stream
        DataInputStream dis = new DataInputStream(s.getInputStream());
        DataOutputStream dos = new DataOutputStream(s.getOutputStream());

        while (true) {
            // Enter the equation in the form//
            "operand1 operation operand2"
            System.out.print("Enter the equation in the form: ");
            System.out.println("'operand operator operand'");

            String inp = sc.nextLine();

            if (inp.equals("bye"))
                break;

            // send the equation to server
            dos.writeUTF(inp);

            // wait till request is processed and sent back to client
            String ans = dis.readUTF();
            System.out.println("Answer = " + ans);
        }
    }
```

```
}

/* OUTPUT
Enter the equation in the form: 'operand operator operand'
78 + 23
Answer = 101
Enter the equation in the form: 'operand operator operand'
15 / 3
Answer = 5
Enter the equation in the form: 'operand operator operand'
43 - 24
Answer = 19
Enter the equation in the form: 'operand operator operand'
12 * 4
Answer = 48
Enter the equation in the form: 'operand operator operand'
bye */
```

2. CalServer.java

```
import java.io.DataInputStream; import
java.io.DataOutputStream; import java.io.IOException; import
java.net.ServerSocket; import java.net.Socket; import
java.net.SocketException; import java.util.StringTokenizer;
public class CalServer { public static void main(String
args[]) throws IOException {

        // Step 1: Establish the socket connection.
        ServerSocket ss = new ServerSocket(4444);
        Socket s = ss.accept();

        // Step 2: Processing the request.
        DataInputStream dis = new DataInputStream(s.getInputStream());
        DataOutputStream dos = new DataOutputStream(s.getOutputStream());

        while (true) {
            // wait for input String
            input = dis.readUTF();

            if (input.equals("bye")) {
                break;
            }

            System.out.println("Equation received : " + input);
            int result;

            // Use StringTokenizer to break the equation into operand and
            // operation
            StringTokenizer st = new StringTokenizer(input);

            int oprnd1 = Integer.parseInt(st.nextToken());
            String operation = st.nextToken(); int oprnd2
```

```
            = Integer.parseInt(st.nextToken()); // perform
            the required operation.
            if (operation.equals("+")) {
                result = oprnd1 + oprnd2;
            }

            else if (operation.equals("-")) {
                result = oprnd1 - oprnd2;
            } else if (operation.equals("*")) {
                result = oprnd1 * oprnd2;
            } else { result = oprnd1 /
                oprnd2;
            }
            System.out.println("Sending the result... [" + oprnd1 + operation + oprnd2
+ " = " + result + "]");

            // send the result back to the client.
            dos.writeUTF(Integer.toString(result));
        }
    }
}



/*
*       OUTPUT
 *
C:\Users\dell\eclipse-workspace\CNL A7 TCP Calculator\src>javac CalServer.java

C:\Users\dell\eclipse-workspace\CNL A7 TCP Calculator\src>java CalServer
Equation received : 78 + 23
Sending the result... [78+23 = 101]
Equation received : 15 / 3
Sending the result... [15/3 = 5]
Equation received : 43 - 24
Sending the result... [43-24 = 19]
Equation received : 12 * 4
Sending the result... [12*4 = 48]
Exception in thread "main" java.net.SocketException: Connection reset at
       java.base/sun.nio.ch.NioSocketImpl.implRead(NioSocketImpl.java:323) at
       java.base/sun.nio.ch.NioSocketImpl.read(NioSocketImpl.java:350) at
       java.base/sun.nio.ch.NioSocketImpl$1.read(NioSocketImpl.java:803) at
       java.base/java.net.Socket$SocketInputStream.read(Socket.java:982) at
       java.base/java.net.Socket$SocketInputStream.read(Socket.java:977) at
java.base/java.io.DataInputStream.readUnsignedShort(DataInputStream.java:341)
       at java.base/java.io.DataInputStream.readUTF(DataInputStream.java:593)
       at java.base/java.io.DataInputStream.readUTF(DataInputStream.java:568)
       at CalServer.main(CalServer.java:22)

C:\Users\dell\eclipse-workspace\CNL A7 TCP Calculator\src>
 * */
```

CLASSMATE
Date :
Page :

~~10~~ TCP calculator. (4)

Q1 What are the State of TCP connection?

(a) LISTEN
- (server) represent waiting for connection request from any remote TCP and port

(b) SYN-SENT
(client) represent waiting for matching connection request af

(c) SYN-Received
waiting for conferm connection request acknowledgment after having both.

Q2 What is anonymus FTP.

→ A host that provides an FTP service may provide anonymus FTP access user typically log into the service with an anonymus or guest when prompted username.
- Many ftp host whose purpose is to provide software update will allow anonymus login Although user are commonly asked to send their email address instead of password.

Q3 Differen betn TCP and UDP

	TCP	UDP
(i)	This connection oriented protocol	- This is connection less protocols.
(ii)	TCP doesn't support multicasting & broadcasting	- UDP connection is message steren
(iii)	It provide error control & flow control	- error control, flow control provided

④ TCP packet is called as segment - UDP packet is called as user datagram

⑤ It support full duplex transmission - doesn't support full duplex transmission.

Q4 What is use of accept()

→ Accept connection with accept() system call this call typically block until client connects with server.

Name : Pushkaraj Chavan.

Class : TE

Div : C

Roll No. : 58