Lab Assignment on Unit II: (Use JAVA/PYTHON)

Write a program to simulate Go back N and Selective Repeat Modes of Sliding Window Protocol in peer to peer mode

Demonstrate the packets captured traces using Wireshark Packet Analyzer Tool for peer to peer mode

PROGRAMS

```
//.....CLIENT SIDE (SELECTIVE REPEAT).....//
import java.lang.System;
import java.net.*;
import java.io.*; import
java.text.*; import
java.util.Random; import
java.util.*;
public class Client { static
   Socket connection;
   public static void main(String a[]) throws SocketException
      { try { int v[] = new int[10];
         int n = 0;
         Random rands = new Random();
         int rand = 0;
         InetAddress addr = InetAddress.getByName("Localhost");
         System.out.println(addr);
         connection = new Socket(addr, 8011);
         DataOutputStream out = new DataOutputStream(
                connection.getOutputStream());
         DataInputStream in = new DataInputStream(
                connection.getInputStream());
         int p = in.read();
         System.out.println("No of frame is:" + p);
         for (int i = 0; i < p; i++) {
            v[i] = in.read();
            System.out.println(v[i]);
            //g[i] = v[i];
         }
```

```
rand = rands.nextInt(p);//FRAME NO. IS RANDOMLY GENERATED
         v[rand] = -1;
         for (int i = 0; i < p; i++)
          {
               System.out.println("Received frame is: " + v[i]);
         for (int i = 0; i < p; i++)
            if (v[i] == -1) {
               System.out.println("Request to retransmit from packet no
                     + (i+1) + " again!!");
               n = i;
               out.write(n);
               out.flush();
            }
         System.out.println();
            v[n] = in.read();
            System.out.println("Received frame is: " + v[n]);
         System.out.println("quiting");
      } catch (Exception e) {
         System.out.println(e);
      }
   }
}
/*----C:\Users\dell\Java\CN\SelRep>javac
Client.java
C:\Users\dell\Java\CN\SelRep>java Client
Localhost/127.0.0.1
No of frame is:8
30
40
50
```

```
60
70
80
90
100
Received frame is: 30
Received frame is: 40
Received frame is: 50
Received frame is: 60
Received frame is: -1
Received frame is: 80
Received frame is: 90
Received frame is: 100
Request to retransmit from packet no 5 again!!
Received frame is: 70
quiting
C:\Users\dell\Java\CN\SelRep>
*/
//.....SERVER SIDE (SELECTIVE REPEAT).....//
import java.io.DataInputStream;
import java.io.DataOutputStream;
import java.io.IOException;
import java.net.ServerSocket;
import java.net.Socket; import
java.net.SocketException;
public class Server { static ServerSocket Serversocket; static
   DataInputStream dis; static DataOutputStream dos; public static
   void main(String[] args) throws SocketException {
      try { int a[] = { 30, 40, 50, 60, 70, 80, 90, 100}
         };
         Serversocket = new ServerSocket(8011);
         System.out.println("waiting for connection"); Socket client =
         Serversocket.accept(); dis = new
         DataInputStream(client.getInputStream()); dos = new
         DataOutputStream(client.getOutputStream());
```

```
System.out.println("Thenumberofpacketssentis:"+a.length); int
         y = a.length; dos.write(y); dos.flush();
         for (int i = 0; i < a.length; i++) {
            dos.write(a[i]);
         dos.flush(); } int
         k = dis.read();
         dos.write(a[k]);
         dos.flush();
      } catch (IOException e) {
         System.out.println(e);
      } finally {
         try {
            dis.close();
            dos.close();
         } catch (IOException e) {
            e.printStackTrace();
         }
      }
   }
}
/*-----OUTPUT-----
C:\Users\dell\Java\CN\SelRep>javac Server.java
C:\Users\dell\Java\CN\SelRep>java Server
waiting for connection The
number of packets sent is:8
C:\Users\dell\Java\CN\SelRep>
*/
```

	4 Go Back Neprotocol. Classmate Date: Page: Page:
81	My we need flow control Mechanism? flow control mechanism can be addsified by we whether or not the teating wed. Sends feedback to the sending node. I flow control in important because it is possible for a sending computer to transmit untormation afort faster rate that the destination computer can teave and processit.
82	Inlust are the ways to control flow Control at DLL! Flow control way freelback Rate. - baseflow control base flow control.
•	In these protocols the - These protocol have built sender send from ofter an nechanism to testical it has received aconomisations the rate of transmission from the user this used of slate without requiring an the data leak layer this is used on the handood by.
02	Khad in Sliding hemdow. ? The sliding window is a technique for sende my multiple of from at a time. It control the data to packet but the two devia where reliable of gradual delivor of data frame is needed it wheel Tip-

Pushkaraj Chavan TEC 58

	CIASSMATE Date:
	[wgv.
04.	How whodow size grow and shrink at West side?
	Semple put et ab a top receive butter for
The state of	incompre data that has not been processed
	yet I by the application, the client &
	server are advertising their window site
	value as they commission
-	Each TCP header will display the most texed
	window value which can grow or surple as
	the consection progresses
-	11 Police A 7 man 2
	How window Size grow Ashrink at Server side?
-	It is TCP buffer for Vincowing data has not
	been processed yet by the Capplication.
	Each TCP header will display the most
	a the connection progressess. In this example
	the client how TCP receives I wondow of 65,5 35
	byte and the server how 3,840
	139 PD GILD IN SET VA NO 3) DEVI
The same of	a partie or other than the same of any and are
	the second of th
10000	
	the second controlling the factor of the second
	the contract of the contract o
	the second secon
	and the second s
	Market and the second and provide the company of the second and th
	o: Chavan TEC 50

Pushkaraj Chavan TEC 58