```csharp
using System;
using System.Data;
using System.Data.SqlClient;

public partial class _Default : System.Web.UI.Page
{
    private DataSet ds=new DataSet();
    private SqlDataAdapter adapter;
    string connString = @"Data Source=DESKTOP-4L6NSGO\sqlexpress;Initial Catalog=mydbase;Integrated Security=True";
    protected void Button1_Click(object sender, EventArgs e)
    {
        using (SqlConnection conn = new SqlConnection(connString))
        {
            try
            {
                adapter = new SqlDataAdapter(TextBox1.Text,connString);
                adapter.Fill(ds);
                GridView1.DataSource = ds;
                GridView1.AutoGenerateColumns = true;
                GridView1.DataBind();
            }
            catch (Exception ex)
            {
                Label1.Text = ex.Message;
            }
        }
    }
}
```

| body | | |

Query: [        ]

[ Run Query ]

| Column0 | Column1 | Column2 |
| --- | --- | --- |
| abc | abc | abc |
| abc | abc | abc |
| abc | abc | abc |
| abc | abc | abc |
| abc | abc | abc |

Label

Server Explorer

- Azure
- Data Connection
  - desktop-4l6ns
    - Tables
    - Views
    - Stored Proce
    - Functions
    - Synonyms
    - Types
    - Assemblies
- Servers

Properties

**desktop-4l6nsgo\sqlexpress.mydbase.dbo** Connection

| **(Identity)** | |
| --- | --- |
| (Name) | mydbase |
| **Connection** | |
| Connection String | Data Source=DESKTOP-4L6NSGO\sqlexpress;Initial Catalog=mydbase;Integrated Security=True |
| Provider | .NET Framework Data Provider for SQL Server |
| State | Open |
| Type | Microsoft SQL Server |
| Version | 12.00.2269 |
| **Misc** | |
| Case Sensitive | False |
| Owner | DESKTOP-4L6NSGO\towsi |