



# Securely Configure Auto-Auth and Token Sink



# What is the Vault Agent?




The Vault Agent is a client daemon that runs alongside an application to enable legacy applications to interact and consume secrets

Vault Agent provides several different features:

- Automatic authentication including renewal
- Secure delivery/storage of tokens (response wrapping)
- Local caching of secrets
- Templating



# Legacy Applications – Auto-Auth



# Vault Agent – Auto-Auth



- The Vault Agent uses a pre-defined auth method to authenticate to Vault and obtain a token
- The token is stored in the "sink", which is essentially just a flat file on a local file system that contains the Vault token
- The application can read this token and invoke the Vault API directly
- This strategy allows the Vault Agent to manage the token and guarantee a valid token is always available to the application



# Vault Agent - Auto Auth



Vault Agent supports many types of auth methods to authenticate and obtain a token

Auth methods are generally the methods you'd associate with "machine-oriented" auth methods

- **AliCloud**
- **AppRole**
- **AWS**
- **Azure**
- **Certificate**
- **CloudFoundary**
- **GCP**
- **JWT**
- **Kerberos**
- **Kubernetes**



# Vault Agent Configuration File

```
auto_auth {
  method "approle" {
    mount_path = "auth/approle"
    config = {
      role_id_file_path = "<path-to-file>"
      secret_id_file_path = "<path-to-file>"
    }
  }
}

sink "file" {
  config = {
    path = "/etc/vault.d/token.txt"
  }
}

vault {
  address = "http://<cluster_IP>:8200"
}
```

**Auto-Auth  
Configuration  
(AppRole)**

**Sink  
Configuration**

**Vault**



# Vault Agent - Sink


As of today, `file` is the only supported method of storing the auto-auth token

Common configuration parameters include:

- `type` – what type of sink to use (again, only `file` is available)
- `path` – location of the file
- `mode` – change the file permissions of the sink file (default is 640)
- `wrap_ttl` = retrieve the token using response wrapping



# Auth-Auth Security Concerns





# Protecting the Token using Response Wrapping




To help secure tokens when using Auth-Auth, you can have Vault response wrap the token when the Vault Agent authenticates

- Response wrapped by the auth method
- Response wrapped by the token sink


The placement of the **`wrap_ttl`** in the Vault Agent configuration file determines where the response wrapping happens.



# Response Wrapping at the Auth Method



# Response Wrapping at the Sink



# Response-Wrapping the Token - Comparison



## Response Wrapped by the Auth Method

---

### Pros:

- Prevents man-in-the-middle attacks (MITM)
- More secure

### Cons:

- Vault agent cannot renew the token

## Response Wrapped by the Sink

---

### Pros:

- Allows the Vault agent to renew the token and re-authenticate when the token expires

### Cons:

- The token gets wrapped **after** it is retrieved from Vault. Therefore, it is vulnerable to MITM attack



# Response-Wrapping the Token - Comparison

## Response Wrapped by the Auth Method

```
pid_file = "/home/vault/pidfile"

auto_auth {
  method "kubernetes" {
    wrap_ttl = "5m"
    mount_path = "auth/kubernetes"
    config = {
      role = "example"
    }
  }
  ...

  vault {
    address = "http://<cluster_IP>:8200"
  }
}
```

## Response Wrapped by the Sink

```
pid_file = "/home/vault/pidfile"

auto_auth {
  method "kubernetes" {
    mount_path = "auth/kubernetes"
    config = {
      role = "example"
    }
  }
  sink "file" {
    wrap_ttl = "5m"
    config = {
      path = "/etc/vault/token"
    }
  }
}
```





# END OF SECTION

 Vault

CERTIFIED  
OPERATIONS  
PROFESSIONAL

