Implementing Access Control

in a Virtual Environment with pfSense

Hands-On Lab Guide

Open-source firewall and routing • segmented network design • rule-based access control

1. Introduction

Access control sits at the heart of every defensible network. The principle is simple — only allow the traffic that has a business reason to flow, and deny everything else — but the implementation is where students discover that firewall rule order matters, that an interface-bound rule behaves differently from a floating rule, that a permissive default is a quiet security failure, and that troubleshooting a denied packet teaches more than reading documentation ever does.

This lab provides a controlled environment for those discoveries. You will build a small segmented network using pfSense, a free and open-source firewall and routing platform that has been used in production by enterprises, universities, and home labs for over two decades. By the end of the lab, you will have a working three-network topology with a trusted LAN, an isolated DMZ, and a path to the internet, all enforced by firewall rules that you wrote and tested yourself.

Learning Objectives

After completing this lab, you will be able to:

- Design and build a segmented network in a virtualized environment using host-only networks and a software firewall.
- Install and perform initial configuration of pfSense, including interface assignment and the web administration console.
- Author firewall rules that enforce least-privilege network access between security zones.
- Implement aliases and schedules to manage rules at scale.
- Use NAT (network address translation) to expose specific services from a DMZ without flattening the network.
- Test and validate firewall rules from multiple vantage points, and read pfSense logs to confirm or deny intended behavior.

Why pfSense

pfSense is built on FreeBSD and the pf packet filter, the same firewall that protects much of OpenBSD's reputation for security. Three properties make it well suited to a teaching lab:

- **It is free.** The Community Edition has no licensing fees, no enrollment requirement, and no time-limited trial.
- **It exposes the concepts directly.** Rules, aliases, NAT, and schedules are surfaced explicitly in the UI rather than abstracted away. What you learn here translates directly to commercial firewalls from Palo Alto, Cisco, Fortinet, and others.
- **It runs anywhere.** A pfSense VM with two virtual NICs and 1 GB of RAM is perfectly capable of routing and filtering everything this lab will throw at it.

2. Prerequisites and Lab Resources

Hardware Requirements

Resource	Recommended	Minimum
Host CPU	4 cores with virtualization extensions (VT-x or AMD-V)	2 cores with virtualization extensions
Host RAM	16 GB	8 GB
Host Storage	60 GB free disk	40 GB free disk
Host OS	Windows 10/11, macOS 12+, Linux	Any 64-bit OS supporting VirtualBox or VMware
Network	Wired or stable Wi-Fi for downloading ISOs	Any internet connection during setup

Software You Will Download

All required software is free for lab use. Download the following before starting:

1. VirtualBox 7.x — https://www.virtualbox.org/wiki/Downloads (the lab uses VirtualBox; VMware Workstation Player works equally well with minor menu differences).
2. pfSense Community Edition installer ISO — https://www.pfsense.org/download/ (select "AMD64" architecture and "ISO" image type).
3. Ubuntu 22.04 Desktop ISO — https://ubuntu.com/download/desktop (used as the LAN client VM).
4. Ubuntu 22.04 Server ISO — https://ubuntu.com/download/server (used as the DMZ web server VM).

Recommended Background Knowledge

- Basic IPv4 subnetting (you should be comfortable reading 192.168.1.0/24 and knowing that 192.168.2.5 is not in that subnet).
- Familiarity with the concept of a default gateway and why traffic crosses one.
- Basic command-line use on Linux (ping, curl, ip a, ssh).

BEFORE YOU START

Take a snapshot of every VM after each major configuration step. You will deliberately misconfigure rules to see what happens, and rolling back to a known-good snapshot is faster than

> rebuilding.

3. Lab Topology

The lab models a small business network with three security zones, separated by a single pfSense firewall acting as the gateway between them. Every packet between zones traverses pfSense and is subject to the rules you write.

Network Layout

Zone	Subnet	pfSense Interface	Purpose
WAN	DHCP from host	WAN (em0)	Path to the internet via the host's NAT engine
LAN	192.168.10.0/24	LAN (em1)	Trusted internal users (e.g., workstations)
DMZ	192.168.20.0/24	OPT1 (em2)	Public-facing services (e.g., web server)

Virtual Machines

VM Name	Operating System	Role
pfSense-FW	pfSense CE 2.7+	Firewall and router with three NICs (WAN, LAN, DMZ)
LAN-Client	Ubuntu Desktop 22.04	Trusted user workstation on the LAN (192.168.10.10)
DMZ-Web	Ubuntu Server 22.04	Web server in the DMZ running Apache (192.168.20.10)

Logical Diagram

```
+-----------------+
|    Internet     |
+-----------------+
        |
 (NAT via host)
        |
 +-------+--------+
```

```
| pfSense-FW WAN |   (DHCP from host)
+----------------+
| pfSense-FW LAN |---192.168.10.1
+----------------+        |
                          |
              +--------------------+
              |  LAN-Client        |
              |  192.168.10.10     |
              +--------------------+

+----------------+
| pfSense-FW OPT1|---192.168.20.1
+----------------+        |
                          |
              +--------------------+
              |  DMZ-Web (Apache)  |
              |  192.168.20.10     |
              +--------------------+
```



Figure 1 – Network Diagram

PART 1

Build the Virtual Networks

Estimated time: **20 minutes**

Before creating any VMs, configure the host-only networks that the pfSense LAN and DMZ interfaces will plug into. Host-only networks are isolated from your physical LAN and from each other, which is exactly the property a lab needs.

Step 1.1 Create the LAN host-only network

5. Open VirtualBox and go to File → Tools → Network Manager.
6. On the Host-only Networks tab, click Create.
7. Select the new entry and click Properties.
8. On the Adapter tab, configure:
    - IPv4 Address: 192.168.10.254
    - IPv4 Network Mask: 255.255.255.0
9. On the DHCP Server tab, ensure Enable Server is unchecked. pfSense will provide DHCP, not VirtualBox.
10. Rename the network to LAB-LAN for clarity.

Step 1.2 Create the DMZ host-only network

11. Click Create again to add a second host-only network.
12. Configure the adapter:
    - IPv4 Address: 192.168.20.254
    - IPv4 Network Mask: 255.255.255.0
13. Disable the DHCP Server on this network as well.
14. Rename the network to LAB-DMZ.

WHY DISABLE DHCP

Two DHCP servers on the same broadcast domain produce inconsistent leases and complete chaos for clients. pfSense will run its own DHCP server on each interface, and that is the one we want answering.

PART 2

Install and Bootstrap pfSense

Estimated time: **30 minutes**

Step 2.1 Create the pfSense VM

15. In VirtualBox, click New.
16. Configure the VM with the following settings:
    - Name: pfSense-FW
    - Type: BSD
    - Version: FreeBSD (64-bit)
    - Memory: 1024 MB
    - Hard disk: Create a virtual hard disk now, VDI, dynamically allocated, 16 GB
17. Before booting, edit the VM's settings and add three network adapters:

Adapter	Attached To	Notes
Adapter 1	NAT	WAN — provides internet via the host
Adapter 2	Host-only Adapter (LAB-LAN)	LAN — trusted internal network
Adapter 3	Host-only Adapter (LAB-DMZ)	DMZ — public-facing services

Table 1 – Adapter Configuration

18. Attach the pfSense ISO to the optical drive under Settings → Storage.

Step 2.2 Run the pfSense installer

19. Boot the VM. When the loader menu appears, press 1 to boot multi-user.
20. At the Copyright and Distribution Notice, press Accept.
21. Select Install.
22. Choose Auto (ZFS) for the partition layout, then stripe with a single disk.
23. When installation completes, choose Reboot. Detach the ISO so the VM does not boot back into the installer.

Step 2.3 Assign interfaces

After the first boot, pfSense launches a text-based assignment wizard. Decline the VLAN setup, then assign the interfaces. The MAC addresses pfSense reports correspond to the order you added the adapters in VirtualBox:

- **WAN interface:** em0 (the NAT adapter)

- **LAN interface:** em1 (the LAB-LAN adapter)
- **OPT1 interface:** em2 (the LAB-DMZ adapter)

Confirm the assignments and let pfSense apply them. After a few seconds, you will see the menu with a list of interface IP addresses.

Step 2.4 Set the LAN IP address

24. From the menu, choose 2 — Set interface(s) IP address.
25. Select the LAN interface.
26. Decline DHCP, then enter:
    - IPv4 address: 192.168.10.1
    - Subnet bit count: 24
    - Upstream gateway: (leave blank)
27. When asked whether to enable the DHCP server on LAN, answer Yes. Use a range from 192.168.10.100 to 192.168.10.200.
28. Decline reverting the web GUI to HTTP.

Step 2.5 Set the DMZ (OPT1) IP address

29. Choose 2 again, then select the OPT1 interface.
30. Configure:
    - IPv4 address: 192.168.20.1
    - Subnet bit count: 24
31. Enable DHCP on OPT1 with a range from 192.168.20.100 to 192.168.20.200.

pfSense is now bootstrapped. The WAN should already have an IP from the host's NAT engine, the LAN serves DHCP at 192.168.10.0/24, and the DMZ serves DHCP at 192.168.20.0/24.

PART 3

Build the Client and Server VMs

Estimated time: **30 minutes**

Step 3.1 Create the LAN client

32. In VirtualBox, create a new VM named LAN-Client. Allocate 2 GB RAM, 20 GB disk, and a single network adapter.
33. Set the network adapter to Host-only Adapter and select LAB-LAN.
34. Install Ubuntu Desktop 22.04 with default options. When the installer asks about networking, accept DHCP.
35. After installation, open a terminal and confirm the IP address:

```
ip a show ens3
# Expected: an address in 192.168.10.0/24 leased from pfSense
ip route
# Expected: default via 192.168.10.1
```

36. Test connectivity:

```
ping -c 4 192.168.10.1     # pfSense LAN gateway
ping -c 4 8.8.8.8          # The internet, via WAN
```

Step 3.2 Create the DMZ web server

37. Create a second VM named DMZ-Web with 1 GB RAM, 20 GB disk, and a single network adapter set to Host-only Adapter, LAB-DMZ.
38. Install Ubuntu Server 22.04. Choose minimal install with OpenSSH server enabled.
39. After installation, install Apache:

```
sudo apt update
sudo apt install apache2 -y
sudo systemctl enable --now apache2
```

40. Customize the default page so you can tell at a glance whether you are reaching it:

```
echo "<h1>DMZ-Web - reachable on $(hostname -I)</h1>" | sudo tee /var/www/html/index.html
```

41. Confirm Apache is listening locally:

```
curl http://localhost
```

```
# Expected: the HTML you just wrote
```

42. Note the DHCP-assigned address (it should be in 192.168.20.0/24). To make rule writing predictable, configure a static address. Edit /etc/netplan/00-installer-config.yaml so it looks like the following, then run sudo netplan apply:

```
network:
  version: 2
  ethernets:
    ens3:
      dhcp4: false
      addresses: [192.168.20.10/24]
      routes:
        - to: default
          via: 192.168.20.1
      nameservers:
        addresses: [192.168.20.1]
```

PART 4

Reach the pfSense Web Console

Estimated time: **10 minutes**

All remaining configuration happens in the pfSense web GUI, which is reachable from any host on the LAN.

Step 4.1 First login

43. From LAN-Client, open Firefox and browse to https://192.168.10.1.
44. Accept the self-signed certificate warning. (You will replace this certificate in a production deployment; in the lab, skip past it.)
45. Log in with the default credentials:
    - Username: admin
    - Password: pfsense
46. Run the Setup Wizard. Confirm the hostname (e.g., pfsense-fw), the domain (lab.local), the time servers, and the WAN/LAN configuration. Accept the defaults you set during the text-based bootstrap.
47. On the final screen, change the admin password to something memorable. Reload the configuration when prompted.

LAB-ONLY SHORTCUTS

Default credentials, self-signed certificates, and HTTP redirects are acceptable inside an isolated lab on a host-only network. Do not carry these habits to a production firewall — the same convenience that helps here will hand the entire network to anyone who can reach the management interface in production.

PART 5

Author the Initial Access Control Rules

Estimated time: **45 minutes**

This is the heart of the lab. You will write firewall rules that enforce a specific access policy across the three zones, then verify that the rules behave as expected. pfSense rules are evaluated top-down on each interface; the first matching rule wins, and any traffic not matched by an explicit rule is denied by default. Understanding the order is half the discipline.

The Access Policy You Will Enforce

From	To	Allowed
LAN	**Internet (WAN)**	HTTP, HTTPS, DNS, ICMP echo-request
LAN	**DMZ**	HTTP and HTTPS to the web server only; SSH from a single admin host
DMZ	**LAN**	Nothing (deny all)
DMZ	**Internet (WAN)**	DNS and HTTP/HTTPS for package updates only
Internet	**DMZ**	HTTP/HTTPS to the web server (via NAT, configured later)
Internet	**LAN**	Nothing (deny all, default behavior)

Table 2 – Access Policy

Step 5.1 Create aliases

Aliases are named groups of hosts, networks, or ports. They make rules readable and make changes safer — you update the alias once, and every rule that references it follows. Navigate to Firewall → Aliases.

Create the following aliases:

Alias Name	Type	Members / Description
LAN_Net	Network	192.168.10.0/24 — the entire LAN
DMZ_Net	Network	192.168.20.0/24 — the entire DMZ
DMZ_Web_Server	Host	192.168.20.10 — the Apache server

Alias Name	Type	Members / Description
LAN_Admin_Hosts	Host	192.168.10.10 — admin workstation (LAN-Client)
Web_Ports	Port	80, 443 — HTTP and HTTPS
Mgmt_Ports	Port	22 — SSH for administrative access

Table 3 - Aliases

Step 5.2 LAN rules

Navigate to Firewall → Rules → LAN. pfSense includes a default "allow all from LAN" rule that we will replace with explicit rules. Either edit it down or delete it and start fresh.

Add the following rules in this order. Order matters: pfSense reads top to bottom and stops at the first match.

#	Action	Protocol	Source	Destination	Port / Description
1	**Pass**	TCP	LAN_Net	DMZ_Web_Server	Web_Ports — Allow LAN to web server
2	**Pass**	TCP	LAN_Admin_Hosts	DMZ_Net	Mgmt_Ports — Allow admin SSH to DMZ
3	**Block**	Any	LAN_Net	DMZ_Net	Block all other LAN→DMZ
4	**Pass**	TCP/UDP	LAN_Net	any	53 — Allow DNS
5	**Pass**	TCP	LAN_Net	any	Web_Ports — Allow web browsing
6	**Pass**	ICMP	LAN_Net	any	echoreq — Allow ping out
7	**Block**	Any	LAN_Net	any	Default deny (logged)

Table 4 – Network LAN ACL

To create each rule, click Add (the up arrow adds at the top, the down arrow at the bottom), then fill in the fields. Save the rule, and after the full set is in place, click Apply Changes at the top of the page.

> **WHY THE EXPLICIT DENY**
>
> pfSense already denies anything not matched by a rule. The reason to add an explicit final block

> rule is logging — without it, denied packets disappear silently. With it, you can review Status → System Logs → Firewall and see exactly what was rejected, which is invaluable for troubleshooting and for understanding what the network is actually doing.

Step 5.3 DMZ (OPT1) rules

Navigate to Firewall → Rules → OPT1. The DMZ has no default rules, which means everything is currently blocked from this interface. You will add only what is needed.

#	Action	Protocol	Source	Destination	Port / Description
1	**Block**	Any	DMZ_Net	LAN_Net	Block DMZ→LAN entirely
2	**Pass**	TCP/UDP	DMZ_Net	any	53 — Allow DNS
3	**Pass**	TCP	DMZ_Net	any	Web_Ports — Allow updates over HTTP/HTTPS
4	**Block**	Any	DMZ_Net	any	Default deny (logged)

Table 5 – Network DMZ-specific ACLs

Note the placement of the DMZ→LAN block: it is the first rule. If a later "allow web" rule were placed above it, it would not match LAN traffic (LAN is destination, not port), but a more permissive rule placed above could accidentally let DMZ-originated traffic into the trusted zone. Always block the dangerous flows explicitly and at the top.

PART 6

Expose the Web Server with NAT

Estimated time: **20 minutes**

Internal servers in the DMZ are not reachable from the internet by default — they have private IP addresses behind pfSense. To allow external clients to reach the web server, configure a port forward (destination NAT) that maps a port on the WAN interface to the DMZ web server. pfSense automatically creates a corresponding firewall rule to permit the forwarded traffic.

Step 6.1 Create the port forward

48. Navigate to Firewall → NAT → Port Forward.
49. Click Add.
50. Configure the rule:
    - Interface: WAN
    - Protocol: TCP
    - Destination: WAN address
    - Destination port range: HTTP (80) to HTTP (80) — repeat the process for HTTPS (443)
    - Redirect target IP: DMZ_Web_Server (use the alias)
    - Redirect target port: HTTP (80)
    - Description: Inbound HTTP to DMZ web server
51. Leave Filter rule association set to Add associated filter rule. This automatically creates the matching rule on the WAN interface.
52. Save and Apply Changes.

Step 6.2 Verify the auto-generated rule

Navigate to Firewall → Rules → WAN. You should see a new rule allowing TCP traffic from any source to the DMZ_Web_Server on port 80. The same configuration with port 443 produces a parallel rule for HTTPS.

LAB CAVEAT

Because the WAN side of pfSense is itself behind the host's NAT, true external internet traffic cannot reach the DMZ web server in this lab without additional port forwarding on the host. The NAT rule is still meaningful — it teaches the configuration pattern, and it can be tested by adding a fourth VM on a different host-only network simulating an external client.

PART 7

Test and Validate

Estimated time: **45 minutes**

A firewall rule that has not been tested is a hope, not a control. Walk through every entry in the access policy and confirm that the configured behavior matches the intended behavior.

Step 7.1 Test from LAN-Client

Run each of the following commands and predict the result before you press Enter. The match between prediction and outcome is what tells you whether you understand the rules.

```
# Should SUCCEED — LAN→DMZ web allowed
curl -m 5 http://192.168.20.10

# Should SUCCEED — admin SSH from LAN_Admin_Hosts
ssh -o ConnectTimeout=5 ubuntu@192.168.20.10

# Should FAIL — LAN→DMZ on a non-allowed port (e.g., NFS)
curl -m 5 http://192.168.20.10:2049

# Should SUCCEED — LAN→Internet HTTP
curl -m 5 http://example.com

# Should SUCCEED — DNS resolution
dig +short example.com

# Should SUCCEED — outbound ICMP
ping -c 2 8.8.8.8

# Should FAIL — outbound on non-allowed protocol/port
nc -vz -w 5 8.8.8.8 23     # Telnet to anywhere
```

Step 7.2 Test from DMZ-Web

SSH into DMZ-Web (from LAN-Client) and run:

```
# Should FAIL — DMZ→LAN blocked
curl -m 5 http://192.168.10.10

# Should FAIL — DMZ→pfSense LAN interface blocked (it sits in LAN_Net)
ping -c 2 192.168.10.1
```

```
# Should SUCCEED — DMZ→Internet for updates
sudo apt update

# Should FAIL — DMZ→Internet on a non-allowed protocol
nc -vz -w 5 8.8.8.8 23
```

Step 7.3 Read the firewall log

Navigate to Status → System Logs → Firewall. The log shows every packet that matched a logged rule. Look for the denials you triggered in the previous steps:

- Each blocked packet appears with its source IP, destination IP, protocol, and the rule that blocked it.
- You can click the red X next to any entry to see the rule that produced it, which is invaluable when troubleshooting unintended denials.
- Filter the log by interface, protocol, source, or destination to focus on a specific test.

Step 7.4 Build a results table

Document the outcome of each test in a table like the one below. Anything that did not match your prediction is a learning opportunity — investigate the logs until you can explain why.

Test	Expected	Actual	Notes / Rule Matched
LAN→DMZ HTTP to web server	Pass		
LAN→DMZ NFS	Block		
LAN→Internet HTTP	Pass		
LAN→Internet Telnet	Block		
DMZ→LAN HTTP	Block		
DMZ→Internet HTTPS update	Pass		

Table 6 – Network Rule Validation Tracker

PART 8

Extending the Lab

Estimated time: **Open-ended**

The base configuration above is enough to demonstrate access control fundamentals. Each of the following extensions deepens a specific capability.

Schedule-Based Rules

Navigate to Firewall → Schedules and create a schedule named Business_Hours covering Monday–Friday, 09:00–17:00. Then add a LAN rule that blocks access to a specific website (use a host alias) only during Business_Hours. Verify that the rule activates and deactivates on the boundary, and inspect what happens to existing connections that started before the boundary.

Block Lists with Aliases

pfSense supports URL Tables (IP) aliases that pull from external feeds. Configure an alias that imports a community block list — for example, the Spamhaus DROP list. Apply it to a WAN rule that drops any inbound traffic from listed sources. Observe how the rule count remains constant while the underlying address list updates automatically.

Captive Portal for User-Based Access

Build a third internal network (GUEST, 192.168.30.0/24) and enable Captive Portal on its interface. Require authentication against a small local user database before granting internet access. This separates per-device access (firewall rules) from per-user access (captive portal) and surfaces the trade-offs between the two.

VPN for Remote Access

Configure OpenVPN on pfSense to allow a remote client (e.g., your physical workstation) to dial into the LAN. Write firewall rules on the OpenVPN interface that constrain VPN clients to a single host or service, demonstrating that least privilege applies to remote access just as much as to wired connections.

Logging and Alerting

Configure pfSense to forward firewall logs via syslog to an external collector — a free option is a basic ELK stack or Graylog instance running in another VM. Build a query that surfaces every denied packet from the DMZ to the LAN over the last 24 hours. This is the lab equivalent of a SIEM rule, and it bridges access control into the detection discipline.

9. Troubleshooting Reference

Common problems and where to look first:

Symptom	Likely Cause and Fix
LAN-Client cannot reach the internet	Check the WAN interface in Status → Interfaces. If it has no IP, the NAT adapter on pfSense-FW is misconfigured. Confirm Adapter 1 is set to NAT in VirtualBox.
LAN-Client cannot reach the pfSense web GUI	Confirm the client received a 192.168.10.x address from DHCP. If not, the LAN interface is on the wrong host-only network. Check VirtualBox network attachment.
A rule that should permit traffic is blocking it	Rule order. Check whether an earlier rule on the same interface matches before the permit rule. Rules are evaluated top to bottom, first match wins.
A rule that should block traffic is permitting it	Two common causes: (1) the traffic matches an earlier permit rule; (2) the rule was created on the wrong interface. pfSense rules apply to traffic entering the firewall on a given interface, not leaving it.
NAT port forward does not work	Check Diagnostics → States and confirm pfSense is seeing the inbound packet. If not, the WAN-side path is broken. Also verify the auto-generated WAN rule is enabled and that the destination port matches what the client is sending.
DMZ web server cannot run apt update	Confirm DNS works first (dig). If DNS is fine but apt fails, check that the DMZ→Internet rule allows ports 80 and 443. apt uses both.

Table 7 – Troubleshooting FAQ

Useful Diagnostic Tools in pfSense

- **Status → System Logs → Firewall** — shows every packet matching a logged rule. The single most valuable troubleshooting view.
- **Diagnostics → Packet Capture** — a built-in tcpdump. Capture on a specific interface, with a host or port filter, to see what is actually arriving at the firewall.
- **Diagnostics → States** — displays every connection currently tracked by the stateful firewall. Useful for confirming that a connection was actually established versus blocked at the SYN.
- **Diagnostics → Test Port** — a quick way to confirm whether pfSense itself can reach a destination on a given port, isolating firewall issues from upstream issues.

10. Lab Deliverables

To consider the lab complete, produce the following artifacts:

53. A screenshot of the pfSense Dashboard showing all three interfaces (WAN, LAN, OPT1) with assigned IP addresses.
54. A screenshot of the LAN rules page with all seven rules visible and Apply Changes confirmed.
55. A screenshot of the OPT1 rules page with the four DMZ rules in place.
56. A screenshot of the NAT port forward configuration and the auto-generated WAN rule.
57. The completed test results table from Step 7.4.
58. A short written reflection (about half a page) addressing: which rule was hardest to get right and why; what the firewall log revealed that you would not have predicted; and one production scenario where the access policy you implemented would need to change.

11. Conclusion

Access control becomes intuitive once you have written the rules, watched them block legitimate traffic, fixed them, watched them permit traffic they should not have, and fixed them again. The pfSense interface makes every step of this loop visible — the rule list, the log, the state table, and the packet capture all sit one or two clicks apart from each other, which is exactly the property that makes pfSense a good teaching platform.

The configuration patterns you used here — segmented zones, ordered rules with explicit denies, named aliases, scheduled exceptions, and NAT for controlled exposure — appear in every commercial firewall you will encounter. The vendor name on the box changes; the discipline does not. Returning to this lab whenever you need to test a rule change before pushing it to production is the habit that separates network security as a working skill from network security as something you read about.