Here is the table code for the next lecture:

```html
<table class="w-full text-sm text-left text-gray-500 dark:text-gray-400">
    <thead class="text-xs text-gray-700 uppercase dark:bg-gray-700 dark:text-gray-400">
        <tr class="border">
            <th scope="col" class="py-3 px-6">
                #
            </th>
            <th scope="col" class="py-3 px-6">
                title
            </th>
            <th scope="col" class="py-3 px-6">
                book id
            </th>
            <th scope="col" class="py-3 px-6">
                qr code
            </th>
            <th scope="col" class="py-3 px-6">
                status
            </th>
            <th scope="col" class="py-3 px-6">
                available
            </th>
            <th scope="col" class="py-3 px-6">
                select
            </th>
            <th scope="col" class="py-3 px-6">
                delete
            </th>
        </tr>
    </thead>
    <tbody>
        {% for obj in object.books %}
        <tr class="border-b dark:bg-gray-800 dark:border-gray-700 {% if not obj.is_read  %}font-bold{% endif %}">
            <td scope="row" class="py-4 px-6 font-medium text-gray-900 whitespace-nowrap dark:text-white">
            </td>
            <td class="py-4 px-6">
            </td>
            <td class="py-4 px-6">
            </td>
            <td class="py-4 px-6">
            </td>
            <td class="py-4 px-6">
            </td>
            <td class="py-4 px-6">
            </td>
            <td class="py-4 px-6">
            </td>
            <td class="py-4 px-6">
            </td>
        </tr>
        {% endfor %}
    </tbody>
</table>
```