

**EXAMPLE 6: VARIABLES ARE
GLOBAL UNLESS DECLARED**

**IN JAVASCRIPT, IT IS PERFECTLY LEGAL TO USE A
VARIABLE WITHOUT "DECLARING IT"**

```
e = 2.71828;  
console.log("The value of e is" + e)
```

**ASSIGN A VALUE TO A VARIABLE WITHOUT EVER
HAVING DECLARED IT BEFORE**

IN JAVASCRIPT, IT IS PERFECTLY LEGAL TO USE A
VARIABLE WITHOUT "DECLARING IT"

```
e = 2.71828;
```

```
console.log("The value of e is" + e)
```

AND YOU CAN NOW USE ITS
VALUE, NO PROBLEM AT ALL!

ERRM, THERE IS ONE LITTLE
PROBLEM, ACTUALLY

IN JAVASCRIPT, IT IS PERFECTLY LEGAL TO USE A
VARIABLE WITHOUT "DECLARING IT"

**VARIABLES USED WITHOUT
DECLARATION BECOME
GLOBAL BY DEFAULT**

ERRM, THERE IS
PROBLEM, ACTUALLY

IN JAVASCRIPT, IT IS PERFECTLY LEGAL TO USE A
VARIABLE WITHOUT "DECLARING IT"

**VARIABLES USED WITHOUT
DECLARATION BECOME
GLOBAL BY DEFAULT**

ERRM, THERE IS
PROBLEM, ACTUALLY

IN JAVASCRIPT, IT IS PERFECTLY LEGAL TO USE A
VARIABLE WITHOUT "DECLARING IT"

VARIABLES USED WITHOUT
DECLARATION **BECOME**
GLOBAL BY DEFAULT

AND THAT'S A REAL PROBLEM.

PROBLEM, ACTUALLY

IN JAVASCRIPT, IT IS PERFECTLY LEGAL TO USE A
VARIABLE WITHOUT "DECLARING IT"

```
e = 2.71828;
```

```
console.log("The value of e is" + e);
```

VARIABLES USED WITHOUT DECLARATION BECOME GLOBAL BY
AND THAT'S A REAL

ALWAYS DECLARE VARIABLES
USED BEFORE USING THEM

ALWAYS DECLARE VARIABLES USED BEFORE USING THEM

```
e = 2.718281828;
```

```
console.log("The value of e is" + e);
```


ALWAYS DECLARE VARIABLES USED BEFORE USING THEM

```
var e = 2.71828;  
console.log("The value of e is" + e);
```

```
<script>  
window.onload = printX;  
var x = 10;  
function printX() {  
  var x = 10;  
  var pi = 3.1415;  
  console.log("Inside printX: x = " + x);  
  console.log("Inside printX: e = " + e);  
  console.log("Inside printX: pi = " + pi);  
  printAnotherX();  
}  
  
function printAnotherX() {  
  var x = 20;  
  console.log("Inside printAnotherX: x = " + x);  
  console.log("Inside printAnotherX: e = " + e);  
  console.log("Inside printAnotherX: pi = " + pi);  
}
```

SIMPLY TACK ON THE WORD **var** BEFORE
YOU USE THE VARIABLE FOR THE FIRST TIME
- IT WILL ENSURE THE VARIABLE IS LOCAL.

SIMPLY TACK ON THE WORD `var` BEFORE YOU USE THE VARIABLE FOR THE FIRST TIME - IT WILL ENSURE THE VARIABLE IS LOCAL.

```
window.onload = printX;
```

```
var x = 5;
```

```
function printX() {
```

```
    var x = 10;
```

```
    var pi = 3.1415;
```

```
    e = 2.71828;
```

```
    console.log("Inside printX: x = " + x);
```

```
    console.log("Inside printX: e = " + e);
```

```
    console.log("Inside printX: pi = " + pi);
```

```
    printAnotherX();
```

```
}
```

```
function printAnotherX() {
```

```
    var x = 20;
```

```
    console.log("Inside printAnotherX: x = " + x);
```

```
    console.log("Inside printAnotherX: e = " + e);
```

```
    console.log("Inside printAnotherX: pi = " + pi);
```

```
}
```

```
</script>
```

```
Inside printX: x = 10
```

```
Inside printX: e = 2.71828
```

```
Inside printX: pi = 3.1415
```

```
Inside printAnotherX: x = 20
```

```
Inside printAnotherX: e = 2.71828
```

```
✖ ▶ Uncaught ReferenceError: pi is not defined
```

SIMPLY TACK ON THE WORD `var` BEFORE YOU USE THE VARIABLE FOR THE FIRST TIME - IT WILL ENSURE THE VARIABLE IS LOCAL.

```
window.onload = printX;
```

```
var x = 5;
```

```
function printX() {
```

```
    var x = 10;
```

```
    var pi = 3.1415;
```

```
    e = 2.71828;
```

```
    console.log("Inside printX: x = " + x);
```

```
    console.log("Inside printX: e = " + e);
```

```
    console.log("Inside printX: pi = " + pi);
```

```
    printAnotherX();
```

```
}
```

```
function printAnotherX() {
```

```
    var x = 20;
```

```
    console.log("Inside printAnotherX: x = " + x);
```

```
    console.log("Inside printAnotherX: e = " + e);
```

```
    console.log("Inside printAnotherX: pi = " + pi);
```

```
}
```

```
</script>
```

```
Inside printX: x = 10
```

```
Inside printX: e = 2.71828
```

```
Inside printX: pi = 3.1415
```

```
Inside printAnotherX: x = 20
```

```
Inside printAnotherX: e = 2.71828
```

```
✖ ▶ Uncaught ReferenceError: pi is not defined
```

SIMPLY TACK ON THE WORD `var` BEFORE YOU USE THE VARIABLE FOR THE FIRST TIME - IT WILL ENSURE THE VARIABLE IS LOCAL.

```
<script>  
window.onload = printX;
```

```
var x = 5;
```

```
function printX() {
```

```
    var x = 10;
```

```
    var pi = 3.1415;
```

```
    e = 2.71828;
```

```
    console.log("Inside printX: x = " + x);
```

```
    console.log("Inside printX: e = " + e);
```

```
    console.log("Inside printX: pi = " + pi);
```

```
    printAnotherX();
```

```
}
```

```
function printAnotherX() {
```

```
    var x = 20;
```

```
    console.log("Inside printAnotherX: x = " + x);
```

```
    console.log("Inside printAnotherX: e = " + e);
```

```
    console.log("Inside printAnotherX: pi = " + pi);
```

```
}
```

```
</script>
```

```
Inside printX: x = 10
```

```
Inside printX: e = 2.71828
```

```
Inside printX: pi = 3.1415
```

```
Inside printAnotherX: x = 20
```

```
Inside printAnotherX: e = 2.71828
```

```
✖ ▶ Uncaught ReferenceError: pi is not defined
```

**WE HAVE A VARIABLE NOT
EXPLICITLY DECLARED..**

SIMPLY TACK ON THE WORD `var` BEFORE YOU USE THE VARIABLE FOR THE FIRST TIME - IT WILL ENSURE THE VARIABLE IS LOCAL.

```
<script>
window.onload = printX;
var x = 5;
function printX() {
  var x = 10;
  var pi = 3.1415;
  e = 2.71828;
  console.log("Inside printX: x = " + x);
  console.log("Inside printX: e = " + e);
  console.log("Inside printX: pi = " + pi);
  printAnotherX();
}

function printAnotherX() {
  var x = 20;
  console.log("Inside printAnotherX: x = " + x);
  console.log("Inside printAnotherX: e = " + e);
  console.log("Inside printAnotherX: pi = " + pi);
}
```

WE HAVE A VARIABLE NOT EXPLICITLY DECLARED..

```
Inside printX: x = 10
Inside printX: e = 2.71828
Inside printX: pi = 3.1415
Inside printAnotherX: x = 20
Inside printAnotherX: e = 2.71828
```

✖ ▶ Uncaught ReferenceError: pi is not defined

AND SO IT IS ACCESSIBLE FROM ANOTHER FUNCTION

```
</script>
```

SIMPLY TACK ON THE WORD `var` BEFORE YOU USE THE VARIABLE FOR THE FIRST TIME - IT WILL ENSURE THE VARIABLE IS LOCAL.

```
<script>  
window.onload = printX;
```

```
var x = 5;
```

```
function printX() {
```

```
  var x = 10;
```

```
  var pi = 3.1415;
```

```
  e = 2.71828;
```

```
  console.log("Inside printX: x = " + x);
```

```
  console.log("Inside printX: e = " + e);
```

```
  console.log("Inside printX: pi = " + pi);
```

```
}  
printAnotherX();
```

```
function printAnotherX() {
```

```
  var x = 20;
```

```
  console.log("Inside printAnotherX: x = " + x);
```

```
  console.log("Inside printAnotherX: e = " + e);
```

```
  console.log("Inside printAnotherX: pi = " + pi);
```

```
}
```

```
</script>
```

```
Inside printX: x = 10
```

```
Inside printX: e = 2.71828
```

```
Inside printX: pi = 3.1415
```

```
Inside printAnotherX: x = 20
```

```
Inside printAnotherX: e = 2.71828
```

```
✖ ▶ Uncaught ReferenceError: pi is not defined
```

AND SO IT IS ACCESSIBLE FROM ANOTHER FUNCTION

SIMPLY TACK ON THE WORD `var` BEFORE YOU USE THE VARIABLE FOR THE FIRST TIME - IT WILL ENSURE THE VARIABLE IS LOCAL.

```
<script>  
window.onload = printX;
```

```
var x = 5;
```

```
function printX() {
```

```
    var x = 10;
```

```
    var pi = 3.1415;
```

```
    e = 2.71828;
```

```
    console.log("Inside printX: x = " + x);
```

```
    console.log("Inside printX: e = " + e);
```

```
    console.log("Inside printX: pi = " + pi);
```

```
    printAnotherX();
```

```
}
```

```
function printAnotherX() {
```

```
    var x = 20;
```

```
    console.log("Inside printAnotherX: x = " + x);
```

```
    console.log("Inside printAnotherX: e = " + e);
```

```
    console.log("Inside printAnotherX: pi = " + pi);
```

```
}
```

```
</script>
```

```
Inside printX: x = 10
```

```
Inside printX: e = 2.71828
```

```
Inside printX: pi = 3.1415
```

```
Inside printAnotherX: x = 20
```

```
Inside printAnotherX: e = 2.71828
```

```
✖ ▶ Uncaught ReferenceError: pi is not defined
```

IF WE HAVE A VARIABLE THAT IS EXPLICITLY DECLARED..

SIMPLY TACK ON THE WORD `var` BEFORE YOU USE THE VARIABLE FOR THE FIRST TIME - IT WILL ENSURE THE VARIABLE IS LOCAL.

```
<script>  
window.onload = printX;
```

```
var x = 5;
```

```
function printX() {
```

```
  var x = 10;
```

```
  var pi = 3.1415;
```

```
  e = 2.71828;
```

```
  console.log("Inside printX: x = " + x);
```

```
  console.log("Inside printX: e = " + e);
```

```
  console.log("Inside printX: pi = " + pi);
```

```
  printAnotherX();
```

```
}
```

```
function printAnotherX() {
```

```
  var x = 20;
```

```
  console.log("Inside printAnotherX: x = " + x);
```

```
  console.log("Inside printAnotherX: e = " + e);
```

```
  console.log("Inside printAnotherX: pi = " + pi);
```

```
}
```

```
</script>
```

```
Inside printX: x = 10
```

```
Inside printX: e = 2.71828
```

```
Inside printX: pi = 3.1415
```

```
Inside printAnotherX: x = 20
```

```
Inside printAnotherX: e = 2.71828
```

```
✖ ▶ Uncaught ReferenceError: pi is not defined
```

IF WE HAVE A VARIABLE THAT IS EXPLICITLY DECLARED..

THEN IT IS NOT ACCESSIBLE IN A DIFFERENT FUNCTION

SIMPLY TACK ON THE WORD `var` BEFORE YOU USE THE VARIABLE FOR THE FIRST TIME - IT WILL ENSURE THE VARIABLE IS LOCAL.

```
<script>
window.onload = printX;
var x = 5;
function printX() {
  var x = 10;
  var pi = 3.1415;
  e = 2.71828;
  console.log("Inside printX: x = " + x);
  console.log("Inside printX: e = " + e);
  console.log("Inside printX: pi = " + pi);
  printAnotherX();
}

```

IF WE HAVE A VARIABLE THAT IS EXPLICITLY DECLARED..

```
Inside printX: x = 10
Inside printX: e = 2.71828
Inside printX: pi = 3.1415
Inside printAnotherX: x = 20
Inside printAnotherX: e = 2.71828
Uncaught ReferenceError: pi is not defined
```

```
function printAnotherX() {
  var x = 20;
  console.log("Inside printAnotherX: x = " + x);
  console.log("Inside printAnotherX: e = " + e);
  console.log("Inside printAnotherX: pi = " + pi);
}

```

THEN IT IS NOT ACCESSIBLE IN A DIFFERENT FUNCTION

</script>