# Ridgeline Apparel Supply

## Pro Tee Fabric Specification

Document ref: RAS-FS-2026-014 | Issued: 10 January 2026 | Supersedes: RAS-FS-2025-098

This specification covers the performance-blend fabric, garment construction, testing regime and commercial terms for the Pashun Pro Tee US range, produced at the Ridgeline Apparel Supply facility, Georgia, USA. Distributed to Pashun Sports Ltd for reference by Production, Quality and Buying teams. This document supersedes RAS-FS-2025-098 in full and should be read alongside lot-specific test certificates referenced in Section 10.

Confidentiality: Standard supplier reference document. Contains no information confidential beyond ordinary commercial terms between Ridgeline Apparel Supply and Pashun Sports Ltd.

## Table of Contents

1. Facility and Manufacturing Overview

2. Material Composition

3. Yarn and Fibre Specification

4. Fabric Finishes and Treatments

5. Performance Test Standards

6. Wash-Cycle Durability Testing

7. Garment Size Grading and Tolerances

8. Colourways, Tolerances and Dye Lot Records

9. Care and Aftercare Instructions

10. Test Certificate Log

11. Certifications and Compliance

12. Restricted Substances List (RSL)

13. Trims and Components Specification

14. Print and Graphic Placement Specification

15. Sustainability Statement

16. Packaging and Logistics Specification

17. Commercial Terms

18. Quality Assurance and Inspection Process

19. Non-Conformance and Rejection Procedure

20. Appendix A — Spectrophotometer Readings

21. Glossary of Terms

22. Contacts and Document Control

23. Revision History

# 1. Facility and Manufacturing Overview

The Pashun Pro Tee US range is produced end-to-end at Ridgeline Apparel Supply's vertically integrated facility in Georgia, USA, covering yarn spinning, knitting, dyeing, finishing and cut-and-sew under one roof. Printing, embroidery and trim supply are handled by long-standing approved subcontractors within a 150-mile radius, keeping the supply chain domestic and lead times predictable.

Ridgeline Apparel Supply has manufactured performance-blend fabric for the activewear sector since 2011 and has supplied Pashun Sports Ltd since 2024. The facility operates a single production shift with capacity to flex to a second shift for peak seasonal volume, subject to 4 weeks' notice.

# 2. Material Composition

The Pashun Pro Tee is constructed from a two-layer performance-blend fabric system: an outer face fabric providing the visible finish and stretch, and an interior wicking mesh providing moisture management against the skin.

Combined weight tolerance of ±5% accounts for normal batch-to-batch variation in fibre density and finishing add-on weight. Fabric weight is verified per lot in accordance with ASTM D3776, sampled at three points across the roll width and averaged.

Face fabric knit direction runs consistently with the body's vertical axis to preserve stretch recovery across the chest and shoulders; interior mesh is cut on a cross-grain to maximise airflow through the underarm and lower back panels.

# 3. Yarn and Fibre Specification

Recycled fibre content is independently verified under the Global Recycled Standard (GRS) chain-of-custody model. Batch-level transaction certificates are retained by Ridgeline Apparel Supply and made available to Pashun Sports on request for sustainability reporting purposes.

Elastane content is sourced from a single approved subcontractor (Coastal Elastomers LLC, South Carolina) to maintain consistent recovery characteristics across production runs. Any change of elastane supplier requires re-validation against Section 5 test standards before use on a live purchase order.

# 4. Fabric Finishes and Treatments

All finishes are applied prior to cut-and-sew and are validated for durability against the wash-cycle schedule in Section 6. Finish chemistry is reviewed annually against the OEKO-TEX Standard 100 restricted substances list (see Section 10).

# 5. Performance Test Standards

Testing is performed by an accredited third-party laboratory (SGS Testing, Atlanta, GA) on a per-lot sampling basis. Full test reports are retained for seven years from production date and referenced in the Test Certificate Log (Section 10).

# 6. Wash-Cycle Durability Testing

Accelerated home-laundering simulation, conducted per AATCC 135 conditions (machine wash, 30°C, tumble dry low), tracked across a representative sample to validate garment performance across its expected lifetime.

Results shown are the mean of five sample garments (Navy colourway, size M) drawn from production lot NAV-4412. Interior mesh air permeability is retested at wash 30 and wash 50 as part of the extended durability programme; both results remain within the Section 5 requirement of ≥150 ft³/min/ft².

# 7. Garment Size Grading and Tolerances

Finished garment measurements, taken flat, unstretched, per size. All measurements in centimetres unless stated otherwise.

7.1 Measurement Tolerances (Summary)

7.2 Full Tolerance Matrix by Size

Full tolerance range per measurement point and size, for use by cutting room and inspection staff. Values in parentheses show the acceptable minimum–maximum range.

# 8. Colourways, Tolerances and Dye Lot Records

Each production dye lot is measured against the approved lab dip standard using a spectrophotometer under D65 illuminant, and recorded prior to release for cut-and-sew. A representative extract of recent dye lot records is shown below for each colourway; full records are retained by the Ridgeline Apparel Supply dye house for the life of the range.

8.1 Navy — Dye Lot Record (extract)

8.2 Charcoal — Dye Lot Record (extract)

# 9. Care and Aftercare Instructions

- Machine wash cold (30°C), inside out
- Do not use fabric softener — degrades wicking finish over time
- Tumble dry low or line dry
- Do not iron directly on printed logo areas
- Do not dry clean
- Do not bleach
- Wash with similar colours for the first three washes to minimise dye transfer risk
- Avoid prolonged exposure to direct sunlight when line drying to protect colourfastness

Care instructions are printed on the neck label using internationally recognised care symbols (per ASTM D5489) alongside the plain-language instructions above, to satisfy both US and general international labelling conventions.

# 10. Test Certificate Log

Extract of test certificates issued against recent production, covering the certification period since the last major revision of this specification. Full log available on request from Ridgeline Apparel Supply Quality & Compliance.

10.1 Certificates — Navy Production Lots

10.2 Certificates — Charcoal Production Lots

# 11. Certifications and Compliance

Fabric composition and labelling comply with US Federal Trade Commission textile labelling requirements (16 CFR Part 303) and the Textile Fiber Products Identification Act. Flammability performance complies with 16 CFR Part 1610 (Standard for the Flammability of Clothing Textiles).

Certification renewals are tracked centrally by the Ridgeline Apparel Supply Quality & Compliance team; Pashun Sports is notified in advance of any certificate due to lapse within the term of an open purchase order.

# 12. Restricted Substances List (RSL)

All components of the Pashun Pro Tee — fabric, dyes, finishes, trims and packaging — are tested against the Ridgeline Apparel Supply Restricted Substances List, aligned to AFIRM Group and OEKO-TEX Standard 100 requirements. Testing frequency is annual per component, or on introduction of a new supplier, finish or trim.

Where a restricted substance test result falls above 80% of the stated limit, the affected supplier is placed on an enhanced monitoring schedule (quarterly retest) until three consecutive passing results are recorded.

# 13. Trims and Components Specification

All trims and components are subject to the same Restricted Substances List testing described in Section 12. Trim suppliers are approved annually and audited against Ridgeline Apparel Supply's supplier code of conduct.

# 14. Print and Graphic Placement Specification

Placement, method and maximum dimensions for garment decoration options approved for the Pashun Pro Tee US range. Placements not listed here require sign-off from both Ridgeline Apparel Supply Production and Pashun Sports Design before sampling.

All print and transfer inks are tested against the Restricted Substances List (Section 12) prior to approval for production use. Woven badges are pre-shrunk before application to avoid puckering after laundering.

# 15. Sustainability Statement

Ridgeline Apparel Supply's approach to the Pashun Pro Tee fabric centres on three commitments: recycled fibre content in the face fabric (Section 3), domestic and largely in-house production to reduce transport-related emissions (Section 1), and packaging materials selected to minimise virgin plastic use (Section 16).

- Face fabric contains a minimum of 92% GRS-certified recycled polyester by weight

- Facility wastewater is treated on-site prior to discharge, in line with Georgia Environmental Protection Division requirements
- Cutting room fabric waste is baled and sent to an approved textile recycler rather than landfill
- Facility energy use is benchmarked annually via the Higg Facility Environmental Module (see Section 11)

Pashun Sports may request an annual sustainability summary covering recycled content volumes, water use and waste diversion rates for the Pro Tee US range specifically.

# 16. Packaging and Logistics Specification

Packaging materials are selected to minimise plastic use where feasible; the outer polybag is recyclable LDPE and cartons are made from a minimum 70% recycled corrugate content.

# 17. Commercial Terms

Lead times quoted assume no change to approved colourways or fabric composition after purchase order confirmation. Requests for new colourways, print placements, or fabric substitutions restart the sampling and approval process described in Section 15 and may extend the standard lead time.

# 18. Quality Assurance and Inspection Process

Inspection is carried out at three stages of production:

- In-line inspection during cutting and sewing, checking seam construction and measurement conformance against Section 6
- Pre-final inspection at 80% of production completion, AQL 2.5 sampling per lot
- Final random inspection (FRI) prior to shipment, covering visual defects, measurement, labelling and packaging conformance

Inspection results are logged against the relevant production lot number and cross-referenced to the test certificates in Section 10. Any lot failing FRI is quarantined and subject to the non-conformance procedure in Section 19 before release is considered.

# 19. Non-Conformance and Rejection Procedure

Where a lot fails inspection or test against the standards in this specification, Ridgeline Apparel Supply will:

- Notify Pashun Sports Quality contact within 2 business days of the failed result, referencing the affected lot number(s)
- Provide root-cause analysis within 5 business days
- Offer a corrective action plan (rework, re-test, or replacement production) at no additional cost to Pashun Sports where the failure is attributable to Ridgeline Apparel Supply's production or materials
- Retain rejected samples for a minimum of 90 days for joint review if requested

Disputed results may be referred to an independent third-party laboratory, with costs borne by the party whose original result is not upheld.

# 20. Appendix A — Spectrophotometer Readings

Raw CIE L*a*b* colour readings taken under D65 illuminant, 10° observer, for a representative extract of recent dye lots per colourway. Retained to support Delta-E calculations referenced in Section 8.

A.1 Navy

A.2 Charcoal

# 21. Glossary of Terms

# 22. Contacts and Document Control

Questions regarding this specification, including test methodology, certification scope, or the commercial terms in Section 17, should be directed to the Ridgeline Apparel Supply Quality & Compliance team via the standard supplier communication channel, referencing the document number on the cover page.

This document is controlled. Printed or locally saved copies are uncontrolled and should be checked against the version held on the Pashun Sports T-Shirts team site before use.

Distribution of this document, or of the certificates and data referenced within it, outside Pashun Sports Ltd requires prior written consent from Ridgeline Apparel Supply, other than for the purpose of statutory or regulatory disclosure.

Any discrepancy noticed between this specification and a physically received shipment should be reported within 5 business days of receipt, quoting the purchase order number, production lot number and, where applicable, the relevant section of this document.

# 23. Revision History

Ridgeline Apparel Supply — Quality & Compliance Team

This document has been shared with Pashun Sports Ltd for production reference and contains no information confidential beyond standard supplier terms.

| Process | Location | Facility |
|---|---|---|
| Yarn spinning | Georgia, USA | Ridgeline Apparel Supply — in-house |
| Knitting | Georgia, USA | Ridgeline Apparel Supply — in-house |
| Dyeing and finishing | Georgia, USA | Ridgeline Apparel Supply — in-house dye house |
| Cut and sew | Georgia, USA | Ridgeline Apparel Supply — in-house |
| Screen and DTG printing | Georgia, USA | Palmetto Print Co. (approved subcontractor) |
| Embroidery | South Carolina, USA | Palmetto Print Co. (approved subcontractor) |
| Label and trim supply | Georgia, USA | Summit Trim & Labels Co. |
| Final packing and palletisation | Georgia, USA | Ridgeline Apparel Supply — in-house |
| Outbound freight | Savannah, GA (port) | Harbor Freight Logistics |

| Layer | Composition | Weight (GSM) |
|---|---|---|
| Face fabric | 92% recycled polyester, 8% elastane | 165 GSM |
| Interior wicking mesh | 100% polyester micro-mesh | 85 GSM |

| | | |
|---|---|---|
| Combined fabric weight | — | 180 GSM ±5% |

| Property | Face Fabric Yarn | Interior Mesh Yarn |
|---|---|---|
| Fibre type | Recycled polyester (rPET), 8% elastane | 100% polyester filament |
| Yarn count | 150 denier | 70 denier |
| Knit structure | Interlock, 4-way stretch | Micro-mesh, open construction |
| Yarn twist | Z-twist, 700 TPM | S-twist, 550 TPM |
| Recycled content certification | GRS-certified rPET (cert. no. GRS-2024-RAS-118) | N/A — virgin polyester |
| Origin of raw fibre | Post-consumer PET bottles, sourced Southeast USA | Domestic virgin polyester, Georgia mill |

| Finish / Treatment | Purpose | Applied At | Durability Claim |
|---|---|---|---|
| Moisture-wick finish | Draws sweat to fabric surface for evaporation | Face fabric, post-dye | 50 home launderings |
| Anti-odour treatment (silver-ion) | Inhibits bacterial growth causing odour | Face fabric, post-dye | 30 home launderings |
| UV-protective finish | Contributes to UPF 30+ rating | Face fabric, post-dye | Life of garment (per AATCC 183 retest at 25 |
| Anti-pill mechanical finish | Reduces surface pilling in wear | Interior mesh | Ongoing, verified at wash 30 |

| Property | Test Method | Requirement | Typical Result |
|---|---|---|---|
| Moisture wicking rate | AATCC 195 | ≥ 200% | 224% |
| Colourfastness to washing | AATCC 61 | Grade 4 min | Grade 4-5 |
| Colourfastness to crocking (dry) | AATCC 8 | Grade 4 min | Grade 4-5 |
| Colourfastness to perspiration | AATCC 15 | Grade 4 min | Grade 4 |
| Pilling resistance | ASTM D3512, 7200 cycles | Grade 3 min | Grade 4 |
| UPF rating | AATCC 183 | UPF 30+ | UPF 35 |
| Shrinkage (wash x5) | AATCC 135 | ≤ 3% | 2.1% |
| Tensile strength (warp/weft) | ASTM D5034 | ≥ 25 lbf | 31 lbf |
| Bursting strength | ASTM D3786 | ≥ 40 lbf/in² | 52 lbf/in² |
| Air permeability (interior mesh) | ASTM D737 | ≥ 150 ft³/min/ft² | 178 ft³/min/ft² |
| Seam slippage | ASTM D434 | ≤ 6mm at 15 lbf | 3.8mm |
| Flammability | 16 CFR Part 1610 | Class 1 | Class 1 (pass) |

| Wash Cycle | Shrinkage – Warp (%) | Shrinkage – Weft (%) | Colour Change (Grade) | Pilling (Grade) | Wicking Rate (%) |
|---|---|---|---|---|---|
| Wash 1 | 0.4 | 0.3 | 5 | 5 | 231 |
| Wash 5 | 1.1 | 0.9 | 4-5 | 4-5 | 227 |
| Wash 10 | 1.8 | 1.5 | 4-5 | 4 | 224 |
| Wash 20 | 2.4 | 2.0 | 4 | 4 | 219 |
| Wash 30 | 2.9 | 2.4 | 4 | 3-4 | 212 |
| Wash 50 | 3.4 | 2.8 | 3-4 | 3 | 203 |

| Size | Chest (cm) | Body Length (cm) | Sleeve Length (cm) | Hem Width (cm) | Armhole (cm) | Neck Width (cm) |
|---|---|---|---|---|---|---|
| XS | 88.0 | 66.0 | 19.5 | 46.0 | 20.5 | 17.0 |
| S | 94.0 | 68.0 | 20.5 | 49.0 | 21.5 | 17.5 |
| M | 100.0 | 70.0 | 21.5 | 52.0 | 22.5 | 18.0 |
| L | 106.0 | 72.0 | 22.5 | 55.0 | 23.5 | 18.5 |
| XL | 112.0 | 74.0 | 23.5 | 58.0 | 24.5 | 19.0 |
| XXL | 118.0 | 76.0 | 24.5 | 61.0 | 25.5 | 19.5 |

| Measurement Point | Tolerance (±cm) | Method Reference |
|---|---|---|
| Chest, 2.5cm below armhole | 1.0 | RAS-QA-M01 |
| Body length, HPS to hem | 1.5 | RAS-QA-M02 |
| Sleeve length, shoulder seam to cuff | 0.8 | RAS-QA-M03 |
| Hem width, flat | 1.0 | RAS-QA-M04 |
| Armhole, straight measure | 0.6 | RAS-QA-M05 |
| Neck width, flat | 0.5 | RAS-QA-M06 |
| Neck rib height | 0.3 | RAS-QA-M07 |
| Shoulder seam to shoulder seam | 0.8 | RAS-QA-M08 |

| Size | Chest (±1cm) | Body Length (±1.5cm) | Sleeve Length (±0.8cm) | Hem Width (±1cm) | Armhole (±0.6cm) | Neck Width (±0.5cm) |
|---|---|---|---|---|---|---|
| XS | 88.0 (87.0–89.0) | 66.0 (64.5–67.5) | 19.5 (18.7–20.3) | 46.0 (45.0–47.0) | 20.5 (19.9–21.1) | 17.0 (16.5–17.5) |
| S | 94.0 (93.0–95.0) | 68.0 (66.5–69.5) | 20.5 (19.7–21.3) | 49.0 (48.0–50.0) | 21.5 (20.9–22.1) | 17.5 (17.0–18.0) |
| M | 100.0 (99.0–101.0) | 70.0 (68.5–71.5) | 21.5 (20.7–22.3) | 52.0 (51.0–53.0) | 22.5 (21.9–23.1) | 18.0 (17.5–18.5) |
| L | 106.0 (105.0–107.0) | 72.0 (70.5–73.5) | 22.5 (21.7–23.3) | 55.0 (54.0–56.0) | 23.5 (22.9–24.1) | 18.5 (18.0–19.0) |
| XL | 112.0 (111.0–113.0) | 74.0 (72.5–75.5) | 23.5 (22.7–24.3) | 58.0 (57.0–59.0) | 24.5 (23.9–25.1) | 19.0 (18.5–19.5) |
| XXL | 118.0 (117.0–119.0) | 76.0 (74.5–77.5) | 24.5 (23.7–25.3) | 61.0 (60.0–62.0) | 25.5 (24.9–26.1) | 19.5 (19.0–20.0) |

| Colourway | Pantone Ref | Delta-E Tolerance |
|---|---|---|
| Navy | 19-4023 TPX | ≤ 1.0 |
| Charcoal | 19-4007 TPX | ≤ 1.0 |

| Dye Lot | Production Date | Delta-E (measured) | Result | Inspector |
|---|---|---|---|---|
| NAV-4401 | 2025-10-07 | 0.45 | Pass | T. Okonkwo |
| NAV-4402 | 2025-10-13 | 0.88 | Pass | R. Millward |
| NAV-4403 | 2025-10-19 | 0.30 | Pass | S. Achebe |
| NAV-4404 | 2025-10-25 | 0.76 | Pass | J. Fennimore |
| NAV-4405 | 2025-10-31 | 0.96 | Pass | T. Okonkwo |
| NAV-4406 | 2025-11-06 | 0.52 | Pass | R. Millward |

| | | | | |
|---|---|---|---|---|
| NAV-4407 | 2025-11-12 | 0.82 | Pass | S. Achebe |
| NAV-4408 | 2025-11-18 | 0.47 | Pass | J. Fennimore |
| NAV-4409 | 2025-11-24 | 0.76 | Pass | T. Okonkwo |
| NAV-4410 | 2025-11-30 | 0.65 | Pass | R. Millward |
| NAV-4411 | 2025-12-06 | 0.86 | Pass | S. Achebe |
| NAV-4412 | 2025-12-12 | 0.89 | Pass | J. Fennimore |
| NAV-4413 | 2025-12-18 | 0.85 | Pass | T. Okonkwo |
| NAV-4414 | 2025-12-24 | 0.85 | Pass | R. Millward |
| NAV-4415 | 2025-12-30 | 0.36 | Pass | S. Achebe |
| NAV-4416 | 2026-01-05 | 0.97 | Pass | J. Fennimore |
| NAV-4417 | 2026-01-11 | 0.87 | Pass | T. Okonkwo |
| NAV-4418 | 2026-01-17 | 0.75 | Pass | R. Millward |
| NAV-4419 | 2026-01-23 | 0.45 | Pass | S. Achebe |
| NAV-4420 | 2026-01-29 | 0.34 | Pass | J. Fennimore |
| NAV-4421 | 2026-02-04 | 0.54 | Pass | T. Okonkwo |
| NAV-4422 | 2026-02-10 | 0.83 | Pass | R. Millward |
| NAV-4423 | 2026-02-16 | 0.47 | Pass | S. Achebe |
| NAV-4424 | 2026-02-22 | 0.57 | Pass | J. Fennimore |
| NAV-4425 | 2026-02-28 | 0.91 | Pass | T. Okonkwo |
| NAV-4426 | 2026-03-06 | 0.54 | Pass | R. Millward |
| NAV-4427 | 2026-03-12 | 0.41 | Pass | S. Achebe |
| NAV-4428 | 2026-03-18 | 0.94 | Pass | J. Fennimore |
| NAV-4429 | 2026-03-24 | 0.55 | Pass | T. Okonkwo |
| NAV-4430 | 2026-03-30 | 0.79 | Pass | R. Millward |
| NAV-4431 | 2026-04-05 | 0.99 | Pass | S. Achebe |
| NAV-4432 | 2026-04-11 | 0.80 | Pass | J. Fennimore |

| Dye Lot | Production Date | Delta-E (measured) | Result | Inspector |
|---|---|---|---|---|
| CHA-5201 | 2025-10-07 | 0.76 | Pass | T. Okonkwo |
| CHA-5202 | 2025-10-13 | 0.98 | Pass | R. Millward |
| CHA-5203 | 2025-10-19 | 0.72 | Pass | S. Achebe |
| CHA-5204 | 2025-10-25 | 0.68 | Pass | J. Fennimore |
| CHA-5205 | 2025-10-31 | 0.98 | Pass | T. Okonkwo |
| CHA-5206 | 2025-11-06 | 0.82 | Pass | R. Millward |
| CHA-5207 | 2025-11-12 | 0.40 | Pass | S. Achebe |
| CHA-5208 | 2025-11-18 | 0.45 | Pass | J. Fennimore |
| CHA-5209 | 2025-11-24 | 0.62 | Pass | T. Okonkwo |

| | | | | |
|---|---|---|---|---|
| CHA-5210 | 2025-11-30 | 0.77 | Pass | R. Millward |
| CHA-5211 | 2025-12-06 | 0.30 | Pass | S. Achebe |
| CHA-5212 | 2025-12-12 | 0.55 | Pass | J. Fennimore |
| CHA-5213 | 2025-12-18 | 0.61 | Pass | T. Okonkwo |
| CHA-5214 | 2025-12-24 | 0.43 | Pass | R. Millward |
| CHA-5215 | 2025-12-30 | 0.62 | Pass | S. Achebe |
| CHA-5216 | 2026-01-05 | 0.47 | Pass | J. Fennimore |
| CHA-5217 | 2026-01-11 | 0.78 | Pass | T. Okonkwo |
| CHA-5218 | 2026-01-17 | 0.77 | Pass | R. Millward |
| CHA-5219 | 2026-01-23 | 0.56 | Pass | S. Achebe |
| CHA-5220 | 2026-01-29 | 0.42 | Pass | J. Fennimore |
| CHA-5221 | 2026-02-04 | 0.93 | Pass | T. Okonkwo |
| CHA-5222 | 2026-02-10 | 0.47 | Pass | R. Millward |
| CHA-5223 | 2026-02-16 | 0.99 | Pass | S. Achebe |
| CHA-5224 | 2026-02-22 | 0.62 | Pass | J. Fennimore |
| CHA-5225 | 2026-02-28 | 0.73 | Pass | T. Okonkwo |
| CHA-5226 | 2026-03-06 | 0.68 | Pass | R. Millward |
| CHA-5227 | 2026-03-12 | 0.38 | Pass | S. Achebe |
| CHA-5228 | 2026-03-18 | 0.50 | Pass | J. Fennimore |
| CHA-5229 | 2026-03-24 | 0.75 | Pass | T. Okonkwo |
| CHA-5230 | 2026-03-30 | 0.96 | Pass | R. Millward |
| CHA-5231 | 2026-04-05 | 0.67 | Pass | S. Achebe |
| CHA-5232 | 2026-04-11 | 0.35 | Pass | J. Fennimore |

| Certificate No. | Test Standard | Production Lot Range | Date Issued | Result |
|---|---|---|---|---|
| RAS-TC-2025-1040 | AATCC 195 | 4400–4411 | 2025-10-24 | Pass |
| RAS-TC-2025-1041 | AATCC 61 | 4412–4423 | 2025-11-02 | Pass |
| RAS-TC-2025-1042 | ASTM D3512 | 4424–4435 | 2025-11-11 | Pass |
| RAS-TC-2025-1043 | AATCC 183 | 4436–4447 | 2025-11-20 | Pass |
| RAS-TC-2025-1044 | AATCC 135 | 4448–4459 | 2025-11-29 | Pass |
| RAS-TC-2025-1045 | ASTM D5034 | 4460–4471 | 2025-12-08 | Pass |
| RAS-TC-2025-1046 | AATCC 195 | 4472–4483 | 2025-12-17 | Pass |
| RAS-TC-2025-1047 | AATCC 61 | 4484–4495 | 2025-12-26 | Pass |
| RAS-TC-2025-1048 | ASTM D3512 | 4496–4507 | 2026-01-04 | Pass |
| RAS-TC-2025-1049 | AATCC 183 | 4508–4519 | 2026-01-13 | Pass |
| RAS-TC-2025-1050 | AATCC 135 | 4520–4531 | 2026-01-22 | Pass |
| RAS-TC-2025-1051 | ASTM D5034 | 4532–4543 | 2026-01-31 | Pass |

| | | | | |
|---|---|---|---|---|
| RAS-TC-2025-1052 | AATCC 195 | 4544–4555 | 2026-02-09 | Pass |
| RAS-TC-2025-1053 | AATCC 61 | 4556–4567 | 2026-02-18 | Pass |
| RAS-TC-2025-1054 | ASTM D3512 | 4568–4579 | 2026-02-27 | Pass |
| RAS-TC-2025-1055 | AATCC 183 | 4580–4591 | 2026-03-08 | Pass |
| RAS-TC-2025-1056 | AATCC 135 | 4592–4603 | 2026-03-17 | Pass |
| RAS-TC-2025-1057 | ASTM D5034 | 4604–4615 | 2026-03-26 | Pass |
| RAS-TC-2025-1058 | AATCC 195 | 4616–4627 | 2026-04-04 | Pass |
| RAS-TC-2025-1059 | AATCC 61 | 4628–4639 | 2026-04-13 | Pass |

| Certificate No. | Test Standard | Production Lot Range | Date Issued | Result |
|---|---|---|---|---|
| RAS-TC-2025-1040 | AATCC 195 | 4400–4411 | 2025-10-24 | Pass |
| RAS-TC-2025-1041 | AATCC 61 | 4412–4423 | 2025-11-02 | Pass |
| RAS-TC-2025-1042 | ASTM D3512 | 4424–4435 | 2025-11-11 | Pass |
| RAS-TC-2025-1043 | AATCC 183 | 4436–4447 | 2025-11-20 | Pass |
| RAS-TC-2025-1044 | AATCC 135 | 4448–4459 | 2025-11-29 | Pass |
| RAS-TC-2025-1045 | ASTM D5034 | 4460–4471 | 2025-12-08 | Pass |
| RAS-TC-2025-1046 | AATCC 195 | 4472–4483 | 2025-12-17 | Pass |
| RAS-TC-2025-1047 | AATCC 61 | 4484–4495 | 2025-12-26 | Pass |
| RAS-TC-2025-1048 | ASTM D3512 | 4496–4507 | 2026-01-04 | Pass |
| RAS-TC-2025-1049 | AATCC 183 | 4508–4519 | 2026-01-13 | Pass |
| RAS-TC-2025-1050 | AATCC 135 | 4520–4531 | 2026-01-22 | Pass |
| RAS-TC-2025-1051 | ASTM D5034 | 4532–4543 | 2026-01-31 | Pass |
| RAS-TC-2025-1052 | AATCC 195 | 4544–4555 | 2026-02-09 | Pass |
| RAS-TC-2025-1053 | AATCC 61 | 4556–4567 | 2026-02-18 | Pass |
| RAS-TC-2025-1054 | ASTM D3512 | 4568–4579 | 2026-02-27 | Pass |
| RAS-TC-2025-1055 | AATCC 183 | 4580–4591 | 2026-03-08 | Pass |
| RAS-TC-2025-1056 | AATCC 135 | 4592–4603 | 2026-03-17 | Pass |
| RAS-TC-2025-1057 | ASTM D5034 | 4604–4615 | 2026-03-26 | Pass |
| RAS-TC-2025-1058 | AATCC 195 | 4616–4627 | 2026-04-04 | Pass |
| RAS-TC-2025-1059 | AATCC 61 | 4628–4639 | 2026-04-13 | Pass |

| Certification / Standard | Scope | Certificate No. | Valid To |
|---|---|---|---|
| OEKO-TEX Standard 100 | Face fabric and interior mesh, Class II | OTX-2025-RAS-4471 | 30 Nov 2026 |
| Global Recycled Standard (GRS) | Recycled polyester content, face fabric | GRS-2024-RAS-118 | 14 Mar 2027 |
| ISO 9001:2015 | Ridgeline Apparel Supply facility, Georgia | ISO9001-GA-0092 | 19 Aug 2027 |
| Higg Facility Environmental Module (FEM) | Ridgeline Apparel Supply facility, Georgia | HIGG-FEM-2025-0341 | Self-assessed, verified 2025 |

| Restricted Substance | Limit | Test Method | Applicable Component |
|---|---|---|---|
| Lead (Pb) | ≤ 90 ppm | CPSIA / ASTM F963 | All accessible components |
| Cadmium (Cd) | ≤ 40 ppm | EN 1122 | Trims, prints |
| Formaldehyde (free) | ≤ 75 ppm | ISO 14184-1 | Face fabric, interior mesh |
| Azo dyes (banned amines) | Not detectable (≤ 20 ppm) | ISO 17234-1 | Dyed fabric, all colourways |
| Nickel release | ≤ 0.5 µg/cm²/week | EN 1811 | Metal trims, zip pulls |
| Phthalates (DEHP, DBP, BBP, DINP, DIDP, DNOP) | ≤ 0.1% each | CPSC-CH-C1001 | Printed graphics, plastisol |
| PFAS (per- and polyfluoroalkyl substances) | Not intentionally added | CEN/TS 15968 | All finishes |
| Organotin compounds (TBT, DBT) | ≤ 1 ppm (Sn) | ISO 17353 | Elastane, finishes |
| Alkylphenol ethoxylates (APEO) | ≤ 100 ppm | LC-MS screening | Dye house effluent / finishing |
| Chlorinated phenols (PCP, TeCP) | ≤ 0.5 ppm | EN ISO 17070 | Fabric, packaging |
| Short-chain chlorinated paraffins (SCCP) | ≤ 1500 ppm | EN ISO 18219 | Coatings, finishes |
| Extractable heavy metals (As, Sb, Cr, Co, Cu, Hg) | Per OEKO-TEX Class II limits | ISO 105-E04 / EN ISO 17072-1 | All dyed components |
| pH value (aqueous extract) | 4.0–7.5 | ISO 3071 | Face fabric, interior mesh |
| Volatile organic compounds (VOC) | ≤ 0.5 mg/m³ chamber test | ISO 16000-9 | Finished garment |
| Perfluorooctanoic acid (PFOA) | ≤ 1 ppm | CEN/TS 15968 | DWR finishes (not applied to |

| Component | Specification | Supplier |
|---|---|---|
| Neck label | Woven, 100% polyester, heat-cut edge | Summit Trim & Labels Co. |
| Care/content label | Printed satin, water-based ink | Summit Trim & Labels Co. |
| Main hem tape | Self-fabric, 1.2cm finished width | Ridgeline Apparel Supply (in-house) |
| Shoulder tape (reinforcement) | Polyester twill tape, 1.0cm | Summit Trim & Labels Co. |
| Hangtag | Recycled card stock, 350gsm, string attachment | Summit Trim & Labels Co. |
| Sewing thread | Core-spun polyester, Tex 27 (body), Tex 18 (topstitch) | Coats Group, Georgia |

| Placement | Position | Method | Max Size |
|---|---|---|---|
| Left chest logo | 8cm below HPS, centred on left chest panel | Direct-to-garment print | 8cm x 6cm |
| Centre back neck tape print | Inside neck tape | Heat transfer | 18cm x 2cm |
| Left sleeve badge | 4cm above hem, centred | Woven badge, sewn | 5cm x 5cm |
| Lower back hem print (seasonal only) | 3cm above hem, centred | Screen print | 20cm x 4cm |

| Item | Specification |
|---|---|
| Fold method | Standard flat-fold, tissue-wrapped |
| Polybag | Recyclable LDPE, printed warning label per 16 CFR 1500 |
| Carton size | 60cm x 40cm x 35cm, double-wall corrugate |
| Units per carton | 50 units (single colourway, mixed size run per size curve) |
| Carton weight (approx.) | 11.5kg |

| | |
|---|---|
| Labelling | Barcode (UPC-A), style/colour/size ticket, country of origin label (Made in USA) |
| Pallet configuration | 40 cartons per pallet, 8 layers x 5 cartons |

| Term | Detail |
|---|---|
| Minimum order quantity | 250 units per colourway, per style |
| Standard lead time | 12 weeks from confirmed purchase order |
| Fabric usage | 0.35m² per unit (adult sizes S–XXL) |
| Quality tolerance | AQL 2.5, general inspection level II |
| Payment terms | 30% deposit on order confirmation, balance on shipment |
| Incoterm | FOB Savannah, GA |
| Currency | USD |
| Price validity | 90 days from quotation date, subject to raw material index review thereafter |

| Dye Lot | L* | a* | b* | Delta-E vs Standard |
|---|---|---|---|---|
| NAV-SP-4001 | 18.61 | 2.21 | -14.06 | 0.57 |
| NAV-SP-4002 | 18.68 | 2.17 | -14.19 | 0.76 |
| NAV-SP-4003 | 18.37 | 2.25 | -14.06 | 0.33 |
| NAV-SP-4004 | 18.48 | 2.08 | -14.33 | 0.43 |
| NAV-SP-4005 | 18.23 | 1.99 | -14.22 | 0.51 |
| NAV-SP-4006 | 18.47 | 2.16 | -14.18 | 0.70 |
| NAV-SP-4007 | 18.15 | 2.03 | -14.02 | 0.99 |
| NAV-SP-4008 | 18.40 | 2.07 | -14.25 | 0.50 |
| NAV-SP-4009 | 18.15 | 2.04 | -14.05 | 0.77 |
| NAV-SP-4010 | 18.58 | 2.10 | -14.18 | 0.49 |
| NAV-SP-4011 | 18.22 | 2.21 | -14.08 | 0.96 |
| NAV-SP-4012 | 18.13 | 2.06 | -14.16 | 0.25 |
| NAV-SP-4013 | 18.48 | 2.01 | -14.08 | 0.67 |
| NAV-SP-4014 | 18.31 | 2.00 | -14.12 | 0.36 |
| NAV-SP-4015 | 18.20 | 2.19 | -14.20 | 0.50 |
| NAV-SP-4016 | 18.62 | 2.16 | -14.11 | 0.23 |
| NAV-SP-4017 | 18.23 | 2.02 | -14.02 | 0.78 |
| NAV-SP-4018 | 18.17 | 2.11 | -14.18 | 0.80 |

| Dye Lot | L* | a* | b* | Delta-E vs Standard |
|---|---|---|---|---|
| CHA-SP-4001 | 32.84 | 0.36 | -0.91 | 0.55 |
| CHA-SP-4002 | 32.64 | 0.29 | -1.15 | 0.44 |
| CHA-SP-4003 | 32.44 | 0.30 | -1.22 | 0.88 |

| | | | | |
|---|---|---|---|---|
| CHA-SP-4004 | 32.34 | 0.38 | -1.13 | 0.76 |
| CHA-SP-4005 | 32.86 | 0.28 | -0.92 | 0.87 |
| CHA-SP-4006 | 32.78 | 0.49 | -1.13 | 0.24 |
| CHA-SP-4007 | 32.31 | 0.51 | -0.97 | 0.25 |
| CHA-SP-4008 | 32.38 | 0.53 | -1.20 | 0.94 |
| CHA-SP-4009 | 32.32 | 0.36 | -1.25 | 0.68 |
| CHA-SP-4010 | 32.39 | 0.33 | -1.04 | 0.74 |
| CHA-SP-4011 | 32.42 | 0.44 | -1.06 | 0.48 |
| CHA-SP-4012 | 32.89 | 0.27 | -1.03 | 0.86 |
| CHA-SP-4013 | 32.54 | 0.31 | -1.03 | 0.93 |
| CHA-SP-4014 | 32.47 | 0.39 | -1.17 | 0.27 |
| CHA-SP-4015 | 32.45 | 0.37 | -1.15 | 0.98 |
| CHA-SP-4016 | 32.79 | 0.48 | -1.29 | 0.22 |
| CHA-SP-4017 | 32.43 | 0.48 | -0.94 | 0.73 |
| CHA-SP-4018 | 32.35 | 0.34 | -0.91 | 0.76 |

| Term | Definition |
|---|---|
| GSM | Grams per square metre — standard fabric weight measurement |
| AQL | Acceptable Quality Limit — statistical sampling standard for inspection (ISO 2859-1) |
| Delta-E (ΔE) | Numeric measure of colour difference between a sample and the approved standard; lower is closer to standard |
| TPX | Textile Paper eXtract — Pantone's fabric-based colour reference format |
| UPF | Ultraviolet Protection Factor — rating of a fabric's ability to block UV radiation |
| rPET | Recycled polyethylene terephthalate — recycled polyester fibre |
| HPS | High Point Shoulder — reference point used in garment measurement |
| TPM | Turns Per Metre — measure of yarn twist |
| Grade (colourfastness/pilling) | AATCC grey-scale or pilling-scale rating, 1 (poor) to 5 (no change) |

| Role | Team | Notes |
|---|---|---|
| Quality & Compliance | Ridgeline Apparel Supply | Fabric testing, certification, RSL queries |
| Production Planning | Ridgeline Apparel Supply | Lead time, capacity, purchase order confirmation |
| Account Management | Ridgeline Apparel Supply | Commercial terms, pricing, contract queries |
| Production | Pashun Sports Ltd | Internal point of contact for purchase order queries |

| Version | Date | Change |
|---|---|---|
| RAS-FS-2025-098 | 22 Sep 2025 | Initial issue — UK range |
| RAS-FS-2026-014 | 10 Jan 2026 | Added Charcoal colourway; updated MOQ and lead time for US range; expanded test standards, size grading, dye |