

# **Introducing RESTORE and RECOVER Commands**


**By Ahmed Baraka**

# Objectives

---

In this lecture, you will learn how to perform the following:

- Describe the difference between non-critical and critical data loss
- Describe the actions performed by the **RESTORE** and **RECOVER** commands
- Describe the steps to prepare a database for a recovery procedure



# Data Loss Categories

---

- **Physical failure**
  - missing or corrupted data file
- **Logical failure**
  - application or user error



# About Database File Loss

---

- Possible causes of database file loss:
  - Human error
  - Application error
  - Media failure
  - Hardware failure
- Database file categories:
  - **Non-critical**
    - Losing it does not stop the database
    - Losing it may have significant impact on the application
  - **Critical**
    - The database cannot run without it



# RMAN Restore and Recover

## Database



## Backup Files

Backupsets or  
Datafilecopy

Archived Redo  
Log Files  
+  
Incremental  
Backups

# RMAN Restore and Recover

## Database



---

## Backup Files

Backupsets or  
Datafilecopy

Archived Redo  
Log Files  
+  
Incremental  
Backups

# RMAN Restore and Recover

## Database



## Backup Files

Backupsets or  
Datafilecopy

Archived Redo  
Log Files  
+  
Incremental  
Backups

# RMAN Restore and Recover

Database



Backup Files

RESTORE


Backupsets or  
Datafilecopy

Archived Redo  
Log Files  
+  
Incremental  
Backups




# RMAN Restore and Recover

Database




# RMAN Restore and Recover

Database



# RMAN Restore and Recover

Database



# About Restoring and Recovering

---

- **RESOTRE** command:
  - Creating datafiles from backups (backupsets or datafile copies)
- **RECOVER** command:
  - Applying changes from redo logs and incremental backups to a restored data file to bring the data file forward to a desired point in time
- **Complete database recovery:**
  - Recovering to the failure time
  - Restoring lost files from backups and applying **all** the changes
- **Incomplete recovery or point-in-time recovery (PITR):**
  - Recovering the data to some point before the failure time
  - Restoring lost files from backup and applying **some** changes

# More about RESTORE Command

---

- **Prerequisites**

- The database must be started, mounted, or open with the tablespaces or data files to be restored offline

- **Capabilities**

- Restore datafiles, archived logs, control file and SPFILE
- Can restore files to their default location or to a different location
- You can specify which backup files to use
- Exclude specific tablespaces from restore
- Check on block corruption in backup files
- List the backup files that will be used without restoring the data files

# About RECOVER Command

---

- **Prerequisites**

- Required archived logs (and incremental backup) must exist


- **Capabilities**

- Perform complete and incomplete recovery (PITR)
- Apply incremental backups to a data file **copy**
- Recover a corrupt blocks within a data file

# Preparing for Recovery

---

- Identify the database files to restore or recover
- Determine the DBID of the database
- Validate backups before restoring them
- Restore archived redo logs needed for recovery
- Provide the password required to decrypt encrypted backups



# Summary

---

In this lecture, you should have learnt how to perform the following:

- Describe the difference between non-critical and critical data loss
- Describe the actions performed by the **RESTORE** and **RECOVER** commands
- Describe the steps to prepare a database for a recovery procedure

