Lab: Wire Up `dotenv` in Playwright

1) Install

1. Open your Boilerplate Project
2. Open a terminal and run

```
npm i dotenv –save-dev
```

---

2) Create `.env`

1. Create a **.env** in the root of your project
2. Paste in the following code

```
BASE_URL=http://localhost:3000
API_TOKEN=replace_me
```

3. Open your **.gitignore**
4. Add this line to the end

```
.env
```

---

3) Load `.env` in Playwright config

1. Open your **playwright.config.js**
2. Add the following lines to the top

```
import dotenv from 'dotenv';

// Load .env before anything reads process.env

dotenv.config();
```

---

4) Update ESLint Config

1. Open your **eslint.config.mjs**
2. Replace the contents with this code:

```
// eslint.config.mjs
import js from '@eslint/js';
import globals from 'globals';
import playwright from 'eslint-plugin-playwright';
import { defineConfig } from 'eslint/config';

export default defineConfig([
  // 1) Default: browser code (your app)
  {
    files: ['**/*.{js,mjs,cjs}'],
    languageOptions: {
      globals: {
        ...globals.browser, // window, document, etc.
      },
      // parserOptions: { sourceType: 'module' }, // uncomment if needed
    },
    // Flat config uses objects, not strings:
    ...js.configs.recommended,
  },

  // 2) Node contexts: Playwright tests, config files, scripts
  {
    files: [
      'playwright.config.*',
      'tests/**/*.{js,mjs,cjs,ts}',
      'e2e/**/*.{js,mjs,cjs,ts}',
      '**/*.config.{js,mjs,cjs}',   // other tool configs
      'scripts/**/*.{js,mjs,cjs,ts}'
    ],
    languageOptions: {
      globals: {
        ...globals.node, // process, __dirname, module, require (CJS), etc.
      },
    },
    // Playwright recommended rules (gives you test/expect globals + rules)
    plugins: { playwright },
    rules: {
      ...playwright.configs.recommended.rules,
    },
  },
]);
```