Lab 3: Custom Run Scripts

Goal: add a few handy `npm run` scripts.

1) Minimal spec setup

Inside your boilerplate project:

Create a new spec file in the tests directory called **sample.spec.js**

Paste in the code below.

```
import { test, expect } from "@playwright/test";



test.describe("sample suite", () => {

  test("Test one ", async ({ page }) => {

    // Add steps

  });



  test("Test two @smoke", async ({ page }) => {

    // Add steps

  });

});
```

---

2) Open `package.json`

Open the **package.json** file.

---

3) Add these scripts

Paste the block below inside the `"scripts"` section (keep existing ones if you already have them):

```
{
  "scripts": {
    "test": "playwright test",
    "test:ui": "playwright test --ui",
    "test:headed": "playwright test --headed",
    "test:debug": "playwright test --debug",
    "test:chromium": "playwright test --project=chromium",
    "test:firefox": "playwright test --project=firefox",
    "test:webkit": "playwright test --project=webkit",
    "test:single": "playwright test --workers=1",
    "test:smoke": "playwright test -g \"@smoke\"",
    "report": "playwright show-report"
  }
}
```

What each does (quick):

- `test` – run the full suite (default).
- `test:ui` – open the **Playwright Test UI Runner**.
- `test:headed` – run with a visible browser (good for debugging/demos).
- `test:debug` – open the **Inspector**; step through tests.
- `test:chromium|firefox|webkit` – target a specific browser project.
- `test:single` – disable parallelism (one worker) to isolate issues.

- `test:smoke` – run only tests tagged `@smoke` (title-based tag).
- `report` – open the last HTML report.

---

4) Save and run a couple to verify

In the terminal (from your project root):

```
npm run test          # full run
npm run test:headed    # visible browser
npm run test:chromium  # chromium only
npm run test:single    # one worker
npm run test:ui        # UI Runner
```

If you've run tests at least once, you can open the last report:

```
npm run report
```

---

5) Pass extra flags when you need them

Anything after `--` is forwarded to Playwright:

```
npm run test:chromium -- -g "add a todo item"
npm run test -- tests/todo-page.spec.ts:42
```

Done When

- You can run: `npm run test`, `test:headed`, `test:debug`, `test:chromium`, `test:single`, `test:smoke`, and `report` without errors.
- At least one test is tagged `@smoke` and runs via `npm run test:smoke`.