

Parent process ID spoofing

Understanding PPID concept

Understanding PPID spoofing concept

Function used in PPID spoofing :

```
BOOL UpdateProcThreadAttribute(  
    ✓ LPPROC_THREAD_ATTRIBUTE_LIST lpAttributeList,    //Attribute list  
    DWORD dwFlags,  
    ✓ DWORD_PTR Attribute,    //attribute flag ( for parent spoofing PROC_THREAD_ATTRIBUTE_PARENT_PROCESS )  
    ✓ PVOID lpValue,          // pointer to the data ( parent process handle )  
    SIZE_T cbSize,  
    PVOID lpPreviousValue,  
    PSIZE_T lpReturnSize  
);
```

* This function lets you "inject" special settings (like custom handles, **parent process**, mitigation policies, etc.) into the new process's creation configuration.

Function used in PPID spoofing :

1. Prepare extended startupinfo structure which contains lpAttributeList

2. Get the size of AttribList

InitializeProcThreadAttributeList ()

3. Allocate memory

HeapAlloc ()

4. Initialize AttribList

InitializeProcThreadAttributeList ()

5. Add the parent process to attribList

UpdateProcThreadAttribute ()

```
BOOL UpdateProcThreadAttribute(  
    ✓ LPPROC_THREAD_ATTRIBUTE_LIST lpAttributeList, //Attribute list  
    DWORD dwFlags,  
    DWORD_PTR Attribute, //attribute flag ( for parent spoofing PROC_THREAD_ATTRIBUTE_PARENT_PROCESS )  
    PVOID lpValue, // pointer to the data ( parent process handle )  
    SIZE_T cbSize,  
    PVOID lpPreviousValue,  
    PSIZE_T lpReturnSize  
);
```

* This function lets you "inject" special settings (like custom handles, parent process, mitigation policies, etc.) into the new process's creation configuration.