

Lab 7 - Argo Image Updater

Author: Gourav Shah

Publisher: School of Devops

Version : v2024.06.04.01

Project: Connect CI Pipeline set up with Argo Workflow and Argo Events with the CD Pipeline created with ArgoCD and Argo Rollouts. Set up a workflow where

- Whenever there is change to the `main` branch of the application code, it triggers the CI Pipeline with Argo Events + Argo Workflow. The result of this is a new image being published to the container registry.
- Set up a watcher which is monitor the container registry, this is where argo image updater comes in. Whenever a new tag with a certain pattern is available in the registry, update the image tag in the `main` branch of the deployment repo with it. Auto commit to GitHub.
- Change to the image tag should be automatically picked up by Argo CD and it should trigger the deployment to staging. Since its been integrated with argo rollouts, it implments the release strategy (e.g. Blue/Green) configured with the rollout spec.
- Deployment to prod is just one pull request away. Whenever the change (e.g. new image tag) is merged from master to release branch, prod deployment should get triggered based on another application deployment flow set up with Argo CD. And that GitOps in action for you...

Set up automatic Image Updater with ArgoCD

Install **Argo CD Image Updater** as,

```
kubectl apply -n argocd -f https://raw.githubusercontent.com/argoproj-labs/argocd-image-updater/stable/manifests/install.yaml
```

Create a Secret with your GitHub credentials so that the image updater can discover and commit the image tags to git repository.

```
kubectl -n argocd create secret generic git-creds \
```

```
--from-literal=username=xxxxxx \  
--from-literal=password=ghp_yyyyyy
```

Note : replace `xxxxxx` with your GitHub Username and `ghp_yyyyyy` with GitHub Access Token with write access to repository. If you do not already have token, create it from GitHub

Marking Staging Application for Auto Image Updates

When you set up staging deployment, ArgoCD has created a application object for you. You would need to add a few annotations to it so that the Image Updater knows that this application is been marked for image auto update.

Observe the existing application created from ArgoCD UI as,

```
kubectl get application -n argocd  
  
kubectl describe application -n argocd vote-staging
```

specifically observe the annotations

```
Annotations:  <none>
```

To update this application with appropriate annotations create a patch file with the name and content given below,

File : `argo_applications_vote-staging_patch.yaml`

```
metadata:  
  annotations:  
    argocd-image-updater.argoproj.io/git-branch: main  
    argocd-image-updater.argoproj.io/image-list: myimage=xxxxxx/vote  
    argocd-image-updater.argoproj.io/myimage.allow-tags: regexp:^[0-9a-f]{7}$  
    argocd-image-updater.argoproj.io/myimage.ignore-tags: latest, dev  
    argocd-image-updater.argoproj.io/myimage.update-strategy: latest  
    argocd-image-updater.argoproj.io/myimage.kustomize.image-name:  
schoolofdevops/vote  
    argocd-image-updater.argoproj.io/myimage.force-update: "true"  
    argocd-image-updater.argoproj.io/write-back-method: git:secret:argocd/git-
```

```
creds
```

```
argocd-image-updater.argoproj.io/write-back-target: "kustomization:../base"
```

Source: [Mark Staging App for Automatic Image Updates from Argo](#)

Where,

- Replace `xxxxxx/vote` with your own repo in the `argocd-image-updater.argoproj.io/image-list` annotation.

Apply the above patch as,

```
kubectl patch application --type=merge -n argocd vote-staging --patch-file  
argo_applications_vote-staging_patch.yaml
```

Validate annotations are added,

```
kubectl describe application -n argocd vote-staging
```


[sample output]

```
...  
Labels:      <none>  
Annotations: argocd-image-updater.argoproj.io/git-branch: main  
              argocd-image-updater.argoproj.io/image-list: myimage=initcron/  
argovote  
              argocd-image-updater.argoproj.io/myimage.allow-tags:  
regex:^[0-9a-f]{7}$  
              argocd-image-updater.argoproj.io/myimage.force-update: true  
              argocd-image-updater.argoproj.io/myimage.ignore-tags: latest, dev  
              argocd-image-updater.argoproj.io/myimage.kustomize.image-name:  
schoolofdevops/vote  
              argocd-image-updater.argoproj.io/myimage.update-strategy: latest  
              argocd-image-updater.argoproj.io/write-back-method:  
git:secret:argocd/git-creds  
              argocd-image-updater.argoproj.io/write-back-target:  
kustomization:../base  
API Version: argoproj.io/v1alpha1
```


Kind: Application

...

If everything goes well, within a few minutes, you should see a commit to the main branch of the `vote-deploy` repository that you have.



And a few minutes after that, you should see the staging deployment on ArgoCD pick up the newly updated image tag and deploy it.



You could tally it from Rollout Dashboard that it has picked up the new image with commit hash as tag

Summary

Strategy


BlueGreen

Containers

Edit

vote

initcron/vote:52eea4d



Revisions

Revision 2

initcron/vote:52eea4d

vote-7f75548656

✓

stable

active

✓

Revision 1

schoolofdevops/vote:v3

Rollback

and also validate with

```
kubectl describe application -n argocd vote-staging
```

where you should see the following in the output status

```
Summary:
  Images:
    initcron/vote:52eea4d
Sync:
  Compared To:
    Destination:
      Namespace: staging
      Server:      https://kubernetes.default.svc
    Source:
```

From now, its just matter of creating a pull request and merging it to release branch to deploy to prod.

You could check the logs for the image updater which is running in `argocd` namespace by using a command similar to

```
kubect1 logs -f -l "app.kubernetes.io/name=argocd-image-updater" -n argocd
```

Thats all ! If you have gotten till here, congratulate yourself as you have just built a simplistic but completely working modern CI/CD Pipeline ! Hurray !!

[#courses/argo/labs/v1](#)