

AKS storage using Azure Blob



Houssem Dellai



Storage options for AKS

- + **Azure Disk**

LRS, ZRS, Shared, Standard, Premium, Ultra

- + **Azure File**

- + **Azure Blob**

NFS v3.0, BlobFuse

- + **NetApp Files**

<> Code

Issues7

Pull requests2

Discussions

Actions

Projects1

Security

Insights

master


5 branches

32 tags

Go to file

Add file

<> Code

	Merge pull request #807 from andyzhangx/fuse2-test	348a3a1 4 days ago	1,599 commits
.github	Merge pull request #737 from andyzhangx/encryption		4 months ago
charts	chore: upgrade to csi-node-driver-registrar v2.6.2		last month
deploy	doc: refine volumeHandle doc		5 days ago
docs	doc: refine volumeHandle doc		5 days ago
hack	test: fix verify-helm-chart-index test error		2 months ago
pkg	Merge branch 'master' of https://github.com/kubernetes-sigs/blob-csi-...		last week
test	test: add blobfuse2 external tests		5 days ago
vendor	Squashed commit of the following:		last week
.gitignore	change blobfuse-proxy from daemonset to initContainer		6 months ago
.travis.yml	fix: test failures		2 years ago
CONTRIBUTING.md	Resolved issue of broken link		3 months ago
LICENSE	Initial commit		4 years ago
Makefile	Merge branch 'master' of https://github.com/kubernetes-sigs/blob-csi-...		last week
OWNERS	Update OWNERS		3 years ago
README.md	Update README.md		last week

About

Azure Blob Storage CSI driver

k8s-sig-cloud-provider


- Readme
- Apache-2.0 license
- Code of conduct
- Security policy
- 91 stars
- 8 watching
- 69 forks

Releases32

v1.18.0 releaseLateston Nov 25, 2022

+ 31 releases

Contributors37




```
$ az aks create --name $AKS_NAME --resource-group $AKS_RG --enable-blob-driver
```

```
$ kubectl get pods -n kube-system | grep csi
```

# NAME	READY	STATUS	RESTARTS	AGE
# csi-azuredisk-node-8wlc8	3/3	Running	0	100m
# csi-azuredisk-node-9z2wt	3/3	Running	0	100m
# csi-azuredisk-node-q9pwk	3/3	Running	0	100m
# csi-azurefile-node-7tzps	3/3	Running	0	100m
# csi-azurefile-node-8lwrl	3/3	Running	0	100m
# csi-azurefile-node-zdnpn	3/3	Running	0	100m
# csi-blob-node-8spm4	3/3	Running	0	100m
# csi-blob-node-ctv9c	3/3	Running	0	100m
# csi-blob-node-jbx9r	3/3	Running	0	100m

```
$ kubectl get storageclass
```








# NAME	PROVISIONER	RECLAIMPOLICY	VOLUMEBINDINGMODE	ALLOWVOLUMEEXPANSION	AGE
# azureblob-fuse-premium	blob.csi.azure.com	Delete	Immediate	true	6m23s
# azureblob-nfs-premium	blob.csi.azure.com	Delete	Immediate	true	6m23s
# azurefile	file.csi.azure.com	Delete	Immediate	true	67m
# azurefile-csi	file.csi.azure.com	Delete	Immediate	true	67m
# azurefile-csi-premium	file.csi.azure.com	Delete	Immediate	true	67m
# azurefile-premium	file.csi.azure.com	Delete	Immediate	true	67m
# default (default)	disk.csi.azure.com	Delete	WaitForFirstConsumer	true	67m
# managed	disk.csi.azure.com	Delete	WaitForFirstConsumer	true	67m
# managed-csi	disk.csi.azure.com	Delete	WaitForFirstConsumer	true	67m
# managed-csi-premium	disk.csi.azure.com	Delete	WaitForFirstConsumer	true	67m
# managed-premium	disk.csi.azure.com	Delete	WaitForFirstConsumer	true	67m

Using Azure Blob storage

```
apiVersion: apps/v1
kind: StatefulSet
metadata:
  name: statefulset-blob-nfs
  labels:
    app: nginx
spec:
  serviceName: statefulset-blob-nfs
  replicas: 1
  selector:
    matchLabels:
      app: nginx
  template:
    metadata:
      labels:
        app: nginx
```


```
spec:
  containers:
    - name: statefulset-blob-nfs
      image: nginx
      volumeMounts:
        - name: persistent-storage
          mountPath: /mnt/azureblob
  volumeClaimTemplates:
    - metadata:
        name: persistent-storage
        annotations:
          volume.beta.kubernetes.io/storage-class:
            azureblob-nfs-premium
      spec:
        accessModes: ["ReadWriteMany"]
        resources:
          requests:
            storage: 100Gi
```






Created resources


<input type="checkbox"/> Name ↑↓	Type ↑↓
<input type="checkbox"/>  aks-agentpool-15709612-nsg	Network security group
<input type="checkbox"/>  aks-cluster-agentpool	Managed Identity
<input type="checkbox"/>  aks-nodepool1-32086527-vmss	Virtual machine scale set
<input type="checkbox"/>  aks-vnet-15709612	Virtual network
<input type="checkbox"/>  b7eb1a21-c24a-4286-a901-7cfde4cd37c3	Public IP address
<input type="checkbox"/>  kubernetes	Load balancer
<input checked="" type="checkbox"/>  nfs783d52556e8447a681cb	Storage account

```
kubectl get sts,pods,pvc,pv
```


# NAME	READY	AGE			
# statefulset.apps/statefulset-blob-nfs	1/1	49m			
# NAME	READY	STATUS	RESTARTS	AGE	
# pod/statefulset-blob-nfs-0	1/1	Running	0	49m	
# NAME		STATUS	CAPACITY		
# persistentvolumeclaim/persistent-storage-statefulset-blob-nfs-0		Bound	100Gi		
# NAME		CAPACITY	ACCESS MODES	RECLAIM POLICY	
# persistentvolume/pvc-e458e45c-47ca-443f-807a-6b101a9b9614		100Gi	RWX	Delete	

 Search

- <<
-  Container
-  Change access level
-  Restore containers
- >
-  Refresh
- |
-  Delete

 Storage browser


Data storage









 Containers






Search containers by prefix

☐ Show deleted containers

Name	Last modified	Public access level	Lease state
<input type="checkbox"/> pvc-e458e45c-47ca-443f-807a-6b101a9b9614	1/1/2023, 9:07:56 AM	Private	Available

 Search

- <<
-  Upload
-  Add Directory
-  Refresh
- |
-  Rename
-  Delete
-  Change tier
-  Acquire lease
-  Break lease


-  Overview
-  Diagnose and solve problems
-  Access Control (IAM)
- Settings
-  Shared access tokens
-  Manage ACL


Authentication method: Access key ([Switch to Azure AD User Account](#))


Location: pvc-e458e45c-47ca-443f-807a-6b101a9b9614

Search blobs by prefix (case-sensitive)


☐ Show deleted objects


Name	Modified	Access tier	Archive status	Blob type	Size	Lease state
<input type="checkbox"/>  data	1/1/2023, 10:11:12 AM			Block blob	1.75 KiB	Available

 pvc-e458e45c-47ca-443f-807a-6b101a9...
Container

 Search

<<

 Upload

 Add Directory

>>


Authentication method: Access key ([Switch to Azure AD User Account](#))


Location: pvc-e458e45c-47ca-443f-807a-6b101a9b9614


Search blobs by prefix (case-...


☐ Show deleted objects


Settings


 Shared access tokens


 Manage ACL


 Access policy


 Properties


Name
<input type="checkbox"/>  data

 data
Blob


 Save

 Discard

 Download

 Refresh

|


 Delete

Overview

Versions

Edit

Generate SAS

 The file 'data' may not render correctly as it contains an unrecognized extension.

1	Sun Jan 1 08:08:08 UTC 2023
2	Sun Jan 1 08:09:08 UTC 2023
3	Sun Jan 1 08:10:09 UTC 2023
4	Sun Jan 1 08:11:09 UTC 2023
5	Sun Jan 1 08:12:09 UTC 2023
6	Sun Jan 1 08:13:09 UTC 2023
7	Sun Jan 1 08:14:09 UTC 2023
8	Sun Jan 1 08:15:09 UTC 2023


Created resources

kubectl get secret

# NAME	TYPE	DATA	AGE
# secret/azure-storage-account-fuse8d87a1d1a8324d7484f-secret	Opaque	2	46m

kubectl get secret azure-storage-account-fuse8d87a1d1a8324d7484f-secret -o yaml

```
# apiVersion: v1
# data:
#   azurestorageaccountkey: RXk4SHVwUURvZGMydjlnTXJ3THN5Ym1GMUpsWjdVaVQrcDE4L2dDFMUmbU3RXd1V5R2c9PQ==
#   azurestorageaccountname: ZnVzZThkODdhMWQxYTgzMjRkNzQ4NGY=
# kind: Secret
```

 **nfs783d52556e8447a681cb** | Access keys ☆ ⋮

Storage account

Search

Storage browser

Data storage

Containers

Security + networking

Networking

Access keys

Shared access signature

Encryption

🕒 Set rotation reminder

🔄 Refresh

Storage account name

nfs783d52556e8447a681cb

key1 🔄 Rotate key

Last rotated: 1/1/2023 (0 days ago)

Key

xUAkAo5gmU1U4VZ8pJpkugOONQzaAuoSAouuuRXXoUuy2na6CrdasRQ2w/RVg...

Hide

Connection string

DefaultEndpointsProtocol=https;AccountName=nfs783d52556e8447a681cb;Acc...

Hide

Access to Storage Account

Mounting blobfuse requires account key. [Link.](#)

Mounting blob storage NFSv3 does not need account key.

Select Enabled from selected virtual networks and IP addresses with same vnet as agent node.

The screenshot shows the 'Networking' settings page for a storage account named 'nfs783d52556e8447a681cb'. The left sidebar contains a navigation menu with categories: Storage browser, Data storage (Containers), Security + networking (Networking, Access keys, Shared access signature, Encryption, Microsoft Defender for Cloud), Data management (Redundancy, Data protection, Blob inventory, Lifecycle management), and Settings. The main content area has two tabs: 'Firewalls and virtual networks' (selected) and 'Private endpoint connections'. Below the tabs are 'Save', 'Discard', and 'Refresh' buttons. The 'Public network access' section has three radio buttons: 'Enabled from all networks', 'Enabled from selected virtual networks and IP addresses' (selected), and 'Disabled'. A link 'Configure network security for your storage accounts. Learn more' is provided. The 'Virtual networks' section includes buttons to 'Add existing virtual network' and 'Add new virtual network'. A table lists the virtual networks:

Virtual Network	Subnet	Address range	Endpoint Status	Resource Group	Subscription
aks-vnet-15709612	1			mc_rg-aks-storage-blob_a...	Microsoft-Azure-NonProd
	aks-subnet	10.224.0.0/16	✓ Enabled	mc_rg-aks-storage-blob_a...	Microsoft-Azure-NonProd

The 'Firewall' section has a checkbox 'Add IP ranges to allow access from the internet or your on-premises networks. Learn more.' which is checked. Below it is a checkbox 'Add your client IP address ('176.177.25.47')' which is also checked. An 'Address range' section contains a text input field labeled 'IP address or CIDR'.

Blob with User Identity

Supports authentication using Azure Managed Identity.

More details:

<https://github.com/qxsch/Azure-Aks/tree/master/aks-blobfuse-mi>

```
apiVersion: v1
kind: PersistentVolume
metadata:
  name: pv-blob2
spec:
  capacity:
    storage: 10Gi
  accessModes:
    - ReadWriteMany
  persistentVolumeReclaimPolicy: Retain
  storageClassName: azureblob-fuse-premium
  mountOptions:
    - -o allow_other
    - --file-cache-timeout-in-seconds=120
  csi:
    driver: blob.csi.azure.com
    readOnly: false
    volumeHandle: pv-blob2
    volumeAttributes:
      protocol: fuse
      resourceGroup: aks-fuseblob-mi
      storageAccount: myaksblob
      containerName: mycontainer
      AzureStorageAuthType: MSI
      AzureStorageIdentityObjectID: "xxxxxxxxx"
```

Bring your own existing storage account

```
apiVersion: storage.k8s.io/v1
kind: StorageClass
metadata:
  name: blob-fuse
provisioner: blob.csi.azure.com
parameters:
  resourceGroup: EXISTING_RESOURCE_GROUP_NAME
  storageAccount: EXISTING_STORAGE_ACCOUNT_NAME #
cross subscription not supported
  containerName: EXISTING_CONTAINER_NAME
reclaimPolicy: Retain
volumeBindingMode: Immediate
```

More details: https://github.com/kubernetes-sigs/blob-csi-driver/blob/master/deploy/example/e2e_usage.md#option2-bring-your-own-storage-account

More options with Azure Blob

More details:

<https://github.com/kubernetes-sigs/blob-csi-driver/blob/master/docs/driver-parameters.md>

```
apiVersion: storage.k8s.io/v1
kind: StorageClass
metadata:
  name: custom-azureblob-nfs-standard-grs
parameters:
  protocol: nfs # fuse, fuse2, nfs
  skuName: Standard_LRS # Premium_LRS, Standard_GRS, Standard_RAGRS
  location: westeurope
  resourceGroup: rg-aks-storage # should be existing
  storageAccount: storageblobaks013
  containerName: "existing container name"
  containerNamePrefix: "aks-pvc-blob"
  allowBlobPublicAccess: "false"
  tags: "tier=frontend,costcenter=10005"
  server: "accountname.privatelink.blob.core.windows.net"
provisioner: blob.csi.azure.com
volumeBindingMode: Immediate
allowVolumeExpansion: true
reclaimPolicy: Delete # Retain
```

Save secret in Azure Keyvault

More details:

<https://github.com/kubernetes-sigs/blob-csi-driver/blob/master/docs/read-from-keyvault.md>

```
apiVersion: v1
kind: PersistentVolume
metadata:
  name: pv-blob-keyvault
spec:
  capacity:
    storage: 10Gi
  accessModes:
    - ReadWriteMany
  persistentVolumeReclaimPolicy: Retain
  storageClassName: blob-fuse
  csi:
    driver: blob.csi.azure.com
    readOnly: false
    volumeHandle: unique-volumeid
    volumeAttributes:
      containerName: EXISTING_CONTAINER_NAME
      storageAccountName: EXISTING_STORAGE_ACCOUNT_NAME
      keyVaultURL: https://xxx.vault.azure.net/
      keyVaultSecretName: xxx
```


Limitations of Azure Blob

Although Blob CSI Driver allows ReadWriteMany access mode to be used, its functionality is limited by the underlying volume-mounting technology.

If azure-storage-fuse is being used to mount a Blob storage container, multiple nodes are allowed to mount the same container, but for just read-only scenarios.

It means, you can still use ReadWriteMany mode to claim a volume, but you should carefully avoid writing to one single file from multiple nodes as there will be data corruption.

NFSv3, in the contrast, fully supports ReadWriteMany access mode.

More details: <https://github.com/kubernetes-sigs/blob-csi-driver/blob/master/docs/limitations.md>